





ICONOGRAPHY OF FRIDGES & FREEZERS, DISHWASHERS, WASHERS & DRYERS, SINKS AND TAPS ON BACK COVER FLAP

REMOTE CONTROL AIR RENEWAL

Welcome

If there is something that we are passionate about, it is knowing that some things can last forever...

edesa

For this reason, our priority in Edesa is to accompany you from the same day you choose us. Innovate to maintain that relationship that has united us, and never disappoint you providing new solutions with the idea to respond effectively to your needs, improving your quality of life.

Thanks to this attitude here we show our range of products, so you can choose the ones that best adapt to your liking and needs.

Because your comfort and satisfaction are our best reward.....

Edesa is a lifestyle

It is dynamism and creativity. It is freshness at your home. Edesa is the brand for those who are looking for different options to the current offers in the market.

For those who believe that appliances are also part of home decoration, according to our personality and likings. Closeness, complicity, new trends, lifestyles and creativity are the values that distinguish our brand.

With 84 years of experience, and still with the emotion of the first day

Edesa deals with the manufacture and sale of household appliances since 1941. It has since been pioneering and a national benchmark in hobs, ovens, washing machines and water heaters.

We launch a new range of Edesa domestic apliances with a renewed vitality, and desiring to offer the best of us. We have come to stay, keeping our essence with new projects and solutions for every home.

We seek to be more competitive, more efficient and above all to develop household appliances adapted to the market needs. With innovative designs, offering features according to the market demands and being able to offer a better lifestyle at home.

Committed with you

Edesa has a clear tendency to satisfy our customer needs offering functional, efficient, reliable and long-lasting products. We wish to accompany you from the first day you choose us.

We are committed to maintain our relationship and to keep working to preserve it providing a continued attention to a society which is constantly moving. Because your comfort and satisfaction are our best reward.



CNA GROUP

CNA Group is a leading household appliances worldwide manufacturer.

We have been developing our products for more than 70 years and trying to offer an excellent product in both design and performance.



edesa

Founded in Barcelona, Spain, in 1947, since then it has been a pioneer in the domestic extraction business with a wide range of products including exhaust fans, conventional and decorative cooker hoods, hobs, ovens, microwaves, taps, sinks, washing machines, dryers, dishwashers, refrigerators, wine coolers, water heaters and equipment with the use of high quality materials treated in an environmentally friendly way and looking forward the energy efficiency.

At present the CNA Group headquarters are based in Madrid. We supply more than 100 customers on daily basis in the five continents and attend them with our wide network of professionals and from our offices in Spain, Uk and Hong Kong.



As part of our commitment with our customers, in CNA Group to achieve excellent quality, latest technology and sustainable products, we invest over 6 million euros per year.

CNA group has an important balance between manufacturing, innovation and diversification, positioning itself with a differentiated industrial model.

With a total of 5 plants in the world and 2.400 employees, the industrial group has a production capacity over 6.5 million units, producing between others, 2 million cooker hoods and becoming one of the main manufacturers in the world. Total surface facilities are over 150.000m².

We have recently inaugurated new commercial offices and a new showroom in Madrid, the capital of Spain, where we show our latest developments in household appliances.



ONCE UPON A TIME EDESA

edesa

1941

1950

1964

Edesa's foundation

Leading the national market in terms of manufacturing and selling appliances (water heaters, braziers, stoves and household kitchens).

Launch of the first national compression refrigerator, leading sales for more than 15 years.

Launch of the super automatic washing machine and rectangular type dryers, according to the structure of the washing machines.







2008

& Escala Collection.

ort <u>Classic</u>

2011

Pop, Sport, Romantic, Metallic Zen, Urban & Deluxe Collection.



edesa y tú, ¿cómo eres?



2013

Home & Urban Collection.



1941

Sp

1945

1970



1985









1955

Butane gas is being introduced for domestic purposes in Spain. Edesa launches kitchens adapted to the new combustible.

1971

Begin the dishwashers manufacture and the launch of the fridge-freezer into the market.



Edesa experiences a admirable leap going from the 6th to the 4th position in the ranking of the most sold, thanks to an effort to renew the products that changed its catalogue and increased sales in unknown areas like the built-in or the dishwashers.

Edesa is reinforced as a successful brand focused on the Iberian market.





2014

Incorporation at CNA Group as Edesa Industrial S.L.

2018

Centralization of the CNA Group brands in the new premises in Madrid.

A new stage in Edesa's life and appearance.

2022

After more than 80 years we are still

NEAR YOU

edesa edesa

with you

2019

2022



1999



2018







edesə

HOBS	8-43	
OVENS & MICROWAVES	44-69	AR. D
HOODS	70-97	
FRIDGES & FREEZERS	98-141	
DISHWASHERS	142-163	
WASHERS & DRYERS	164-181	
SINKS	182-207	
TAPS	208-220	

edesə

HOB WITH INTEGRAT	ED			INDUCTION HOB			
EIS-7423 DD R	P.22	EIS-6321 DD R	P.23	EIM-9530 R	P.24	EIM-8430	P.24
NEW	-	NEW				banno de la compositione de la c)
EIM-6422 B	P.25	EIT-6422 B	P.25	EIM-6331 HT BQ B	P.26	EIMS-6332 B	P.26
				Constraints of the second seco			2011 2011 2012 2013
EIMS-6330 B BK	P.27	EIMS-6330 B WH	P.27	EIMS-6330 B	P.29	EIM-6330 B	P.28
		NEW					
EIM-6330 B	P.29	EIM-6328 B WH	P.28	EIS-6330 R	P.30	EIT-6329 B	P.30
		Let be the second secon					
	D 6 -		5.01		5.65		
EIT-6328 R	P.31	EIS-3220 B	P.31	EIS-3220 B	P.32	EVT-6422 R	P.32

edesə

9

EVT-6330 B P.33	EVT-6328 B P.33	EVT-6328 R P.34	EVT-3220 B P.34
5 ZONES GAS HOB EGG-9051 TI TR CI N P.35	EGG-7551 TI TR CI N P.35	EGG-6041 TI TR CI N P.36	EGG-6041 TI TR CI B P.36
4 ZONES GAS HOB EGX-6041 TI TR CI N P.36	EGX-6041 TI TR CI B P.36	EGX-6041 TI N P.37	EGX-6041 TI B P.37
3 ZONES GAS HOB EGG-6031 TI TR CI N P.37	EGG-6031 TI TR CI B P.37	EGX-6031 TI TR CI N P.38	EGX-6031 TI TR CI B P.38
2 ZONES GAS HOB EGG-3021 TI N P.38	EGX-3022 TI N P.39	Ê	A Branch

Efficiency, speed and safety

INDUCTION HOBS WHICH PROVIDE THE SAFETY WE ALL ARE LOOKING FOR IN THE KITCHEN.

Edesa Induction hobs allow you to cook with the minimum energy consumption and the maximum speed, guaranteeing in every moment the security when using.

Booster programme

Get it ready sooner than expected. Our hobs have a power level that allows to accelerate the cooking in record time.

Stop&Go

This function enables to interrupt and restart cooking programs to attend to any unexpected event.

When receiving a phone call or attending children, Stop&Go function is perfect, since it can be used in any time when cooking, turning all zones off and restarting cooking with the same settings on your return.





Timer function

orget the clock. With the Timer Function you can set the exact cooking length so that the hob warns you and stops when the time passes. A dish will get burned never again!

Giant 32 cm cooking zone

We know that you want that food equally cook on the entire surface of the pan.

Now it is possible with the giant zone of 32cm diameter of our induction hobs. The XXL format inductor of this zone improves its efficiency and allows a uniform and continuous heat distribution. This makes that your paellas, tortillas, crepes and others notably improve.

Continuous power regulation

Continuous power regulation for stable and accurate power delivery during cooking.

Safety lock

For young and elderly, safety comes first. Activating the safety locking option of our induction and ceramic hobs the control panel is disabled. Thus, we avoid that the cooking process can accidentally be modified.





SMOOTH

Residual heat indicator

Edesa hobs have a light indicator which warns that a cooking zone is still warm for a few minutes after its use

Safety thermostat

The incorporation of the safety thermostat is focused on the protection of the hob to guarantee an even longer lifetime. This system allows to limite the operating temperature of the hob and its components to ensure a stable and a long-lasting operation.



Cooking programs

Being aware of users needs has allowed to Edesa to launch new functions adapted to the real demands. With a simple button you can program your induction, so it can cook according to your liking.

Melting Function: Set up to cook at 45-55°C to melt butter, chocolate, warm up milk or defrost food.

KEEP WARM FUNCTION: It allows at a temperature of 65-70°C to keep the already-cooked food warm before serving it or slowly warm up cold food (not frozen).

SIMMERING FUNCTION: It allows to simmer at a temperature of 85-95°C. Ideal for purée and rice.



Thanks to its new ventilation system, it is no longer necessary to leave a front ventilation slot, allowing you to make the most of the space.

Models EIT 6422, EIM 6328 B WH, EIS 6330 R, EIT 6329 B y EIT 6328 R.

INSTALLATION DIAGRAM FOR INDUCTION HOBS



MINIMUM DISTANCES FOR THE CORRECT VENTILATION

Connectivity

Enjoy the speed in adjusting the hood thanks to automatic communication with the plate. The extraction power is adjusted according to the temperature of the cooking zones used. You will not need to manually adjust the extraction during cooking and as an option you can control it from the hood panel.

Automatic disconnection

The control panel for Edesa hobs has been developed to offer an always safe cooking. Thus, the hob is programmed to turn it off if it has been working at the same cooking level and without any modification for a long period.

Surface suction

Save space and enjoy maximum efficiency, with the new flexible countertop and integrated surface hood.

With its powerful extractor hood, you will quickly extract directly from where the vapors and fumes are generated.

Kitchen is in its 4 areas, convertible into two large double areas, without any fear that the fumes from the cooking will invade your home.



Filtering system

Large surface outer grid that enhances suction speed and facilitates water condensation to prevent it from entering the interior.

V-shaped filter with a larger grease filtering surface, condensation, liquid collection area, and dishwasher safe.





Pleated carbon filter. Powerful carbon filter inspired by industrial filters with high grease absorption capacity, noise reduction, and particle retention. The filters are easily accessible from the suction area and have a lifespan of up to 1 year. Optional regenerable ceramic carbon filters with 144cm² of filtration. The filters are easily accessible from the suction area, regenerable in the oven or dishwasher, and have a lifespan of 3 years.

Types of installation:

Direct outlet to the outside. Possibility of minimal ducting to the outside. Optional accessory of an external grille that prevents cold air and insects from entering the house.





Protect the interior of the furniture and walls from moisture with the included deflector. Air ducting is not necessary; clean air is evenly distributed through the unseen areas of the furniture, significantly increasing storage capacity and simplifying the interior drawers or shelves.

Ease of installation

With the **easy fix** installation, the plate is secured without the need for additional supports.





Flexibility or large format? With Edesa, you have it all.

Freedom of space and large storage. Unlimited design in your kitchen, create spacious and open areas where you can cook without barriers.

Increase your storage capacity under the countertop with up to 45 liters more capacity thanks to its height of 17 centimeters. Because we know you like to have everything at hand while cooking.

Possibility of ducting the air outlet to the exterior of the baseboard.

BASEBOARD OUTLET



Option for baseboard outlet grille or baseboard cutout.

BASEBOARD CUTOUT



With a double liquid collection tank..

The first tank is for condensation and small liquid spills, the second is for collecting large amounts of liquids that have been accidentally spilled.

Easy access to the first tank from the suction area and a practical drain valve from the bottom. Both tanks are removable and dishwasher safe. Additionally, its brushless motor will continue to function without issue, even if large amounts of liquids are spilled.



Compact design

Don't worry about the width of your furniture. Thanks to its compact design, you can install it in a 60cm wide cabinet with a countertop thicker than 22mm.



Accessories

	02890001	DUCTING SET SL1 222X89	
	02890002	COMPACT BEND 90° 222X89	1
	02890003	BEND 90° 222X89	
P	02890004	PIPE HOLDER 222X89	
P	02890005	CONNECTOR 222X89	and research
	02890006	FLAT DUCT 0,5M 222X89	
	02890007	ROUND-FLAT ADAPTER 150/222X89	
	02890008	FLEXIBLE FLAT DUCT 0,5M 222X89	
(m)	02890009	HORIZONTAL BEND 90° 222X89	
Sent.	02890010	HORIZONTAL BEND 15° 222X89	
	02890011	WALL DEFELCTOR SL1	
	02890014	CERAMIC CARBON FILTERS SET CERÁMICOS SL1	
	02890015	PLEATED CARBON FILTERS SET SL1	

HOBS



BBQ function

To become a real chef, the Barbecue function will be your ally.

With only one touch, the HoriZone Tech area regulates the power and, together with the special cast iron grill, a much more homogeneous heat is obtained throughout the cooking surface.

This way, vegetables, meat or fish do not lose their juiciness and flavor.



Cast iron grill for barbecue. **Dimensions:** 455 x 272 x 35 mm **Weight:** 4,6 Kg

COD.: 03002004 EAN-13: 8422248080125

COMPATIBLE MODELS:

EIS-7423 DD R 220-240V 50-60Hz, EIT-7422 DD B /A, EIS-6321 DD R 220-240V 50-60Hz, EIM-9530 R /A, EIM-8430 R/A, EIM-6331 HT BQ B /A.





HoriZone

It is a flexible cooking concept. This cooking module offers twice the possibilities, combining both zones together or using them independently.

When combined, it allows us to use rectangular grilling/barbecue pans and to cook fish. This area allows using one or several pots, of any shape and size, at the same time.

Throughout its 800cm2 surface it is provided a uniform temperature for optimal cooking.

This area adapts the uniform distribution of heat to the diameter of the pot you place. Thus, never mind if you boil pasta for 3 or 7, the area will always adapt to your needs.

Adaptative heating zones

Induction hobs recognize the pot and adjust the power to the surface, maximizing the effectiveness of the cooking.

Thus, minimizing heat losses and maximizing savings.







Automatic extraction according to the cooking power level and Auto cooking function that allows the burner to operate at maximum power for a limited time based on the selected power level.

The high extraction capacity is not at odds with good A+ energy efficiency; the new Flow in models miss nothing with their 691m³/h and extraction speed of 10m/s.



Power limitation

If your contracted power is less than the maximum power of the induction hob, you will not have problems using it normally since you can limit it to adjust it to the contracted power.

Variety of designs

We are delighted you can choose what best fits you with Edesa. For that reason, we want you to select the design you like the most: aluminum frame, front bevel or rounded edges.





With two installation options, on the countertop or perfectly integrated with the countertop surface.







Super slim finish

Our gas hobs with the most premium stainless-steel surface of our range have an ultra-thin finishing in order for the insert is visually slimmer, becoming a product with slim and minimalist lines.

EDESA LOOKS FOR ELEGANCE AND FUNCTIONALITY IN THE DETAILS ..

More solid, stronger and resistant grills

Gas hobs of this range are equipped with high stability cast iron grills which provide higher strength and durability when cooking.

The entire gas cooker range has large grates that offer greater safety when moving pans, since they are more robust and perfect for large pans.



Triple corona

Edesa offers a wide range of gas hobs, both with tempered glass and stainless-steel finishing.

The majority of our models are equipped with a powerful 4 kW triple crown burner for improved speed and efficiency when cooking.



Easy control panels, one control per zone or centralized

Control panels of this range of products have been designed with the same intuitive pattern in order to facilitate cooking.

Choose the one you like most: A control for each zone that allows you to quickly and effectively use the hob or, if you prefer a more minimalist design, choose a control panel with the centralized power selector, with a simple and intuitive operation.

Apart from the basic control system, which allows to control the power per zone or centralized through the "-" and "+" buttons, Edesa has developed a whole range of slider controls. It will seem that you are using your mobile phone!





Multi Slider Touch

This system with individual slider control allow to display in every moment the level of power and the timing for each cooking zone. Among the most special functions of this control panel, we highlight the preset cooking functions as well as the barbecue function for the most exclusive models.



Multi-Touch Control

This system with individual touch control for each cooking zone allows you to view the power level and timer settings at any moment. Each cooking zone has its own display, allowing an independent operation across the entire cooking surface.





Mono-touch

This system allows you to control the power and time selection of our hob from a single touch control.



HOB WI	TH INTEG	RATED VEI	NTILATION		
EIS-74	23 DD	R Rou	nded		NEW
Cod.:	922272	094 - EA I	N: 84222	4837340)]
В	\mathcal{Q}				\bigcirc
booster programme	TIMER	POWER SELECTION PER ZONE	SLIDING CONTROL	COOKING FUNCTIONS	RESIDUAL HEAT INDICATIOR
	IN				

-Induction hob and automatic cooker hood with rounded edge

- -4 Zone: Two HoriZone Tech of 21x40cm (four of 21cm)
- -Mono Slider Touch control panel

STOP&GO

- -Installation height 17cm
- -Individual power selector per cooking zone, with 9 levels, Booster and Auto
- -Timer selector
- -Preset cooking functions (Defrost, Keep Warm, Simmer)
- -Stop&Go function
- -Safety lock

SAFETY LOCK

- -Residual heat indicator
- -Max. Power: 7,4 kW









HOB WI	TH INTEG	RATED VEN	ITILATION			
EIS-63		NEW				
Cod.: 922272093 - EAN: 8422248373371						
В	\mathcal{Q}				\bigcirc	
BOOSTER PROGRAMME	TIMER	POWER SELECTION PER ZONE	SLIDING CONTROL	COOKING FUNCTIONS	RESIDUAL HEAT INDICATIOR	

- -Frontal bevelled induction hob and automatic cooker hood
- -3 Zones: One of 23x23 cm, ofe of 16 cm and one of 18 cm.
- -Mono Slider Touch control panel

STOP&GC

- -Installation height 17cm
- -Individual power selector per cooking zone, with 9 levels and Booster
- -Timer selector

- -Preset cooking functions (Defrost, Keep Warm, Simmer)
- -Stop&Go function
- -Safety lock
- -Residual heat indicator
- -Max. Power: 6,7 kW



edesə







5 ZONE	s induct	FION			
EIM-9	530 R		Rc	ounded	
Cod.: 922272056 - EAN: 8422248109635					
HORIZONE	3 0 ZONE	BOOSTER	TIMER	POWER SELECTION PER ZONE	SLIDING CONTROL
COOKING FUNCTIONS	BARBECUE FUNCTION	SAFETY LOCK	RESIDUAL HEAT INDICATIOR	SAFETY THERMOSTAT	STOP& GO

-Frontal bevelled induction hob and automatic cooker hood -5 Zones: Four of 21x20 cm. One of 30 cm. Flexzone: 21x40 cm. -Mono Slider Touch control panel

-Individual power selector per cooking zone, with 9 levels and Booster

-Timer selector

-Preset cooking functions (Defrost, Keep Warm, Simmer)

- -Stop&Go function
- -Safety lock
- -Residual heat indicator
- -Max. Power: 9 kW

03002004 Cast iron grill grate for barbecue



4 ZONES	4 ZONES INDUCTION						
EIM-8	EIM-8430 R Rounded						
Cod.: 922272057 - EAN: 8422248109642							
HORIZONE	3 0 ZONE	BOOSTER	TIMER	POWER			
TECH	Ô		\bigcirc	SELECTION PER ZONE			
COOKING FUNCTIONS	BARBECUE FUNCTION	SAFETY LOCK	RESIDUAL HEAT INDICATIOR	SAFETY THERMOSTAT	STOP&GO		

-Induction hob with rounded edge

- 4 Zone: Two of 21x20 cm. One of 30 cm. One of 18 cm. Flexzone: 21x40 cm
- -Multi Slider Touch control panel
- -Individual power selector per cooking zone, with 9 levels and Booster
- -Timer selector
- -Preset cooking functions (Defrost, Keep Warm, Simmer)

-Stop&Go function

- -Safety lock
- -Residual heat indicator

-Max. Power: 7,2 kW



* measurements in mm







						? .					
4 zones induc	TION					4 ZONES	INDUCT	ION			
EIM-6422 B		Fro	ont bevel			EIT-64	22 B		Frc	ont bevel	
Cod.: 922272052 - EAN: 8422248109581				Cod.: 922272083 - EAN: 8422248355841				1			
BOOSTER TIMER						B	TIMER			RESIDUAL	SAFETY
	SÉLÉCTION PER ZONE	CONTROL	FUNCTIONS					FUNCTIONS		HEAT INDICATIOR	THERMOSTAT
RESIDUAL SAFETY HEAT THERMOST/ INDICATIOR	STOP&GO					STOP&GO					
Frantal bayallad ir	duction hob					Frontal boy	collocd ind	uction bob			

- -Frontal bevelled induction hob
- -4 Zone: One of 22 cm, one of 20 cm and two of 18 cm diameter
- -Multi Slider Touch control panel
- -Individual power selector per cooking zone, with 9 levels and Booster
- -Timer selector
- -Preset cooking functions (Defrost, Keep Warm, Simmer)
- -Stop&Go function
- -Safety lock
- -Residual heat indicator
- -Max. Power: 7,2 kW

- -Frontal bevelled induction hob
- -4 Zone: One of 21 cm, one of 18 cm and two of 16 cm diameter
- -Touch control panel
- -AUTO 2 connectivity with cooker hood
- -Centralized power selector, with 9 levels and Booster -Timer selector
- -Preset cooking functions (Defrost, Keep Warm, Simmer)
- -Stop&Go function
- -Safety lock
- -Residual heat indicator
- -Power management. Max. Power: 7 kW
- -Installation without front slot







measurements in mm



3 ZONE	s induct	ION			
EIM-6	5331 HT	BQ B	Fro	ont bevel	
Cod.:	9222720	55 - EAN:	84222481	09628	
	Ø 30	B	\Box		
HORIZONE TECH	30 ZONE	BOOSTER PROGRAMME	TIMER	POWER SELECTION PER ZONE	SLIDING CONTROL
	Ô	P	\bigcirc		$ \triangleright$
COOKING FUNCTIONS	BARBECUE FUNCTION	SAFETY LOCK	RESIDUAL HEAT INDICATIOR	SAFETY THERMOSTAT	STOP&GO

-Frontal bevelled induction hob

-3 Zone: One of 30 cm and one HorizoneTech of 21x40 cm (two of 21 cm)

- -Multi Slider Touch control panel
- -Individual power selector per cooking zone, with 9 levels and Booster
- -Timer selector
- -Preset cooking functions (Keep Warm and BBQ function)
- -Stop&Go function
- -Safety lock
- -Residual heat indicator
- -Max. Power: 7 kW









?

3 ZONES INDUCTION

EIMS-6332 B Front bevel Cod.: 922272040 - EAN: 8422248108546



-Smooth power induction hob with frontal bevel

-3 Zone: One of 32/18 cm, one of 21 cm and one 18 cm diameter

- -Multi Slider Touch control panel
- -AUTO 2 connectivity with cooker hood
- -Individual power selector per cooking zone, with 9 levels and Booster
- -Timer selector
- -Preset cooking functions (Defrost, Keep Warm, Simmer
- -Stop&Go function
- -Safety lock
- -Residual heat indicator
- -Power management. Max. Power: 7,1 kW





* measurements in mm





3 ZONES INDUCTION

EIMS-6330 B BK Front bevel Cod.: 922272043 - EAN: 8422248108584





* measurements in mm

-Smooth power induction hob with frontal bevel

- -3 Zone: One of 30/18 cm, one of 21 cm and one 18 cm diameter
- -Multi Slider Touch control panel
- -AUTO 2 connectivity with cooker hood
- -Individual power selector per cooking zone, with 9 levels and Booster
- -Timer selector
- -Preset cooking functions (Defrost, Keep Warm, Simmer)
- -Stop&Go function
- -Safety lock
- -Residual heat indicator
- -Power management. Max. Power: 7,1 kW







3 ZONES INDUCTION		
EIMS-6330 B WH	Front bevel	NEW
Cod.: 922272091 - EA	N: 8422248373210	







3 ZONES INDUCTION						
EIM-	EIM-6330 B			ont bevel		
Cod.	Cod.: 922272045 - EAN:			09345		
30 ZONE	B BOOSTER PROGRAMME	TIMER TIMER SAFETY THERMOSTAT	POWER SELECTION PER ZONE	SLIDING	COOKING FUNCTIONS	

-Frontal bevelled induction hob

-3 Zone: One of 30 cm, one of 22 cm and one of 18 cm diameter

-Multi Slider Touch control panel

-Individual power selector per cooking zone, with 9 levels and Booster

- -Timer selector
- -Preset cooking functions(Defrost, Keep Warm, Simmer)
- -Stop&Go function
- -Safety lock
- -Residual heat indicator
- -Max. Power: 7,1 kW



**	
*	-

3 ZONES INDUCTION

EIM-6	NEW				
Cod.:	92227208	9 - EAN:	84222483	55896	
Ø 30	В	\mathcal{Q}			
30 ZONE	BOOSTER PROGRAMME	TIMER	POWER SELECTION PER ZONE	SLIDING CONTROL	COOKING FUNCTIONS
Π.	\bigcirc		$ \triangleright$		
SAFETY LOCK	RESIDUAL HEAT INDICATIOR	SAFETY THERMOSTAT	stop&go		

-Frontal bevelled induction hob

-3 Zone: One of 28 cm, one of 22 cm and one of 18 cm diameter

-Multi Slider Touch control panel

-Individual power selector per cooking zone, with 9 levels and Booster

- -Timer selector
- -Preset cooking functions(Defrost, Keep Warm, Simmer)
- -Stop&Go function
- -Safety lock
- -Residual heat indicator
- -Power management. Max. Power: 7,1 kW
- -Installation without front slot







* measurements in mm

edesa

HOBS





3 ZONE	s inducti	ON				3 ZON
EIMS-	6330 B		Fro	EIM-		
Cod.:	92227206	6 - EAN:	8422248	97830		Cod.
BOOSTER PROGRAMME	TIMER TIMER SAFETY THERMOSTAT	POWER SELECTION PER ZONE	SLIDING CONTROL	COOKING FUNCTIONS	SAFETY LOCK	BOOSTER PROGRAMM
-Smooth p -3 Zone: O diameter -Multi Slide -AUTO 2 cc -Individual Booster -Timer sele	ne of 30/18 r Touch co onnectivity power sele ctor	3 cm, one ntrol pane with cook ector per c	of 21 cm a I er hood	nd one 18 ne, with 9 k		-Frontal & -3 Zone: (diamete -Multi Slic -Individuo Booster -Timer se -Preset c

-Preset cooking functions(Defrost, Keep Warm, Simmer)

- -Stop&Go function
- -Safety lock
- -Residual heat indicator

-Power management. Max. Power: 7,1 kW

565

3 ZONES INDUCTION						
EIM-6330 B Front bevel						
Cod.: 922272053 - EAN: 8422248197823						
	\sim			1775	_0_	





SAFETY LOCK

Т



Ш fety Mostat

6
SAF
THERN

COOKING FUNCTIONS

ГЩ

RESIDUAL HEAT



- rontal bevelled induction hob
- Zone: One of 30 cm, one of 22 cm and one of 18 cm diameter
- Multi Slider Touch control panel
- ndividual power selector per cooking zone, with 9 levels and Booster
- imer selector
- Preset cooking functions (Defrost, Keep Warm, Simmer)
- -Stop&Go function
- -Safety lock
- -Residual heat indicator
- -Max. Power: 7,1 kW



495



⁺ measurements in mm







EIS-63	k	NEW				
Cod.: 922272084 - EAN: 8422248355858						
B		۲.	\bigcirc		Q	
BOOSTER PROGRAMME	POWER SELECTION PER ZONE	SAFETY LOCK	RESIDUAL HEAT INDICATIOR	COOKING FUNCTIONS	TIMER	



3 ZONES INDUCTION

EIT-6329 B

NEW Front bevel Cod.: 922272087 - EAN: 8422248355889

RESIDUAL

HEAT INDICATIOR







-Frontal bevelled induction hob

- -3 Zone: One of 30 cm, one of 22 cm and one of 18 cm diameter
- -Mono Slider Touch control panel
- -AUTO 2 connectivity with cooker hood
- -Centralized power selector, with 9 levels and Booster -Timer selector

-Preset cooking functions (Defrost, Keep Warm, Simmer) -Safety lock

-Residual heat indicator

-Power management. Max. Power: 7,1 kW

-Installation without front slot

- -Frontal bevelled induction hob
- -3 Zone: One of 28 cm, one of 21 cm and one of 16 cm
- diameter
- -Touch control panel
- -Centralized power selector, with 9 levels and Booster
- -Timer selector
- -Stop&Go function
- -Safety lock
- -Residual heat indicator
- -Power management. Max. Power: 7,1 kW
- -Installation without front slot







* measurements in mm



edesa

HOBS



~

3 ZONES INDUCTION

EIT-6328 R Rounded

Cod.: 922272085 - EAN: 8422248355865





SAFETY THERMOSTAT



2 ZONES INDUCTION

EIS-3220 B Front bevel						
Cod.: 922272082 - EAN: 8422248344753						
B	\mathbf{r}			P .	(\bigcirc)	









HEAT INDICATIOR

SAFETY THERMOSTAT

- -Induction hob with rounded edge
- -3 Zone: One of 28 cm, one of 22 cm and one of 18 cm diameter
- -Touch control panel
- -Centralized power selector, with 9 levels and Booster
- -Timer selector
- -Preset cooking functions (Defrost, Keep Warm, Simmer)
- -Stop&Go function
- -Safety lock
- -Residual heat indicator
- -Power management. Max. Power: 7 kW

-Installation without front slot

-Frontal bevelled induction hob

-2 Zone: One of 20 cm and one of 18 cm diameter

POWER SELECTION PER ZONE

- -Mono Slider Touch control panel
- -Centralized power selector, with 9 levels and Booster
- -Timer selector
- -Safety lock
- -Residual heat indicator
- -Max. Power: 3,5 kW









⁴ measurements in mm

31







2 ZONES	s induc [.]	TION					4 ZON	es vitroce	RAMIC
EIS-3220 B Front bevel			EVT-	6422 R					
Cod.:	9222720	47 - EAN:	84222481	09390			Cod.	: 92227204	- EAN:
B	${\mathfrak O}$	T.		\bigcirc	- [-		\Box	T.	\bigcirc
BOOSTER PROGRAMME	TIMER	SAFETY LOCK	HORIZONE TECH	RESIDUAL HEAT INDICATIOR	SAFETY THERMOSTAT		TIMER	SAFETY LOCK	RESIDUAL HEAT INDICATIOR

EVT-6	422 R		Rounded			
Cod.:	92227204	1 - EAN: 8	3422248108553	}		
M	P	(\mathfrak{O})				
	10	1221				

SAFETY THERMOSTAT

-Frontal bevelled induction hob

- -2 Zone: One of 20 cm and one of 18 cm diameter
- -Mono Slider Touch control panel
- -Centralized power selector, with 9 levels and Booster
- -Timer selector
- -Safety lock
- -Residual heat indicator
- -Max. Power: 3,5 kW

- -Radiant vitroceramic hob with rounded edge
- -4 Zone: One of 21,5 cm, one of 18,5 cm and two of 15 cm
- diameter
- -Touch control panel
- -Centralized power selector, with 9 levels
- -Timer selector
- -Safety lock
- -Residual heat indicator
- -Max. Power: 6,5 kW





* measurements in mm

edesa 🖁





3 zones vitro	CERAMIC		3 ZONES VITROCERAMIC			
EVT-6330 B	Front bevel	NEW	EVT-6328 B		Front bevel	
Cod.: 922272092 - EAN: 8422248373227			Cod.: 922272049 - EAN: 8422248109550			
TIMER SAFETY LOO	CK RESIDUAL HEAT INDICATIOR		TIMER SAFETY LOC	K RESIDUAL HEAT INDICATIOR	SAFETY THERMOSTAT	

-Frontal bevelled radiant vitroceramic hob

- -3 Zone: One of 30/19 cm, one of 18/12 cm and one of 15 cm diameter
- -Touch control panel
- -Centralized power selector, with 9 levels
- -Timer selector
- -Safety lock
- -Residual heat indicator
- -Max. Power: 6,2 kW

-Frontal bevelled radiant vitroceramic hob

- -3 Zone: One of 28/22/15,5 cm, one of 18,5 cm and one of 15
- cm diameter
- -Touch control panel
- -Centralized power selector, with 9 levels
- -Timer selector
- -Safety lock
- -Residual heat indicator
- -Max. Power: 5,7 kW







t measurements in mm







3 ZONES VITROCERAMIC	
EVT-6328 R	Rounded
Cod.: 922272050 - EAN: 8422248109567	



2 ZONES VITROCERAMIC

EVT-3220 B	Front bevel
Cod.: 922272064 - EAN: 8422248111256	





-Radiant vitroceramic hob with rounded edge -3 Zone: One of 28/22 cm, one of 18,5 cm and one of 15 cm

- diameter
- -Touch control panel
- -Centralized power selector, with 9 levels
- -Timer selector
- -Safety lock
- -Residual heat indicator -Max. Power: 5,7 kW

-Radiant vitroceramic hob with rounded edge

- -2 Zone: One of 19/12 cm and one of 15,5 cm diameter
- -Touch control panel
- -Centralized power selector, with 9 levels
- -Timer selector
- -Safety lock
- -Residual heat indicator
- -Max. Power: 3,2 kW






edesə





5 ZONE	es gas ho	В		
EGG	-9051 TI	TR CI N	Black g	lass
Cod.:	92227206	7 - EAN:	8422248198318	
A	4		E	
SAFETY GAS SHUT-OFF	AUTO SWITCH ON	TRIPLE RING BURNER	CAST IRON GRILLS	

	Inste	alled	Included as accesory	
EGG-9051 TI TR CI N	Injector	Gas Pressure	Injector	Gas Pressure
	G20	20mbar	G30	30mbar

-Natural gas hob with 5 burners

-Cast iron 3 independent pan supports on tempered glass -One high efficiency (4 kW) triple ring burner, one super-fast burner, two semi-fast burners and one auxiliary burner -Frontal controls

-Electronic start-up built into control

-Gas shut-off safety system

-Includes optional injectors for Butane Gas -Total gas power: 11,5 kW

5 zones	gas hob			
EGG-7	551 TI TR CI	Ν	Black glass	
Cod.: 9	22272068 - EA	N: 8422248	3198325	
4				



	Inste	alled	Included of	is accesory
EGG-7551 TI TR CI N	Injector	Gas Pressure	Injector	Gas Pressure

G20	20mbar	G30	30mbar

-Natural gas hob with 5 burners

-Cast iron 3 independent pan supports on tempered glass -One high efficiency (4 kW) triple ring burner, one super-fast burner, two semi-fast burners and one auxiliary burner -Frontal controls

-Electronic start-up built into control

-Gas shut-off safety system

-Includes optional injectors for Butane Gas

-Total gas power: 11,5 kW













edesə

S. Steel

S. Steel

Included as accesory

Gas Pressure

Injector

330

	C20	20 mala arr	C 30	20mala arr
EGG-6041 TI TR CI N	Injector	Gas Pressure	Injector	Gas Pressure
EGG-6041 TI TR CI N	Inst	alled	Included o	is accesory
0.101 011 0	Donne	UNILLO		
	N BURNE		ч	
SAFETY GAS AUTO	SWITCH TRIPLE R	NG CAST IRON		
	/ (()			
A				
000007222			0170017	
Cod.: 9222	272070 - E	N: 842224	8198349	
			black gla	55
EGG-604	L1 TI TR C	IB	Black gla	cc
Cod.: 9222	272069 - E/	N: 842224	8198332	
	-		U	
EGG-604	1 TI TR C	IN	Black gla	SS
4 ZONES GA				

-Natural	aas	hob	with	4	burners	

-Cast iron 2 independent pan supports on tempered glass -One triple ring burner (4kW), one fast burner, one semi-fast burner and one auxiliary burner

-Frontal controls

- -Electronic start-up built into control
- -Gas shut-off safety system
- -Includes optional injectors for Butane Gas
- -Total gas power: 9,75 kW

-Natural gas hob with 4 burners	

Injector

-Cast iron 2 independent pan supports on stainless steel surface -One triple ring burner (3,3kW), one fast burner, one semi-fast burner and one auxiliary burner

CAST IRON GRILLS

Gas Pressure

-Frontal controls

SAFETY GAS

EGX-6041 TI TR CI N EGX-6041 TI TR CI B

- -Electronic start-up built into control
- -Gas shut-off safety system

4 ZONES GAS HOB

EGX-6041 TI TR CI N

EGX-6041 TI TR CI B

AUTO SWITCH ON

Cod.: 922272071 - EAN: 8422248198363

Cod.: 922272072 - EAN: 8422248198370

TRIPLE RING BURNER

-Includes optional injectors for Butane Gas

-Total gas power: 9 kW







HOBS



4 ZONES GAS HOB

EGX-6041 TI N	S. Steel
Cod.: 922272073 - EAN: 84	122248198387
EGX-6041 TI B	S. Steel
Cod.: 922272074 - EAN: 84	122248198400



EGX-6041 TI N EGX-6041 TI B	Installed Included as accesory				
	Injector	Gas Pressure	Injector	Gas Pressure	
	G20	20mbar	G30	30mbar	

-Natural gas hob with 4 burners

-Enameled pan 2 supports on stainless steel surface

-One fast burner, two semi-fast burners and one auxiliary burner -Lateral controls

- -Electronic start-up built into control
- -Gas shut-off safety system
- -Includes optional injectors for Butane Gas
- -Total gas power: 7,5 kW



3 ZON	es gas ho	ЭB	
EGG	-6031 TI	TR CI N	Black glass
Cod.	92227207	′5 - EAN:	8422248198417
EGG	-6031 TI	TR CI B	Black glass
Cod.	92227207	′6 - EAN:	8422248198424
SAFETY GAS SHUT-OFF	AUTO SWITCH ON	TRIPLE RING BURNER	CAST IRON GRILLS

FOO JOAT TITE OLM		anoa			
EGG-6031 TI TR CI N EGG-6031 TI TR CI B	Injector	Gas Pressure	Injector	Gas Pressure	
EGG-8031 II IK CI B	G20	20mbar	G30	30mbar	

Included as accesory

-Natural gas hob with 3 burners

-Cast iron 2 independent pan supports on tempered glass

-One triple ring burner (4kW), one fast burner and one auxiliary burner

-Frontal controls

-Electronic start-up built into control

-Gas shut-off safety system

-Includes optional injectors for Butane Gas

-Total gas power: 8 kW















3 ZONES GAS HOB	
EGX-6031 TI TR CI N	S. Steel
Cod.: 922272077 - EAN:	8422248198431
EGX-6031 TI TR CI B	S. Steel
Cod.: 922272078 - EAN:	8422248198448
	m

AFETY GAS	AUTO S
SHUT-OFF	0

SWITCH TRIPLE RING CAST IRON DN BURNER GRILLS

EGX-6031 TI TR CI N	Inste	alled	Included as accesory		
	Injector	Gas Pressure	Injector	Gas Pressure	
EGX-6031 TI TR CI B	G20	20mbar	G30	30mbar	

-Butane gas hob with 3 burners

-Cast iron 2 independent pan supports on tempered glass -One triple ring burner (4kW), one fast burner and one auxiliary burner

- -Frontal controls
- -Electronic start-up built into control
- -Gas shut-off safety system
- -Includes optional injectors for Butane Gas

-Total gas power: 8 kW





2 zones gas hob	
EGG-3021 TI N	Black glass
Cod.: 922272079 - EAN	8422248198455



	Inst	alled	Included as accesory		
EGG-3021 TI N	Injector	Gas Pressure	Injector	Gas Pressu	
	G20	20mbar	G30	30mbar	

-Natural gas	hob with 2 bu	rners

- -Cast iron pan supports on tempered glass surface
- -One fast burner and one auxiliary burner
- -Frontal controls
- -Electronic start-up built into control
- -Gas shut-off safety system
- -Includes optional injectors for Butane Gas
- -Total gas power: 4 kW





re





2 ZONES GAS HOB	
EGX-3022 TI N	Stainless steel
Cod.: 922272080 - EAN: 8	422248198462



	Inst	alled	Included as accesory		
EGG-3021 TI N	Injector	Gas Pressure	Injector	Gas Pressure	
	G20	20mbar	G30	30mbar	

- -Natural gas hob with 2 burners
- -Enameled pan supports on stainless steel surface
- -One fast burner and one auxiliary burner
- -Frontal controls
- -Electronic start-up built into control
- -Gas shut-off safety system
- -Includes optional injectors for Butane Gas
- -Total gas power: 4 kW







edesə

Code EAN	922272094 8422248373401	922272093 8422248373371	922272056 8422248109635	922272057 8422248109642	922272052 8422248109581	922272083 8422248355841	922272055 8422248109628	
Model	EIS-7423 DD R	EIS-6321 DD R	EIM-9530 R	EIM-8430 R	EIM-6422 B	EIT-6422 B	EIM-6331 HT BQ B	
Туре	Induction	Induction	Induction	Induction	Induction	Induction	Induction	
Product fiche		2					2	
Cooking zones Right front zone: Diameter (mm)	4 210x190	3 230x230	5 210x200	4	4	4	3 300	
Right front zone: Power (kW)	210x190	230x230	210x200	1,2	1,2	1,2	2,5	
Right front zone: Booster (kW)	3	2,6	2,8	1,2	-	-	3,5	
Right front zone: Consumption (Wh/kg)	190,8	191	182,7	1,5	195,4	195,4	199,3	
Right rear zone: Diameter (mm)	210x190	-	210x200	-	200	193,4	-	
Right rear zone: Power (kW)	2,2	_	1,5	-	1,8	1,8	-	
Right rear zone: Booster (kW)	2,2	-	2		-	-	-	
Right rear zone: Consumption (Wh/kg)	190,8	-	182,9		180,8	180,8		
Central front zone: Diameter (mm)	-	-	-	-	-	-	-	
Central front zone: Diameter (mm) Central front zone: Power (kW)		-		()		-		
Central front zone: Booster (kW)	-	-	-	-	-	-	-	
Central front zone: Consumption (Wh/kg)	-		-	-	()	-		
Central rear zone: Diameter (mm)	-	-	300	300		-	-	
Central rear zone: Diameter (mm) Central rear zone: Power (kW)	-	-	2,3	2,3		-		
Central rear zone: Power (kW) Central rear zone: Booster (kW)	-	-	2,3	2,3	-	-	-	
	-	-	3 216,3	3 216,3	· · · · · · · · · · · · · · · · · · ·	-	-	
Central rear zone: Consumption (Wh/kg)	-	140			220		100	
Front left zone: Diameter (mm)	210x190	160	210x200	210x200	220	210	190	
Front left zone: Power (kW)	2,2	1,2	1,5	1,5	2,3	2,3	2	
Front left zone: Booster (kW)	3	1,5	2	2	-	-	2,8	
Front left zone: Consumption (Wh/kg)	190,8	192,5	182,9	182,9	182,9	182,9	185,8	
Left rear zone: Diameter (mm)	210x190	180	210x200	210x200	180	160	190	
Left rear zone: Power (kW)	2,2	2	2	2	1,2	1,2	1,5	
Left rear zone: Booster (kW)	2,6	2,3	2,8	2,8	- <u> </u>	-	2	
Left rear zone: Consumption (Wh/kg)	190,8	185,8	182,7	182,7	183,4	183,4	181,7	
Energy consumption of the hob (Wh/kg)	191,5	188,5	189,5	190,4	185,6	185,6	184,7	
Dimensions								
Product width (mm)	770	590	900	850	590	590	590	
Product depth (mm)	520	520	520	520	520	520	520	
Product height (mm)	170	170	60	60	58	58	60	
Built-in width (mm)	750	560	875	745	565	560	565	
Built-in depth (mm)	490	490	495	495	495	490	495	
Ventilation slot (mm)		-	5	5	5	-	5	
	Easy fix	Easy fix	-	Quick-fix System		a tak fiv System		
Fixing system	EUSY IIX	EUSY IIA	QUICK-IIA System	QUICK-IIX System	QUICK-IIA System	QUICK-IIA Syste	QUICK-IIX System	_
Finishing								
Colour	Black	Black	Black	Black	Black	Black	Black	
Aesthetic	Rounded	Rounded	Front bevel	Front bevel	Front bevel	Front bevel	Front bevel	
Control								
Control type	Mono Slider Touch	Mono Slider Touch	Independent Slider for each area	Independent Slider for each area	Multi Slider Touch	Touch	Multi Slider Touch	
Power selection (+/-)	Centralized	Centralized	Individual per	Individual per	Individual per	Individual per	Individual per	
	00111-01-2							
Power levels	2 Distance		zone	zone	zone	zone	zone	
	9 + Booster	9 + Booster	zone 9 + Booster			zone 9 + Booster		
Connectivity	9 + Booster -			zone	zone	zone 9 + Booster AUTO 2	zone	
Connectivity Cooking functions by temperature	-	9 + Booster - -	9 + Booster - -	zone 9 + Booster -	zone	zone 9 + Booster AUTO 2	zone 9 + Booster - -	
Connectivity Cooking functions by temperature Cooking functions	- - •	9 + Booster - -	9 + Booster - -	zone 9 + Booster - -	zone 9 + Booster - -	zone 9 + Booster AUTO 2	zone 9 + Booster - -	
Connectivity Cooking functions by temperature Cooking functions Cooking zone division by power	-	9 + Booster - -	9 + Booster - -	zone 9 + Booster -	zone	zone 9 + Booster AUTO 2 - -	zone 9 + Booster - -	
Connectivity Cooking functions by temperature Cooking functions Cooking zone division by power Pot displacement recognition	- - •	9 + Booster - -	9 + Booster - -	zone 9 + Booster - -	zone 9 + Booster - -	zone 9 + Booster AUTO 2	zone 9 + Booster - -	
Connectivity Cooking functions by temperature Cooking functions Cooking zone division by power Pot displacement recognition Pasta/rice timer function	- - •	9 + Booster - -	9 + Booster - -	zone 9 + Booster - -	zone 9 + Booster - -	zone 9 + Booster AUTO 2 - -	zone 9 + Booster - -	
Connectivity Cooking functions by temperature Cooking functions Cooking zone division by power Pot displacement recognition Pasta/rice timer function Automatic start function	- - - - - -	9 + Booster - - - - - - -	9 + Booster - - - - - - - - -	zone 9 + Booster - - - - - - -	zone 9 + Booster - - - - - -	zone 9 + Booster AUTO 2 - - - - -	zone 9 + Booster - - - - - -	
Connectivity Cooking functions by temperature Cooking functions Cooking zone division by power Pot displacement recognition Pasta/rice timer function Automatic start function Pan speed function	- - - - -	9 + Booster - - - - - - - -	9 + Booster - -	zone 9 + Booster - -	zone 9 + Booster - -	zone 9 + Booster AUTO 2 - -	zone 9 + Booster - -	
Connectivity Cooking functions by temperature Cooking functions Cooking zone division by power Pot displacement recognition Pasta/rice timer function Automatic start function Pan speed function Demo mode	- - - - - - -	9 + Booster - - - - - - - •	9 + Booster - - - - - - - - - - - -	zone 9 + Booster - - - - - - - - - - - -	zone 9 + Booster - - - - - - - - - - - -	zone 9 + Booster AUTO 2 - - - - - - - - -	zone 9 + Booster - - - - - - - - - - - -	
Connectivity Cooking functions by temperature Cooking functions Cooking zone division by power Pot displacement recognition Pasta/rice timer function Automatic start function Pan speed function Demo mode AUTO cooking function	- - - - - - - - -	9 + Booster - - - - - - - - - - - - -	9 + Booster - - - - - - - - -	zone 9 + Booster - - - - - - -	zone 9 + Booster - - - - - -	zone 9 + Booster AUTO 2 - - - - -	zone 9 + Booster - - - - - -	
Connectivity Cooking functions by temperature Cooking functions Cooking zone division by power Pot displacement recognition Pasta/rice timer function Automatic start function Pan speed function Demo mode AUTO cooking function Memory function	- - - - - - - - - - - - - - - - - - -	9 + Booster - - - - - - - - - - - - -	9 + Booster - - - - - - - - - - - - -	zone 9 + Booster - - - - - - - - - - - - - -	zone 9 + Booster - - - - - - - - - - - - - -	zone 9 + Booster AUTO 2 - - - - - - - - - - - - - -	zone 9 + Booster - - - - - - - - - - - - - -	
Connectivity Cooking functions by temperature Cooking functions Cooking zone division by power Pot displacement recognition Pasta/rice timer function Automatic start function Pan speed function Demo mode AUTO cooking function Memory function Timer	- - - - - - - - - - - - - - - - - - -	9 + Booster - - - - - - - - - - - - -	9 + Booster - - - - - - - - - - - -	zone 9 + Booster - - - - - - - - - - - -	zone 9 + Booster - - - - - - - - - - - -	zone 9 + Booster AUTO 2 - - - - - - - - -	zone 9 + Booster - - - - - - - - - - - -	
Connectivity Cooking functions by temperature Cooking functions Cooking zone division by power Pot displacement recognition Pasta/rice timer function Automatic start function Pan speed function Demo mode AUTO cooking function Memory function Timer Countdown alarm	- - - - - - - - - - - - - - - - - - -	9 + Booster - - - - - - - - - - - - -	9 + Booster - - - - - - - - - - - - -	zone 9 + Booster - - - - - - - - - - - - - - - - -	zone 9 + Booster - - - - - - - - - - - - - - - - - - -	zone 9 + Booster AUTO 2 - - - - - - - - - - - - - -	zone 9 + Booster - - - - - - - - - - - - - - - - - - -	
Connectivity Cooking functions by temperature Cooking functions Cooking zone division by power Pot displacement recognition Pasta/rice timer function Automatic start function Pan speed function Demo mode AUTO cooking function Memory function Timer Countdown alarm Pause function	- - - - - - - - - - - - - - - - - - -	9 + Booster - - - - - - - - - - - - -	9 + Booster - - - - - - - - - - - - -	zone 9 + Booster - - - - - - - - - - - - - -	zone 9 + Booster - - - - - - - - - - - - - -	zone 9 + Booster AUTO 2 - - - - - - - - - - - - - - - - - - -	zone 9 + Booster - - - - - - - - - - - - - - -	
Connectivity Cooking functions by temperature Cooking functions Cooking zone division by power Pot displacement recognition Pasta/rice timer function Automatic start function Pan speed function Demo mode AUTO cooking function Memory function Timer Countdown alarm Pause function Power management	- - - - - - - - - - - - - - - - - - -	9 + Booster - - - - - - - - - - - - -	9 + Booster - - - - - - - - - - - - -	zone 9 + Booster - - - - - - - - - - - - - - - - -	zone 9 + Booster - - - - - - - - - - - - - - - - - - -	zone 9 + Booster AUTO 2 - - - - - - - - - - - - - -	zone 9 + Booster - - - - - - - - - - - - - - - - - - -	
Connectivity Cooking functions by temperature Cooking functions Cooking zone division by power Pot displacement recognition Pasta/rice timer function Automatic start function Pan speed function Demo mode AUTO cooking function Memory function Timer Countdown alarm Pause function Power management Security	- - - - - - - - - - - - - - - - - - -	9 + Booster - - - - - - - - - - - - -	9 + Booster - - - - - - - - - - - - -	zone 9 + Booster - - - - - - - - - - - - - - - -	zone 9 + Booster - - - - - - - - - - - - - - - - - - -	zone 9 + Booster AUTO 2 - - - - - - - - - - - - - - - - - - -	zone 9 + Booster - - - - - - - - - - - - - - - - - - -	
Connectivity Cooking functions by temperature Cooking functions Cooking zone division by power Pot displacement recognition Pasta/rice timer function Automatic start function Pan speed function Demo mode AUTO cooking function Memory function Timer Countdown alarm Pause function Power management	- - - - - - - - - - - - - - - - - - -	9 + Booster - - - - - - - - - - - - -	9 + Booster - - - - - - - - - - - - -	zone 9 + Booster - - - - - - - - - - - - - - - -	zone 9 + Booster - - - - - - - - - - - - - - - - - - -	zone 9 + Booster AUTO 2 - - - - - - - - - - - - - - - - - - -	zone 9 + Booster - - - - - - - - - - - - - - - - - - -	
Connectivity Cooking functions by temperature Cooking functions Cooking zone division by power Pot displacement recognition Pasta/rice timer function Automatic start function Pan speed function Demo mode AUTO cooking function Memory function Timer Countdown alarm Pause function Power management Security	- - - - - - - - - - - - - - - - - - -	9 + Booster - - - - - - - - - - - - -	9 + Booster - - - - - - - - - - - - -	zone 9 + Booster - - - - - - - - - - - - - - - - - - -	zone 9 + Booster - - - - - - - - - - - - - - - - - - -	zone 9 + Booster AUTO 2 - - - - - - - - - - - - - - - - - - -	zone 9 + Booster - - - - - - - - - - - - - - - - - - -	
Connectivity Cooking functions by temperature Cooking functions Cooking zone division by power Pot displacement recognition Pasta/rice timer function Automatic start function Pan speed function Demo mode AUTO cooking function Memory function Timer Countdown alarm Pause function Power management Security Safety lock	- - - - - - - - - - - - - - - - - - -	9 + Booster - - - - - - - - - - - - -	9 + Booster - - - - - - - - - - - - -	zone 9 + Booster - - - - - - - - - - - - - - - - - - -	zone 9 + Booster - - - - - - - - - - - - - - - - - - -	zone 9 + Booster AUTO 2 - - - - - - - - - - - - -	zone 9 + Booster - - - - - - - - - - - - - - - - - - -	
Connectivity Cooking functions by temperature Cooking functions Cooking zone division by power Pot displacement recognition Pasta/rice timer function Automatic start function Pan speed function Demo mode AUTO cooking function Memory function Timer Countdown alarm Pause function Power management Security Safety lock Residual heat indicator	- - - - - - - - - - - - - - - - - - -	9 + Booster - - - - - - - - - - - - -	9 + Booster - - - - - - - - - - - - -	zone 9 + Booster - - - - - - - - - - - - - - - - - - -	zone 9 + Booster - - - - - - - - - - - - - - - - - - -	zone 9 + Booster AUTO 2 - - - - - - - - - - - - -	zone 9 + Booster - - - - - - - - - - - - - - - - - - -	
Connectivity Cooking functions by temperature Cooking functions Cooking zone division by power Pot displacement recognition Pasta/rice timer function Automatic start function Pan speed function Demo mode AUTO cooking function Memory function Timer Countdown alarm Pause function Power management Safety lock Residual heat indicator Automatic pan detection Automatic safety switch-off		9 + Booster - - - - - - - - - - - - -	9 + Booster - - - - - - - - - - - - -	zone 9 + Booster - - - - - - - - - - - - - - - - - - -	zone 9 + Booster - - - - - - - - - - - - - - - - - - -	zone 9 + Booster AUTO 2 - - - - - - - - - - - - -	zone 9 + Booster - - - - - - - - - - - - - - - - - - -	
Connectivity Cooking functions by temperature Cooking functions Cooking zone division by power Pot displacement recognition Pasta/rice timer function Automatic start function Pan speed function Demo mode AUTO cooking function Memory function Timer Countdown alarm Pause function Power management Security Safety lock Residual heat indicator Automatic pan detection Automatic safety switch-off Protection against liquid spillage		9 + Booster - - - - - - - - - - - - -	9 + Booster - - - - - - - - - - - - -	zone 9 + Booster - - - - - - - - - - - - - - - - - - -	zone 9 + Booster - - - - - - - - - - - - - - - - - - -	zone 9 + Booster AUTO 2 - - - - - - - - - - - - - - - - - - -	zone 9 + Booster - - - - - - - - - - - - - - - - - - -	
Connectivity Cooking functions by temperature Cooking functions Cooking zone division by power Pot displacement recognition Pasta/rice timer function Automatic start function Pan speed function Demo mode AUTO cooking function Memory function Timer Countdown alarm Pause function Power management Security Safety lock Residual heat indicator Automatic pan detection Automatic safety switch-off Protection against liquid spillage Electrical connection		9 + Booster - - - - - - - - - - - - -	9 + Booster - - - - - - - - - - - - -	zone 9 + Booster - - - - - - - - - - - - - - - - - - -	zone 9 + Booster - - - - - - - - - - - - - - - - - - -	zone 9 + Booster AUTO 2 - - - - - - - - - - - - -	zone 9 + Booster - - - - - - - - - - - - - - - - - - -	
Connectivity Cooking functions by temperature Cooking functions Cooking zone division by power Pot displacement recognition Pasta/rice timer function Automatic start function Pan speed function Demo mode AUTO cooking function Memory function Timer Countdown alarm Pause function Power management Saceurity Safety lock Residual heat indicator Automatic safety switch-off Protection against liquid spillage Electrical connection Nominal voltage (V)	- - - - - - - - - - - - - - - - - - -	9 + Booster - - - - - - - - - - - - -	9 + Booster - - - - - - - - - - - - -	zone 9 + Booster - - - - - - - - - - - - - - - - - - -	zone 9 + Booster - - - - - - - - - - - - - - - - - - -	zone 9 + Booster AUTO 2 - - - - - - - - - - - - -	zone 9 + Booster - - - - - - - - - - - - - - - - - - -	
Connectivity Cooking functions by temperature Cooking functions Cooking zone division by power Pot displacement recognition Pasta/rice timer function Automatic start function Pan speed function Demo mode AUTO cooking function Memory function Timer Countdown alarm Pause function Power management Security Safety lock Residual heat indicator Automatic pan detection Automatic safety switch-off Protection against liquid spillage Electrical connection		9 + Booster - - - - - - - - - - - - -	9 + Booster - - - - - - - - - - - - -	zone 9 + Booster - - - - - - - - - - - - - - - - - - -	zone 9 + Booster - - - - - - - - - - - - - - - - - - -	zone 9 + Booster AUTO 2 - - - - - - - - - - - - -	zone 9 + Booster - - - - - - - - - - - - - - - - - - -	

All the boxes marked with a ${\mbox{\circ}}$ are equivalent to a Yes Accessories / ${\mbox{\circ}}$ NOT INCLUDED ${\mbox{\circ}}$ INCLUDED

922272040 8422248108546	922272043 8422248108584	922272091 8422248373210	922272045 8422248109345	922272089 8422248355902	922272066 8422248197830	922272053 8422248197823	922272084 8422248355858	922272087 8422248355889
EIMS-6332 B	EIMS-6330 B BK	EIMS-6330 B WH	EIM-6330 B	EIM-6328 B WH	EIMS-6330 B	EIM-6330 B /B	EIS-6330 R	EIT-6329 B
Induction	Induction	Induction	Induction	Induction		Induction	Induction	Induction
3	3	3	3	3	3	3	3	3
-	-	-	-	-	-	-	-	-
-	-	-	-	-	-	-	-	-
-	-	-	-	-	-	-	-	-
320/180	300/180	300/180	300	280	300/180	300	300	280
3/1,5	3/1,5	3/1,5	2,3	2,3	3/1,5	2,3	2,3	2,3
3,6/1,8 175,4	3,6/1,8 180,8	3,6/1,8 180,8	3 180,8	3 180,8	3,6/1,8 180,8	3 180,8	3 180,8	3 180,8
-	-	-	-	-	-	-	-	-
-	-	-	-	-	-	-	-	-
-	-	-	-	-	-	-	-	-
-	-	-	-	-	-	-	-	-
-	-	-	-	-	-	-	-	-
-	-	-	-	-	-	-	-	-
-	-	-	-	-	-	-	-	-
210 2,3	210 2,3	210 2,3	220 2,3	220 2,3	210 2,3	220 2,3	220 2,3	210 2,3
2,5	2,5	2,5	2,5	2,5	2,5	2,5	2,5	2,3
191,5	184,1	184,1	184,1	184,1	184,1	184,1	184,1	184,1
180	180	180	160	160	180	160	160	160
1,2	1,2	1,2	1,2	1,2	1,2	1,2	1,2	1,2
1,5 194,8	1,5 181,7	1,5 181,7	1,5 181,7	1,5 181,7	1,5 181,7	1,5 181,7	1,5 181,7	1,5 181,7
187,2	182,2	182,2	182,2	182,2	182,2	182,2	182,2	182,2
630	590	590	590	590	590	590	590	590
520	520	520	520	520	520	520	520	520
60	60	58	58	58	60	58	58	58
565	565	565	565	565	565	565	565	565
495 5	495 5	495 5	495 5	495	495 5	495 5	495	495
Quick-Fix System	Quick-Fix System	Quick-Fix System	Quick-fix System	Quick-fix System	Quick-Fix System	Quick-fix System	Quick-fix System	Quick-fix System
Black	Black	White	Black	White	Black	Black	Black	Black
Front bevel	Front bevel	Front bevel	Front bevel	Front bevel	Front bevel	Front bevel	Front bevel	Front bevel
Independent Slider for each area	Independent Slider for each area	Independent Slider for each area	Multi Slider Touch	Multi Slider Touch	Independent Slider for each area	Multi Slider Touch	Mono Slider Touch	Multi Touch
Individual per	Individual per	Individual per	Individual per	Individual per	Individual per	Individual per	Centralized	Individual per
zone 9 + Booster	zone 9 + Booster	zone 9 + Booster	zone 9 + Booster	zone 9 + Booster	zone 9 + Booster	zone 9 + Booster	9 + Booster	zone 9 + Booster
AUTO 2	AUTO 2	AUTO 2	-	-	AUTO 2	-	AUTO 2	-
-	-	-	-	-	-	-	-	-
•	•	•	•	•	•	•	•	-
-	-	-	-	-	-	-	-	-
-	-	-	-	-	-	-	-	-
-	-	-	-	-	-	-	-	-
-	-	-	-	-	-	-	-	-
-	-	-	-	-	-	-	-	-
-	-	-	-	-	-	-	-	-
•	•	•	•	•	•	•	•	•
•	•	•	•	•	•	•	•	•
•	•	•	-	•	•	-	•	•
•	•	•	•	•	•	•	•	•
•	•	•	•	•	•	•	•	•
•	•	•	•	•	•	•	•	•
•	•	•	•	•	•	•	•	•
220.240	220.240	220.040	220.040	220.040	220.040	220.040	220.040	000.040
220-240 50-60	220-240 50-60	220-240 50-60	220-240 50-60	220-240 50-60	220-240 50-60	220-240 50-60	220-240 50-60	220-240 50-60
		-	-					
- 7,1	- 7,1	7,1	7,1	- 7,1	- 7,1	- 7,1	- 7,1	- 7,1

Code EAN	922272085 8422248355865	922272047 8422248109390	922272041 8422248108553	922272092 8422248373227	922272049 8422248109550	922272050 8422248109567	922272064 8422248111256
Model	EIT-6328 R	EIS-3220 B	EVT-6422 R	EVT-6330 B	EVT-6328 B	EVT-6328 R	EVT-3220 B
Туре	Induction	Induction	Radiant	Radiant	Radiant	Radiant	Radiant
Product fiche		-					-
Cooking zones	3	2	4	3	3	3	2
Right front zone: Diameter (mm)	-	180	185	180/120	185	185	-
Right front zone: Power (kW)	-	1,2	1,8	1,8/1	1,8	1,8	-
Right front zone: Booster (kW) Right front zone: Consumption (Wh/kg)	-	1,5 183,5	- 195,4	- 147,1	- 147,1	- 190,8	-
Right rear zone: Diameter (mm)	280	200	195,4	147,1	147,1	150	-
Right rear zone: Power (kW)	2,3	200	1,2	1,2	1,2	1,2	-
Right rear zone: Booster (kW)	3	2,3	-	-	-	-	-
Right rear zone: Consumption (Wh/kg)	180,8	180,9	205,3	147	147	185,4	_
Central front zone: Diameter (mm)	-	-	-	-	-	-	159
Central front zone: Power (kW)	-	-	-	-	-	-	1,2
Central front zone: Booster (kW)	-	-	-	-	-	-	-
Central front zone: Consumption (Wh/kg)	-	-	-	-	-	-	190,5
Central rear zone: Diameter (mm)	-	-	-	-	-	-	190/120
Central rear zone: Power (kW)	-	-	-	-	-	-	2,0/1,0
Central rear zone: Booster (kW)	-	-	-	-	-	-	-
Central rear zone: Consumption (Wh/kg)	-	-	-	-	-	-	181,3
Front left zone: Diameter (mm)	220	-	150	-	-	-	-
Front left zone: Power (kW)	2,3	-	1,2	-	-	-	-
Front left zone: Booster (kW)	2,6	-	-	-	-	-	-
Front left zone: Consumption (Wh/kg)	184,1	-	185,4	-	-	-	
Left rear zone: Diameter (mm)	160	-	215	300/190	280/220/155	280/220	-
Left rear zone: Power (kW)	1,2	-	2,3	3/2	2,7/1,95/1,05	2,7/1,5	-
Left rear zone: Booster (kW)	1,5	-	-		-	-	-
Left rear zone: Consumption (Wh/kg)	181,7	-	189,9	193,5	140,1	193,5	-
Energy consumption of the hob (Wh/kg)	182,2	182,2	194	189,9	144,7	189,9	185,9
Dimensions							
Product width (mm)	590	290	590	590	590	590	290
Product depth (mm)	520	520	520	520	520	520	520
Product height (mm)	58	70	52	58	47	58	47
Built-in width (mm)	565	265	560	560	560	560	265
Built-in depth (mm)	495	495	490	490	490	490	495
Ventilation slot (mm)	-	5	-	-	-	-	-
Fixing system	Quick-fix System	Quick-Fix System	Quick-Fix System	Quick-Fix System	Quick-Fix System	Quick-Fix System	Quick-Fix System
Finishing							
Colour	Black	Black	Black	Black	Black	Black	Black
Aesthetic	Rounded	Front bevel	Rounded	Rounded	Front bevel	Rounded	Front bevel
Control							
	- ·	Mono Slider	- I	T 1	- 1	- ·	. .
Control type	Touch	Touch	Touch	Touch	Touch	Touch	Touch
Power selection (+/-)	Centralized	Centralized	Centralized	Centralized	Centralized	Centralized	Centralized
Power levels	9 + Booster	9 + Booster	9	9	9	9	9
Connectivity	-	-	-	-	-	-	-
Cooking functions by temperature							
	-	-	-	-	-	-	-
Cooking functions	•	-	-	-	-	-	-
	- • -	-			-	-	
Cooking functions	- • -			- - - -			
Cooking functions Cooking zone division by power	- - - -	- - - -	- - - -	- - - -	- - - -	- - - -	
Cooking functions Cooking zone division by power Pot displacement recognition		- - - - - -		- - - - - -	- - - - -	- - - - -	
Cooking functions Cooking zone division by power Pot displacement recognition Pasta/rice timer function Automatic start function Pan speed function	- - - - -				- - - - - -		
Cooking functions Cooking zone division by power Pot displacement recognition Pasta/rice timer function Automatic start function Pan speed function Demo mode	- - - - - -	- - - - - - - -	- - - - - - - -	- - - - - - - - -	- - - - - - - - -	- - - - - - - - -	- - - - - - - - -
Cooking functions Cooking zone division by power Pot displacement recognition Pasta/rice timer function Automatic start function Pan speed function Demo mode AUTO cooking function	- - - - - - - - -	- - - - - - - - - -	- - - - - - - - -	- - - - - - - - -	- - - - - - - - -	- - - - - - - - -	
Cooking functions Cooking zone division by power Pot displacement recognition Pasta/rice timer function Automatic start function Pan speed function Demo mode AUTO cooking function Memory function	- - - - - - - - - - - -	- - - - - - - - - - -	- - - - - - - - - - - -	- - - - - - - - - - - - -	- - - - - - - - - - - -	- - - - - - - - - -	- - - - - - - - - - - - - - - - -
Cooking functions Cooking zone division by power Pot displacement recognition Pasta/rice timer function Automatic start function Pan speed function Demo mode AUTO cooking function Memory function Timer	- - - - - - - - - - - - - - - -	- - - - - - - - - - -	- - - - - - - - - - - - -	- - - - - - - - - - - -	- - - - - - - - - - -	- - - - - - - - - - - - - -	- - - - - - - - - - -
Cooking functions Cooking zone division by power Pot displacement recognition Pasta/rice timer function Automatic start function Pan speed function Demo mode AUTO cooking function Memory function Timer Countdown alarm	- - - - - - - - - - - - - - - - - - -	- - - - - - - - - - - - - - - - - - -	- - - - - - - - - - - - - -	•	- - - - - - - - - - - - - - -	- - - - - - - - - - - - - - - - - - -	- - - - - - - - - - - - -
Cooking functions Cooking zone division by power Pot displacement recognition Pasta/rice timer function Automatic start function Pan speed function Demo mode AUTO cooking function Memory function Timer Countdown alarm Pause function	- - - - - - - - - - - - - - - - - - -	- - - - - - - - - - - - - - - - - - -			- - - - - - - - - - - - -	- - - - - - - - - - - - -	- - - - - - - - - - - - - -
Cooking functions Cooking zone division by power Pot displacement recognition Pasta/rice timer function Automatic start function Pan speed function Demo mode AUTO cooking function Memory function Timer Countdown alarm Pause function Power management	- - - - - - - - - - - - - - - - - - -			•			
Cooking functions Cooking zone division by power Pot displacement recognition Pasta/rice timer function Automatic start function Pan speed function Demo mode AUTO cooking function Memory function Timer Countdown alarm Pause function Power management Security	•	• - -	• - -	• - -	- - -	-	- - - - - - - - - - - - - - - - - - -
Cooking functions Cooking zone division by power Pot displacement recognition Pasta/rice timer function Automatic start function Pan speed function Demo mode AUTO cooking function Memory function Timer Countdown alarm Pause function Power management Security Safety lock	•	• - -	• - -	• - - -	• • • •	- - -	- - - - - - - - - - - - - - - -
Cooking functions Cooking zone division by power Pot displacement recognition Pasta/rice timer function Automatic start function Pan speed function Demo mode AUTO cooking function Memory function Timer Countdown alarm Pause function Power management Security Safety lock Residual heat indicator	•	• - -	• - -	• - -	- - -	-	- - - - - - - - - - - - - - - - - - -
Cooking functions Cooking zone division by power Pot displacement recognition Pasta/rice timer function Automatic start function Pan speed function Demo mode AUTO cooking function Memory function Timer Countdown alarm Pause function Power management Secuty Safety lock Residual heat indicator Automatic pan detection	•	• - - - -	• - - - -	• - - - - -	•	- - -	
Cooking functions Cooking zone division by power Pot displacement recognition Pasta/rice timer function Automatic start function Pan speed function Demo mode AUTO cooking function Memory function Timer Countdown alarm Pause function Power management Safety lock Residual heat indicator Automatic pan detection Automatic safety switch-off	•	• • • • •	• 	• 	- - - - - -	- - - - - -	
Cooking functions Cooking zone division by power Pot displacement recognition Pasta/rice timer function Automatic start function Pan speed function Demo mode AUTO cooking function Memory function Timer Countdown alarm Pause function Power management Security Safety lock Residual heat indicator Automatic pan detection Automatic safety switch-off Protection against liquid spillage	•	• - - - -	• - - - -	• - - - - -	•	- - -	
Cooking functions Cooking zone division by power Pot displacement recognition Pasta/rice timer function Automatic start function Pan speed function Demo mode AUTO cooking function Memory function Timer Countdown alarm Pause function Power management Security Safety lock Residual heat indicator Automatic pan detection Automatic safety switch-off Protection against liquid spillage Electrical connection	•		•		- - - - - - - - - - - - - -	- - - - - - - - - - -	_
Cooking functions Cooking zone division by power Pot displacement recognition Pasta/rice timer function Automatic start function Pan speed function Demo mode AUTO cooking function Memory function Timer Countdown alarm Pause function Power management Security Safety lock Residual heat indicator Automatic pan detection Automatic safety switch-off Protection against liquid spillage Electrical connection Nominal voltage (V)	220-240	• - • • • • • • • • • • • • • • • • • •	• - - - - - 220-240	• - - - - - 220-240	- - - - 220-240	- - - - 220-240	220-240
Cooking functions Cooking zone division by power Pot displacement recognition Pasta/rice timer function Automatic start function Pan speed function Demo mode AUTO cooking function Memory function Timer Countdown alarm Pause function Power management Security Safety lock Residual heat indicator Automatic pan detection Automatic safety switch-off Protection against liquid spillage Electrical connection	•		•		- - - - - - - - - - - - - -	- - - - - - - - - - -	_

Code	922272067	922272068	922272069	922272070	922272071	922272072	922272073
EAN	8422248198318	8422248198325	8422248198332	8422248198349	8422248198363	8422248198370	8422248198387
Model	EGG-9051 TI TR CI N	EGG-7551 TI TR CI N	EGG-6041 TI TR CI N	EGG-6041 TI TR CI B	EGX-6041 TI TR CI N	EGX-6041 TI TR CI B	EGX-6041 TI N
Type (Glass /St.Steel /Enamelled)	Glass	Glass	Glass	Glass	S. Steel	S. Steel	S. Steel
Product fiche							
Suitable for City Gas	•	•	•	-	•	-	•
Suitable for LPG	-	-	-	•	-	•	-
Number of burners	5	5	4	4	4	4	4
Triple ring power [kW]	4	4	4	4	3,3	3,3	-
Fast power [kW]	3	3	3	3	3	3	3
Semi-fast power [kW]	1,75	1,75	1,75	1,75	1,75	1,75	1,75
Semi-fast power [kW]	1,75	1,75	-	-	-	-	1,75
Auxilliar power [kW]	1	1	1	1	1	1	1
Triple ring consumption (I/h)	381 l/h	381 l/h	381 l/h	291 g/h	333 l/h	255 g/h	-
Fast consumption (I/h)	238 l/h	238 l/h	238 l/h	182 g/h	238 l/h	182 g/h	238 l/h
Semi-fast 1 consumption (I/h)	166 l/h	166 l/h	166 l/h	127 g/h	166 l/h	127 g/h	166 l/h
Semi-fast 2 consumption (I/h)	166 l/h	166 l/h	-	-	-	-	166 l/h
Auxilliar consumption (I/h)	95 l/h	95 l/h	95 l/h	73 g/h	95 l/h	73 g/h	95 l/h
Dimensions						, in the second s	
Appliance width [mm]	870	690	580	580	580	580	580
Appliance depth [mm]	520	520	520	520	510	510	510
Appliance height [mm]	51,5	51,5	51,5	51,5	48	48	48
Built-in width [mm]	840	560	560	560	560	560	560
Built-in depth [mm]	490	490	490	490	490	490	490
Anchor system	Fixation brackets	Fixation brackets					
Characteristics							
Plug-in autoignition	•	•	•	•	•	•	•
Enamelled Grills/Burners	-	-	-	-	-	-	•
Cast Iron Grills/Burners	•	•	•	•	•	•	-
Security							
Safety valve	•	•	•	•	•	•	•
Electrical Connection							
Nominal voltage (V)	220-240	220-240	220-240	220-240	220-240	220-240	220-240
Mains frequency (Hz)	50-60	50-60	50-60	50-60	50-60	50-60	50-60
Product power (kW)	11,5	11,5	9,75	9,75	9,05	9,05	7,5
Accesories							
"LPG butane/natural kit conver-	_	_	_	_	_		_
sor (included)"	•	•	•	•	•	•	•

Code	922272074	922272075	922272076	922272077	922272078	922272079	922272080
EAN	8422248198400	8422248198417	8422248198424	8422248198431	8422248198448	8422248198455	8422248198462
Model	EGX-6041 TI B	EGG-6031 TI TR CI N	EGG-6031 TI TR CI B	EGX-6031 TI TR CI N	EGX-6031 TI TR CI B	EGG-3021 TI N	EGX-3022 TI N
Type (Glass /St.Steel /Enamelled) Product fiche	S. Steel	Glass	Glass	S. Steel	S. Steel	Glass	S. Steel
Suitable for City Gas	-	•	-	•	-	•	•
Suitable for LPG	•	-	•	-	•	-	-
Number of burners	4	3	3	3	3	2	2
Triple ring power [kW]	-	4	4	4	4	-	-
Fast power [kW]	3	3	3	3	3	3	3
Semi-fast power [kW]	1,75	-	-	-	-	-	-
Semi-fast power [kW]	1,75	-	-	-	-	-	-
Auxilliar power [kW]	1	1	1	1	1	1	1
Triple ring consumption (I/h)	-	381 l/h	291 g/h	381 l/h	291 g/h	-	-
Fast consumption (I/h)	182 g/h	238 l/h	182 g/h	238 l/h	182 g/h	238 l/h	286 l/h
Semi-fast 1 consumption (I/h)	127 g/h	-	-	-	-	-	-
Semi-fast 2 consumption (I/h)	127 g/h	-	-	-	-	-	-
Auxilliar consumption (I/h)	73 g/h	95 l/h	73 g/h	95 l/h	73 g/h	95 l/h	95 l/h
Dimensions							
Appliance width [mm]	580	580	580	580	580	290	300
Appliance depth [mm]	510	520	520	510	510	520	520
Appliance height [mm]	48	51,5	51,5	48	48	51,5	45
Built-in width [mm]	560	560	560	560	560	276	280
Built-in depth [mm]	490	490	490	490	490	490	480
Anchor system	Fixation brackets	Fixation brackets	Fixation brackets	Fixation brackets	Fixation brackets	Fixation brackets	Fixation brackets
Characteristics							
Plug-in autoignition	•	•	•	•	•	•	•
Enamelled Grills/Burners	•	-	-	-	-	-	•
Cast Iron Grills/Burners	-	•	•	•	•	•	-
Security							
Safety valve	•	•	•	•	•	•	•
Electrical Connection							
Nominal voltage (V)	220-240	220-240	220-240	220-240	220-240	220-240	220-240
Mains frequency (Hz)	50-60	50-60	50-60	50-60	50-60	50-60	50-60
Product power (kW)	7,5	8	8	8	8	4	4
Accesories							
LPG butane/natural kit conversor	•	•	•	•	•	•	•
(included)	-	-	-	-	-	-	-

HOBS

MULTIFUNCTION PYROL	ITIC	MULTIFUNCTION PLUS					
EOE-8411 P X	P.52	EOE-7050 FBK	P.53	EOE-7050 FWH	P.53	EOE-7040 BK	P.54
entropy of the second sec						in the second seco	
				MULTIFUNCTION			
EOE-7040 WH	P.54	EOE-7040 X	P.55	EOE-6040 X	P.56	EOE-6020 X	P.56
* * *	14	ECE-7040 X	1.33	EGE-8040 X	1.30		
STATIC EOE-5020 X	P.57	EOE-5010 X	P.58	EOE-5010 WH	P.58	MULTIFUNCTION PLU EOE-4530 X	JS 45cm P.59
						(a) Esta (b) Esta (b)	
		MULTIFUNCTION 45cm	ı				
EOE-4530 BK	P.59	EOE-4520 X	P.60				
NEW		· · · · · · · · · · · · · · · · · · ·					
					-		a lo

edesa





OVENS AND MICROWAVES

25L BUILT IN MICROW	/AVE					23L BUILT IN MICROV	VAVE
EMW-2530-IG BK	P.61	EMW-2530-IG WH	P.61	EMW-2510-IG X	P.62	EMW-2320-IG X	P.62
						Bore 	
edesa				eória		edres .	
	/AVE						
20L BUILT IN MICROW MW-2021-IG BK	/AVE P.64	EMW-2020-IG WH	P.64	EMW-2020-IG X	P.65	EMW-2020-I X	P.65
		EMW-2020-IG WH	P.64	EMW-2020-IG X	P.65	EMW-2020-I X	P.65
		EMW-2020-IG WH	P.64	EMW-2020-IG X	P.65	EMW-2020-I X	P.65
			P.64	EMW-2020-IG X	P.65	EMW-2020-I X	P.65
			P.64	EMW-2020-IG X	P.65	EMW-2020-I X	P.65
			P.64	EMW-2020-IG X	P.65	EMW-2020-I X	P.65



OVENS ACCESORIES

BAKING AND PIZZA STONE



07090048 390x327mm EAN-13: 8422248087018 EOE-5020 X, EOE-4530 X

Stone accessory to traditionally bake bread and pizza.

TELESCOPIC GUIDE

07090025 EAN-13: 8422248071000	EOE-8411 P X
PSCP - Clipable Pull System Plus 100% extraction	٦.
07090068 EAN-13: 8422248365062	EOE 7050 FBK EOE 7050 FWH,
	EOE-7040 BK, EOE-7040 WH, EOE-6040 X, EOE-6020 X
PSC - Clipable Pull System 50% extraction.	
07090044 EAN-13: 8422248080071	EOE-4530 X
PSCP - Clipable Pull System Plus 100% extraction	٦.



Telescopic guides: Easy removal of the trays

The comfort in the kitchen is a key factor when choosing our appliances. Therefore, our ovens have telescopic guides that allow the trays to be removed from the oven, facilitating cooking and guaranteeing a higher safety level when handling food.

Accessories that make the difference

The "traditional baking stone for pizza and bread" allows traditional stone baking. Thanks to this new accessory you will get great results in your recipes for pizzas and bread..

edesa

Compact ovens of 45 cm

This is the solution for users who have a limited space. These ovens are designed for cavities 45 cm high with enough space and capacity to cook recipes for the whole family.

Maximum internal capacity: 80 L

For cuisine lovers who require of an extra capacity without sacrificing space in the kitchen, here we launch large capacity ovens.

The internal cavity is optimized to allow the cooking of large pieces of meat or fish, or even to allow simultaneous preparations up to 6 different levels.



edesa

The best self-cleaning in the market with Edesa pyrolisis

If you are looking for self-cleaning system, then you will find it in our Edesa pyrolytic range.

The fundamental advance of the pyrolysis of these models is the design of its interior cavity and its door, which allows to achieve a total inner isolation and all corners remain completely clean.

In addition, this design that takes full advantage of the generated heat is more efficient to ensure the minimum consumption.

To adapt to the needs of each user, these ovens allow cleaning by pyrolysis through 2 different functions, depending on the time and degree of soiling.

Easy-clean, the most comfortable cleaning

If you are searching for an alternative to the pyrolysis, then the Easy-clean program of our multifunction plus and multifunction ovens is your best option.

The interior of the oven has a very low porosity enamel which prevents grease from getting stuck on the walls while cooking.

In addition, the Edesa ovens offer the Easy-clean system either manually or automatically. Using steam it facilates the cleaning and helps to remove dirt very comfortably and easily, depositing it in the bottom of the oven.

All you need to do is spray water inside the oven, select the program and in just a few minutes you will get the oven clean.



Energy efficiency A

The environmental commitment and energy saving are our responsibility. That is why our new A class ovens consume up to 20% less than the previous generation.

That means an important saving in your electricity bill as well as a lower environmental impact.



Control panels for all likings

From the simple mechanical controls to the most exclusive LCD screens, Edesa ovens allow a quick and intuitive programming.

Thanks to the push pull buttons, you can access to all programs or select the temperature with a simple touch. Furthermore, as they are built into the panel, they are much easier to clean..

Electronic precision

In Edesa we innovate to guarantee reliability and precision.

The electronic control of Edesa precisely keeps the selected temperature. In this way, food is always being cooked at its ideal temperature.

This accuracy also allows to cook delicate dishes at low temperature, maintaining its nutritional properties and its flavor to the maximum. Because health also matters to us



Cold door with four glasses and tangential ventilation

Safety in the kitchen is essential for us. Therefore, in our range we have cold door ovens with up to four glasses.

Our ovens also have cooling tangential ventilation which attracts cold air and mixes it with hot air to ensure low temperatures both on the surface and on the nearby furniture.

The perfect insulation of the oven door guarantees a full safety and contributes to optimize to the maximum the cooking quality, the pyrolytic cleaning and the energy consumption, since it minimizes heat losses.

The largest in its category

The 315 mm diameter rotating plate in the 25L microwaves offer the best conditions to easily introduce dishes and guarantee the uniform heating of the food.



Functionality

Edesa microwaves offer different cooking possibilities; from sophisticated preparations using micro and grill to the simple heating of a soup using the micro function.

And if you are looking for perfection in your dishes, microwaves can be set according to temperature and weight of the food, thus getting succulent meals.

<u>お</u>



Thanks to the Quick Start function, you can operate the microwave with a simple touch.

Programmed recipes will help you to get the most out of your microwave.



Comfort

Speed

The "Memory" function allows to record the usual cooking in order not to have to reprogram it in future cooking.

edesə

Multiply your cooking possibilities with the "Pull System"

The Pull System can be placed in any height of the oven. It also provides a guided access to the tray more comfortable and safe when dressing the dishes while cooking.

In addition, this multipurpose system of Edesa offers you more cooking options to improve your dishes:

- Traditional cooking; using the tray or grid.

- Roasts, placing the system on the tray that works as a juice collector.

Our ovens include different types of guides that allow an easy and safe access to the interior cavity of the oven:

Clipable Pull System (PSC)

This evolution of the Clip-on Pull System allows to fasten telescopic guides to any height of the oven walls, facilitating the horizontal slide of the tray up to 50 %.

Clipable Pull System Plus (PSCP)

The PSCP allows to remove telescopic guides to 100 % and fasten them to any height. In other words, it allows the full access to the oven tray avoiding any interference with the heating zones.







Cooking column, for the most exclusive kitchens

If you want your kitchen to stand out, choose an Edesa. Glass oven and microwave with a decorative stainless steel frame, which gives that touch to your kitchen to make it shine. And if you prefer smooth, easy-to-clean glass surfaces, now they are also available.















70 L MULTIFUNCTION PYROLITIC

EOE-8411 P X Stainless steel Cod.: 921270253 - EAN: 8422248100304









PUSH-PULL KNOBS



45mm



-70 liters multifunction plus pyrolitic independent oven -Black glass door with stainless steel control panel

-Start-stop programmer

-8 cooking programs and 3 special programs multifunction plus oven

-Pyrolitic enamel

-2 programs to pyrolitic cleaning system

-Push pull knobs

-Cold door: 4 glasses door and tangential ventilation -Led technology display

- -Telescopic guides 50% removables, PSC
- -1 enamelled tray of 45 mm

-Simple grid





edesa

edesa





80 L MULTIFUNCTION PLUS EOE-7050 FBK Black Cod.: 921270258 - EAN: 8422248110716 25mm Δ LED ÷ ÷ DIGITAL DISPLAY PUSH-PULL KNOBS DEEP TRAY PAN DEEP TRAY PAN ENERGY EFFICIENCY PULL SYSTEM CLIPABLE



-80 liters Easy-clean multifunction plus independent oven

- -Black/White glass door and control panel
- -Start-stop programmer
- -7 cooking programs multifunction plus oven
- -ETC Easy-To-Clean enamel
- -Easy-clean cleaning system
- -Push pull knobs
- -Cold door: 3 glasses door and tangential ventilation
- -Led technology display
- -Telescopic guides 50% removables, PSC
- -2 enamelled tray 50mm and 25 mm
- -Simple grid





edesə





80 L MULTIFUNCTION PLUS

EOE-7040 WH	White
Cod.: 921270261 - EA	N: 8422248111263



80 L MULTIFUNCTION PLUS



-80 liters Easy-clean multifunction plus independent oven

- -Black/White glass door and control panel
- -Start-stop programmer
- -7 cooking programs multifunction plus oven
- -ETC Easy-To-Clean enamel
- -Easy-clean cleaning system
- -Push pull knobs
- -2 glasses door and tangential ventilation
- -Led technology display
- -Telescopic guides 50% removables, PSC
- -2 enamelled tray 50mm and 25 mm
- -Simple grid







80 L MULTIFUNCTION PLUS

EOE-7	7040 X		Stain	less steel	
Cod.:	92127026	2 - EAN:	84222481	10754	
Α	LED		50mm	25mm	Ŀ
ENERGY EFFICIENCY	DIGITAL DISPLAY	PUSH-PULL KNOBS	DEEP TRAY PAN	DEEP TRAY PAN	PULL SYSTEN CLIPABLE

-80 liters Easy-clean multifunction plus independent oven

- -Black glass door with stainless steel control panel
- -Start-stop programmer
- -7 cooking programs multifunction plus oven
- -ETC Easy-To-Clean enamel
- -Easy-clean cleaning system
- -Push pull knobs
- -2 glasses door and tangential ventilation
- -Led technology display
- -Telescopic guides 50% removables, PSC
- -2 enamelled tray 50mm and 25 mm
- -Simple grid







edesə



80 L MULTIFUNCTION				
EOE-6040 X	Stainless steel			
Cod.: 921270264 - EAN: 8422248111287				



-80 liters Easy-clean multifunction independent oven -Black glass door with stainless steel control panel -Start-stop programmer

- -7 cooking programs multifunction oven
- -ETC Easy-To-Clean enamel
- -Manual Easy-clean cleaning system
- -2 glasses door and tangential ventilation
- -Telescopic guides 50% removables, PSC
- -2 enamelled tray 50mm and 25 mm
- -Simple grid



80 L MULTIFUNCTION

EOE-6	020 X		Stainless stee	el	
Cod.:	Cod.: 921270255 - EAN: 8422248110402				
Δ	50mm	25mm			



-80 liters Easy-clean multifunction independent oven -Black glass door with stainless steel control panel

- -Timing programming and stop
- -7 cooking programs multifunction oven
- -ETC Easy-To-Clean enamel
- -Manual Easy-clean cleaning system
- -2 glasses door and tangential ventilation
- -Telescopic guides 50% removables, PSC
- -2 enamelled tray 50mm and 25 mm
- -Simple grid







66 L STATIC

EOE-5020 X

Stainless steel

Cod.: 921270256 - EAN: 8422248110419



-66 liters static independent oven

- -Black glass door with stainless steel control panel
- -Timing programming and stop
- -4 cooking programs static oven
- -ETC Easy-To-Clean enamel
- -Manual Easy-clean cleaning system
- -2 glasses door and tangential ventilation
- -Enamelled tray of 50 mm
- -Simple grid





edesa



Stainless steel



62 L STATIC		
EOE-5010 WH	White	
Cod.: 921270266 - EAN	: 8422248190497	



62 L STATIC EOE-5010 X



50mm

÷

-62 liters static independent oven -Black/White glass door with stainless steel control panel -4 cooking programs static oven -ETC Easy-To-Clean enamel

Cod.: 921270260 - EAN: 8422248111133

- -Manual Easy-clean cleaning system
- -2 glasses door and tangential ventilation
- -Enamelled tray of 25 mm





edesa



45 CM MULTIFUNCTION PLUS Stainless steel EOE-4530 X Cod.: 921270252 - EAN: 8422248098168





45 CM MULTIFUNCTION PLUS

EOE-4530 BK			Black		NEW
Cod.: 921270268 - EAN: 8422248372916					
Α	4	LEO		Ľ_‡	50mm

PUSH-PULL KNOBS

DEEP TRAY PAN

PULL SYSTEM CLIPABLE

















-40 liters multifunction plus independent oven, height of 45 cm

-Black glass door with stainless steel control panel

DIGITAL DISPLAY

- -6 cooking programs and 2 special program multifunction plus oven
- -ETC Easy-To-Clean enamel
- -Manual Easy-clean cleaning system
- -Push pull knobs
- -Cold door: 3 glasses door and tangential ventilation
- -LED technology display
- -Telescopic guides 100% removables, PSCP
- -Enamelled tray of 50 mm
- -Simple grid



OVENS AND MICROWAVES

edesə



45 CM MULTIFUNCTION			
EOE-4520 X	Stainless steel		
Cod.: 921270217 - EAN: 8435436108891			



-40 liters multifunction plus independent oven, height of 45 cm

- -Black glass door with stainless steel control panel
- -6 cooking programs and 2 special program multifunction plus oven
- -ETC Easy-To-Clean enamel
- -Manual Easy-clean cleaning system
- -Push pull knobs
- -Cold door: 3 glasses door and tangential ventilation
- -LED technology display
- -Telescopic guides 100% removables, PSCP
- -Enamelled tray of 50 mm
- -Simple grid









25 L BULT IN MICROWAVE	
EMW-2530-IG BK	Black glass
Cod.: 929270361 - EAN: 8	422248101882



- -25 litres, 900 W and with 1000 W grill built-in microwave without frame
- -Stainless steel cavity and touch door opening
- -Defrosting, heating and cooking by time and type of meal
- -5 levels of power cooking selection
- -1 level of power grill selection
- -5 Microwave levels, grill, 2 grill + micro and 8 programed functions
- -Quartz grill
- -95 min. time selector with display
- -Quick start selector
- -LED technology display. Touch buttoms and rotating selector
- -Safety lock for children and elderly
- -Revolving dish ø 315 mm and Grill rack
- -Maximum diameter for a dish 320 mm



25 L BULT IN MICROWAVE					
EMW-2530-IG WH	White glass				
Cod.: 929270362 - EAN:	8422248101899				



edesə





25 L BULT IN MICROWAVE WITH INTEGRATED FRAME

	EMW-2510-IG X Black/Stainless steel							
	Cod.: 929270360 - EAN: 8422248083911							
	25 L	LED	<u>_</u> 3	~~~	<u></u>	!!		
(INNER CAPACITY	DIGITAL DISPLAY	QUICK START	GRILL	PROGRAMMED FUNCTIONS	WITH PLUG		

-25 litres, 900 W and with 1000 W grill built-in microwave -Stainless steel cavity

- -Defrosting, heating and cooking by time and type of meal -5 levels of power cooking selection
- -1 level of power grill selection
- -5 Microwave levels, grill, 2 grill + micro and 8 programed
- functions
- -Quartz grill
- -95 min. time selector with display
- -Quick start selector
- -LED technology display. Touch. Rotating selector
- -Safety lock for children and elderly
- -Revolving dish ø 315 mm and Grill rack
- -Maximum diameter for a dish 320 mm
- -Microwave decorative stainless steel frame integrated



23 L BULT IN MICROWAVE WITH INTEGRATED FRAME

 EMW-2320-IG X
 Stainless steel

 Cod.: 929270347 - EAN: 8435436111921



- -23 litres, 800 W and with 1200 W grill built-in microwave -Stainless steel cavity
- -Defrosting, heating and cooking by time and type of meal
- -5 levels of power cooking selection
- -2 levels of power grill selection
- -5 Microwave levels, 2 grill, 2 grill + micro and 6 programed
- functions
- -Quartz grill
- -60 min. time selector with display
- -Memory function
- -Quick start selector
- -LED technology display. Touch. Rotating selector
- -Safety lock for children and elderly
- -Revolving dish ø 315 mm and Grill rack
- -Maximum diameter for a dish 320 mm
- -Microwave decorative stainless steel frame integrated







edesa





20 L BULT IN MICROWAVE WITH INTEGRATED FRAME

EMW-	2021-I	G BK	Black gla	SS	NEW
Cod.:	9292703	67 - EAN: 8	84222483	73104	
20 L	LED		~~~	÷	
INNER CAPACITY	DIGITAL DISPLAY	QUICK START	GRILL	WITH PLUG	

measurements in mm

- -20 litres, 700 W and with 800 W grill buit-in microwave without frame
- -Stainless steel cavity
- -Defrosting, heating and cooking by time and type of meal
- -5 levels of power cooking selection
- -2 levels of power grill selection

- -5 Microwave levels, 2 grill, 2 grill + micro
- -Quartz grill
- -60 min. time selector with display
- -Quick start selector
- -LED technology display. Touch buttoms and rotating selector
- -Safety lock for children and elderly
- -Revolving dish ø 245 mm and Grill rack
- -Maximum diameter for a dish 250 mm
- -Wall unit installation



20 L BULT IN MICROWAVE WITH INTEGRATED FRAME EMW-2020-IG WH White glass Cod.: 929270364 - EAN: 8422248101912



edesə





20 L BULT IN MICROWAVE WITH INTEGRATED FRAME

EMW-2020-IG X	Stainless steel
Cod.: 929270344 - EAN: 843	35436110771



-20 litres, 700 W and with 800 W grill built-in microwave

- -Stainless steel cavity
- -Defrosting, heating and cooking by time and type of meal
- -5 levels of power cooking selection
- -2 levels of power grill selection
- -5 Microwave levels, 2 grill, 2 grill + micro and 6 programed functions
- -Quartz grill
- -60 min. time selector with display
- -Memory function
- -Quick start selector
- -LED technology display. Touch. Rotating selector
- -Safety lock for children and elderly
- -Revolving dish ø 245 mm and Grill rack
- -Maximum diameter for a dish 250 mm
- -Microwave decorative stainless steel frame integrated
- -Wall unit installation



20 L BULT IN MICROWAVE WITH INTEGRATED FRAME

EMW-2020-I X Stainless steel						
Cod.:	Cod.: 929270346 - EAN: 8435436111914					
20 L	LEO	_ * 3	~~~	<u> </u>		





WITH PLUG



-20 litres and 700 W built-in microwave

- -Stainless steel cavity
- -Defrosting, heating and automatic cooking
- -5 levels of power selection
- -5 Microwave levels, slow cook, clear and 6 programed functions
- -60 min. time selector with display
- -Memory function
- -Quick start selector
- -LED technology display
- -Safety lock for children and elderly
- -Revolving dish ø 245 mm
- -Maximum diameter for a dish 250 mm
- -Microwave decorative stainless steel frame integrated
- -Wall unit installation



OVENS

edesə

Code	921270253	921270258	921270259	921270263	921270261	921270262	
EAN	8422248100304	8422248110716	8422248110723	8422248111270	8422248111263	8422248110754	
Nodel	EOE-8411 P X	EOE-7050 FBK	EOE-7050 FWH	EOE-7040 BK	EOE-7040 WH	EOE-7040 X	
ïpo (Elétrico/Gás) Product fiche	Electric	Electric	Electric	Electric	Electric	Electric	
Energy efficiency index (IEE conventional/multifunction)	94	94,4	94,4	94,4	94,4	94,4	
Energy efficiency Class	A	A	A	A	A	A	
Conventional mode energy consumption (according to EN 50304/2009) [KWh]	0,99	0,85	0,85	0,85	0,85	0,85	
Multifunction mode energy consumption (according to EN 50304/2009) [kWh] Cavity volume [I]	0,79 70	0,84 80	0,84 80	0,84 80	0,84 80	0,84 80	
Cavity volume (I) Dimensions	70	80	80	80	80	80	
Dimensions External dimensions							
Appliance width [mm]	595	595	595	595	595	595	
Appliance width [mm] Appliance height [mm]	595	595	595	595	595	595	
Appliance height [mm]	555	543	543	543	543	543	
Appliance aepin [mm] Cavity width [mm]	487	477	543 477	543 477	477	477	
Cavity wath [mm] Cavity height [mm]	350	394	394	394	394	394	
Cavity depth [mm]	420	425	425	425	425	425	
Characteristics	TLU	720	720	740	TLU	TLU	
	Black glass +	Black Glass	White alass	Plack Class	White alloss	Black glass +	
Finishing	Stainless Steel	BIOCK GIUSS	White glass	Black Glass	White glass	Stainless Steel	
Door lock option	•		-	-	-	-	
Tray levels	5	6	6	6	6	6	4
Fan Number of light	Tangential	Tangencial	Tangencial	Tangencial	Tangencial	Tangencial	
Number of lights	1	1	1	1	1	1	4
Controls Control type	Deep out knobs	Dep out knobs	Dep out knobs	Dep out knobs	Dep out knobs	Dep out knobs	
Control type	Pop out knobs	Pop out knobs	Pop out knobs	Pop out knobs	Pop out knobs	Pop out knobs	
Screen Technology Working pilot light	LED	LED	LED	LED	LED	LED	
Working pilot light	•	•	•	•	•	•	
Thermostat pilot light Min. temperature [°C]	• 50	• 40	• 40	• 40	• 40	• 40	
Min. temperature [°C] Cleaning	50	40	40	40	40	40	
Enamel	Pyrolitic	ETC Easy-To-	ETC Easy-To-	ETC Easy-To-	ETC Easy-To-	ETC Easy-To-	
		Clean enamel	Clean enamel	Clean enamel	Clean enamel	Clean enamel	
Type of cavity / lateral grill	Chromed	Chromed	Chromed	Chromed	Chromed	Chromed	
Inner glass Purolitic Cleaning	Removable	Removable	Removable	Removable	Removable	Removable	
Pyrolitic Cleaning Min. Pyrolisis duration (min)	16.20	- /	-		- /		
Min. Pyrolisis duration (min)	1h 30' 2b		-	-			
Max. Pyrolisis duration (min)	2h	-	-	-	-	-	
EasyClean Cleaning Programs	•	•	•	•	•	•	
Programs Functions	11	0	0	0	0	0	
Functions Fast preheat	11	8	8	8	8	8	
Fast preheat Inner light	•	/	-				
Security							
Number of door glasses	4	3	3	2	2	2	
Cooling fan	•	•	•	•	2 •	2 •	
Security Thermostat	•	•	•	•	•	•	
Security automatic desconnection	•	•	•	•	•	•	
Automatic door block	Pyrolisis						
Electrical connection	T yronoid						
Grill power [W]	2000	1000+2000	1000+2000	1000+2000	1000+2000	1000+2000	
Top heating element power [W]	950	900	900	900	900	900	
Underfloor element Power [W]	1100	1200	1200	1200	1200	1200	
Back element Power [W]	2000	2300	2300	2300	2300	2300	
Total Power [kW]	3200	2300	2300	2300	2300	2300	
	0200		220-240 / 50	220-240 / 50	220-240 / 50	220-240 / 50	
Nominal voltage [V] / Mains frequency [Hz]	220-240 / 50	220-240 / 50	///-/40/30		440 4		
	220-240 / 50				15	15	
Light power [W]	220-240 / 50 25	220-240 / 50 15	15	15	15	15	
Light power [W] Accessories		15	15	15	15		
Light power [W] Accessories Grill	25	15				15 1 1	
Light power [W] Accessories Grill Flat tray	25	15 1 1	15	15	1	1 1	
	25	15	15	15 1 1	1 1	1	

All the boxes marked with a ${\scriptstyle \bullet}$ are equivalent to a Yes

Accessories / \circ NOT INCLUDED • INCLUDED

(1) Delegated Regulation (EU) No.65 / 2014 of 2013 October 1 that complements Directive 2010/30 / EU of the European Parliament and of the Council in relation to the energy labeling of domestic ovens and hoods. (2) Class range from A +++ (more efficient) to B (less efficient). (3) Measurement obtained according to EN-60350-2 legal standard.

921270264 8422248111287 EOE-6040 X	921270255 8422248110402 EOE-6020 X	921270256 8422248110419 EOE-5020 X	921270260 84222481111133 EOE-5010 X	921270266 8422248190497 EOE-5010 WH	921270252 8422248098168 EOE-4530 X	921270268 8422248372916 EOE-4530 BK	921270217 8435436108891 EOE-4520 X
Electric	Electric	Electric	Electric	Electric	Electric	Electric	Electric
94,4	94,4	95,2	95,1	95,1	97,2	97,2	94
A	A	A	A	A	A	A	А
0,85	0,85	0,79	0,77	0,77	0,7	0,7	0,7
0,84	0,84	-	-	-	0,71	0,71	0,71
80	80	66	62	62	40	40	40
595	595	595	595	595	595	595	595
595	595	595	595	595	456	456	456
543	543	543	543	543	531	531	502
477	477	440	440	440	260	260	260
394	394	316	316	316	380	380	380
425	425	444	444	444	400	400	400
Black glass + Stain- less Steel	White glass	Stainless steel	Black Glass	Stainless steel			
- 6	- 6	- 4	- 4	- 4	- 4	- 4	3
Tangencial	Tangencial	Tangencial	Tangencial	Tangencial	Tangential	Tangential	Tangential
1	1	1	1	1	1	1	1
Fix knobs	Fix knobs	Fix knobs	Fix knobs	Fix knobs	Pop out knobs	Pop out knobs	Fix knobs
LED	-	-	-	-	LED	LED	-
•	•	•	•	•	•	•	•
•	•	•	•	•	•	•	•
40	40	40	40	40	50	50	50
ETC Easy-To-Clean enamel	ETC Easy-To-Clean enamel	ETC Easy-To-Clean enamel	ETC Easy-To-Clean enamel	ETC Easy-To-Clean enamel	ETC Easy-To-Clean enamel	ETC Easy-To-Clean enamel	ETC Easy-To-Clean enamel
Chromed	Chromed	Embossed	Embossed	Embossed	Chromed	Chromed	Embossed
Removable	Removable	Removable	Removable	Removable	-	-	-
-	-	-	-	-	-	-	-
-	-	-	-	-	-	-	-
-	-	-	-	-	-	-	-
Manual	Manual	Manual	Manual	Manual	•	•	•
-	-						
7	7	4	4	4	8	8	6
-	-	-	-	-	-	-	-
•	•	•	•	•	•	•	•
2	2	2	2	2	3	3	3
•	•	•	2	2 •	ی •	ی •	ى •
•	•	•	•	•	•	•	•
•	•	•	•	•	•	•	•
-	-	-	-	-	-	-	-
1000+2000	1000+2000	1000+2000	1000+2000	1000+2000	2380	2380	2200
900	900	900	900	900	900	900	900
-	-	1200	1200	1200	1300	1300	1300
2300	2300	-	-	-	2000	2000	-
2300	2300	2300	2300	2300	2,38	2,38	2,38
220-240 / 50	220-240 / 50	220-240 / 50	220-240 / 50	220-240 / 50	220-240 / 50-60	220-240 / 50-60	220-240 / 50-60
15	15	15	15	15	25	25	25
1	1	1	-	-	1	1	1
1	1	-	1	1	-	-	-
1	1	1	-	-	1	1	1
1 x PSC-50%	1 x PSC-50%	-	-	-	1 x PSCP-100%	1 x PSCP-100%	-
-	-	-	-	-	•	•	•

MICROWAVES

Code	929270361	929270362	929270360	929270347	
EAN	8422248101882	8422248101899	8422248083911	8435436111921	
Model	EMW-2530-IG BK	EMW-2530-IG WH	EMW-2510-IG X	EMW-2320-IG X	
ype (Built in / free standing)	Built in	Built in	Built in	Built in	
Npe (Built in / tree standing) Wall unit installation	Dollinit	DUILIT	DUITIT		
Wall unif installation Dimensions					
External dimensions: height [mm]	386	386	388	390	
External dimensions: height [mm] External dimensions: width [mm]	595	386 595	388 595	390 592	
External almensions: wiath [mm] External dimensions: depth [mm]	376	376	380	348	
External dimensions: depth [mm] Cavity height [mm]	376	376	380	348 205	
Cavity height [mm] Cavity widht [mm]	208	208 328	333	205	
Cavity widht [mm] Cavity depth [mm]	328	328 369	333 355	330 330	
Cavity depth [mm] Characteristics	307	307	300	330	
Finishing Door opening System	Lateral by touch	t stard by touch	t stard by touch	t stard by button	
Door opening System	Lateral by touch	Lateral by touch	Lateral by touch	Lateral by button	
Cavity capacity [L]	25 Staipless steel	25 Staipless steel	25 Staipless steel	23 Staipless steel	
Cavity construction type	Stainless steel	Stainless steel	Stainless steel	Stainless steel	
Inside light	•	•	•	•	
Opening door angle [degrees]	90	90	90	88	
Noise level db[A]	63	63	63	59	
Control					
Control type	Electronic	Electronic	Electronic	Electronic	
Display technology	Electronic display	Electronic display	Electronic display	Electronic display	
Electronic timer	•	•	•	•	
Manual timer	-	-	-	- 1	
Start/Stop button	•	•	•	•	
Timer [min]	95	95	95	60	
Power selector	•	•	•	•	
Function and temperature selector	Function selector	Function selector	Function selector	Function selector	
Working indicator	LED display	LED display	LED display	LED display	
Weight selector	•	•	•	•	
Functions					
Number of programmes	8	8	8	9	
N° of microwave programs	5	5	5	5	
N° of grill cooking programs	1	1	1	2	
N° of grill+mw cooking programs	2	2	2	2	
Auto cook	8/ Pizza; Meat; Vegetables; 8 Pasta; Potatoes; Fish; Drinks; F Popcorn	8/ Pizza; Meat; Vegetables;	8/ Pizza; Meat; Vegetables;	(/ Heating: Vegetables:	
Grill	•	•	•	•	
Grill Simultaneous grill + microwave		•	•	•	
		•	•	•	
Simultaneous grill + microwave	•	•	• • • •	• • • •	
Simultaneous grill + microwave Defrosting, heating and cooking by food type	•	•	• • • •	• • • • •	
Simultaneous grill + microwave Defrosting, heating and cooking by food type Memories	• • • •	• • -	• • • • • • • • • • • • • • • • • • • •	• • • • • • • •	
Simultaneous grill + microwave Defrosting, heating and cooking by food type Memories Quick start	• • • •	• • -	• • • • • • • • • • • • • • • • • • • •	• • • • •	
Simultaneous grill + microwave Defrosting, heating and cooking by food type Memories Quick start Cleaning system	• • • •	• • -	• • • • • •	• • • • • •	
Simultaneous grill + microwave Defrosting, heating and cooking by food type Memories Quick start Cleaning system Safety		• • • •	-	-	
Simultaneous grill + microwave Defrosting, heating and cooking by food type Memories Quick start Cleaning system Safety Safety thermostat		• • • •	-	-	
Simultaneous grill + microwave Defrosting, heating and cooking by food type Memories Quick start Cleaning system Safety Safety thermostat Safety automatic disconnection		• • • • • •	- • •	- •	
Simultaneous grill + microwave Defrosting, heating and cooking by food type Memories Quick start Cleaning system Safety Safety thermostat Safety automatic disconnection Child safety lock		• • - • • • •	- • •	- • •	
Simultaneous grill + microwave Defrosting, heating and cooking by food type Memories Quick start Cleaning system Safety Safety thermostat Safety automatic disconnection Child safety lock Door temperature	• • • • • • • • • • • • • • • • • • •	• • • • • • • • • • • • • •	- • • • 65	- • • 65	
Simultaneous grill + microwave Defrosting, heating and cooking by food type Memories Quick start Cleaning system Safety Safety thermostat Safety automatic disconnection Child safety lock Door temperature N° of glasses in the door Connection	• • • • • • • • • • • • • • • • • • •	• • • • • • • • • • • • • •	- • • • 65	- • • 65 1	
Simultaneous grill + microwave Defrosting, heating and cooking by food type Memories Quick start Cleaning system Safety Safety thermostat Safety automatic disconnection Child safety lock Door temperature N° of glasses in the door Connection Grill power [kW]	• • • • • • • • • • • • • • • • • • •	• • • • • • • • • • • • • • • • • • •	- • • 65 1	- • • 65 1	
Simultaneous grill + microwave Defrosting, heating and cooking by food type Memories Quick start Cleaning system Safety Safety thermostat Safety automatic disconnection Child safety lock Door temperature N° of glasses in the door Connection Grill power [kW] Microwave power [W]	• • • • • • • • • • • • • • • • • • •	• • • • • • • • • • • • • •	- • • 65 1 1 900	- • • 65 1 1,2 800	
Simultaneous grill + microwave Defrosting, heating and cooking by food type Memories Quick start Cleaning system Safety Safety thermostat Safety automatic disconnection Child safety lock Door temperature N° of glasses in the door Connection Grill power [kW] Microwave power [W] Total power [kW]	• • • • • • • • • • • • • • • • • • •	• • • • • • • • • • • • • •	- • • 65 1 1 900 1,25	- • • 65 1 1.2 800 1.28	
Simultaneous grill + microwave Defrosting, heating and cooking by food type Memories Quick start Cleaning system Safety Safety thermostat Safety automatic disconnection Child safety lock Door temperature N° of glasses in the door Connection Grill power [kW] Microwave power [W] Total power [kW] Voltage / Frecuency [V/Hz]	• • • • • • • • • • • • • • • • • • •	• • • • • • • • • • • • • •	- • • 65 1 1 900	- • • 65 1 1,2 800	
Simultaneous grill + microwave Defrosting, heating and cooking by food type Memories Quick start Cleaning system Safety Safety thermostat Safety automatic disconnection Child safety lock Door temperature N° of glasses in the door Connection Grill power [kW] Microwave power [W] Total power [kW] Voltage / Frecuency [V/Hz] Power cord length	• • • • • • • • • • • • • • • • • • •	• • • • • • • • • • • • • •	- • • 65 1 1 900 1,25 230 / 50	- • • 65 1 1.2 800 1,28 230-240 / 50	
Simultaneous grill + microwave Defrosting, heating and cooking by food type Memories Quick start Cleaning system Safety Safety Mermostat Safety automatic disconnection Child safety lock Door temperature N° of glasses in the door Connection Grill power [kW] Microwave power [W] Total power [kW] Voltage / Frecuency [V/Hz] Power cord length Plug type	• • • • • • • • • • • • • • • • • • •	• • • • • • • • • • • • • •	- • • 65 1 1 900 1,25	- • • 65 1 1.2 800 1.28	
Simultaneous grill + microwave Defrosting, heating and cooking by food type Memories Quick start Cleaning system Safety Safety thermostat Safety automatic disconnection Child safety lock Door temperature N° of glasses in the door Connection Grill power [kW] Microwave power [W] Total power [kW] Voltage / Frecuency [V/Hz] Power cord length Plug type Accesories	• • • • • • • • • • • • • • • • • • •	• • • • • • • • • • • • • •	- • • 65 1 1 900 1,25 230 / 50 Standard Schuko	- • • 65 1 1.2 800 1.28 230-240 / 50 Standard Schuko	
Simultaneous grill + microwave Defrosting, heating and cooking by food type Memories Quick start Cleaning system Safety Safety Mermostat Safety automatic disconnection Child safety lock Door temperature N° of glasses in the door Connection Grill power [kW] Microwave power [W] Microwave power [W] Total power [kW] Voltage / Frecuency [V/Hz] Power cord length Plug type Accesories Rotatory removable glass	• • • • • • • • • • • • • • • • • • •	• - • • • • • • • • • • • • •	- • • 65 1 1 900 1,25 230 / 50 Standard Schuko	- • • 65 1 1.2 800 1.28 230-240 / 50 Standard Schuko •	
Simultaneous grill + microwave Defrosting, heating and cooking by food type Memories Quick start Cleaning system Safety Safety Mermostat Safety automatic disconnection Child safety lock Door temperature N° of glasses in the door Connection Grill power [kW] Microwave power [W] Total power [kW] Voltage / Frecuency [V/Hz] Power cord length Plug type Accesories Rotatory removable glass	• • • • • • • • • • • • • • • • • • •	• • • • • • • • • • • • • •	- • • 65 1 1 900 1,25 230 / 50 Standard Schuko • 315	- • • 65 1 1,2 800 1,28 230-240 / 50 Standard Schuko • 315	
Simultaneous grill + microwave Defrosting, heating and cooking by food type Memories Quick start Cleaning system Safety Safety thermostat Safety automatic disconnection Child safety lock Door temperature N° of glasses in the door Connection Grill power [kW] Microwave power [W] Total power [kW] Voltage / Frecuency [V/Hz] Power cord length Plug type Accesories Rotatory removable glass	• • • • • • • • • • • • • • • • • • •	• - • • • • • • • • • • • • •	- • • 65 1 1 900 1,25 230 / 50 Standard Schuko	- • • 65 1 1.2 800 1.28 230-240 / 50 Standard Schuko •	

edesə

OVENS AND MICROWAVES

929270367	929270364	929270344	929270346
8422248373104	8422248101912	8435436110771	8435436111914
EMW-2021-IG BK	EMW-2020-IG WH	EMW-2020-IG X	EMW-2020-I X
Built in	Built in	Built in	Built in
•	•	•	•
390	386	390	390
595	594	595	595
293	297	293	293
180	205	180	180
315	305	315	315
295	280	295	295
Lateral by button	Lateral by button	Lateral by button	Lateral by button
20	20	20	20
Stainless steel	Stainless steel	Stainless steel	Stainless steel
•	•	•	•
88	90	90	90
68	68	59	59
Electronic	Electronic	Electronic	Electronic
Electronic display	Electronic display	Electronic display	Electronic display
•	•	•	•
-	-	-	-
•	•	•	•
60	95	60	60
•	•	•	•
Function selector	Function selector	Function selector	Function selector
LED display	LED display	LED display	LED display
•	•	•	•
9	8	9	8
9 5	8 5	9 5	8 5
5	5	5	5
5 2	5	5 2	5
5 2	5 1 2 8/ Pizza; Meat; Vegetables; Pasta; Potatoes; Fish; Drinks;	5 2 2 6/ Heating; Vegetables;	5 - - 6/ Heating; Vegetables;
5 2 2 -	5 1 2 8/ Pizza; Meat; Vegetables; Pasta; Potatoes; Fish; Drinks; Popcorn	5 2 2 6/ Heating; Vegetables;	5 - - 6/ Heating; Vegetables;
5 2 2 -	5 1 2 8/ Pizza; Meat; Vegetables; Pasta; Potatoes; Fish; Drinks; Popcorn •	5 2 2 6/ Heating; Vegetables;	5 - - 6/ Heating; Vegetables;
5 2 2 - •	5 1 2 8/ Pizza; Meat; Vegetables; Pasta; Potatoes; Fish; Drinks; Popcorn •	5 2 2 6/ Heating; Vegetables;	5 - - 6/ Heating; Vegetables;
5 2 2 - •	5 1 2 8/ Pizza; Meat; Vegetables; Pasta; Potatoes; Fish; Drinks; Popcorn •	5 2 2 6/ Heating; Vegetables;	5 - - 6/ Heating; Vegetables; Pasta; Fish; Chicken; Veal - - - - - - -
5 2 2 - - - -	5 1 2 8/ Pizza; Meat; Vegetables; Pasta; Potatoes; Fish; Drinks; Popcorn • • • •	5 2 2 6/ Heating; Vegetables; Pasta; Fish; Chicken; Veal • • •	5 - - 6/ Heating; Vegetables; Pasta; Fish; Chicken; Veal - - - • •
5 2 2 - - - - - - - -	5 1 2 8/ Pizza; Meat; Vegetables; Pasta; Potatoes; Fish; Drinks; Popcorn • • • •	5 2 2 6/ Heating; Vegetables; Pasta; Fish; Chicken; Veal • • •	5 - - 6/ Heating; Vegetables; Pasta; Fish; Chicken; Veal - - - - - - -
5 2 2 - - - - - - - -	5 1 2 8/ Pizza; Meat; Vegetables; Pasta; Potatoes; Fish; Drinks; Popcorn • • • •	5 2 2 6/ Heating; Vegetables; Pasta; Fish; Chicken; Veal • • •	5 - - 6/ Heating; Vegetables; Pasta; Fish; Chicken; Veal - - - - - - -
5 2 2 - - - - - - - - - - - -	5 1 2 8/ Pizza; Meat; Vegetables; Pasta; Potatoes; Fish; Drinks; Popcorn • • • • • • •	5 2 2 6/ Heating; Vegetables; Pasta; Fish; Chicken; Veal • • • • • • • • • • •	5 - - - 6/ Heating; Vegetables; Pasta; Fish; Chicken; Veal - - - - - - - Odours
5 2 2 - - - - - - - - -	5 1 2 8/ Pizza; Meat; Vegetables; Pasta; Potatoes; Fish; Drinks; Popcorn • • • • • • • • • • • • •	5 2 2 6/ Heating; Vegetables; Pasta; Fish; Chicken; Veal • • • • • • • • • • • • • • • • • • •	5 - - 6/ Heating; Vegetables; Pasta; Fish; Chicken; Veal - - - - - - - - - - - - - - - - - - -
5 2 2 - - - - - -	5 1 2 8/ Pizza; Meat; Vegetables; Pasta; Potatoes; Fish; Drinks; Popcorn • • • • • • • •	5 2 2 6/ Heating: Vegetables: Pasta: Fish: Chicken: Veal • • • • • • • •	5 - - 6/ Heating; Vegetables; Pasta; Fish; Chicken; Veal - - - - - 0 dours
5 2 2 - - - - - - - - -	5 1 2 8/ Pizza; Meat; Vegetables; Pasta; Potatoes; Fish; Drinks; Popcorn • • • • • • • • • • • • •	5 2 2 6/ Heating; Vegetables; Pasta; Fish; Chicken; Veal • • • • • • • • • • • • • • • • • • •	5 - - 6/ Heating; Vegetables; Pasta; Fish; Chicken; Veal - - - - - - - - - - - - - - - - - - -
5 2 2 - - - - - - - - - - - - - - - - -	5 1 2 8/ Pizza; Meat; Vegetables; Pasta; Potatoes; Fish; Drinks; Popcorn • • • • • • • • • • • • •	5 2 2 6/ Heating; Vegetables; Pasta; Fish; Chicken; Veal • • • • • • • • • • • • • • • • • • •	5 - - 6/ Heating; Vegetables; Pasta; Fish; Chicken; Veal - - - - - 0 dours 0 dours - 0 dours 40 1
5 2 2 - - - - - - - - - - - - - - - - -	5 1 2 8/ Pizza; Meat; Vegetables; Pasta; Potatoes; Fish; Drinks; Popcorn • • • • • • • • • • • • •	5 2 2 6/ Heating; Vegetables; Pasta; Fish; Chicken; Veal • • • • • • • • • • • • • • • • • • •	5 - - - - - - - - - - - - - - - - - - -
5 2 2 - - - - - - - - - - - - - - - - -	5 1 2 8/ Pizza; Meat; Vegetables; Pasta; Potatoes; Fish; Drinks; Popcorn • • • • • • • • • • • • •	5 2 2 6/ Heating; Vegetables; Pasta; Fish; Chicken; Veal • • • • • • • • • • • • • • • • • • •	5 - - - - - - - - - - - - - - - - - - -
5 2 2 - - - - - - - - - - - - - - - - -	5 1 2 8/ Pizza; Meat; Vegetables; Pasta; Potatoes; Fish; Drinks; Popcorn • • • • • • • • • • • • •	5 2 2 6/ Heating; Vegetables; Pasta; Fish; Chicken; Veal • • • • • • • • • • • • • • • • • • •	5 - - - - - - - - - - - - - - - - - - -
5 2 2 - - - - - - - - - - - - - - - - -	5 1 2 8/ Pizza; Meat; Vegetables; Pasta; Potatoes; Fish; Drinks; Popcorn • • • • • • • • • • • • •	5 2 2 6/ Heating; Vegetables; Pasta; Fish; Chicken; Veal • • • • • • • • • • • • • • • • • • •	5 - - - - - - - - - - - - - - - - - - -
5 2 2 2 - - - - - - - - - - - - - - - -	5 1 2 8/ Pizza; Meat; Vegetables; Pasta; Potatoes; Fish; Drinks; Popcorn • • • • • • • • • • • • •	5 2 2 6/ Heating; Vegetables; Pasta; Fish; Chicken; Veal	5 - - - - - - - - - - - - - - - - - - -
5 2 2 - - - - - - - - - - - - - - - - -	5 1 2 8/ Pizza; Meat; Vegetables; Pasta; Potatoes; Fish; Drinks; Popcorn • • • • • • • • • • • • •	5 2 2 6/ Heating; Vegetables; Pasta; Fish; Chicken; Veal • • • • • • • • • • • • • • • • • • •	5 - - - - - - - - - - - - - - - - - - -
5 2 2 2 - - - - - - - - - - - - - - - -	5 1 2 8/ Pizza; Meat; Vegetables; Pasta; Potatoes; Fish; Drinks; Popcorn • • • • • • • • • • • • •	5 2 2 6/ Heating; Vegetables; Pasta; Fish; Chicken; Veal	5 - - - - - - - - - - - - - - - - - - -
5 2 2 3 3 4 5 4 5 1 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7	5 1 2 8/ Pizza; Meat; Vegetables; Pasta; Potatoes; Fish; Drinks; Popcorn • • • • • • • • • • • • •	5 2 2 6/ Heating; Vegetables; Pasta; Fish; Chicken; Veal	5 - - - - - - - - - - - - - - - - - - -
5 2 2 3 - - - - - - - - - - - - - - - - -	5 1 2 8/ Pizza; Meat; Vegetables; Pasta; Potatoes; Fish; Drinks; Popcorn • • • • • • • • • • • • •	5 2 2 6/ Heating; Vegetables; Pasta; Fish; Chicken; Veal	5 - - - - - - - - - - - - - - - - - - -
5 2 2 3 3 4 5 4 5 1 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7	5 1 2 8/ Pizza; Meat; Vegetables; Pasta; Potatoes; Fish; Drinks; Popcorn • • • • • • • • • • • • •	5 2 2 6/ Heating; Vegetables; Pasta; Fish; Chicken; Veal	5 - - - - - - - - - - - - - - - - - - -
5 2 2 3 4 4 5 4 5 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7	5 1 2 8/ Pizza; Meat; Vegetables; Pasta; Potatoes; Fish; Drinks; Popcorn • • • • • • • • • • • • •	5 2 2 6/ Heating; Vegetables; Pasta; Fish; Chicken; Veal	5 - - - - - - - - - - - - - - - - - - -

HOODS			edesə
HOB WITH INTEGRATED VENTILATION EIS-7423 DD R 78	EIS-6321 DD R 79	CEILING DECORATIVE ECC-1832 WH 80	ECC-1832 X 80
NEW VERTICAL DECORATIVE ECV-98321 GBK 81	ECV-98321 GWH 81	BOX DECORATIVE ECB-97220 GBK 82	ECB-97220 GWH 82
ECB-77220 GBK 82	ECB-77220 GWH 82	ECB-9611 X 83	ECB-7611 X 83
		ana - 11111	
ECB-6611 X 83	ECB-9411 X 84	ECB-7411 X 84	ECB-6411 X 84
1000 - 1000 - 1000 - 1000 - 1000 - 1000 - 1000 - 1000 - 1000 - 1000 - 1000 - 1000 - 1000 - 1000 - 1000 - 1000 -	NW 1/177	an 4117	ana - 17337
PYRAMID DECORATIVE ECP-9611 X 85	ECP-7611 X 85	ECP-6611X 85	ECP-6611 BK 85
edesə

ECP-94110 X	86	PYRAMID DECORATIVE ECP-74110 X 86	ECP-64110 X 86	INTEGRATION ECI-96110 X 87
NEW		NEW	NEW	
		FILTER GROUP		FILTER GROUP
ECI-66110 X	87	ECG-8632 GBK 88	ECG-8632 GWH 88	ECG-5811 X 89
		No. of the second		
ECG-5811 BK	89	TELESCOPIC ECT-6411 X 90	ECT-6411 WH 90	ECT-5411 X 92
Contraction of the second seco				
STANDARD ECS-6213 X	91	ECS-6213 WH 91	STANDARD ECS-61110 X 93	NEW ECS-61110 WH 93
2			and address of the	
			edes	9

Surface suction

Save space and enjoy maximum efficiency, with the new flexible countertop and integrated surface hood. With its powerful extractor hood, you will quickly extract directly from where the vapors and fumes are generated. Kitchen is in its 4 areas, convertible into two large double areas, without any fear that the fumes from the cooking will invade your home.





Improved efficiency

We have been working very hard to get unbeatable energy efficiencies. Thanks to the renewed components, our hoods are at the forefront in terms of energy savings.

(9	d	e	S	9

	02890001	DUCTING SET SL1 222X89
	02890002	COMPACT BEND 90° 222X89
der	02890003	BEND 90° 222X89
P	02890004	PIPE HOLDER 222X89
P	02890005	CONNECTOR 222X89
	02890006	FLAT DUCT 0,5M 222X89
	02890007	ROUND-FLAT ADAPTER 150/222X89
	02890008	FLEXIBLE FLAT DUCT 0,5M 222X89
	02890009	HORIZONTAL BEND 90° 222X89
SPD	02890010	HORIZONTAL BEND 15° 222X89
	02890011	WALL DEFELCTOR SL1
	02890014	CERAMIC CARBON FILTERS SET CERÁMICOS SL1
	02890015	PLEATED CARBON FILTERS SET SL1

High efficiency lighting

Lighting is essential when cooking. Our hoods are provided with low consumption LED lighting with very low consumption, providing a more efficient and bright lighting.

It allows using and adjusting the intensity of the light even the hood is working or not.



Maximum extraction

We bet on hoods which extract the smoke our dishes produce thanks to Edesa's high efficiency motors.

Make sure smoke becomes extinct from your kitchen by just pressing a button.

Maximum power turbo

Have you ever got distracted and in a matter of seconds the kitchen has filled with smoke?

The Turbo function is very useful in these cases, because with a simple touch the hood is boosted at full power for 5 minutes. When time has passed, it returns to the previous speed.



Extraction and silence

Edesa complies with the data declaration regulation in terms of extraction capacity and sound power, in accordance with the most demanding regulation. All the operating data of Edesa hoods have been valued according to the rules and codes of conduct established by CECED.

When comparing values, Edesa always recommends doing it in sound power, since it is the mesure that neutrally measures the environmental conditions.

UNE-EN 61591 Standard

The UNE-EN-61591 regulation, specific for hoods, shows the real extraction capacity of the hood in cubic metres/hour (m^3/h) and pressure (Pa) measured in a control point. In order to make a reliable comparison of the suction capacity and the noise level data, these measured data should be taken according to the regulation. Any comparison between values not measured according to this European regulation, has no value.



UNE-EN 60704 Standard

The UNE-EN 60704-2-13 regulation, specific for hoods, shows the maximum sound power of the hood in decibels (dB (A)) during operation.

Measurements are being performed in anechonic or semi-anechonic chambers.





Complete range of motors Edesa

Hoods in this catalogue include a wide variety of motors which features have been adjusted to their use.

Among the most powerful motors we highlight **BT4DC**, with an extraction capacity of up to 842 m³/h, being positioned among the most efficient in the market.

		Maximun speed		Minimun speed	
Motor	Motor power (W)	Air flow (m³/h)	Acustic power (db)	Air flow (m³/h)	Acustic power (db)
BT3	280	850	67	340	50
ТА	270	580	70	385	56
BT4DC	135	842	64	283	46
SL1 BLDC	165	691	68	325	50





Time function

If we want to leave the hood turned on, with this function it automatically switches off after a while, thus getting the air of the kitchen completely clean when finishing cooking.

Filter cleaning indicator

The hood automatically warns when its filters should be cleaned.

Connectivity

Enjoy the speed of hood adjustment thanks to automatic communication with the hob. The extraction power is adjusted according to the temperature of the cooking zones used. You will not need to manually adjust the extraction during cooking and as an option you can control it from the hood panel.



Horizontal adjustment

Quick and precise installation. There is no need for an installation template. With the horizontal levelling adjustment, you can leave your new hood perfectly level.

Air renewal function

Breathe clean air by renewing it every 10 minutes. This way you can eliminate unpleasant odours and breathe clean, fresh air. The hood will operate automatically for 10 minutes every hour, unnoticeably. If you need it urgently, you also have the option of using the renova turbo function. The rapid air renewal takes place with the interval of 5 minutes at maximum speed, 3 minutes at 5th speed and 3 minutes at 4th speed.









edesa



HOB WITH INTEGRATED VENTILATION NEW EIS-7423 R Rounded Cod.: 922272094 - EAN: 8422248373401 B ГЩ BOOSTER PROGRAMME POWER SELECTION PER ZONE TIMER RESIDUAL SLIDING CONTROL COOKING FUNCTIONS HEAT INDICATIOR **P**

SAFETY LOCK STOP&GO





- -Nivel sonoro Máx / Mín: 68 / 50 dB(A)
- -Installation height 17cm
- -Timer function for automatic switch-off
- -Filter saturation indicator
- -Metallic filter washable in dishwasher
- -Carbon filter included





B. %

B

 \bigcirc



HOODS

HOB WITH INTEGRATED VENTILATION

EIS-63	21 DD R		Rounde	ed	NEW
Cod.: 922272093 - EAN: 8422248373371					
R	X			\bigcirc	63









٩, SAFETY LOCK POWER SELECTION PER ZONE



HEAT





STOP&GO

- -Induction hob and automatic cooker hood
- -A+ energetic efficiency class
- -Surface extraction
- -5 extraction levels and booster
- -Mono Slider Touch control panel
- -Motor Brushless de 165 W, BLDC
- -Max / Min extraction rate: 673,2 / 251 m3/h
- -Nivel sonoro Máx / Mín: 68 / 51 dB(A)
- -Installation height 17cm
- -Timer function for automatic switch-off
- -Filter saturation indicator
- -Standard metallic filter washable in dishwasher
- -Carbon filter included



measurements in mm

79













VERTICAL DECORATIVE

ECV-98321 GBK	90 cm - S. steel / black
Cod.: 932271954 - EAN	: 8422248356497

ECV-98321 GWH 90 cm - S. steel / white

Cod.: 932271955 - EAN: 8422248356503











-90 cm wide angle decorative hood with AUTO2 connectivity hood

-A+++ energetic efficiency class

MOTOR

- -Perimeter extraction with Pneumatic opening
- -5 extraction levels, booster and fresh function
- -Backlighted touch control panel
- -BRUSHLESS motor. Ultra silent. Maximum energy consumption 135W
- -Max / Min extraction rate: 842 / 282m³/h
- -Max / Min noise levels: 64 / 46 dB(A)
- -LED strip lighting
- -Light dimmer switch
- -Timer function for automatic switch-off
- -Filter saturation indicator
- -Lower filter anti-condensation
- -Standard metallic filter with plastic handle washable in dishwasher







BOX DECORATIVE

ECB-97220 GBK	90 cm - S. steel / black
Cod.: 932271957 - EAN:	822248363396
ECB-97220 GWH	90 cm - S. steel / white
Cod.: 932271958 - EAN:	8422248363402

ECB-77220 GBK	70 cm - S. steel / black
Cod.: 932271959 - EAN	: 8422248363419
ECB-77220 GWH	70 cm - S. steel / white



-90/70 cm wide box decorative hood with 5 cm wide frontal
-A++ energetic efficiency class
-Larger extraction surface
-3 extraction levels
-Backlighted touch control panel
-73W BLDC motor
-Max / Min extraction rate: 617 / 203 m³/h
-Max / Min noise levels: 65 / 43 dB(A)
-Lighting LED lamp
-Timer function for automatic switch-off
-Standard metallic filter

Optional carbon filter accesory: 02807001 Decorative extension tube accesory: 02862304 Back draught shutter accesory included



measurements in mm







BOX DECORATIVE

ECB-9611 X	90 cm - S. steel	NEW
Cod.: 932271909 - EA	N: 8435436112461	
ECB-7611 X	70 cm - S. steel	NEW
Cod.: 932271910 - EA	N: 8435436112478	
ECB-6611 X	60 cm - S. steel	NEW
Cod.: 932271911 - EA	N: 8435436112485	



-90/70/60 cm wide box decorative hood with 5,6 cm wide frontal -C energetic efficiency class

- -3 extraction levels
- -Mechanic knobs control panel
- -270 W motor, TA
- -Max / Min extraction rate: 645 / 385 m³/h
- -Max / Min noise levels: 70 / 56 dB(A)
- -2 lighting ECOLED lamps, A class
- -Standard metallic filter with plastic handle washable in dishwasher
- Optional Carbon filter accesory: 02859391 Optional washable carbon filter accesory: 0280918 Decorative extension tube accesory: 02861301 Back draught shutter accesory included



* measurements in mm





HOODS



BOX DECORATIVE

ECB-9411 X	90 cm - S. steel
Cod.: 932271886 - EAI	N: 8435436108686
ECB-7411 X	70 cm - S. steel
Cod.: 932271887 - EAI	N: 8435436108693
FCB-6411 X	60 cm - S. steel

Cod.: 932271888 - EAN: 8435436108709	



-90/70/60 cm wide box decorative hood with 5,5 cm wide frontal -C energetic efficiency class -3 extraction levels

-Mechanic knobs control panel

-95 W motor, K7plus

-Max / Min extraction rate: 400 / 210 m³/h

-Max / Min noise levels: 62 / 50 dB(A)

-2 lighting LED lamps, E14

-Standard metallic filter with plastic handle washable in dishwasher

Optional Carbon filter accesory: 02859394 Optional washable carbon filter accesory: 02800918 Optional decordtive extension tube accesory: 02861302 Back draught shutter accesory included











PYRAMID DECORATIVE

ECP-9611 X	90 cm - S. steel		
Cod.: 932271915 - EAN	: 8435436112522		
ECP-6611 X	60 cm - S. steel		
Cod.: 932271917 - EAN	1: 8435436112546		
ECP-7611 X	70 cm - S. steel		
Cod.: 932271916 - EAN	: 8435436112539		
LIGHT ECOLED WITH EFFICIENCY LIGHT PLUG			
-90/70/60 cm wide pyramide decorative hood -C energetic efficiency class -3 extraction levels -Mechanic knobs control panel -270 W motor, TA -Max / Min extraction rate: 645 / 385 m ³ /h -Max / Min noise levels: 71,8 / 57,8 dB(A)			
-2 lighting ECOLED lamps, A class			
-Standard metallic filter with pla dishwasher	astic handle washable in		
Optional carbon filter accesory: 02859391 Optional washable carbon filter accesory: 028 Optional decordive extension tube accesory: Back draught shutter accesory included			
222	167		



шШ	
⊆	
measurements	









PYRAMID DECORATIVE

ECP-94110 X	90 cm - S. steel	NEW
Cod.: 932271961 - E	AN: 8422248371339	
ECP-74110 X	70 cm - S. steel	NEW
Cod.: 932271962 - E	AN: 8422248371353	
ECP-64110 X	60 cm - S. steel	NEW
Cod.: 932271963 - E	AN: 8422248371377	



-90/70/60 cm wide pyramide decorative hood -A energetic efficiency class

- -3 extraction levels
- -Mechanic knobs control panel
- -110 W motor, K10
- -Max / Min extraction rate: 480 / 175 m³/h
- -Max / Min noise levels: 69 / 56 dB(A)
- -High efficiency compact Strip LED lighting, A class
- -Standard metallic filter with plastic handle washable in dishwasher

Optional Carbon filter accesory Optional washable carbon filter accesory Optional decorative extension tube accesory













* measurements in mm

INTEGRATION

ECI-96110 X	90 cm - S. steel
Cod.: 932271948 - EAN	8422248355292
ECI-66110 X	60 cm - S. steel
Cod.: 932271947 - EAN	8422248355285

ECO

ECOLED LIGHT

-90 cm wide furniture built-in hood

-C energetic efficiency class

-3 extraction levels

-Mechanic knobs control panel

-M3R motor. Ultra silent. Maximum energy consumption 270W

-Max / Min extraction rate: 645 / 385 m³/h

-Max / Min noise levels: 70 / 56 dB(A)

-Lighting LED bars, A class

-Standard metallic filter with plastic handle washable in dishwasher

Optional Carbon filter accesory: 02859398 Back draught shutter accesory included













FILTER GROUP	
ECG-8632 GBK	70 cm - Black
Cod.: 932271941 - EAN:	8422248198493

ECG-8632 GWH	70 cm - White
Cod.: 932271942 - EAN	8422248198509



-70 cm wide furniture built-in hood

- -B energetic efficiency class
- -Perimeter extraction
- -3 extraction levels
- -Backlighted Touch Control Panel
- -186 W motor
- -Max / Min extraction rate: 587/ 246 m³/h
- -Max / Min noise levels: 68 / 47 dB(A)
- -Lighting LED bars, A class
- -Standard metallic filter with plastic handle washable in dishwasher

Optional Carbon filter accesory: 02859405



* measurements in mm









FILTER GROUP

ECG-5811 BK	60 cm - Black
Cod.: 932271944 - EA	N: 8422248350969

 ECG-5811 X
 60 cm - S. steel

 Cod.: 932271899 - EAN: 8435436110962



-60 cm wide furniture built-in hood -C energetic efficiency class -3 extraction levels -Mechanic knobs control panel -240 W motor, BT2 -Max / Min extraction rate: 645 / 300 m³/h -Max / Min noise levels: 65 / 50 dB(A) -2 lighting ECOLED lamps -Standard metallic filter with plastic handle washable in dishwasher

Optional Carbon filter accesory: 02859398 Optional washable carbon filter accesory: 02811003 Optional metallic filter accesory: 02811000



* measurements in mm







TELESCOPIC

ECT-6411 X	60 cm - S. steel
Cod.: 932271920 - EAN	:8435436112577

 ECT-6411 WH
 60 cm - White

 Cod.:
 932271919 - EAN:
 8435436112560



-60 cm wide telescopic hood
-C energetic efficiency class
-2 extraction levels
-Mechanic knobs control panel
-100 W motor, TF 2003
-Max / Min extraction rate: 390 / 150 m³/h
-Max / Min noise levels: 57 / 45,5 dB(A)
-2 lighting ECOLED lamps, A class
-Standard metallic filter with plastic handle washable in dishwasher

Optional carbon filter accesory: 02825263 Back draught shutter accesory included









STANDARD

ECS-6213 X	60 cm - S. steel
Cod.: 932271921 -	EAN: 8422248087391

60 cm - White

ECS-6213 WH

Cod.: 932271922 - **EAN:** 8422248087407



LED LIGHT

-60 cm wide standard hood

-D energetic efficiency class

-3 extraction levels

-Mechanic knobs control panel

-50 W two motors, L1

-Max / Min extraction rate: 300 / 100 m³/h

-Max / Min noise levels: 60 / 59 dB(A)

-2 lighting LED lamps, E14

-Standard metallic filter with plastic handle washable in dishwasher / Aluminium filter

Optional carbon filter accesory: 02846763 Back draught shutter accesory included









TELESCOPIC ECT-5411 X NEW 60 cm - S. steel Cod.: 932271964 - EAN: 8422248379052



LIGHT EFFICIENCY

-50 cm wide telescopic hood -B energetic efficiency class -2 extraction levels -Mechanic knobs control panel -65 W motor Max / Min extraction rate: 344 / 175 m³/h -Max / Min noise levels: 64 / 51 dB(A) -High efficiency compact Strip LED lighting, A class -Standard metallic filter with plastic handle washable in dishwasher -Optional Carbon filter accesory -Back draught shutter accesory included







STANDARD ECS-61110 X 60 cm - S. steel Cod.: 932271945 - EAN: 8422248350976

ECS-61110 WH	60 cm - White
Cod.: 932271946 - EA	N: 8422248350983



Optional carbon filter accesory: 02846764 Back draught shutter accesory included

-60 cm wide standard hood
-C energetic efficiency class
-3 extraction levels
-Mechanic knobs control panel
-65W tangential motor
-Max / Min extraction rate: 195 / 107 m³/h
-Max / Min noise levels: 69 / 56 dB(A)
-Lighting LED lamp, E14
-Standard metallic filter with plastic handle washable in dishwasher / Aluminium filter





edesa

Code	922272094	922272093	932271943	932271953	932271954	932271955	932271959	932271960	
EAN Model	8422248373401 EIS-7423 DD B	8422248373371 EIS-6321 DD R	8422248344821 ECC-1832 WH	8422248355490 ECC-1832 X	8422248356497 ECV-98321 GBK	8422248356503 ECV-98321 GWH	8422248363419 ECB-77220 GBK	8422248363426 ECB-77220 GWH	
Type Product fiche according to directives	Flow In	Flow In	Ceiling	Vertical decorative	Vertical decorative	Vertical decorative	Box decorative	Box decorative	
EU65/2014 - EN61591, EN60704-2-13, EN50564 AEC (Anual Energy consumption) (kWh/annum)	43,4	43,3	58,9	58,9	16,8	16,8	11,7	11,7	
EEI class (Energy Efficiency Class)	A+	A+	A	A	A+++	A+++	A++	A++	
FDE (Fluid Dynamic Efficiency)	35,4	34,9	31,5	31,5	40,3	40,3	29,3	29,3	
FDE class (Fluid Dynamic Efficiency Class)	A	A	A	A	A	A	A	A	
LE (Lighting Efficiency) (lux/W)	-		36,6	36,6	23,7	23,7	39	39	
LE class (Lighting Efficiency Class)	-		A	A	В	В	A	A	
GFE (Grease Filtering Efficiency)	65,9	66,8	91,2	91,2	75,5	75,5	71,1	71,1	
GFE Class (Grease Filtering Efficiency class)	D	D	B	B	C 283	C	C	C	
Air flow at minimum speed (m ³ /h) Air flow at maximum speed (m ³ /h)	325,6 535	251 515	340 600	340 600	283 640,5	283 640,5	212 627,5	212 627,5	
Air flow at intensive speed (TURBO) (m ³ /h)	691,5	673,2	850	850	842	842	-	-	
Sound Power Level at minimum speed (dB)	50	51	50	50	46	46	43	43	
Sound Power Level at maximum speed (dB)	68	68	65	65	64	64	65	65	
Sound Power Level at intensive speed (TURBO) (dB)	74	74	67	67	69	69	-	-	
P₀ (Power Consumption in off mode) (W)	0,48	0,48	0,3	0,3	0,35	0,35	0,38	0,38	
P _s (Power Consumption in standby) (W)	-	-	0	0	0	0	-	-	
Integration directive EU 66/2014	-	-							
f (Time Increase Factor)	0,7	0,7	0,9	0,9	0,5	0,5	0,9	0,9	
EEI (Energy Efficiency Index)	40	39,9	54,6	54,6	27,5	27,5	36,2	36,2	
Q_{BEP} (Flow Rate at Best Efficiency Point) (m ³ /h) P_{BEP} (Static Pressure Difference at Best	379,8	331,3	350,4	350,4	369,6	369,6	237,6	237,6	
Efficiency Point) (Pa)	570	644	380	380	314	314	120,3	120,3	
W _{BEP} (Electric Power Input at Best Efficiency Point) (W)	169,7	169,6	132,8	132,8	80	80	27,1	27,1	
W _L (Nominal Power Consumption of Lighting system) (W)	-	-	14	14	3	3	3,8	3,8	
E_{MIDDLE} (Average Illumination of Lighting system on Cooking surface) (lux)	-	-	513	513	71	71	149	149	
External Dimensions									
Width (mm)	770	590	1000	1000	900	900	700	700	_
Depth (mm)	520	520	600	600	346	346	505	505	
Total max height(mm	170	170	500	500	1.580	1.580	830	830	
Total min height(mm	170	170	285	285	815	815	450	450	
Outlet Diameter (mm)	220x90	220x90	150	150	150/125	150/125	150	150	_
Characteristics	-	-	DTO	DTO	DT4D0	DT4D0	1*70W/DLDO	1*70\A/ DI DO	
Motor Extraction Levels	SL1 BLDC 5+1	SL1 BLDC 5+1	BT3 3+1	BT3 3+1	BT4DC 5 + 1	BT4DC 5 + 1	1*73W BLDC 3	1*73W BLDC 3	
Maximum Power Consumption	165	165	280	280	140	140	76	76	
Maximum Pressure	650	640	450	450	357	357	342	342	
Intensive Speed (TURBO) Pressure	900	870	470	470	365	365	-	-	
Control Type	Slider	Slider	TC4i	TC4i	TCD6i	TCD6i	ATC01	ATC01	
Automatic shut-down timer	•	•	•	•	•	•	•	•	
Electronic Filter Saturation Indicator	•	•	•	•	•	•	-	-	
Filter Type	Full Black Aluminium + plastic basket	Full Black Aluminium + plastic basket	Metallic	Metallic	Metallic	Metallic	Aluminium	Aluminium	
Anti-grease Filter Number	1	1	3	3	1+1	1+1	2	2	
Inner Shield	-	-	-	-	-	-	-	-	
Lighting				- - - -			1.50	150	
Light Type Adjustable Intensity Lighting	-		EcoLed	EcoLed	SS Led	SS Led	LED	LED	
Nº of Lamps	-	-	4	4	1	1	2	2	
Installation	_	-	4	4	1	1	2	2	
Minimum height distance to a electric		-	650	650	400	400	650	650	
worktop hob (mm)	-	-	000	000	400	400	000	050	
Minimum height distance to a gas worktop hob (mm) Instalation with Outlet tube to the exterior / Recircu-	-	-	550	550	650	650	650	650	
Instalation with Outlet tube to the exterior / Recircu- lating	•	•	Both	Both	Both	Both	Both	Both	
Easy Instalation System	•	٠	٠	٠	 horizontal leveling 	 horizontal leveling 	٠	•	
Electric Connection						-			
Total Rush Power (W)	7200	6500	294	294	143	143	76	76	
Rated Voltage (V)	220-240	220-240	220-240	220-240	220-240	220-240	220-240	220-240	
Network Frequency (Hz) Electrical Insulation Class	50/60 Class I	50/60 CLASS I	50 Class II	50 Class II	50~60 Class I	50~60 Class I	50 Class I	50 Class I	
Plug	-		EU - 2 pins	EU - 2 pins	-	-	Type F	Type F	
Accessories				p			.,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,	.,,=	
Upper Decorative tube Extension	-	-	-	-	02861300	02861300	-	-	
White Decorative Tube	-	-	-	-	02861001	02861001	-	-	
Black Decorative Tube	-	-	-	-	02861401	02861401	-	-	
Island Tube Enhancer	-	-	-	-	-	-	-	-	
Check Valve	-	-	02832006	02832006	02832004	02832004	-	-	
MAX PRO Metal Filter	-	-	02800917	02800917	-	-	-	-	
Metal Filter	-		02800200*	02800200*	02800930 / 02800925	02800930 / 02800925	-	-	
DUAL Filter (metal + active charcoal)			02800918	02800918	02800922 /	02800922 /	-	-	
	-				02800927	02800927			
Active Charcoal Filter	-	02890014	02859398	02859398	02800927 02859318	02800927 02859318	-	-	
Active Charcoal Filter Noiseless Flexible Duct Decorative panel accesory (APD) (Optional)	-	02890014					-	-	

Delegated Regulation (EU) No. 65 / 2014 of 2013 October 1 that complements Directive 2010/30 / EU of the European Parliament and of the Council in relation to the energy labeling of domestic ovens and hoods. (2) Class range from A ++ (more efficient) to E (less efficient). (3) Class range from A (more efficient) to F (less efficient). (4) Class range from A (more efficient) to G (less efficient). (5) Delegated Regulation (EU) No. 66 / 2014 of January 14, that complements Directive 2009/125/CE of the European Parliament and of the Council concerning the ecological design requirements applicable to domestic ovens, hobs and hoods.

	ec	desa	
71915	932271916	932271917	
6110500	0425426112520	0405406110546	

932271957 822248363396	932271958 8422248363402	932271909 8435436112461	932271910 8435436112478	932271911 8435436112485	932271886 8435436108686		932271888 8435436108709	932271915 8435436112522	932271916 8435436112539	932271917 8435436112546
ECB-97220 GBK	ECB-97220 GWH	ECB-9611 X	ECB-7611 X	ECB-6611 X	ECB-9411 X	ECB-7411 X	ECB-6411 X	ECP-9611 X	ECP-7611 X	ECP-6611 X
Box decorative	Box decorative	Box decorative	Box decorative	Box decorative	Box decorative	Box decorative	Box decorative	Pyramid decorative	Pyramid decorative	Pyramid decorative
10,8	10,8	102.5	102.5	102.5	51.9	51.9	51.9	95.7	95.7	95.7
A++ 29,3	A++ 29,3	C 16.3	C 16.3	C 16.3	C 9.8	C 9.8	C 9.8	C 17.8	C 17.8	C 17.8
A	A	D	D	D	E	E	E	D	D	D
35,1	35,1	36	36	36	8.4	8.4	8.4	38.4	38.4	38.4
A 65,2	A 65,2	A 88.5	A 88.5	A 88.5	E 74.6	E 74.6	E 74.6	A 90.3	A 90.3	A 90.3
D	D	B	B	B	D	D	D	B	B	B
203,3	203,3	385	385	385	210	210	210	385	385	385
617,5 -	617,5	645 -	645	645 -	400	400	400	645 -	645 -	- 645
- 43	43	56	- 56	56	50	50	50	- 57.8	- 57.8	57.8
65	65	70	70	70	62	62	62	71.8	71.8	71.8
-	-	-	-	-	-	-	-	-	-	-
0,4	0,4	0	0	0	0	0	0	0	0	0
-	-	0	0	0	0	0	0	0	0	0
0,9	0,9	1.4	1.4	1.4	1.6	1.6	1.6	1.4	1.4	1.4
35	35	83.4	83.4	83.4	84.4	84.4	84.4	80.1	80.1	80.1
207,5	207,5	375.3	375.3	375.3	208.6	208.6	208.6	371.8	371.8	371.8
125	125	295	295	295	123	123	123	314	314	314
24,6	24,6	188.8	188.8	188.8	72.9	72.9	72.9	182.5	182.5	182.5
3,8	3,8	7	7	7	11	11	11	7	7	7
133	133	252	252	252	92.5	92.5	92.5	269	269	269
900	900	900	700	600	900	700	600	900	700	600
505 830	505 830	500 1,045	500 1,045	500 1,045	475 932	475 932	475 932	500 1,020	500 1,020	500 1,020
450	450	730	730	730	675	675	675	720	720	720
150	150	125	125	125	150/125	150/125	150/125	150/125	150/125	150/125
1*73W BLDC	1*73W BLDC	TA	TA	TA	K7 Plus	K7 Plus	K7 Plus	TA	TA	TA
3 76	3 76	3 270	3 270	3 270	3 95	3 95	3 95	3 270	3 270	3 270
344	344	430	430	430	200	200	200	430	430	430
- ATC01	- ATC01	- Mechanic	- Mechanic	- Mechanic	- Mechanic	- Mechanic	- Mechanic	- Mechanic	- Mechanic	- Mechanic
•	Alcol	-	-	-	-	-	-	-	-	-
- Aluminium	-	-	- Aluminium	-	- Aluminium	- Aluminium	- Aluminium	- Aluminium	-	-
	Aluminium	Aluminium		Aluminium					Aluminium	Aluminium
3	3	3	3	2	3	2	2	3	3	2
LED	LED	ECOLED	ECOLED	ECOLED	LED	LED	LED	ECOLED	ECOLED	ECOLED
-	-	-	-	-	-	-	-	-	-	-
2	2	2	2	2	2	2	2	2	2	2
650	650	650	650	650	650	650	650	650	650	650
650	650	650	650	650	650	650	650	650	650	650
Both	Both	Both	Both	Both	Both	Both	Both	Both	Both	Both
٠	•	•	•	•	•	•	•	•	•	•
76	76	077	077	077	106	106	106	077	077	077
76 220-240	76 220-240	277 220-240	277 220-240	277 220-240	106 220-240	106 220-240	106 220-240	277 220-240	277 220-240	277 220-240
50	50	50-60	50-60	50-60	50-60	50-60	50-60	50-60	50-60	50-60
Class I	Class I	Class II	Class II	Class II	Class II	Class II	Class II	Class II	Class II	Class II
Type F	Type F							•		
-	-	02861301	02861301	02861301	02861302	02861302	02861302	02862301	02862301	02862301
-	-	-	-	-	-	-	-	-	-	-
-	-	-	-	-	-	-	-	-	-	-
-	-	02800917	02800917	02800917	02800917	02800917	02800917	02800917	02800917	02800917
-	-	02800905	02800905	02800905	02800905	02800905	02800905	02800905	02800905	02800905
-	-	02800918	02800918	02800918	02800918	02800918	02800918	02800918	02800918	02800918
-	_	02859391	02859391	02859391	02859394	02859394	02859394	02859391	02859391	02859391
-	-	02893002	02893002	02893002	02893002	02893002	02893002	02893002	02893002	02893002
-	-	02841300	02866300	02840300	02841300	02866300	02840300	02841300	02866300	02840300

edesə

Code EAN Model	932271956 8422248358736 ECP-6611 BK	932271961 8422248371339 ECP-94110 X	932271962 8422248371353 ECP-74110 X	932271963 8422248371377 ECP-64110 X	932271948 8422248355292 ECI-96110 X	932271947 8422248355285 ECI-66110 X		932271942 8422248198509 ECG-8632 GBK	
		Pyramid	Pyramid	Pyramid					
Type Product fiche according to directives EU65/2014 - EN61591, EN60704-2-13, EN50564	Pyramid decorative	decorative	decorative	decorative	Integrated	Integrated	Filter group	Filter group	
	95.7	95.7	95.7	95.7	100,9	100,9	63	63	
AEC (Anual Energy consumption) (kWh/annum)	00.7 C				î				
EEI class (Energy Efficiency Class)	17.8	C 17.8	C 17.8	C 17.8	C 16,3	C 16,3	B 24,7	B 24,7	
FDE (Fluid Dynamic Efficiency) FDE class (Fluid Dynamic Efficiency Class)	D	D	D	D	D	D	24,7 B	24,7 B	
LE (Lighting Efficiency) (lux/W)	38.4	38.4	38.4	38.4	21,4	21,4	31,2	31,2	
LE class (Lighting Efficiency Class)	А	A	А	A	B	B	A	A	
GFE (Grease Filtering Efficiency)	90.3	90.3	90.3	90.3	88,5	88,5	66,7	66,7	
GFE Class (Grease Filtering Efficiency class)	В	B	B	B	B	В	D	D	
Air flow at minimum speed (m³/h) Air flow at maximum speed (m³/h)	385 645	175 480	175 480	175 480	385 645	385 645	246 587	246 587	
Air flow at intensive speed (TURBO) (m ³ /h)	-	-	-	-	-	-	-	-	
Sound Power Level at minimum speed (dB)	57.8	56	56	56	56	56	47,6	47,6	
Sound Power Level at maximum speed (dB)	71.8	69	69	69	70	70	68,1	68,1	
Sound Power Level at intensive speed (TURBO) (dB) Po (Power Consumption in off mode) (W)	- 0	- 0	- 0	- 0	- 0	-	- 0	- 0	
P_{s} (Power Consumption in standby) (W)	0	0	0	0	0	0	0.49	0.49	
Integration directive EU 66/2014	-	-	-		-		5,.5	5,.5	
f (Time Increase Factor)	1.4	1.4	1.4	1.4	1,4	1,4	1,11	1,11	
EEI (Energy Efficiency Index)	80.1	80.1	80.1	80.1	82,4	82,4	64,3	64,3	
Q _{BEP} (Flow Rate at Best Efficiency Point) (m ³ /h)	371.8	371.8	371.8	371.8	375,3	375,3	317,5	317,5	
P _{BEP} (Static Pressure Difference at Best Efficiency Point) (Pa)	314	314	314	314	295	295	408	408	
W _{BEP} (Electric Power Input at Best Efficiency Point) (W)	182.5	182.5	182.5	182.5	188,8	188,8	145,7	145,7	
WL (Nominal Power Consumption of Lighting system) (W) E _{MIDDE} (Average Illumination of Lighting system on	7	7	7	7	6	6	6	6	
Cooking surface) (lux)	269	269	269	269	128,3	128,3	187	187	
External Dimensions Width (mm)	600	900	700	600	898	598	700	700	
Depth (mm)	500	500	500	500	310-350	310-350	270	270	
Total max height(mm	1,020	1,020	1,020	1,020	280	280	240	240	
Total min height(mm	720	720	720	720	280	280	240	240	
Outlet Diameter (mm)	150/125	150/125	150/125	150/125	150/125	150/125	125/150	125/150	
Characteristics	TA	ΤA	ΤΛ	ТА	MOD	MOD	196\//	186W	
Motor Extraction Levels	TA 3	TA 3	TA 3	TA 3	M3R 3	M3R 3	186W 3	3	
Maximum Power Consumption	270	270	270	270	270	270	186	186	
Maximum Pressure	430	430	430	430	430	430	484	484	
ntensive Speed (TURBO) Pressure	-	-	-	-	-	-	-	-	
Control Type	Mechanic	Mechanic	Mechanic	Mechanic	Mechanic	Mechanic	Backlighted touch	Backlighted touch	
Automatic shut-down timer	-	-	-	-	-	-	•	•	
Electronic Filter Saturation Indicator	-	-	-	-	-	-	-	-	
Filter Type Anti-grease Filter Number Inner Shield	Aluminium 2	Aluminium 3	Aluminium 3	Aluminium 2	Metallic 2	Metallic 2	Aluminium 2	Aluminium 2	
Lighting	-	-	-	-	-	-	-	-	
Light Type	ECOLED	ECOLED	ECOLED	ECOLED	CSLED	CSLED	Stripled	Stripled	
Adjustable Intensity Lighting	-	-	-	-	-	-	-	-	
№ of Lamps	2	2	2	2	2	2	1	1	
Installation Minimum height distance to a electric									
worktop hob (mm) Minimum height distance to a gas worktop hob	650 650	650 650	650 650	650 650	550 650	550 650	650 550	650 550	
(mm) Instalation with Outlet tube to the exterior /									
Recirculating	Both	Both	Both	Both	Both	Both	Both	Both	
Easy Instalation System	•	•	•	•	•	•	•	•	
Electric Connection Total Rush Power (W)	277	277	277	277	276	276	189,5	189,5	
Rated Voltage (V)	220-240	220-240	220-240	220-240	220-240	220-240	220-240	220-240	
Network Frequency (Hz)	50-60	50-60	50-60	50-60	50	50	50-60	50-60	
Electrical Insulation Class	Class II	Class II	Class II	Class II	Class I	Class I	Class I	Class I	
Plug	•	•	•	•	-	-	-	-	
Accessories	02962201	02962201	02962201	02962001	02961000	02961200			
Upper Decorative tube Extension White Decorative Tube	02862301	02862301	02862301	02862301	02861306	02861306	-	-	
Black Decorative Tube	-	-	-	-	-	-	-	-	
sland Tube Enhancer	-	-	-	-	-	-	-	-	
Check Valve	•	Included	Included	Included	Included	Included	-	-	
MAX PRO Metal Filter	02800917	02800917	02800917	02800917	-	-	-	-	
Metal Filter DUAL Filter (metal + active charcoal)	02800905 02800918	02800905 02800918	02800905 02800918	02800905 02800918	02800212	02800211	02811018	02811018	
Active Charcoal Filter	02800918	02800918	02800918	02800918	- 02859398	- 02859398	- 02859405	- 02859405	
Noiseless Flexible Duct	02893002	02893002	02893002	02893002	02893002	02893002	-	-	
	02840300	02841300	02866300	02840300	-	-	-	-	

(1) Delegated Regulation (EU) No. 65 / 2014 of 2013 October 1 that complements Directive 2010/30 / EU of the European Parliament and of the Council in relation to the energy labeling of domestic ovens and hoods. (2) Class range from A ++ (more efficient) to E (less efficient). (3) Class range from A (more efficient) to F (less efficient). (4) Class range from A (more efficient) to F (less efficient). (5) Delegated Regulation (EU) No.66 / 2014 of January 14, that complements Directive 2009/125/CE of the European Parliament and of the Council concerning the ecological design requirements applicable to domestic ovens, hobs and hoods.

932271899 8435436110962	932271944 8422248350969	932271920 8435436112577	932271919 8435436112560	932271964 8422248379052	932271921 8422248087391	932271922 8422248087407	932271945 8422248350976	932271946 8422248350983
ECG-5811 X	ECG-5811 BK	ECT-6411 X	ECT-6411 WH	ECT-5411 X	ECS-6213 X	ECS-6213 WH	ECS-61110 X	ECS-61110 WH
Filter group	Filter group	Telescopic	Telescopic	Telescopic	Standard	Standard	Standard	Standard
106.3	106.3	44.5	44.5	27,3	52.6	52.6	45,1	45,1
C	C	C	C	B	D	D	С	C
15.7 D	15.7 D	11.9 E	11.9 E	16 D	9.1 E	9.1 E	9,4 E	9,4 E
24.3	24.3	36	36	44	8.4	8.4	14,5	14,5
B	B	A	A	A	E	E	D	D
91.2	91.2	68	68	67	68	68	79,6	79,6
В	В	D	D	D	D	D	C	C
300	300	150	150	175	100	100	107,5	107,5
645	645	390	390	344	300	300	195,6	195,6
-	-	-	-	-	-	-	-	-
50	50	45.5	45.5	51	60	60	56	56
65	65	57	57	64	69	67	69	69
-	-	-	-	-	-	1000	-	-
0	0	0	0	0	0	500	0	0
0	0	0	0	0	0	285	0	0
1.4	1.4	1.6	1.6	1.4	1.7	1.7	1,7	1,7
84.7	84.7	78.2	78.2	61,6	85.6	85.6	82,4	82,4
419.7	419.7	198.2	198.2	206,4	150.4	150.4	116,2	116,2
261	261	148	148	142	158	158	192	192
193.5	193.5	68.6	68.6	50,9	73	73	66,2	66,2
7	7	7	7	1,8	11	11	5,5	5,5
 170	170	252	252	79	92.5	92.5	80	80
492	492	600	600	500	600	600	600	600
277	277	280-440	280-440	282-463	450	450	452	452
290	290	180	180	200	120	120	85	85
290	290	180	180	200	120	120	85	85
150 / 125	150 / 125	120	120	150	120	120	120	120
DTO	DTO	TF 2003	TF 2003	0514	11	11	1.151	1.151
BT2 3	BT2 3	2	2	65W 2	L1 3	L1 3	L1N 3	L1N 3
240	240	100	100	67	50	50	65	65
405	405	194	194	225	190	190	325	325
-	-	-	-	-	-	-	-	-
Mechanic	Mechanic	Mechanic	Mechanic	Mechanic	Mechanic slider	Mechanic slider	Mechanic	Mechanic
-	-	-	-	-	-	-	-	-
- Aluminium	- Aluminium	- Aluminium	- Aluminium	- Aluminium	- Aluminium mesh	- Aluminium mesh	- Metallic	- Metallic
2	2	2	2	2	2	1	2	2
-	-	-	-	-	-	-	-	-
ECOLED	ECOLED	ECOLED	ECOLED	CSLED	LED	LED	LED E-14	LED E-14
-	-	-	-	-	-	-	-	-
2	2	2	2	1	2	2	1	1
650	650	650	650	650	650	650	550	550
550	550	550	550	550	650	650	650	650
Both								
•	•	•	•	•	•	•	•	•
207	207	107	107	67	66	66	65,5	65,5
220-240	220-240	220-240	220-240	220-240	220-240	220-240	220-240	220-240
50-60	50-60 Class II	50-60 Class I	50-60	50-60 Class I	50-60	50-60	50 Class I	50 Class I
Class II	Class II	Class I	Class II	Class I	Class II	Class II	Class I	Class I
-	-			-				
-	-	-	-		-	-	-	-
-	-	-	-		-	-	-	-
-	-	-	-		-	-	-	-
- Included -	- Included -	- Included -	- Included -	•	- Included -	- Included -	- 02849002 -	- 02849002 -
02811000	02811000	02825272	02825272		02803260	02803260	02833170	02833170
02811003	02811003	-	-		-	-	-	-
02859398	02859398	02825263	02825263	02859495	02846763	02846763	02846764	02846764
02893002	02893002	-	-		-	-	-	-
-	-	-	-		-	-	-	-

All the boxes marked with a ${\mbox{\circ}}$ are equivalent to a Yes Accessories / ${\mbox{\circ}}$ NOT INCLUDED ${\mbox{\circ}}$ INCLUDED

edesa

edesə

TOTAL NO FROST	l		· · · · · · · · · · · · · · · · · · ·
ESS-1833 NF EX 112	ESS-1832 NF EX 112	EFC-2035 NF EX 113	EFC-1822 NF GBK 113
METAL DUAL NO FROST EFC-7832 DNF EX 114	TOTAL NO FROST EFC-2032 NF EX 114	EFC-2032 NF WH 115	EFC-1833 NF EX 115
EFC-1833 NF WH 116	EFC-1835 NF EX 116	EFC-1834 NF EX 117	EFC-1834 NF WH 117
NEW	NEW	I IIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIII	NEW
EFC-1821 NF EX 118	EFC-1821 NF WH 118	STATIC COMBI EFC-1822 NF WH 119	EFC-1821 ST WH 119
BUILT IN	STATIC TWO DOORS		
EFC-1711-I 120	EFT-1711 EX 120	EFT-1711 WH 121	EFT-1612 WH 121

NEW

98



		TOTAL NO FROST					
EFT-1411 WH	122	EFS-1823 NF EX	122	EZS-1823 NF EX	123	EFS-1823 NF WH	123
			Ī]		
EZS-1823 NF WH	124	EFS-0813 WH	124	EZS-0813 WH	125	EFS-0814	125
				STATIC BUILT IN			
EFS-0911 WH	126	EFS-0411 WH	126	EFS-0513 I	127	EFS-0514 I	127
EZS-0513 I	128	TOTAL NO FROST EZS-1732 NF EX	128	EZS-1732 NF WH	129	DEFROST FREEZER EZS-1412 WH	139
	120		120		127		107
HORIZONTAL DEFROS		NEW					
EZH-5011 13	30 EZH -	4211 130	EZH-3511	130 EZH-:	3011	130 EZH-2811	132
-		2					
EZH-2014 13	32 EZH -	2011 132	EZH-1011	133 EZH-	3011	134 EZH-2811	134
		-		0,			8

NEW







FRIDGES AND FREEZERS



Cold is better distributed with Metal DUAL No Frost

Some of the models in the new Edesa range offer the Metal DUAL No Frost cooling system, which offers significant improvements compared to other systems on the market.

If you are looking for a perfect control, this novelty will help you achieve it, because the "dual" system allows you to select the temperature of the refrigerator and freezer with complete independence.

If you want to place the entire purchase and not break the cold chain, Edesa has the solution for you. It is possible to select the "Super" function to achieve the selected temperature more quickly, both in the refrigerator part, and in the freezer part, and independently.

Another advantage is that it distributes more efficiently the cold air inside thanks to the "Metal" system, thus offering a much more stable temperature with lower consumption.

In order to highlight even more all its qualities, the interior decoration of the refrigerator has metallic details with sophisticated designs, which identify it better with its high quality range.

DUAL NF



edesa



Avoid frost in the whole fridge with the functions TOTAL No Frost

Refrigerators withTOTAL No Frost technology differ from static refrigerators, mainly in that they do not produce frost.

Thanks to its fan that distributes dry and cold air homogeneously and uniformly in the refrigerator and freezer, food is refrigerated avoiding the formation of moisture and, consequently, ice on the walls of the appliance.

This system allows food to be stored for longer than the traditional system.

With the TOTAL DeFrost automatic defrost you can open and close the door as many times as you want without the annoying formation of frost in your freezer cabinet. In Edesa we always think about the environment and with TOTAL DeFrost the electricity consumption is reduced compared to models without this technology.

TOTAL NF





*C 8

6

4

3

2

8

(8)

Control panel

A new control panel for the Edesa Metal Dual No Frost and Total No Frost refrigerators, that offers a simple and easy-to-understand operation.

For the most efficient refrigerators of our range, we have designed a sophisticated and elegant control panel, with LED lighting, which has a thermostat to regulate the temperature of the freezer and refrigerator compartments.

It also allows to set the function Super cooling or Super freezing.



edesə

Edesa is elegance, design and safety glass.

If you are looking for an elegant refrigerator that calls attention in a sophisticated way, the new real glass doors of Edesa will be your solution.

The black glass model to create kitchens more elegant and sophisticated.



LED screen on door Pantalla

Thanks to the LED screen on the door, you will be aware of the temperature at which your food is being kept or quickly readjust settings of your refrigerator.

Visual and useful.

edesa

High-intensity LED lighting

Most of our models are equipped with the latest LED technology.

It is much more intense, thus achieving greater clarity in the whole refrigerator, consuming less and lasting longer.

The LED technology provides immediate illumination, without flashing or blinking, of high intensity, clean and cold.

It improves the visualization of the products and does not radiate heat towards them, thus contributing to a better functioning of the device.

Some of these refrigerators have a LED column lighting inside, which provides a perfect view of all the foods, even if the shelves are full.

The most sophisticated models offer a surprising progressive lighting when opening the door.







The door on door which adapts to current kitchens

Your kitchen dimensions are limited?

Table top fridge and table top freezer are the perfect door on door combination you were looking for. The most versatile and easy to use appliances to offer comfort and the largest possible space, with an F efficiency.



Horizontal freezers

Because families continue to grow and need more freezing space, Edesa thinks of you. Whether you don't need to go much to shopping or you prefer to be well stocked with ice cubes, with Edesa's horizontal freezers you can have from 59 liters to 418 liters of freezing capacity.

	1
¥.	
 	_

At Edesa we think about making your daily life easy. Do you need more lighting to see the content? No problem, with the LED lighting there will be no hidden corners.




Side by side refrigerators

Do you want to dispose of a large storage space without renouncing to a low consumption?

Thanks to its inverter motor, both the sound, low consumption and durability of your Side by side refrigerator is beyond doubt.

Forget about complex installations. With its hidden handles and the opening of the doors at 90°, you will have access to all its corners regardless of how it is installed, walls, furniture... and always with all the information at sight thanks to its Touch Display.

Table top refrigerators

Sometimes you don't have much space in your kitchen or office, or you just like to keep the cold beer next to the couch to watch your favorite show —Reduced dimensions— it will fit your house or your motorhome because we know that you also like to enjoy nature.



Integration refrigerators

In Edesa we have all the options to equip your kitchen. If you are passionate about design or you do not have much space in your kitchen and you want to gain space without giving up design, the integration refrigerators are the best solution to create open spaces due to their installation in both column and under-countertop units.

Side by side models

If you want a top kitchen, this is your favourite model. Easy to assemble thanks to the mounting kit, thus it is installed in just few minutes.

One door refrigerator and one door freezer, with stainless steel finishing and an easy-to-open handle, will make the kitchen stands out.

Inner remains in harmony with its elegant outer, thanks to the LED column lighting and the transparent glass shelves in addition to the digital temperature control on inner display.

This door on door is designed for large families or people who need a large storage capacity in both the fridge and the freezer.



Do you have a small kitchen? Opening Zero Clearance

That is why our combined refrigerators include the Zero Clearance opening that allows to open the refrigerator doors up to 90°, even though the appliance is installed attached to the wall, thus ensuring the opening of the drawers and allowing to remove all the shelves if necessary.



edes

All this is possible thanks to a type of special hinges that incorporate the 60 and 70 cm wide Edesa combined refrigerators.

We care about the details and functionality in your kitchen.

Details that make a difference

In Edesa we take care of every last detail. We know that small things are sometimes the most important.

In the majority of our combined refrigerators we have included a small bottle rack so that you can place two bottles safely and without taking up a lot of space.

Tempered glass for resistant interior shelves

Edesa gives priority to the quality and safety of everyone in the house.

That is why it is important to use resistant and durable materials that offer good long-term results.

The shelves of the Edesa refrigerators are manufactured in a resistant material, as is the real tempered glass, which provides a greater safety and quality.

Adaptability

Inner design of our refrigerators is thought to be adapted to your storage needs, allowing you to place the trays at the required height to perfectly optimize the entire space.

In this way you can place food by height according to the cold they need. Your desserts will always be ready!

If every day is different for you, the same happens to your refrigerator.

edesə

Edesa Fresh Box Drawer

Another novelty is the new Fresh Box drawers, ideal for keeping fruits and vegetables intact.

This drawer maintains a higher humidity percentage than the rest of the refrigerator compartments, thus ensuring that the food inside does not dry out.

This space is optimal to preserve the properties and vitamins of vegetables and fruits for a longer time.

Low temperature drawer

EDESA brings as a novelty a new space inside its refrigerators. A space that makes our everyday life easier.

The low temperature drawer is maintained at a constant temperature close to zero degrees.

The technical specialists reveal that this temperature is the ideal to preserve the properties of meat and fish intact.

Keeping the temperature low, without freezing the food, it is possible to preserve them fresh for much longer.

Super freezing function

Very useful when you arrive from shopping with frozen products.

Activating this function, the temperature will quickly decrease and the food will get frozen in a record time, thus keeping all properties.

Super cooling function

It allows quickly cooling the food in a record time.

Holiday function

It allows a significant energy saving when the refrigerator is not being used during the holiday periods.



Season function

Why should our refrigerator be working at full capacity when it can adapt itself to the outside temperature?

To answer this question, Edesa has introduced the Season function to its combi fridge-freezers. Thus, we can save energy because the refrigerator allows us to specify the room temperature to adapt to it.

<10 °C room temperature - WINTER position (colder)

> 35 °C room temperature - SUMMER position (cold)





We love challenges, so we are working on reducing the energy consumption of our refrigerators to reach again the maximum energy classification according to the recent delegated regulation (EU) 2019/2016. So that you and your family can enjoy a cleaner world, the values have been rescaled, with classes A+++, A++ and A+ disappearing, starting from class A. This does not mean that now your fridge consumes more than before, but that the scale has changed.

With your new Edesa class D fridge, you will have significant energy and economic savings on your electricity bill, as well as a lower environmental impact.

With the Inverter motors you will have triple tranquility; you will notice a lower consumption of electricity in your bill, less noise and the guarantee of a longer duration of its motor.



Designed for warm climates

Edesa refrigerators have been designed to work in Mediterranean climates.

That is why they optimally work when outside temperature reaches at most 43 °C.



edesa

edesə





1.79 M SIDE BY SIDE NO FROST REFRIGERATORESS-1832 NF EXStainless SteelCod.: 924271323 - EAN: 8422248350532



- -1.77mm TOTAL No Frost Side by side fridge
- -Energy efficiency D

D

ENERGY EFFICIENCY

-TOTAL No Frost technology in refrigerator and freezer

1.77 M SIDE BY SIDE NO FROST REFRIGERATOR

Cod.: 924271324 - EAN: 8422248350549

LED

EXTERNAL LED DISPLAY Stainless Steel

FUNCTION IN REFRIGERATOR

AND FRFF7F

WITH PLUG

-Independent electronic temperature regulation in refrigerator -90° opening door

LED

LED LIGHT

-Electronic LED touch control on door

ESS-1833 NF EX

TOTAL NO FROST

- -"Super" function in refrigerator and freezer
- -Holiday function
- -Refrigerator: 2 Fresh Box drawer
- -Freezer: 2 large-capacity drawers
- -Integrated door handle
- -Net capacity (L): 555 (349 + 206)
- -Electric consumption : 256 kW/year
- -Climate class SN/N/ST/T (10-43°)
- -LED lighting
- 897 1765 706

- -1.79mm TOTAL No Frost Side by side fridge
- Energy efficiency E
- -TOTAL No Frost technology in refrigerator and freezer
- Independent electronic temperature regulation in refrigerator -90° opening door
- -Electronic LED touch control on door
- -"Super" function in refrigerator and freezer
- -Refrigerator: 2 Fresh Box drawer
- -Freezer: 2 large-capacity drawers
- -Integrated door handle
- -Net capacity (L): 519 (334 + 185)
- -Electric consumption : 309 kW/year
- -Climate class SN/N/ST/T (10-38°)
- -LED lighting





1.88 M DUAL NO FROST COMBINED

EFC-2035 NF EX	Stainless Steel
Cod.: 924271321 - EAN: 8422	248343107



1.86 M DUAL NO FROST COMBINED

EFC-1822 NF GBK Black Glass Cod.: 924271309 - EAN: 8422248343084





edesa

FRIDGES AND FREEZERS

- -2m combi TOTAL No Frost fridge
- -Energy efficiency D
- -TOTAL No Frost technology in refrigerator and freezer
- -Independent electronic temperature regulation in refrigerator and freezer
- -Electronic LED touch control on door
- -"Super" function in freezer
- -Refrigerator: 2 Fresh Box drawer
- -Freezer: 3 large-capacity drawers
- -Metallic winerack
- -Bar metallic handle
- -Net capacity (L): 336 (238 + 98)
- -Electric consumption : 197 kW/year
- -Climate class SN/N/ST/T (10-43°)
- -LED lighting
- -Reversible doors





- -Independent electronic temperature regulation in refrigerator and freezer
- -Electronic LED touch control on door
- -"Super" function in freezer
- -Refrigerator: 2 Fresh Box drawers
- -Freezer: 3 large-capacity drawers
- -Integrated door handle
- -Net capacity (L): 304 (207 + 97)
- -Electric consumption : 243 kW/year
- -Climate class SN/N/ST/T (10-43°)
- -LED lighting -Reversible doors



edesə



Stainless Steel

"SUPER" FUNCTION IN REFRIGERATOR WITH PLUG

LED

LED LIGHT

1.88 M DUAL NO FROST CO	OMBINED
EFC-7832 DNF EX	Stainless Steel
Cod.: 924271326 - EAN:	8422248350570





- -Metal DUAL No Frost technology in refrigerator and freezer
- -Independent electronic temperature regulation in refrigerator and freezer
- -Metal system that distributes the cold in an efficient and stable way
- -Metallic interior finishes
- -Electronic LED touch control on door
- -"Super" function in refrigerator and freezer
- -Holiday function
- -Refrigerator: 1 low temperature drawer and 2 Fresh Box drawers
- -Freezer: 2 large capacity drawers and separate tray -Bar metallic handle
- -Net capacity (L): 268 (316 + 119)
- -Electric consumption : 336 kW/year
- -Climate class N/ST (16-38°)
- -LED lighting
- -Reversible doors



-2m combi TOTAL No Frost fridge

TOTAL NO FROST

-Energy efficiency E

Ε

ENERGY EFFICIENCY

-TOTAL No Frost technology in refrigerator and freezer

Cod.: 924271264 - EAN: 8422248097024

LED

EXTERNAL LED DISPLAY

- -Electronic temperature regulation in refrigerator
- -Electronic LED touch control on door

2 M FULL NO FROST COMBINED

EFC-2032 NF EX

- -"Super" function in refrigerator
- -Refrigerator: 1 low temperature drawer and 1 Fresh Box drawer
- -Freezer: 3 large-capacity drawers
- -Metallic winerack
- -Bar metallic handle for stainless steel model. Integrated door handle for white model
- -Net capacity (L): 330 (247 + 83)
- -Electric consumption : 231 kW/year
- -Climate class N/ST (16-38°)
- -LED lighting
- -Reversible doors







2 M FULL NO FROST COMBINED

 EFC-2032 NF WH
 White

 Cod.: 924271265 - EAN: 8422248097031



-2m combi TOTAL No Frost fridge

- -Energy efficiency E
- -TOTAL No Frost technology in refrigerator and freezer
- -Electronic temperature regulation in refrigerator
- -Electronic LED touch control on door
- -"Super" function in refrigerator
- -Refrigerator: 1 low temperature drawer and 1 Fresh Box drawer
- -Freezer: 3 large-capacity drawers
- -Metallic winerack
- -Bar metallic handle for stainless steel model. Integrated door
- handle for white model
- -Net capacity (L): 330 (247 + 83)
- -Electric consumption : 231 kW/year
- -Climate class N/ST (16-38°)
- -LED lighting
- -Reversible doors





edesə





1.88 M FULL NO F EFC-18330 N		MBINED White		NEW		full no 18330 i	frost coi NF EX		ss Steel	NEW
Cod.: 92427135	3 - EAN:	84222483	379632		Cod.:	9242713	54 - EAN:	84222483	380935	
ENERGY EFFICIENCY EFFICIENCY	EXTERNAL LED DISPLAY	LED LIGHT	SUPER" FUNCTION IN REFRIGERATOR	WITH PLUG	ENERGY EFFICIENCY	FULL NF TOTAL NO FROST	LED EXTERNAL LED DISPLAY	LED LIGHT	"SUPER" FUNCTION IN REFRIGERATOR	WITH PLUG

- -1.86m combi TOTAL no frost fridge
- -Energy efficiency D
- -TOTAL No Frost technology in refrigerator and freezer
- -Independent electronic temperature regulation in refrigerator and freezer
- -Electronic LED touch control on door
- -"Super" function in refrigerator
- -Refrigerator: 1 low temperature drawer and 1 Fresh Box drawer
- -Freezer: 3 large-capacity drawers
- -Metallic winerack
- -Bar metallic handle
- -Net capacity (L): 304 (207 + 97)
- -Electric consumption : 194 Kw/year
- -Climate class SN/N/ST/T (10-43°)
- -LED lighting
- -Reversible doors



- -1.86m combi TOTAL no frost fridge
- -Energy efficiency D
- -TOTAL No Frost technology in refrigerator and freezer
- -Independent electronic temperature regulation in refrigerator and freezer
- -Electronic LED touch control on door
- -"Super" function in refrigerator
- Refrigerator: 1 low temperature drawer and 1 Fresh Box drawer
- -Freezer: 3 large-capacity drawers
- -Metallic winerack
- -Bar metallic handle
- -Net capacity (L): 304 (207 + 97)
- -Electric consumption : 194 Kw/year
- -Climate class SN/N/ST/T (10-43°)
- -LED lighting
- -Reversible doors







1.88 M	FULL NO	FROST CO	MBINED			1.88 M	FULL NO	FROST COM	MBINED	
EFC-	1834 N	FEX	Stainle	ss Steel	NEW	EFC-	1834 N	FWH	White	
Cod.:	9242713	49 - EAN:	842224	8373753		Cod.:	9242713	51 - EAN:	842224	8373760
E	FULL NF	LED	LED	@ *	#	E	FULL NF	LED	LED	@ *
ENERGY EFFICIENCY	total no Frost	EXTERNAL LED DISPLAY	LED LIGHT	"SUPER" FUNCTION IN FREEZER	WITH PLUG	ENERGY EFFICIENCY	TOTAL NO FROST	EXTERNAL LED DISPLAY	LED LIGHT	"SUPER" FUNCTION IN FREEZER

- -1.86m combi TOTAL no frost fridge
- -Energy efficiency E
- -TOTAL No Frost technology in refrigerator and freezer
- -Electronic temperature regulation in refrigerator
- -Electronic LED touch control on door
- -"Super" function in freezer
- -Refrigerator: 2 Fresh Box drawers
- -Freezer: 3 large-capacity drawers
- -Integrated door handle
- -Net capacity (L): 304 (207 + 97)
- -Electric consumption : 243 Kw/year
- -Climate class SN/N/ST/T (10-43°)
- -LED lighting
- -Reversible doors





- -TOTAL No Frost technology in refrigerator and freezer
- -Electronic temperature regulation in refrigerator
- -Electronic LED touch control on door
- -"Super" function in freezer
- -Refrigerator: 2 Fresh Box drawers
- -Freezer: 3 large-capacity drawers
- -Integrated door handle
- -Net capacity (L): 304 (207 + 97)
- -Electric consumption : 243 Kw/year
- -Climate class SN/N/ST/T (10-43°)
- -LED lighting
- -Reversible doors



FRIDGES AND FREEZERS

* measurements in mm

NEW

WITH PLUG

edesə





1.88 M FULL NO FROST CO	MBINED
EFC-1821 NF EX	Stainless Steel
Cod.: 924271327 - EAN:	8422248350587



1.88 M FULL NO FROST CO	MBINED
EFC-1821 NF WH	White
Cod.: 924271325 - EAN:	8422248350570



-1.88m combi TOTAL No Frost fridge
-Energy efficiency E
-TOTAL No Frost technology in refrigerator and freezer
-Electronic temperature regulation in refrigerator
-Inner electronic LED control
-Refrigerator: 1 vegetable drawer
-Freezer: 3 large-capacity drawers
-Integrated door handle
-Net capacity (L): 310 (224 + 86)
-Electric consumption : 293 kW/year
-Climate class SN/N/ST (10-38°)
-LED lighting
-Reversible doors

- -1.88m combi TOTAL No Frost fridge
- -Energy efficiency E
- -TOTAL No Frost technology in refrigerator and freezer
- -Electronic temperature regulation in refrigerator
- -Inner electronic LED control
- -Refrigerator: 1 vegetable drawer
- -Freezer: 3 large-capacity drawers
- -Integrated door handle
- -Net capacity (L): 310 (224 + 86)
- -Electric consumption : 293 kW/year
- -Climate class SN/N/ST (10-38°)
- -LED lighting
- -Reversible doors









1.80 M FULL NO FROST COMBINED

EFC-1822 NF WH	White
Cod.: 924271328 - EAN:	8422248350600







1.80 M STATIC COMBI	
EFC-1821 ST WH	White
Cod.: 924271329 - EAN:	8422248350617





- -1.80m combi TOTAL No Frost fridge
- -Energy efficiency E
- -Homogeneous cold inside the refrigerator and freezer
- -Independent electronic temperature regulation in refrigerator and freezer
- -Refrigerator: 1 vegetable drawer
- -Freezer: 2 large capacity drawers and separate tray
- -Integrated door handle
- -Net capacity (L): 253 (182 + 71)
- -Electric consumption : 220 kW/year
- -Climate class N/ST (16-38°)
- -LED lighting
- -Reversible doors

- -1.80m combi fridge
- -Energy efficiency E
- -Homogeneous cold inside the refrigerator and freezer
- -Electronic temperature regulation in refrigerator
- -Refrigerator: 1 vegetable drawer
- -Freezer: 3 large-capacity drawers
- -Integrated door handle
- -Net capacity (L): 262 (191 + 71)
- -Electric consumption : 210 kW/year
- -Climate class N/ST (16-38°) -LED lighting
- -Reversible doors











1.70 M BUILT IN COMBI		1.76 M STATIC TWO DO	ORS
EFC-1711 I	White	EFT-1711 EX	Stainless Steel
Cod.: 924271344 - EA	N: 8422248350792	Cod.: 924271330 - EA	N: 8422248350624
ENERGY EFFICIENCY		ENERGY EFFICIENCY EFFICIENCY	
-1.78m built in combi fridge -Energy efficiency E -Homogeneous cold inside -Electronic temperature reg -Refrigerator: 1 vegetable of -Freezer: 3 large-capacity of -Net capacity (L): 249 (179 -Electric consumption: 216 k -Climate class N/ST (16-38°) -LED lighting -Sliding door system -Reversible doors	julation in refrigerator Irawer Irawers + 70)	-1.76m static two doors fridg -Energy efficiency E -Homogeneous cold inside -Mechanical temperature re -Refrigerator: 1 vegetable d -Integrated door handle -Net capacity (L): 294 (225+ -Electric consumption : 207 -Climate class N/ST (16-38°) -Inner light -Reversible doors	the refrigerator egulation drawer 69) kW/year











1.77 M STATIC TWO DOO	RS
EFT-1711 WH	White
Cod.: 924271331 - EAN	: 8422248350631



-1.76m static two doors fridge -Energy efficiency E -Homogeneous cold inside the refrigerator -Mechanical temperature regulation -Refrigerator: 1 vegetable drawer -Integrated door handle -Net capacity (L): 294 (225+69) -Electric consumption : 207 kW/year -Climate class N/ST (16-38°) -Inner light -Reversible doors

1.61 M STATIC TWO DC	ORS	
EFT-1612 WH	White	NEW
Cod.: 924271352 - E/	AN: 8422248373777	7









1 (luc static true de sur fridere
-1.61m static two doors fridge
-Energy efficiency E
-Homogeneous cold inside the refrigerator
-Mechanical temperature regulation
-Refrigerator: 1 vegetable drawer
-Integrated door handle
-Net capacity (L): 243 (202 + 41)
-Electric consumption : 202 Kw/year
-Climate class N/ST (16-38°)
-Inner light

-Reversible doors





edesə



White

7	
	1 11 11 11 11 11 11 11 11 11 11 11 11 1
	6 9 0
	2.4.4

1.85 M NO FROST ONE	DOOR

 EFS-1823 NF EX
 Stainless Steel

 Cod.: 924271311 - EAN: 8422248108720



-1.43m static two doors fridge

Cod.: 924271333 - EAN: 8422248350655

WITH PLUG

- -Energy efficiency E
- -Homogeneous cold inside the refrigerator
- -Mechanical temperature regulation

1.43 M STATIC TWO DOORS

LED

EFT-1411 WH

Ε

ENERGY EFFICIENC)

- -Refrigerator: 1 vegetable drawer
- -Integrated door handle
- -Net capacity (L): 204 (163 + 41)
- -Electric consumption : 176 kW/year
- -Climate class N/ST (16-38°)
- -Inner light
- -Reversible doors





- -Energy efficiency E
- TOTAL No Frost technology
- -Electronic temperature regulation in refrigerator
- -Digital LED screen electronic control
- -"Super" function in refrigerator
- -Refrigerator: 1 low temperature drawer and 1 Fresh Box drawer
- -Metallic winerack
- -Balconies on freezer door
- -Bar metallic handle easy opened
- -Net capacity (L): 362
- -Electric consumption : 118 kW/year
- -Climate class SN/N/ST/T (10-43°)
- -LED strip lightning
- -Reversible doors
- -Includes kit to assemble a Door on Door system with model EZS-1823 NF EX







1.85 M TOTAL NO FROST SINGLE DOOR REFRIGERATOR

1.85 M NO FROST ONE DOOR

EZS-1823 NF EX Stainless Steel

Cod.: 924271310 - EAN: 8422248108713





Е

EFS-1823 NF WH



Cod.: 924271342 - EAN: 8422248350778





White





WITH PLUG

edesa

- -1.85m TOTAL No Frost one door freezer
- -Energy efficiency E
- TOTAL No Frost technology
- -Electronic temperature regulation in freezer
- -DUAL function
- -Digital LED screen electronic control
- -"Super" function in freezer
- -7 large-capacity drawers. 5 closed
- -Bar metallic handle easy opened
- -Net capacity (L): 273
- -Electric consumption : 245 kW/year
- -Climate class SN/N/ST/T (10-43°)
- -Reversible doors





- -Energy efficiency E
- TOTAL No Frost technology
- -Electronic temperature regulation in refrigerator
- -Digital LED screen electronic control
- -"Super" function in refrigerator
- -Refrigerator: 1 low temperature drawer and 1 Fresh Box drawer
- -Metallic winerack
- -Balconies on freezer door
- -Bar metallic handle easy opened
- -Net capacity (L): 362
- -Electric consumption : 118 kW/year
- -Climate class SN/N/ST/T (10-43°)
- -LED strip lightning
- -Reversible doors
- -Includes kit to assemble a Door on Door system with model EZS-1823 NF EX



⁺ measurements in mm

edesə





1.85 M TOTAL NO FROST SINGLE DOOR FREEZER

EZS-1823 NF WH	White	
Cod.: 924271343 - EAN	: 8422248350785	



TABLE TOP 0.85 M REFRIGERATOR

EFS-0813 WH	White	
Cod.: 924271334 - EAN: 8422248350662		

E	LED	¥
ENERGY	LED LIGHT	WITH PLUG

- -1.85m TOTAL No Frost one door freezer
- -Energy efficiency E
- -TOTAL No Frost technology
- -Electronic temperature regulation in freezer
- -DUAL function
- -Digital LED screen electronic control
- -"Super" function in freezer
- -7 large-capacity drawers. 5 closed
- -Bar metallic handle easy opened
- -Net capacity (L): 273
- -Electric consumption : 245 kW/year
- -Climate class SN/N/ST/T (10-43°)
- -Reversible doors



- -Energy efficiency E
- -Homogeneous cold inside the refrigerator
- -Mechanical temperature regulation
- -1 large capacity vegetable box
- -Integrated door handle
- -Net capacity (L): 131
- -Electric consumption : 90 kW/year
- -Climate class SN/N/ST (10-38°)
- -Inner light
- -Reversible doors











0.85 M FREEZER

EZS-0813 WH	White
Cod.: 924271335 - EA	N: 8422248350679



- -0.85m table top static freezer -Energy efficiency E -Homogeneous cold inside the refrigerator -Mechanical temperature regulation -3 large-capacity drawers -Integrated door handle -Net capacity (L): 88 -Electric consumption : 164 kW/year
- -Climate class SN/N/ST (10-38°)
- -Reversible doors

0.85 M REFRIGERATOR

EFS-0814 WH	White
Cod.: 924271336 -	EAN: 8422248350686



-0.85m table top static fridge -Energy efficiency E -Homogeneous cold inside the refrigerator -Mechanical temperature regulation -1 large capacity vegetable box -1 large-capacity drawers -Integrated door handle -Net capacity (L): 113 (97 + 16) -Electric consumption : 142 kW/year -Climate class N/ST (16-38°) -Inner light

-Reversible doors









0.84 M REFRIGERATOR

EFS-0911 WH	White
Cod.: 924271337 - EAN: 8422248350709	



0.5 M STATIC TABLE TOP REFRIGERATOR **EFS-0411 WH** White **Cod.:** 924271338 - **EAN:** 8422248350716



- -0.84m table top static fridge with 0° chiller compartiment. Lower depth
- -Energy efficiency E
- -Homogeneous cold inside the refrigerator
- -Mechanical temperature regulation
- -1 large capacity vegetable box
- -Balconies on freezer door
- -Integrated door handle
- -Net capacity (L): 93
- -Electric consumption : 86 kW/year
- -Climate class SN/N/ST/T (10-43°)

- -0.5m table top static fridge with 0° chiller compartment. Lower depth
 -Energy efficiency E
 -Homogeneous cold inside the refrigerator
- -Mechanical temperature regulation
- -Balconies on freezer door
- -Integrated door handle
- -Net capacity (L): 47
- -Electric consumption : 80 kW/year
- -Climate class N/ST/T (16-43°)





0.82 M BUILT IN REFRIGERATOR

LED

LED LIGHT

-0.82m TOTAL No frost built in fridge

-Digital LED screen electronic control

-"Super" function in refrigerator

-Balconies on freezer door -Net capacity (L): 138

-LED lighting -Reversible doors

-1 large capacity vegetable box

-Electric consumption : 93 kW/year

-Climate class SN/N/ST (10-38°)

-Homogeneous cold inside the refrigerator

-Electronic temperature regulation in refrigerator

Cod.: 924271339 - EAN: 8422248350723

FUNCTION IN FREEZER

EFS-0513 I

-Energy efficiency E

Ε

ENERGY EFFICIENCY

edesə



White

WITH PLUG



0.82 M BUILT IN REFRIGERATOR



- -0.82m built in fridge with freezer
- -Energy efficiency E
- -Electronic temperature regulation in refrigerator
- -Digital LED screen electronic control
- -"Super" function in freezer
- -1 large capacity vegetable box
- -Balconies on freezer door
- -Net capacity (L): 104
- -Electric consumption : 118 kW/year
- -Climate class SN/N/ST (10-38°)
- -LED lighting -Reversible doors

595 818 545



edesa



0.82 M SINGLE DOOR FREEZER

EZS-0513 I	White
Cod.: 924271340 -	EAN: 8422248350730

-Electronic temperature regulation in refrigerator

-Digital LED screen electronic control

-Electric consumption : 178 kW/year

-Climate class SN/N/ST (10-38°)



-0.82m one door freezer

-"Super" function in freezer

-3 large-capacity drawers

-Net capacity (L): 101

-Reversible doors

-Energy efficiency E

NO FROST ONE DOOR FREEZER

Stainless Steel

Cod.: 924271348 - EAN: 8422248373272



EZS-1732 NF EX



NEW

- -1.72m TOTAL no frost freezer
- -Energy efficiency E
- -Homogeneous cold inside the freezer
- -Electronic temperature regulation
- -Electronic control
- -"Super" function in freezer
- -7 large-capacity drawers. 5 closed
- -Bar handle
- -Net capacity (L): 238 -Electric consumption : 234 kW/year
- -Climate class N/ST/T (16-43°)
- -LED lighting
- -Reversible doors









edesa

NO FROST ONE DOOR FREEZER	
EZS-1732 NF WH	White
Cod.: 924271345 - EAN:	8422248350808



-1.72m TOTAL no frost freezer
Energy efficiency E
Homogeneous cold inside the freezer
Electronic temperature regulation
Electronic control
"Super" function in freezer
7 large-capacity drawers. 5 closed
Bar handle
Net capacity (L): 238
Electric consumption : 234 kW/year
Climate class N/ST/T (16-43°)
LED lighting
Reversible doors





-1.42m static freezer -Energy efficiency E -Homogeneous cold inside the freezer -Mechanical temperature regulation -5 large-capacity drawers. 3 closed -Bar handle -Net capacity (L): 160 -Electric consumption : 183 kW/year -Climate class N/ST/T (16-43°) -LED lighting -Reversible doors





* measurements in mm

129

HORIZONTAL FREEZER

METAL DUAL NO FROST

-0.86m horizontal freezer

-Homogeneous cold inside the freezer

-Mechanical temperature regulation

-Electric consumption : 260 kW/year

-Energy efficiency E

-Net capacity (L): 392

-Climate class S T (16-43°)

-DUAL function

-2 baskets

-LED lighting

-External

EZH-5011

Е

ENERGY EFFICIENCY



Cod.: 928271347 - EAN: 8422248350822

LED

LED LIGHT

White

11

WITH PLUG



HORIZONTAL F	REEZER
--------------	--------

EZH-4211	White
Cod.: 928271181 -	EAN: 8422248350839





-0.83m horizontal freezer

- -Energy efficiency E
- -Homogeneous cold inside the freezer
- -Mechanical temperature regulation
- -DUAL function
- -1 baskets -External
- -Net capacity (L): 418
- -Electric consumption : 269 kW/year
- -Climate class SN/N/ST/T (10-43°)









HORIZONTAL FREEZER EZH-3511 White Cod.: 928271183 - EAN: 8422248350860



-0.86m horizontal freezer
-Energy efficiency E
-Homogeneous cold inside the freezer
-Mechanical temperature regulation
-DUAL function
-2 baskets
-External
-Net capacity (L): 349
-Electric consumption : 247 kW/year
-Climate class ST (16-43°)

-LED lighting



HORIZONTAL FREEZER		
EZH-3011	White	
Cod.: 928271184 - EAN	: 8422248350877	



-0.85m horizontal freezer -Energy efficiency E -Homogeneous cold inside the freezer -Mechanical temperature regulation -2 baskets -Recessed handle -Net capacity (L): 293 -Electric consumption : 230 kW/year

-Climate class SN/N/ST/T (10-43°)





FRIDGES AND FREEZERS

edesə





HORIZONTAL FREEZER		
EZH-2811	White	
Cod.: 928271185 - E	AN: 8422248350884	



-0.86m horizontal freezer -Energy efficiency E -Homogeneous cold inside the freezer -Mechanical temperature regulation -DUAL function -1 baskets -External -Net capacity (L): 275 -Electric consumption : 225 kW/year -Climate class ST (16-38°) -LED lighting

HORIZONTAL FREE	EZER	
EZH-2014		
Cod.: 92827118	6 - EAN: 8422248350	0891
-	IED II	



-0.86m horizontal freezer

- -Energy efficiency E
- -Homogeneous cold inside the freezer
- -Mechanical temperature regulation
- -DUAL function
- -1 baskets
- -External
- -Net capacity (L): 209
- -Electric consumption : 203 kW/year
- -Climate class ST (16-38°)
- -LED lighting









edesa

HORIZONTAL FREEZER	
EZH-2011	White
Cod.: 928271187 - EA	N: 8422248350907



- -0.85m horizontal freezer -Energy efficiency E -Homogeneous cold inside the freezer -Mechanical temperature regulation -DUAL function -1 baskets -Recessed handle -Net capacity (L): 198
- -Electric consumption : 200 kW/year
- -Climate class SN/N/ST (10-38°)

HORIZONTAL FREEZER

EZH-1011	White
Cod.: 928271188 -	EAN: 8422248350914



-0.85m horizontal freezer -Energy efficiency E -Homogeneous cold inside the freezer -Mechanical temperature regulation -DUAL function -1 baskets -Recessed handle -Net capacity (L): 99 -Electric consumption : 169 kW/year

-Climate class SN/N/ST (10-38°)





edesə





HORIZONTAL F	REEZER		HORIZONTAL FREEZER				
EZH-1111	White	NEW	EZH-0	611	White		
Cod.: 928271	191 - EAN: 8422248100748		Cod.:	9282711	74 - EAN: 8422248100687		
ENERGY EFFICIENCY WITH PLUG			ENERGY EFFICIENCY	WITH PLUG			

- -0.84m horizontal freezer -Energy efficiency E -Homogeneous cold inside the freezer -Mechanical temperature regulation -Recessed handle -Net capacity (L): 105 -Electric consumption : 162 kW/year
- -Climate class SN/N/ST/T (10-43°)







edesə



FRIDGES AND FREEZERS

Code	924271324	924271323	924271321	924271309	924271326	924271264	924271265	
EAN	8422248350549	8422248350532	8422248343107	8422248343084	8422248350570	8422248097024	8422248097031	
	ESS-1833	ESS-1832	EFC-2035	EFC-1822 NF	EFC-7832 DNF	EFC-2032 NF	EFC-2032 NF	
Model	NFEX	NFEX	NFEX	GBK	EX /A	EX /A	WH/A	
Finish	Stainles Steel	Stainles Steel	Stainles Steel	Black glass	Stainless steel	Stainless steel	White	
Product fiche according to EU Regulation 2019/2016								
Category	7	7	7	7	6	7	7	
Energy efficiency class	D	E	D	E	E	E	E	
Energy consumption [kWh/year]	256	309	197	243	268	231	231	
Refrigerator storage volume [I]	349	334	238	207	316	247	247	
Freezer storage volume **** [I]	206	185	98	97	119	83	83	
Star rating	4	4	4	4	4	4	4	
Frost-free fridge	•	•	•	•	•	•	•	
Frost-free freezer	•	•	•	•	•	•	•	
Power cut safe [h]	6	6	10	10	12	9	9	
Freezing capacity [kg/24h]	12	11	6	6	9	3,89	3,89	
Climate class (2)	SN/N/ST	SN/N/ST	SN/N/ST/T	SN/N/ST/T	N/ST	N/ST	N/ST	
Noise emissions [dBA]	37	42	36	39	41	41	41	
Installation type	Free standing	Free standing	Free standing	Free standing	Free standing	Free standing	Free standing	
	rice standing	i ree stanuing	i ree stanuing	i ree stanuing	Thee scanding	i ree stariurig	i ree stanuing	
Dimmensions								
Height [mm]	1765	1786	2004	1860	1880	2010	2010	
Width [mm]	897	910	595	595	700	595	595	
Depth [mm]	706	646	590	590	666	630	630	
Opening of the door	Right - Left	Right - Left	Right	Right	Right	Right	Right	
Reversible doors	-	-	•	•	•	•	•	
Wheels	•	•	•	•	•	•	•	
	Recessed	Recessed	External metal	Recessed	External metal	External metal	Recessed	
External / Recessed handle	handle	handle	look	handle	look	look	handle	
Control								
Cooling type	Total No Frost	Total No Frost	Total No Frost	Total No Frost	Metal DUAL No	TOTAL No Frost	TOTAL No Frost	
					Frost			
Control	Electronic	Electronic	Electrónico	Electrónico	Electronic	Electronic	Electronic	
Display	•	•	•	•	•	•	•	
Electronic refrigerator temperature regulation	•	•	•	•	•	•	•	
Electronic freezer temperature regulation	•	•	•	•	•	-	-	
Super cooling / Super freezing function	• - •	0 - •	0 - •	0 - •	• - •	•-0	•-0	
Holiday function	•	•	-	-	•	-	-	
Winter-Summer function	-	-	-	-	-	•	•	
Refrigerator equipment								
Number of door balconies	3	3	4	3	4	5	5	
Number of glass shelves	4	4	3	2	3	4	4	
Wine rack	-	•	-	•	-	•	•	
Drawer for fruits and vegetables	2	2	2	1	2	1	1	
Chiller for meat and fish	-	-	-	1	1	1	1	
Metallic inner decoration	-	-	-	-	•	-	-	
Number of egg tray - Egg capacity	2-6	2-6	2-6	2-6	1-6	1-6	1-6	
Freezer equipment								
Number of drawers - closed drawers			1			0.0	0 0	
	2-2	2-2	3-3	3-3	3-2	3-3	3 - 3	
Ice trays - Ice cube capacity	2-2 1-12	2-2 1-20	3-3 1-12	3-3 1-12	3-2 1-12	1-12	3 - 3 1-12	
Ilumination	1-12	1-20	1-12	1-12	1-12	1-12	1-12	
Ilumination Fridge / Freezer lightning	1-12 • - •	1-20 ● - ●	1-12 • - O	1-12 • - O	1-12 • - O	1-12 • - O	1-12 • - O	
Ilumination	1-12	1-20	1-12	1-12	1-12	1-12	1-12	
Ilumination Fridge / Freezer lightning LED lightning Power and water connection	1-12 • - • • - •	1-20 • - • • - •	1-12 • - 0 • - 0	1-12 ● - O ● - O	1-12 ● - O ● - O	1-12 • - 0 • - 0	1-12 ● - O ● - O	
Ilumination Fridge / Freezer lightning LED lightning	1-12 • - •	1-20 ● - ●	1-12 • - O • - O 220-240	1-12 • - O				
Ilumination Fridge / Freezer lightning LED lightning Power and water connection	1-12 • - • • - •	1-20 • - • • - •	1-12 • - 0 • - 0	1-12 ● - O ● - O	1-12 ● - O ● - O	1-12 • - 0 • - 0	1-12 ● - O ● - O	
Ilumination Fridge / Freezer lightning LED lightning Power and water connection Voltage range [V]	1-12 • - • 220-240	1-20 • - • 220-240	1-12 • - O • - O 220-240	1-12 • - O • - O 220-240				
Ilumination Fridge / Freezer lightning LED lightning Power and water connection Voltage range [V] Frecuency [Hz]	1-12 • - • • - • 220-240 50	1-20 • - • 220-240 50	1-12 • - O • - O 220-240 50	1-12 • - O • - O 220-240 50	1-12 O O 220-240 50	1-12 O O 220-240 50	1-12 O - O 220-240 50	
Ilumination Fridge / Freezer lightning LED lightning Power and water connection Voltage range [V] Frecuency [Hz] Rated power [W]	1-12	1-20 • • • • • 220-240 50 185	1-12 - O - O 220-240 50 150	1-12 - O - O 220-240 50 150	1-12 - O - O 220-240 50 130	1-12 - O - O 220-240 50 190	1-12 O O 220-240 50 190	

edesa

	924271353	924271354	924271349	924271351	924271327	924271325	924271328	924271329	924271344	924271330	924271331
8			8422248373753	8422248373760		8422248350570				8422248350624	
	EFC-18330 NF WH	EFC-18330 NF EX	EFC-1834 NF EX	EFC-1834 NF WH	EFC-1821 NF EX /A	EFC-1821 NF WH /A	EFC-1822 NF WH	EFC-1821 ST WH	EFC-1711-I	EFT-1711 EX	EFT-1711 WH
	White	Stainless steel	Stainless steel	White	Stainless steel	White	White	White	Built-in	Stainless steel	White
	7	7	7	7	7	7	7	7	7	7	7
	D	D	E	E	E	E	E	E	E	E	E
	186	186	243	243	235	235	220	210	216	207	207
	210	210	207	207	224	224	182	191	179	225	225
	83	83	97	97	86	86	71	71	70	69	69
	4	4	4	4	4	4	4	4	4	4	4
	•	•	•	•	•	•	•	-	_	-	-
	•	•	•	•	•	•	•	-	-	-	-
	8,5	8,5	10	10	8	8	9,5	12	10	8	8
	3,8	3,8	6	6	3,9	3,9	3,2	3,2	3,2	3,2	3,2
	N/ST	N/ST	SN/N/ST/T	SN/N/ST/T	SN/N/ST	SN/N/ST	N/ST	N/ST	N/ST	N/ST	N/ST
	39	39	39	39	42	42	40	40	39	40	40
					46	42	40	40		40	40
	ree standing	Free standing	Free standing	Free standing	Free standing	Free standing	Free standing	Free standing	Built-in	Free standing	Free standing
	1860	1860	1860	1860	1880	1880	1800	1800	1778	1760	1760
	600	600	595	595	595	595	540	550	540	595	595
	605	605	590	590	630	630	600	560	540	550	550
	Right	Right	Right	Right	Right	Right	Right	Right	Right	Right	Right
	•	•	•	•	•	•	•	•	•	•	•
	•	•	•	•	•	•	-	-	-	•	•
	Recessed	Recessed	Recessed	Recessed	Recessed	Recessed	Recessed	Recessed		Recessed	Recessed
	handle	handle	handle	handle	handle	handle	handle	handle	-	handle	handle
	lotal No Frost	Total No Frost	TOTAL No Frost	TOTAL No Frost	TOTAL No Frost	TOTAL No Frost	IOTAL NO Frost	Static	Static	Satic	Satic
	Electrónico	Electrónico	Electronic	Electronic	Electronic	Electronic	Electronic	Electronic	Mechanic	Mechanic	Mechanic
	-	-	•	•	-	-	-	-	-	-	-
	•	•	•	•	•	•	•	•	•	-	-
	•	•	•	•	-	-	•	-	-	-	-
	-	-	0 - •	0 - •	•-0	•-0	-	-	•-•	-	-
	-	-	-	-	-	-	-	-	-	-	-
	-	-	-	-	-	-	-	-	-	-	-
	3	3	3	3	5	5	3	3	3	3	3
	3	3	2	2	4	4	4	4	4	4	4
	-	-	-	-	-	-	-	-	-	-	-
	1	1	2	2	1	1	1	1	1	1	1
	-	-	-	-	-	-	-	-	-	-	-
	-	-	-	-	-	-	-	-	-	-	-
	2-6	2-6	2-6	2-6	1-6	1-6	1-6	1-6	1-6	1-6	1-6
	2.2	2.2	2.2	2.2	2.2	2.2	2.2	2.2	2.2		-
	3-3	3-3	3-3	3-3	3-3	3-3	3-2	3-3	3-3	-	
	1-12	1-12	1-12	1-12	1-12	1-12	1-12	1-12	1-12	1-12	1-12
	•-0	•-0	•-O	•-0	•-O	•-0	•-0	•-0	•-0	•-O	•-O
	•-0	•-0	•-0	•-0	•-0	•-0	•-0	•-0	•-0	-	-
	220-240	220-240	220-240	220-240	220-240	220-240	220-240	220-240	220-240	220-240	220-240
	50	50	50	50	50	50	50	50	5	50	50
	150	150	50	50	170	170	110		115	98	98
	150	1	0.6	0.6	0.8	0.8	0,9	115 0,75	0,75	0.8	0.8
	Schuko	Schuko	0.6 Schuko	Schuko	0.8 Schuko	0.8 Schuko	0,9 Schuko	0,75 Schuko			0.8 Schuko
	1600	1600	2000	2000	1700	1700	1600	1600	Schuko 1600	Schuko 1700	1700
	1000	1000	2000	2000	1700	1700	1000	1000	1000	1700	1/00

	_								_
Code	924271352	924271333	924271311	924271310	924271342	924271343	924271334	924271335	
EAN	8422248373777	8422248350655					8422248350662	8422248350679	
Model	EFT-1612 WH	EFT-1411 WH	EFS-1823 NF EX	EZS-1823 NF EX	EFS-1823 NF WH	EZS-1823 NF WH	EFS-0813 WH	EZS-0813 WH	
Finish	White	White	Stainles Steel	Stainles Steel	White	White	White	White	
Product fiche according to EU Regulation 2019/2016									
Category	7	7	1	8	1	8	1	8	
Energy efficiency class	E	E	E	E	E	E	E	E	
Energy consumption [kWh/year]	177	176	118	245	118	245	90	167	
Refrigerator storage volume [l]	202	163	362	-	362	-	131	-	
Freezer storage volume **** [I]	41	41	-	273	-)	273		88	
Star rating	4	4	-	4	-	4	-	4	
Frost-free fridge		-	•	-	•	-		-	
Frost-free freezer	-	-	-	•	-	•	-	-	
Power cut safe [h]	12	8	_	8		8		15	
Freezing capacity [kg/24h]	2	2	-	o 12,4	-	o 12,4	-	4	
Climate class (2)	N/ST	N/ST	- SN/N/ST/T	SN/N/ST/T	- SN/N/ST/T	SN/N/ST/T	- SN/N/ST	4 SN/N/ST	
Noise emissions [dBA]	40	40	41	41	41	41	39	39	
Installation type	Free standing	Free standing	Free standing	Free standing	Free standing	Free standing	Free standing	Free standing	
Dimmensions									
Height [mm]	1610	1430	1850	1850	1850	1850	845	845	
Width [mm]	550	550	595	595	595	595	553	553	
Depth [mm]	542	550	618	618	618	618	574	574	
Opening of the door	Right	Right	Right	Left	Right	Left	Right	Right	
Reversible doors	•	•	•	e	•	e	•	e	
Wheels	•	•	•	•	•	•	-	-	
	Recessed	Recessed	External metal	External	External metal	External metal	Recessed		
External / Recessed handle	handle	handle	look	metal look	look	look	handle	Recessed handle	
Control									
Cooling type	Satic	Satic	TOTAL No	TOTAL No	TOTAL No	TOTAL No	Static	Static	
			Frost	Frost	Frost	Frost			
Control	Mechanic	Mechanic	Electronic	Electronic	Electronic	Electronic	Mechanic	Mechanic	
Display	- /	-	•	•	•	•	-	-	
Electronic refrigerator temperature regulation	-	1	•	-	•	-	-	-	
Electronic freezer temperature regulation									
Super cooling / Super freezing function		-	-	•	-	•	-	-	
Holiday function	-	-	- •-0	•	- •- 0	• 0 - •	-	-	
Winter-Summer function	-	-	- •-0 -	-		• 0 - • -	-	-	
		- - - -	- - 0 - -	-		• • - -	- - -	- - -	
Refrigerator equipment	-	-	-	0 - • -	•-0 -	-	-	-	
	-	-	-	0 - • -	•-0 -	-	-	-	
Refrigerator equipment	-	-	-	0-•	•-0 - -	-	-	-	
Refrigerator equipment Number of door balconies	- - 4		5	0-•	•-0 - - 5	-	- - 3	-	
Refrigerator equipment Number of door balconies Number of glass shelves	- - 4	- - 3 4	- - 5 6	- • - - -	•-0 - - 5	-	- - 3 3	-	
Refrigerator equipment Number of door balconies Number of glass shelves Wine rack	- - 4 3 -	- - 3 4 -	- - 5 6	- • - - -	•-0 - - 5	-	- - 3 3 -	-	
Refrigerator equipment Number of door balconies Number of glass shelves Wine rack Drawer for fruits and vegetables	- - 4 3 - 1	- - 3 4 - 1	- - 5 6 • 1		•-0 - - 5 6 • 1	- - - - - - - -	- - 3 3 - 1	- - - - - - -	
Refrigerator equipment Number of door balconies Number of glass shelves Wine rack Drawer for fruits and vegetables Chiller for meat and fish Metallic inner decoration	- - 4 3 - 1 -	- - 3 4 - 1 -	- - 5 6 • 1 1	0-• - - - - - - - - -	● - O - - 5 6 ● 1 1 1	- - - - - - - - - - - - -	- - 3 3 - 1 -	- - - - - - - -	
Refrigerator equipment Number of door balconies Number of glass shelves Wine rack Drawer for fruits and vegetables Chiller for meat and fish	- - 4 3 - 1 - - -	- - 3 4 - 1 - -	- - 5 6 • 1 1 -	O - • - - - - - - - - - - - - -	•-0 - - 5 6 • 1 1 1 -	- - - - - - - - -	- - 3 3 - 1 - -	- - - - - - - - - - -	
Refrigerator equipment Number of door balconies Number of glass shelves Wine rack Drawer for fruits and vegetables Chiller for meat and fish Metallic inner decoration Number of egg tray - Egg capacity	- - 4 3 - 1 - - -	- - 3 4 - 1 - -	- - 5 6 • 1 1 -	O - • - - - - - - - - - - - - -	•-0 - - 5 6 • 1 1 1 -	- - - - - - - - -	- - 3 3 - 1 - -	- - - - - - - - - - -	
Refrigerator equipment Number of door balconies Number of glass shelves Wine rack Drawer for fruits and vegetables Chiller for meat and fish Metallic inner decoration Number of egg tray - Egg capacity Freezer equipment Number of drawers - closed drawers	- - - - - - 1 - - - - - - - - - -	- - 3 4 - 1 - 1-6	- - 5 6 • 1 1 1 - 1-6	O - ● - - - - - - - - - - - - - - - - - -	●-0 - - 5 6 ● 1 1 1 - 1-6	- - - - - - - - - -	- - 3 - 1 - 1-6	- - - - - - - - - -	
Refrigerator equipment Number of door balconies Number of glass shelves Wine rack Drawer for fruits and vegetables Chiller for meat and fish Metallic inner decoration Number of egg tray - Egg capacity Freezer equipment Number of drawers - closed drawers Ice trays - Ice cube capacity	- - - - - - 1-6	- - 3 4 - 1 - 1-6	- - 5 6 • 1 1 1 - 1-6	O - ● - - - - - - - - - - - - - - - - - -	•-0 - - 5 6 • 1 1 1 - 1-6	- - - - - - - - - - - - - - - - - -	- - 3 - - 1 - 1-6	- - - - - - - - - - - - - - - - - - -	
Refrigerator equipment Number of door balconies Number of glass shelves Wine rack Drawer for fruits and vegetables Chiller for meat and fish Metallic inner decoration Number of egg tray - Egg capacity Freezer equipment Number of drawers - closed drawers Ice trays - Ice cube capacity Ilumination	- - - - - - 1-6	- - 3 4 - 1 - 1-6	- - 5 6 • 1 1 1 - 1-6	O - ● - - - - - - - - - - - - - - - - - -	•-0 - - 5 6 • 1 1 1 - 1-6	- - - - - - - - - - - - - - - - - -	- - 3 - - 1 - 1-6	- - - - - - - - - - - - - - - - - - -	
Refrigerator equipment Number of door balconies Number of glass shelves Wine rack Drawer for fruits and vegetables Chiller for meat and fish Metallic inner decoration Number of egg tray - Egg capacity Freezer equipment Number of drawers - closed drawers Ice trays - Ice cube capacity Ilumination Fridge / Freezer lightning	- - - - - - 1-6 - - - - 1-12	- - 3 4 - 1 - 1-6 - 1-12	- - 5 6 • 1 1 1 - 1-6	O - ● - - - - - - - - - - - - - - - - - -	● - O - - 5 6 ● 1 1 1 - 1-6 - -	- - - - - - - - - - - - - - - - - - -	- - 3 3 - 1 - 1-6 - -	- - - - - - - - - - - - - - - - - - -	
Refrigerator equipment Number of door balconies Number of glass shelves Wine rack Drawer for fruits and vegetables Chiller for meat and fish Metallic inner decoration Number of egg tray - Egg capacity Freezer equipment Number of drawers - closed drawers Ice trays - Ice cube capacity Ilumination Fridge / Freezer lightning LED lightning	- - - - - - 1-6 - - 1-12	- - - - - 1-6 - - 1-12	- - 5 6 • 1 1 1 - 1-6 · ·	O-● - - - - - - - - - - - - - - - - - -	● - O - - - 5 6 ● 1 1 1 1 - 1-6 - - - - - - - - - - - - -	- - - - - - - - - - - - - - - - - - -	- - 3 3 - 1 - 1-6 - - -	- - - - - - - - - - - - - - - - - - -	
Refrigerator equipment Number of door balconies Number of glass shelves Wine rack Drawer for fruits and vegetables Chiller for meat and fish Metallic inner decoration Number of egg tray - Egg capacity Freezer equipment Number of drawers - closed drawers Ice trays - Ice cube capacity Ilumination Fridge / Freezer lightning LED lightning Power and water connection	- - - - - - 1-6 - - 1-12	- - 3 4 - 1 - 1-6 - 1-12	- - 5 6 • 1 1 1 - 1-6 · ·	O - ● - - - - - - - - - - - - - - - - - -	● - O - - - - - - - - - - - - - - - - - -	- - - - - - - - - - - - - - - - - - -	- - 3 3 - 1 - 1-6 - - -	- - - - - - - - - - - - - - - - - - -	
Refrigerator equipment Number of door balconies Number of glass shelves Wine rack Drawer for fruits and vegetables Chiller for meat and fish Metallic inner decoration Number of egg tray - Egg capacity Freezer equipment Number of drawers - closed drawers Ice trays - Ice cube capacity Ilumination Fridge / Freezer lightning LED lightning Power and water connection Voltage range [V]	- - - - - - - - - - - - - - - - - - -	- - 3 4 - 1 - 1-6 - - 1-12 - - 0 - 0 - 220-240	- - 5 6 • 1 1 1 - 1-6 · · · · · · · · · · · ·	O - ● - - - - - - - - - - - - - - - - - -	● - O - - - - - - - - - - - - - - - - - -	- - - - - - - - - - - - - - - - - - -	- - 3 3 - 1 1 - 1-6 - - - - - - 220-240	- - - - - - - - - - - - - - - - - - -	
Refrigerator equipment Number of door balconies Number of glass shelves Wine rack Drawer for fruits and vegetables Chiller for meat and fish Metallic inner decoration Number of egg tray - Egg capacity Freezer equipment Number of drawers - closed drawers Ice trays - Ice cube capacity Ilumination Fridge / Freezer lightning LED lightning Power and water connection Voltage range [V] Freeuency [Hz]	- - - - - - 1-6 - - 1-12	- - - - - 1-6 - - - - - - - - - - - - -	- - 5 6 • 1 1 1 - 1-6 · · · · · · · · · · · · · · · · · · ·	O - ● - - - - - - - - - - - - - - - - - -	● - O - - - - - - - - - - - - - - - - - -		- - 3 3 - 1 1 - 1-6 - - - - - 220-240 50	- - - - - - - - - - - - - - - - - - -	
Refrigerator equipment Number of door balconies Number of glass shelves Wine rack Drawer for fruits and vegetables Chiller for meat and fish Metallic inner decoration Number of egg tray - Egg capacity Freezer equipment Number of drawers - closed drawers Ice trays - Ice cube capacity Ilumination Fridge / Freezer lightning LED lightning Power and water connection Voltage range [V] Freeuency [Hz] Rated power [W]	- - - - - - 1-6 - - 1-12 - - - - - - - - - - - - - - -	- - - - - 1-6 - - - - - - - - - - - - -	- - 5 6 • 1 1 1 - 1-6 · · · · · · · · · · · · · · · · · · ·	O - ● - - - - - - - - - - - - - - - - - -	● - O - - - - - - - - - - - - - - - - - -	- - - - - - - - - - - - - - - - - - -	- - - - - - - - - - - - - - - - - - -	- - - - - - - - - - - - - - - - - - -	
Refrigerator equipment Number of door balconies Number of glass shelves Wine rack Drawer for fruits and vegetables Chiller for meat and fish Metallic inner decoration Number of egg tray - Egg capacity Freezer equipment Number of drawers - closed drawers Ice trays - Ice cube capacity Ilumination Fridge / Freezer lightning LED lightning Power and water connection Voltage range [V] Freeuency [Hz]	- - - - - - - - - - - - - - - - - - -	- - - - - 1-6 - - - - - - - - - - - - -	- - 5 6 • 1 1 1 - 1-6 · · · · · · · · · · · · · · · · · · ·	O - ● - - - - - - - - - - - - - - - - - -	● - O - - - - - - - - - - - - - - - - - -		- - 3 3 - 1 1 - 1-6 - - - - - 220-240 50	- - - - - - - - - - - - - - - - - - -	

924271336	924271337	924271338	924271339	924271341	924271340	924271348	924271345	924271346
8422248350686	8422248350709	8422248350716	8422248350723	8422248350747	8422248350730	8422248373272	8422248350808	8422248350815
EFS-0814 WH	EFS-0911 WH	EFS-0411 WH	EFS-0513 I	EFS-0514 I	EZS-0513 I	EZS-1732 NF EX	EZS-1732 NF WH /A	EZS-1412
White	White	White	Built-in	Built-in	Built-in	Stainles Steel	White	White
1	1	1	1	7	0	0	0	0
1 E	1 E	1 E	1 E	7 E	8 E	8 E	8 E	8 E
142	86	80	93	118	178	234	234	183
97	93	47	138	104	-	-	-	-
16	-	-	=	17	101	238	238	160
4	-	-	-	4	4	4	4	4
-	-	-	-	•	-	-	-	-
-	-	-	-	-	-	•	•	-
9	-	-	-	9	14	8	8	9
2	-	-	-	4	9,2	11,1	11,1	7,2
N/ST	SN/N/ST/T	N/ST/T	SN/N/ST	SN/N/ST	SN/N/ST	SN/N/ST/T	SN/N/ST/T	N/ST
39	41	41	37	35	38	41	41	42
Free standing	Free standing	Free standing	Built-in	Built-in	Built-in	Free standing	Free standing	Free standing
845	835	500	818	010	818	1720	1720	1420
553	488	485	595	818 595	595	595	595	550
574	400	465	595	545	545	635	635	550
Right	Right	Right	Right	Right	Right	Right	Right	Right
•	-	-	Mgrit	•	•	•	•	•
-	-	-	-	-	-	-	-	-
Recessed handle	Recessed handle	Recessed handle	-	-	-	External handle	External handle	External handle
0 1 11	o	o		0.11	0.11			01.11
Static	Static	Static	Satic	Satic	Satic	TOTAL No Frost	TOTAL No Frost	Static
Mechanic	Mechanic	Mechanic	Electronic	Electronic	Electronic	Electronic	Electronic	Mechanic
-	-	-	•	•	•	•	•	-
-	-	-	•	•	-	-	-	-
-	-	-	-	•	•	•	•	-
-	-	-	•-O	0 - •	0 - •	0 - •	0 - •	-
-	-	-	-	-	-	-	-	-
-	-	-	-	-	-	-	-	-
3	3	2	2	2		-	-	-
2	3	1	2	1		-	-	-
-	-	-	-	-	-	_	-	_
- 1	- 1	-	- 1	- 1	-	-	-	-
-	-	-	-	-	-	-	-	-
-	-	-	-	-	-	-	-	-
1-6	1-6	1-6	1-6	1-6	-	-	-	-
1-1	1-1	1	-	-	3-3	7-5	7-5	5-3
-	-	-	-	1-12	1-10	-	-	-
•-O	-	-	•-O	•-0	-	-	-	-
•	-	-	•	•	-	-	-	-
220-240	220-240	220-240	220-240	220-240	220-240	220-240	220-240	220-240
50	50	50	50	50	50	50	50	50
90	55	70	60	90	115	150	150	120
0,6	0.5	0.55	0.3	0.4	0,5	0.52	0.52	0.52
Schuko 1600	Schuko 1700	Schuko 1700	Schuko 1500	Schuko 1500	Schuko 1500	Schuko 1700	Schuko 1700	Schuko 1700
1000	1700	1700	1500	1300	1300	1700	1700	1700

Code	928271347	928271181	928271183	928271184	928271185	
EAN	8422248350822	8422248350839	8422248350860	8422248350877	8422248350884	
Model	EZH-5011	EZH-4211	EZH-3511	EZH-3011	EZH-2811	
Finish	White	White	White	White	White	
Product fiche according to EU Regulation 2019/2016	Winto	Winte	Winte	Winte	Winto	
Category	8	8	8	8	8	
Energy efficiency class	E	E	E	E	E	
Energy consumption [kWh/year]	260	269	247	230	255	
Refrigerator storage volume [I]	-	-	-	-	-	
Freezer storage volume [1]	393	418	349	293	275	
Star rating	4	418	4	4	4	
Star rating Frost-free fridge		-	-		-	
Frost-free friege Frost-free freezer	-	-	-	-	-	
Prost-free freezer Power cut safe [h]	- 47	50	- 37	- 25	37	
Power cut safe [h] Freezing capacity [kg/24h]	18	19	23	14	24	
Freezing capacity [kg/24h] Climate class (2)	18 T	19 SN/N/ST/T	ST ST	14 SN/N/ST/T	ST 24	
Climate class (2) Noise emissions [dBA]	42	SN/N/S1/1 44	44	SN/N/S1/1 41	44	
Noise emissions [dBA] Installation type	42 Free Standing	44 Free Standing	44 Free Standing	41 Free Standing	44 Free Standing	
Installation type Dimmensions	Free Standing	Free Stationing	Free Stanuing	Free Standing	Free Standing	
Dimmensions Height [mm]	860	825	860	844	860	
-	860 1700	825	860 1320	844	1090	
Width [mm]	1700 690	1416 750	1320 690	1065 592	1090 690	
Depth [mm]						
Opening of the door	Vertical	Vertical	Vertical	Vertical	Vertical	
Reversible doors						
Wheels	•	•	•		•	
External / Recessed handle	External	External	External	Recessed handle	External	
Control						
Cooling type	Static	Static	Static	Static	Static	
Dual function	•	•	•		•	
Control	Mechanic	Mechanic	Mechanic	Mechanic	Mechanic	
Display	- '	-	-		-	
Electronic refrigerator temperature regulation	- /	- /	- /	- /	- /	
Electronic freezer temperature regulation	-	-	-		-	
Super cooling / Super freezing function	- /	- /	- /	- /	- /	
Holiday function	- '	-	-	- 1	-	
Winter-Summer function	-	-	-	/	-	
Freezer equipment						
Number of drawers - closed drawers	- /	- /	- /	- /	- /	
Ice trays - Ice cube capacity	-	-	-	- 1	-	
Number of baskets	2	1	2	2	1	
Ilumination						
LED lightning	•	-	•	-	•	
Power and water connection						
Voltage range [V]	220-240	220-240	220-240	220-240	220-240	
Frecuency [Hz]	50	50	50	50-60	50	
Rated power [W]	140	86	130	200	130	
Rated current [A]	0,8	2	0,62	1,4	0,57	
Type of plug	Schuko	Schuko	Schuko	Schuko	Schuko	
Power cord length [mm]	2000	1700	2000	1700	2000	

928271186	928271187	928271188	928271191	928271174
8422248350891	8422248350907	8422248350914	8422248375733	8422248100687
E7U 2014	E7U 2011	E7U 1011	E7U 4444	E7U 0611
EZH-2014	EZH-2011	EZH-1011	EZH-1111	EZH-0611
White	White	White	White	White
8	8	8	8	8
E	E	E	E	E
203	200	169	162	154
-	-	-	-	-
209	198	99	105	59
4	4	4	4	4
-	-	-	-	-
-	-	-	-	-
37	20	17	20	22
16,5	9	4,5	12	8,6
ST	SN/N/ST	SN/N/ST	SN/N/ST/T	SN/N/ST/T
39	41	38	43	47
Free Standing	Free Standing	Free Standing	Free Standing	Free Standing
860	850	850	835-860	835
890	770	547	600-630	384
690	560	446	530-568	620
Vertical	Vertical	Vertical	Vertical	Vertical
-	-	-	-	-
•	-	-		-
External	Recessed handle	Recessed handle	Recessed handle	Recessed handle
Static	Static	Static	Static	Static
otatio	-	-	otatio	otatio
		•	-	-
Mechanic	Mechanic	Mechanic	Mechanic	Mechanic
-	-	-	-	-
-	-	-	-	-
-	-	-	-	-
-	-	-	-	-
-	-	-	-	-
-	-	-	-	-
-	-	-	-	-
-	-	-	-	-
1	1	1	-	-
•	-	-	-	-
000 010	000 010	000 010	000 010	000 010
220-240	220-240	220-240	220-240	220-240
50	50	50	50	50
73	130	80	60	60
0.52	0,9	0,5	0.4	0.4
Schuko	Schuko	Schuko	Schuko	Schuko
2000	1700	1700	150	150

FRIDGES AND FREEZERS

DISHWASHERS

60 CM FREE STANDING							
EDW-6242 X	152	EDW-6230 X	154	EDW-6230 WH	154	EDW-6231 X	155
EDW (221 WH	155	EDW /120 V	157		15/		157
EDW-6231 WH	155	EDW-6130 X	156	EDW-6130 WH	156	EDW-6120 WH	157
		, e 19		<u></u>		0.000	
45 CM FREE STANDING EDW-4710 X	150	EDW 4710 WH	150	EDW-4610 X	150	EDW-4610 WH	150
EDW-4/10 X	158	EDW-4710 WH	158	EDW-4610 X	159	EDW-4610 WH	159
				3 (B)		5 W () 8 8 8	
60 CM BUILT IN				45 CM BUILT IN			
EDB-6241-I SL	160	EDB-6130- I	160	EDB-4711-I SL	161	EDB-4610-I	161




REAL INOX - Quality and design go hand in hand with Aisi 430 stainless steel

Edesa dishwashers have been manufactured with high quality materials, which offer a greater durability and safety than others of lower qualities.

The door and panel of the stainless steel dishwashers incorporate the best stainless steel of the sector, the AISI 430, to ensure the user, as well as a gleaming image, an exceptional quality.

The display shows the remaining time of the washing process

Knowing the remaining time to finish the washing can be fundamental to plan your tasks. The display of the Edesa dishwashers will inform you to the minute

Integrated in your kitchen

The entire range of Edesa integrables is designed to comfortably be installed and ergonomics, being able to choose the size that best adapts to you.



Compact Slider, the dispenser that does not fail

The new and improved detergent dispenser system that many of the Edesa dishwashers incorporate has been designed to facilitate washing.

One of its advantages is that the opening is laterally sliding, which helps to always allow the detergent to be released, regardless of whether there are large plates or pots in front.

Another advantage of this dispenser is that being less bulky and occupy less space, the trays inside have larger dimensions, to optimize all the resources of space in the dishwasher.

Finally, its dosing system allows dosing the amount of brightener according to the need of washing to achieve better results in the dishes.



edesa



Enjoy the silence at home

Edesa dishwashers operates silently, allowing you to run it at any time of day without worrying about noise.



edesə

Third tray, order and much more

The third tray makes the dishwashing process more convenient and efficient.

Cutlery organization: Instead of using the traditional basket, the third tray allows you to place the cutlery in an orderly and separate manner, making it easier to collect it later.

Space saving: The third tray saves space in the dishwasher, since it is not necessary to use the lower basket for cutlery, taking advantage of that space to place more plates or pots.



Interior space: folding trays and lots of space

Kitchen without complexes! Use as many pots and tall glasses as necessary, because you have finally found a dishwasher that suits you.

All Edesa dishwashers incorporate folding supports in the lower tray, which allow placing pots, paella pans or any kitchen utensil, whatever their dimensions are.

And that is not all, because the folding supports of the upper tray allow you to place cups on a second level, and thus increase the washing space.

With Edesa you maximize the space, put a single wash cycle with all the dirty utensils and save on the light and water bill.





Push regulation system, details that make a difference

Edesa offers an easier to adjust upper tray.

Thanks to the Push system you can adapt in a much simpler way the perfect height in each wash.

Thus the space is used in a better way, either when you load tall cups in the upper tray or when you wash large pots in the lower tray.



Large capacity and inner versatility

You will not have any problem to wash all your dishes thanks to the large capacity of our dishwashers.

An inner improved design and two folding supports for the cups offer an even greater inner versatility.



Half load

This function is designed for when you need to wash dishes, but you do not have enough to completely fill the dishwasher.

Activating the half load function, the dishwasher will adjust the amount of water and electricity to achieve the best results by washing in both trays with the minimum consumption.

For those who can not decide, Edesa makes it easy

All dishwashers in the new Edesa range allow you to use both all-in-one tablets or liquid soap or powder.

The fact that they are programmed to reach the perfect temperature in the initial phase of the washing, allows the use of all-in-on soap pills, and thus facilitates its use.

Are you looking for a perfect drying? Auto Door opening

The dishwasher range presents an intelligent door opening for its most outstanding model, which consists in an automatically opening once the washing program is finished.

Thanks to this opening system, a faster and more efficient drying is achieved, since all the humidity that has been generated inside goes out to the outside, making the dishes dry with the air.





Edesa triple security system

In Edesa we think that security is fundamental so that you breathe tranquillity at home.

The triple security system of all dishwashers will foresee all the errors so that they do not turn into catastrophes.

This system controls the safety in three areas:

WATER CONTROL SYSTEM, OVERHEATING AND ANTI-OVERFLOW.

With the water control system, and through a solenoid valve, the water flow is closed when the dishwasher is not in operation, ensuring that there will be no unnecessary water losses.

The overheating protection system allows, through a sensor, to ensure that the heating is stopped in case the temperature increases above the safety level.

The last system, the anti-overflow, is a sensor that controls any involuntary leakage of internal water, preventing overflow.

edesa

Bottles

For lightly soiled loads such as glasses, glassware and fine china.

Self-cleaning

The self-cleaning function helps keeping the interior of the appliance clean and free of debris, cleaning the walls, base and filters of the dishwasher.

Hygiene

Helps keeping your kitchen utensils clean and germ-free.

Silence

Lower noise for washing at night or simply staying quiet while washing your dishes.

Silence Inverter

Thanks to the "Silence Inverter" system dishwashers are really efficient, achieving a B class.

The Inverter motor reduces friction, guaranteeing a longer lifetime.

Quick Programs - 30 'and 90'

Our dishwashers have an extra quick 30-minute program that saves water and prevents you from having to wait to fill it when there is little dirt.

The Express 90 minutes program allows you to get the best cleaning in the shortest possible time for the days when you can not wait.

Thus, you will not miss any piece of your crockery; you can use it again in record time.

Deferred programming of up to 24h

Our dishwashers are adapted to your schedule. The deferred programming function allows you to delay its start up to 24 hours. You decide when the washing starts up, so dishes are ready when you need them.













Crystal

Our dishwashers are provided with a special program for glasses, which ensures a brighter finish.

Automatic Program

You no longer have to worry about choosing the right program. Our dishwashers do it for you.

The innovative Automatic program analyses the existing dirt to automatically adjust the temperature and consumption.

Special functions

Extra drying

Thanks to this function you will leave the plates and cups with an even better finish. It increases the temperature and the duration in the drying phase, which allows an excellent result in all the crockery.

Flex Wash

You no longer have to wait to fill the dishwasher. Edesa gives you all the flexibility you need, because thanks to this function you can choose and wash only the load of the lower tray or the load of the upper tray.

Total Clean

This function is ideal for stains that are not easy to remove, for pots with abundant dirt or to completely eliminate the last night dinner remains stuck. Eliminate even the driest dirt thanks to the Edesa Total Clean!

Contributing to the reduction of electricity demand is one of our priorities, which is why we are working on reducing the energy consumption of our dishwashers in order to reach again the maximum energy classification according to the recent delegated regulation (EU) 2019/2017 & 2019/2022. So that you and your family can enjoy a cleaner world, the values have been rescaled, with classes A+++, A++ and A+ disappearing, starting from class A. This does not mean that now your dishwasher consumes more than before, but that the scale has changed.

With your new Edesa class C dishwasher, you will have significant energy and economic savings on your electricity bill, as well as a lower environmental impact.

With the inverter motors you will have triple tranquility; you will notice a lower consumption of electricity in your bill, less noise and the guarantee of 10 years in its motor.















-60 cm, 14 place settings free standing diswasher

-Energy Efficiency C

-3rd Cutlery rack

-9'8 liters of water consumption per cycle

-47 dB (A) of acoustic power

-Triple security system: watercontrol, overheating and anti-overflow

-7 programs

-Special programs: Express 90 ', Fast 30', Glass, Prewash and Automatic

-Functions: Delayed programming up to 24 hours, security lock.

-Special Functions: Total Clean, Flex Wash, Turbo+, pause and extra dry.

-Door with automatic opening

-Slider compact detergent dispenser. Suitable for all-in-1 tablets

-Display with information of: Deferred programming up to 24 hours, remaining time, selected program, salt, rinse aid and selected functions

-Height adjustable basket easily adjustable by Push system, with folding supports

-Bottom basket with folding supports

-Real Inox: door and panel made of authentic stainless steel





edesə

edesa





White

60 CM FREE S	TANDING
EDW-6230	Х

Real stainless steel

Cod.: 926270325 - EAN: 8422248351317











measurements in mm

TRIPLE SECURITY

60 CM FREE STANDING

EDW-6230 WH



Cod.: 926270326 - EAN: 8422248351324

-60 cm, 14 place settings free standing diswasher

-Energy Efficiency D

-11 liters of water consumption per cycle

-47 dB (A) of acoustic power

-Triple security system: watercontrol, overheating and antioverflow

GLASS

-7 programs

-Special programs: Express 90 ', Fast 30', Glass and Prewash -Functions: Delayed programming up to 24 hours

-Automatic opening door

-Slider compact detergent dispenser

-Suitable for all-in-1 tablets

-Display with information of: Deferred programming up to 24 hours, remaining time, selected program, salt and rinse aid -Height adjustable basket easily adjustable by Push system, with folding supports

-Bottom basket with folding supports

-Real Inox: door and panel made of stainless steel EDW-6230 X









	edesə	1.5	y 1 fige 5 fige 5 fige 7 Meets	14 servicies 18 230 - 10 - 10	2
_					_

60 CM FREE STAND	ING		60 C	M FREE STAI	NDING				
EDW-6231 X	Re	al stainless steel	EDV	V-6231 W	'H	White			
Cod.: 926270323 -	EAN: 84222483	51294	Coc	1.: 92627032	24 - EAN: 8	42224835130	0		
ENERGY EFFICIENCY 3RD CUTLERY RACK									
-60 cm, 14 place settir -3rd Cutlery rack -Energy Efficiency D -11 liters of water cons -47 dB (A) of acoustic -Triple security system: overflow	umption per cycle power								

' measurements in mm

- -7 programs
- -Special programs: Express 90 ', Fast 30', Glass and Prewash
- -Functions: Delayed programming up to 24 hours
- -Automatic opening door
- -Slider compact detergent dispenser
- -Suitable for all-in-1 tablets

-Display with information of: Deferred programming up to 24 hours, remaining time, selected program, salt and rinse aid

-Height adjustable basket easily adjustable by Push system, with folding supports

-Bottom basket with folding supports

-Real Inox: door and panel made of stainless steel EDW-6231 X





edesa





60 CM FREE STANDING	
EDW-6130 X	Real stainless steel
Cod.: 926270306 - EAN:	8422248096744

60 CM FREE STANDING		
EDW-6130 WH	White	
Cod.: 926270307 - EAN	8422248096751	

90 Ε DEFERRED PRO-GRAMMING EXPRESS 90' FAST 30 APT TO ALL IN ONE









⁺ measurements in mm







-Energy Efficiency E

- -11 liters of water consumption per cycle
- -49 dB (A) of acoustic power

-Triple security system: watercontrol, overheating and antioverflow

-6 programs

-Special programs: Express 90 ', Fast 30' and Glass

-Functions: Deferred programming 3, 6 or 9 hours and security lock

-Special functions: Media load and pause

- -Compact Slider detergent dispenser
- -Suitable for all-in-1 tablets
- -LED indicators: programs, salt and rinse aid

-Height adjustable top basket with folding supports

-Bottom basket with folding supports

-Real Inox: door and panel made of EDW-6130 X stainless steel





edesa





60 CM FREE STANDING

EDW-6120 WH White										
Cod.: 926270308 - EAN: 8422248096768										
E	%	30	\mathcal{Q}		$\overline{\bigcirc}$					







edesa

TRIPLE SECURITY



13

* 2:36



-60 cm, 12 place settings free standing diswasher

FAST 30'

-Energy Efficiency E

-11 liters of water consumption per cycle

-52 dB (A) of acoustic power

-Triple security system: watercontrol, overheating and anti-overflow -4 programs

-Special programs: Express 90 ' and Fast 30'

-Functions: deferred programming 3, 6 or 9 hours and security lock -Special Functions: Half load and pause

-Smart Inox cavity

-Suitable for all-in-1 tablets

-LED indicators: programs, salt and rinse aid

-Height adjustable top basket with folding supports

-Bottom basket with folding supports





edesa





45 CM FREE STANDING EDW-4710 WH

Cod.: 926270328 - EAN: 8422248351348



45 CM FREE STANDING

EDW-4710 X





* measurements in mm

Real stainless steel









White





-7







-45 cm, 10 place settings free standing diswasher

Cod.: 926270327 - EAN: 8422248351331

-Energy Efficiency D

-8 liters of water consumption per cycle

-47 dB (A) of acoustic power

-Triple security system: watercontrol, overheating and antioverflow

-8 programas

-Special programs: Express 90 ', Auto, Bottles, Glass and Prewash -Functions: deferred programming up to 24 hours and extra drying

-Special Functions: Flex Wash, pause and extra drying -Automatic opening door

-Compact Slider detergent dispenser

-Suitable for all-in-1 tablets

-Display with information of: Deferred programming up to 24 hours, remaining time, selected program, salt and rinse aid -Height adjustable basket easily adjustable by Push system, with folding supports

-Bottom basket with folding supports

-Real Inox: door and panel made of EDW-4710 X stainless steel







White

edesa

45 CM FREE STANDING

EDW-4610 X

Real stainless steel

Cod.: 926270304 - EAN: 8422248096720









WITH PLUG

45 CM FREE STANDING

Cod.: 926270305 - EAN: 8422248096737

EDW-4610 WH

- -45 cm, 10 place settings free standing diswasher
- -Energy Efficiency E
- -9 liters of water consumption per cycle
- -49 dB (A) of acoustic power
- -Triple security system: watercontrol, overheating and antioverflow
- -6 programs
- -Special programs: Express 90 ', Fast 30' and Glass
- -Functions: deferred programming 3, 6 or 9 hours and security lock
- -Special Functions: Half load and pause
- -Compact Slider detergent dispenser
- -Suitable for all-in-1 tablets
- -LED indicators: programs, salt and rinse aid
- -Height adjustable top basket with folding supports
- -Bottom basket with folding supports
- -Real Inox: door and panel made of authentic stainless steel



* measurements in mm



DISHWASHERS

edesa



60 CM SLIDING DOOR BUILT IN

EDB-6241-I SL

Cod.: 926270329 - EAN: 8422248351355





TOTAL CLEAN

SIL ENCE

-Energy Efficiency D

- -10 liters of water consumption per cycle
- -47 dB (A) of acoustic power
- -Triple security system: watercontrol, overheating and antioverflow
- -7 programs

WITH PLUG

-Special programs: Auto Hygiene, Silence, Fast 30' and Glass -Special Functions: Total clean, Flex Wash and pause; deferred programming up to 24 hours

-Auto Door Opening

-Compact Slider detergent dispenser, suitable for all-in-1 tablets -Display with: Deferred programming up to 24 hours, remaining time. LED indicators: selected program, salt and polish -Height adjustable basket with folding supports

-Bottom basket with folding supports





60 CM BUILT IN

EDB-6130-I

Cod.: 926270312 - EAN: 8422248097260



~

TRIPLE SECURITY







EXPRESS 90

DEFERRED PRO GRAMMING



FAST 30

APT TO ALL IN ONE



TRIPLE SECURITY



-60 cm, 13 place settings built in diswasher

- -Energy Efficiency E
- -11 liters of water consumption per cycle
- -49 dB (A) of acoustic power
- -Triple security system: watercontrol, overheating and antioverflow
- -5 programs
- -Special programs: Express 90 ' and Fast 30'

-Functions: delayed programming 3, 6 or 9 hours and extra drying

-Compact Slider detergent dispenser

- -Suitable for all-in-1 tablets
- -LED indicators: programs, salt and rinse aid
- -Height adjustable top basket with folding supports
- -Bottom basket with folding supports



edesa



45 CM SLIDING DOOR BUILT IN

EDB-4711-I SL

Cod.: 926270330 - EAN: 8422248351362





6





TRIPLE SECURITY



- -45 cm, 10 place settings sliding door built in diswasher -3rd Cutlery rack
- -Energy Efficiency D
- -8,5 liters of water consumption per cycle
- -47 dB (A) of acoustic power
- -Triple security system: watercontrol, overheating and antioverflow
- -7 programs

-Special programs: Auto Hygiene, Silence, Fast 30' and Glass -Special Functions: Total clean, Flex Wash and pause; deferred programming up to 24 hours

-Auto Door Opening

-Compact Slider detergent dispenser, suitable for all-in-1 tablets -Display with: Deferred programming up to 24 hours, remaining time. LED indicators: selected program, salt and polish

-Height adjustable basket with folding supports

-Bottom basket with folding supports





45 CM BUILT IN

EDB-4610-I

Cod.: 926270311 - EAN: 8422248096805

FAST 30









DISHWASHERS

EXTRA DRYING WITH



- -Energy Efficiency E
- -9 liters of water consumption per cycle
- -49 dB (A) of acoustic power
- -Triple security system: watercontrol, overheating and anti-
- overflow -5 programs
- -Special programs: Express 90 ', Fast 30' and Glass

-Functions: delayed programming 3, 6 or 9 hours and security lock

-Special Functions: Media load and pause.

- -Compact Slidere detergent dispenser
- -Suitable for all-in-1 tablets
- -LED indicators: programs, salt and rinse aid
- -Height adjustable top basket with folding supports
- -Bottom basket with folding supports



^t measurements in mm

edesə

Code EAN Model	926270299 8422248096676 EDW-6242 X	926270323 8422248351294 EDW-6231 X	926270324 8422248351300 EDW-6231 WH	926270325 8422248351317 EDW-6230 X	926270326 8422248351324 EDW-6230 WH	926270306 8422248096744 EDW-6130 X	
Finish	S. steel	S. steel	White	S. steel	White	S. steel	
Product ficche according to EU Regulation 2019/2022 - 2019/2017 Rated capacity (ps)	14	14	14	14	14	13	
Height (cm)	84,5	84,5	84,5	84,5	84,5	84,5	
Width (cm)	59,8	59,8	59,8	59,8	59,8	59,8	
Depth (cm)	60	60	60	60	60	60	
Energy Efficiency Index (EEI)	43,9	49,9	49,9	49,9	49,9	55,9	
Energy efficiency class	40,0 C					E	
Cleaning performance index (IC)	1,13	1,12	1,12	1,12	1,12	1,13	
Drying performance index (ID)	1,07	1,065	1,065	1,065	1,065	1,07	
Energy consumption in kWh [per cycle], based on the ECO programme		0,849	0,849	0,849	0,849	0,937	
Energy consumption in kWh [per 100 cycle], based on the ECO programme	75	85	85	85	85	94	
Water consumption in litres [per cycle], based on the ECO programme	9,8	11	11	11	11	11	
Duration of the eco programme (Tt) (h:min)	3:18	3:18	3:18	3:18	3:18	3:40	
Тіро	Freestanding	Freestanding	Freestanding	Freestanding	Freestanding	Freestanding	
Airborne acoustical Oise emissions (dB(A)	47	47	47	47	47	49	
Airborne acoustical Oise emission class	С	С	С	С	С	С	
Power consumption in off-mode (Po) (W)	0,49	0,49	0,49	0,49	0,49	0,49	
Power consumption in standby mode (Psm) (W)	-	-	-	-	-	-	
Delay start (W) (if applicable)	1	1	1	1	1	1	
Networked standby (W) (if applicable)	-	-	-	-	-	-	
Technical documentation (UE) 2019/2017			. –				
Standard programme energy consumption (SPEC) (kWh/cycle)	0,747	1,7	1,7	1,7	1,7	0,937	
Does standby mode include the display of information?	•	•	•	•	•	•	
Power consumption in standby mode (Psm)	- 1	- 1	- 1	- 1	- 1	- 1	
Power consumption in delay start (Pds) (if applicable) (W) Duration of the Left-on Mode (TI) (min) (EP)	15	-	1	1	1	15	
Product dimensions	10	-	-	-	-	10	
Height min/max [mm]	845	845	845	845	845	845	
Width [mm]	598	598	598	598	598	598	
Depth [mm]	600	600	600	600	600	600	
Adjustable legs	50	50	50	50	50	50	
Cabinet and door dimensions	00			00	00		
Minimum cabinet height [mm]	-	-	-	-	-	-	
Minimum cabinet width [mm]	-	-	-	-	-	-	
Minimum cabinet depth [mm]	-	-	-	-	-	-	
Max door height (built-in models) [mm]	-	-	-	-	-	-	
Sliding door	-	-	-	-	-	-	
Control panel							
Display / LED	•	•	•	•	•	-	
Salt control pilot light			•	•	•		
Rinse aid control pilot light			•	•	•	-	
Time remaining indicator							
Delay for starting operation	24h	24h	24h	24h	24h	3/6/9h	
Programs and functions	7	7	7	7	7	0	
Number of programs	7	7	7	7	7 65 ºC / 210 min	6	
Intensive[°C-min]	65 ºC / 205 min	65 ºC / 210 min 55 ºC / 180 min	65 ºC / 210 min 55 ºC / 180 min	65 ºC / 210 min 55 ºC / 180 min	55 °C / 210 min	65 ºC / 205 min 55 ºC / 175 min	
Ormal [°C-min] - Universal ECO [°C-min]	- 50 ºC / 198 min	50 °C / 198 min	50 °C / 198 min	50 °C / 198 min	50 °C / 198 min	45 °C / 220 min	
Express 90' [°C-min]	60 ºC / 90 min	55 ºC / 90 min	55 ºC / 90 min	55 ºC / 90 min	55 °C / 90 min	60 °C / 90 min	
Glass [°C-min]	50 °C / 120 min	50 °C / 125 min	50 °C / 125 min	50 °C / 125 min	50 °C / 125 min	50 °C / 120 min	
Rapid 30' [°C-min]	45ºC / 30 min	40ºC / 30 min	40ºC / 30 min	40ºC / 30 min	40ºC / 30 min	50°C / 30 min	
Soak [min]	15 min	15 min	15 min	15 min	15 min	-	
Automatic [ºC-min]	55-65ºC, 90-180 min	-	-	-	-	-	
Start / Pause function	•	•	•	•	•	•	
Half load funtion	•	•	•	•	•	•	
Extra drying function	•	•	•	•	•	-	
Flex wash function (Alternative wash function)	•	•	•	•	•	-	
Total Clean function (Strong wash function)	•	-	-	-	-	-	
Equipment							
Upper basket with height regulation	•	•	•	•	•	•	
Upper basket foldable support for cups	•	•	•	•	•	•	
Upper/Lower basket foldable supports			•	•			
Type of dispenser	Compact Sliding	Compact Sliding	Compact Sliding	Compact Sliding	Compact Sliding	Compact Sliding	
Slide&Go tray	-	-	-	-	-	-	
Third tray	•	•	•	-	-	-	
Additional specifications	Jan market -	Otenede	Otenede	Otenede	Otransle 1	Otransla d	
Motor Automatic deer ener	Inverter	Standard	Standard	Standard	Standard	Standard	
Automatic door open				•		-	
Enabled for all in one detergent	S stool	S stool	S stool	-	S. steel	S stool	
Type of cavity Safety	S. steel	S. steel	S. steel	S. steel	S. Steel	S. steel	
Child lock	•						
Triple security system	•	•	•	•	•	•	
Power and water connection	-	-	-	•	-	-	
Voltage range [V]	220-240	220-240	220-240	220-240	220-240	220-240	
Frecuency [Hz]	50	50	50	50	50	50	
Rated power [W]	1760-2100	1760-2100	1760-2100	1760-2100	1760-2100	1760-2100	
Rated power [W]	8-8.75	8-8.75	8-8.75	8-8.75	8-8.75	8-8.75	
Type of plug	Schuko	Schuko	Schuko	Schuko	Schuko	Schuko	
Power cord length [mm]	1500	1500	1500	1500	1500	1500	
Inlet water hose length [mm]	1500	1500	1500	1500	1500	1500	
Drain water hose length [mm]	1400	1400	1400	1400	1400	1400	
1) A L L L (Isiala at a fficience) to C (Isuant a fficience) (0) Essentia						6 H L	

(1) A + + + (highest efficiency) to G (lowest efficiency). (2) Energy consumption based on 280 standard cleaning cycles using cold water fill and the consumption of the low power modes. Actual energy consumption will depend on how the appliance is used. (3) Water consumption based on 280 standard cleaning cycles. Actual water consumption will depend on how the appliance is used. (3) Water consumption based on 280 standard cleaning cycles. Actual water consumption will depend on how the appliance is used. (4) A (highest efficiency) to G (lowest efficiency). (5) This program is suitable for cleaning soiled normally soiled tableware and that it is the most efficient programme in terms of its combined energy and water consumption for that type of tableware.

926270307 8422248096751 EDW-6130 WH	926270308 8422248096768 EDW-6120 WH	926270327 8422248351331 EDW-4710 X	926270328 8422248351348 EDW-4710 WH	926270304 8422248096720 EDW-4610 X	926270305 8422248096737 EDW-4610 WH	926270329 8422248351355 EDB-6241-I SL	926270312 8422248097260 EDB-6130-I	926270330 8422248351362 EDB-4711-I SL	926270311 8422248096805 EDB-4610-I
White	White	S. steel	White	S. steel	White	Built-in	Built-in	Built-in	Built-in
13	12	10	10	10	10	14	13	10	10
84,5	84,5	84,5	84,5	84,5	84,5	81,5	81,5	81,5	81,5
59,8	59,8	44,8	44,8		44,8	59,8	59,8	44,8	
,				44,8		,	,		44,8
60	60	60	60	60	60	55	55	55	55
55,9	55,9	49,9	49,9	55,9	55,9	49,9	49,9	49,9	55,9
E	E	D	D	E	E	D	D	D	E
1,13	1,13	1,125	1,125	1,13	1,13	1,125	1,13	1,125	1,13
1,07	1,07	1,065	1,065	1,07	1,07	1,065	1,07	1,065	1,07
0,937	0,923	0,674	0,674	0,755	0,755	0,849	0,937	0,674	0,755
94	92	68	68	76	76	85	94	68	76
11	11	8	8	9	9	10	11	8,5	9
3:40	3:50	3:18	3:18	3:55	3:55	3:18	3:18	3:18	3:56
Freestanding	Freestanding	Freestanding	Freestanding	Freestanding	Freestanding	Fully build in	Fully build in	Fully build in	Fully build in
49	52	47	47	49	49	47	49	47	49
С	D	С	С	С	С	С	С	С	С
0,49	0,49	0,49	0,49	0,49	0,49	0,49	0,49	0,49	0,49
-	-	-	-	-	-	-	-	-	-
1	1	1	1	1	1	1	1	1	1
-	-	-	-	-	-	-	-	-	-
0,937	0,923	1,35	1,35	0,755	0,755	1,7	0,937	1,35	0,755
•	•	•	•	•	•	•	•	•	•
-	-	-	-	-	-	-	-	-	-
1	1	1	1	1	1	1	1	1	1
15	15	-	-	15	15	-	-	-	15
845	845	845	845	845	845	815	815	815	815
598	598	448	448	448	448	598	598	448	448
600	600	600	600	600	600	580	580	580	580
50	50	50	50	50	50	50	50	50	50
-	-	-	-	-	-	820	820	820	820
-	-	-	-	-	-	600	600	450	450
			_	-	_	580	580	580	580
_	_	_	_	_	_	800	720	800	720
-	-	_	_	-	_	•	-	•	-
						, in the second s		-	
-	-	•	•	-	-	•	-	•	-
•	•	•	•	•	•	•	•	•	•
•	• -	•	•	• -	• -	•	• -	•	-
● - 3/6/9h	• - 3/6/9h	• • 24h	•	● - 3/6/9h	• - 3/6/9h	•	• - 24h	• • 24h	-
- ● 3/6/9h	- ● 3/6/9h	• • 24h	• • 24h	● - 3/6/9h	- - 3/6/9h	•	• • 24h	• • 24h	-
• • 3/6/9h 6	• • 3/6/9h 4	• • 24h 8	•	• • 3/6/9h 6	• • 3/6/9h 6	•	-	• • 24h 7	-
		8	24h 8	6		24h	24h		- 24h 5
6 65 °C / 205 min	4	8 65 ºC / 205 min	24h 8 65 ℃ / 205 min	6 65 ºC / 205 min	6 65 ºC / 205 min	24h	24h		- 24h 5 65 °C / 205 min
6 65 ºC / 205 min 55 ºC / 175 min	4 65 ℃ / 205 min -	8 65 ºC / 205 min 55 ºC / 175 min	24h 8 65 ℃ / 205 min 55 ℃ / 175 min	6 65 ºC / 205 min 55 ºC / 175 min	6 65 ºC / 205 min 55 ºC / 175 min	24h 7 -	24h 5 - -	7 - -	- 24h 5 65 °C / 205 min 55 °C / 175 min
6 65 ℃ / 205 min 55 ℃ / 175 min 45 ℃ / 220 min	4 65 °C / 205 min - 45 °C / 230 min	8 65 °C / 205 min 55 °C / 175 min 50 °C / 198 min	24h 8 65 °C / 205 min 55 °C / 175 min 50 °C / 198 min	6 65 ℃ / 205 min 55 ℃ / 175 min 45 ℃ / 235 min	6 65 ℃ / 205 min 55 ℃ / 175 min 45 ℃ / 235 min	24h	24h 5 - - 50 ℃ / 198 min	7 - - 50 ºC / 198 min	- 24h 5 65 °C / 205 min 55 °C / 175 min 45 °C / 235 min
6 65 °C / 205 min 55 °C / 175 min 45 °C / 220 min 60 °C / 90 min	4 65 ℃ / 205 min -	8 65 °C / 205 min 55 °C / 175 min 50 °C / 198 min 55 °C / 90 min	24h 8 65 °C / 205 min 55 °C / 175 min 50 °C / 198 min 55 °C / 90 min	6 65 ℃ / 205 min 55 ℃ / 175 min 45 ℃ / 235 min 65 ℃ / 90 min	6 65 ℃ / 205 min 55 ℃ / 175 min 45 ℃ / 235 min 65 ℃ / 90 min	€ 24h 7 - 50 °C / 198 min -	24h 5 - - 50 °C / 198 min 60 °C / 90 min	7 - - 50 °C / 198 min 60 °C / 90 min	- 24h 5 65 °C / 205 min 55 °C / 175 min
6 65 ℃ / 205 min 55 ℃ / 175 min 45 ℃ / 220 min	4 65 °C / 205 min - 45 °C / 230 min	8 65 °C / 205 min 55 °C / 175 min 50 °C / 198 min	24h 8 65 °C / 205 min 55 °C / 175 min 50 °C / 188 min 55 °C / 90 min	6 65 ℃ / 205 min 55 ℃ / 175 min 45 ℃ / 235 min	6 65 ℃ / 205 min 55 ℃ / 175 min 45 ℃ / 235 min 65 ℃ / 90 min	24h 7 -	24h 5 - - 50 ℃ / 198 min	7 - - 50 °C / 198 min 60 °C / 90 min	- 24h 5 65 °C / 205 min 55 °C / 175 min 45 °C / 235 min
6 65 °C / 205 min 55 °C / 175 min 45 °C / 220 min 60 °C / 90 min 50 °C / 120 min	4 65 °C / 205 min - 45 °C / 230 min 60 °C / 90 min -	8 65 °C / 205 min 55 °C / 175 min 50 °C / 198 min 55 °C / 90 min 55 °C / 20 min 35°C / 20 min	24h 8 65 °C / 205 min 55 °C / 175 min 50 °C / 198 min 55 °C / 90 min 55 °C / 20 min 35°C / 20 min	6 65 °C / 205 min 55 °C / 175 min 45 °C / 235 min 65 °C / 90 min 50 °C / 120 min	6 65 °C / 205 min 55 °C / 175 min 45 °C / 235 min 65 °C / 90 min 50 °C / 120 min	24h 7 - 50 °C / 198 min - 50 °C / 120 min	24h 5 - 50 °C / 198 min 60 °C / 90 min 50 °C / 120 min	7 - - 50 °C / 198 min 60 °C / 90 min 50 °C / 120 min	- 24h 5 65 °C / 205 min 55 °C / 175 min 45 °C / 235 min 60 °C / 90 min
6 65 °C / 205 min 55 °C / 175 min 45 °C / 220 min 60 °C / 90 min 50 °C / 120 min	4 65 °C / 205 min - 45 °C / 230 min 60 °C / 90 min -	8 65 °C / 205 min 55 °C / 175 min 50 °C / 198 min 55 °C / 90 min 50 °C / 120 min 35°C / 20 min 15 min	24h 8 65 °C / 205 min 55 °C / 175 min 50 °C / 198 min 55 °C / 90 min 50 °C / 120 min	6 65 °C / 205 min 55 °C / 175 min 45 °C / 235 min 65 °C / 90 min 50 °C / 120 min	6 65 °C / 205 min 55 °C / 175 min 45 °C / 235 min 65 °C / 90 min 50 °C / 120 min	24h 7 - 50 °C / 198 min - 50 °C / 120 min	24h 5 - 50 °C / 198 min 60 °C / 90 min 50 °C / 120 min	7 - 50 °C / 198 min 60 °C / 90 min 50 °C / 120 min 50 °C / 30 min	- 24h 5 65 °C / 205 min 55 °C / 175 min 45 °C / 235 min 60 °C / 90 min
6 65 °C / 205 min 55 °C / 175 min 45 °C / 220 min 60 °C / 90 min 50 °C / 120 min	4 65 °C / 205 min - 45 °C / 230 min 60 °C / 90 min -	8 65 °C / 205 min 55 °C / 175 min 50 °C / 198 min 55 °C / 90 min 50 °C / 120 min 35°C / 20 min 15 min	24h 8 65 °C / 205 min 55 °C / 175 min 50 °C / 198 min 55 °C / 90 min 50 °C / 120 min 35°C / 20 min 35°C / 20 min 15 min	6 65 °C / 205 min 55 °C / 175 min 45 °C / 235 min 65 °C / 90 min 50 °C / 120 min	6 65 °C / 205 min 55 °C / 175 min 45 °C / 235 min 65 °C / 90 min 50 °C / 120 min	24h 7 - 50 °C / 198 min - 50 °C / 120 min 50°C / 30 min	24h 5 - 50 °C / 198 min 60 °C / 90 min 50 °C / 120 min 50 °C / 30 min -	7 - 50 °C / 198 min 60 °C / 90 min 50 °C / 120 min 50 °C / 30 min	- 24h 5 65 °C / 205 min 55 °C / 175 min 45 °C / 235 min 60 °C / 90 min
6 65 °C / 205 min 55 °C / 175 min 45 °C / 220 min 60 °C / 90 min 50 °C / 120 min	4 65 °C / 205 min - 45 °C / 230 min 60 °C / 90 min -	8 65 °C / 205 min 55 °C / 175 min 50 °C / 198 min 55 °C / 90 min 50 °C / 120 min 35°C / 20 min 15 min	24h 8 65 °C / 205 min 55 °C / 175 min 50 °C / 198 min 55 °C / 90 min 50 °C / 120 min 35°C / 20 min 35°C / 20 min 15 min	6 65 °C / 205 min 55 °C / 175 min 45 °C / 235 min 65 °C / 90 min 50 °C / 120 min	6 65 °C / 205 min 55 °C / 175 min 45 °C / 235 min 65 °C / 90 min 50 °C / 120 min	24h 7 - 50 °C / 198 min - 50 °C / 120 min 50°C / 30 min	24h 5 - 50 °C / 198 min 60 °C / 90 min 50 °C / 120 min 50 °C / 30 min -	7 - 50 °C / 198 min 60 °C / 90 min 50 °C / 120 min 50 °C / 30 min	- 24h 5 65 °C / 205 min 55 °C / 175 min 45 °C / 235 min 60 °C / 90 min
6 65 °C / 205 min 55 °C / 175 min 45 °C / 220 min 60 °C / 90 min 50 °C / 120 min	4 65 °C / 205 min - 45 °C / 230 min 60 °C / 90 min -	8 65 °C / 205 min 55 °C / 175 min 50 °C / 198 min 55 °C / 90 min 50 °C / 120 min 35°C / 20 min 15 min	24h 8 65 °C / 205 min 55 °C / 175 min 50 °C / 198 min 55 °C / 90 min 50 °C / 120 min 35°C / 20 min 35°C / 20 min 15 min	6 65 °C / 205 min 55 °C / 175 min 45 °C / 235 min 65 °C / 90 min 50 °C / 120 min	6 65 °C / 205 min 55 °C / 175 min 45 °C / 235 min 65 °C / 90 min 50 °C / 120 min 50 °C / 30 min -	24h 7 - 50 °C / 198 min - 50 °C / 120 min 50°C / 30 min	24h 5 - 50 °C / 198 min 60 °C / 90 min 50 °C / 120 min 50 °C / 30 min -	7 - 50 °C / 198 min 60 °C / 90 min 50 °C / 120 min 50 °C / 30 min	- 24h 5 65 °C / 205 min 55 °C / 175 min 45 °C / 235 min 60 °C / 90 min
6 65 °C / 205 min 55 °C / 175 min 45 °C / 220 min 60 °C / 90 min 50 °C / 120 min	4 65 °C / 205 min - 45 °C / 230 min 60 °C / 90 min -	8 65 °C / 205 min 55 °C / 175 min 50 °C / 198 min 55 °C / 90 min 50 °C / 120 min 35°C / 20 min 15 min	24h 8 65 °C / 205 min 55 °C / 175 min 50 °C / 198 min 55 °C / 90 min 50 °C / 120 min 35°C / 20 min 35°C / 20 min 15 min	6 65 °C / 205 min 55 °C / 175 min 45 °C / 235 min 65 °C / 90 min 50 °C / 120 min	6 65 °C / 205 min 55 °C / 175 min 45 °C / 235 min 65 °C / 90 min 50 °C / 120 min 50 °C / 30 min -	24h 7 - 50 °C / 198 min - 50 °C / 120 min 50°C / 30 min	24h 5 - 50 °C / 198 min 60 °C / 90 min 50 °C / 120 min 50 °C / 30 min -	7 - 50 °C / 198 min 60 °C / 90 min 50 °C / 120 min 50 °C / 30 min	- 24h 5 65 °C / 205 min 55 °C / 175 min 45 °C / 235 min 60 °C / 90 min
6 65 °C / 205 min 55 °C / 175 min 45 °C / 220 min 60 °C / 90 min 50 °C / 120 min	4 65 °C / 205 min - 45 °C / 230 min 60 °C / 90 min -	8 65 °C / 205 min 55 °C / 175 min 50 °C / 198 min 55 °C / 90 min 50 °C / 120 min 35°C / 20 min 15 min	24h 8 65 °C / 205 min 55 °C / 175 min 50 °C / 198 min 55 °C / 90 min 50 °C / 120 min 35°C / 20 min 35°C / 20 min 15 min	6 65 °C / 205 min 55 °C / 175 min 45 °C / 235 min 65 °C / 90 min 50 °C / 120 min	6 65 °C / 205 min 55 °C / 175 min 45 °C / 235 min 65 °C / 90 min 50 °C / 120 min 50 °C / 30 min -	24h 7 - 50 °C / 198 min - 50 °C / 120 min 50°C / 30 min	24h 5 - 50 °C / 198 min 60 °C / 90 min 50 °C / 120 min 50 °C / 30 min -	7 - 50 °C / 198 min 60 °C / 90 min 50 °C / 120 min 50 °C / 30 min	- 24h 5 65 °C / 205 min 55 °C / 175 min 45 °C / 235 min 60 °C / 90 min
6 65 °C / 205 min 55 °C / 175 min 45 °C / 220 min 60 °C / 90 min 50 °C / 120 min	4 65 °C / 205 min - 45 °C / 230 min 60 °C / 90 min -	8 65 °C / 205 min 55 °C / 175 min 50 °C / 198 min 55 °C / 90 min 50 °C / 120 min 35°C / 20 min 15 min	24h 8 65 °C / 205 min 55 °C / 175 min 50 °C / 198 min 55 °C / 90 min 50 °C / 120 min 35°C / 20 min 35°C / 20 min 15 min	6 65 °C / 205 min 55 °C / 175 min 45 °C / 235 min 65 °C / 90 min 50 °C / 120 min	6 65 °C / 205 min 55 °C / 175 min 45 °C / 235 min 65 °C / 90 min 50 °C / 120 min 50 °C / 30 min -	24h 7 - 50 °C / 198 min - 50 °C / 120 min 50°C / 30 min	24h 5 - 50 °C / 198 min 60 °C / 90 min 50 °C / 120 min 50 °C / 30 min -	7 - 50 °C / 198 min 60 °C / 90 min 50 °C / 120 min 50 °C / 30 min	- 24h 5 65 °C / 205 min 55 °C / 175 min 45 °C / 235 min 60 °C / 90 min
6 65 °C / 205 min 55 °C / 175 min 45 °C / 220 min 60 °C / 90 min 50 °C / 120 min	4 65 °C / 205 min - 45 °C / 230 min 60 °C / 90 min -	8 65 °C / 205 min 55 °C / 175 min 50 °C / 198 min 55 °C / 90 min 50 °C / 120 min 35°C / 20 min 15 min	24h 8 65 °C / 205 min 55 °C / 175 min 50 °C / 198 min 55 °C / 90 min 50 °C / 120 min 35°C / 20 min 35°C / 20 min 15 min	6 65 °C / 205 min 55 °C / 175 min 45 °C / 235 min 65 °C / 90 min 50 °C / 120 min	6 65 °C / 205 min 55 °C / 175 min 45 °C / 235 min 65 °C / 90 min 50 °C / 120 min 50 °C / 30 min -	24h 7 - 50 °C / 198 min - 50 °C / 120 min 50°C / 30 min	24h 5 - 50 °C / 198 min 60 °C / 90 min 50 °C / 120 min 50 °C / 30 min -	7 - 50 °C / 198 min 60 °C / 90 min 50 °C / 120 min 50 °C / 30 min	- 24h 5 65 °C / 205 min 55 °C / 175 min 45 °C / 235 min 60 °C / 90 min
6 65 °C / 205 min 55 °C / 175 min 45 °C / 220 min 60 °C / 90 min 50 °C / 120 min	4 65 °C / 205 min - 45 °C / 230 min 60 °C / 90 min -	8 65 °C / 205 min 55 °C / 175 min 50 °C / 198 min 55 °C / 90 min 50 °C / 120 min 35°C / 20 min 15 min	24h 8 65 °C / 205 min 55 °C / 175 min 50 °C / 198 min 55 °C / 90 min 50 °C / 120 min 35°C / 20 min 35°C / 20 min 15 min	6 65 °C / 205 min 55 °C / 175 min 45 °C / 235 min 65 °C / 90 min 50 °C / 120 min	6 65 °C / 205 min 55 °C / 175 min 45 °C / 235 min 65 °C / 90 min 50 °C / 120 min 50 °C / 30 min -	24h 7 - 50 °C / 198 min - 50 °C / 120 min 50°C / 30 min	24h 5 - 50 °C / 198 min 60 °C / 90 min 50 °C / 120 min 50 °C / 30 min -	7 - 50 °C / 198 min 60 °C / 90 min 50 °C / 120 min 50 °C / 30 min	- 24h 5 65 °C / 205 min 55 °C / 175 min 45 °C / 235 min 60 °C / 90 min
6 65 °C / 205 min 55 °C / 175 min 45 °C / 220 min 60 °C / 90 min 50 °C / 120 min	4 65 °C / 205 min - 45 °C / 230 min 60 °C / 90 min - 50°C / 30 min - - - - - - -	8 65 °C / 205 min 55 °C / 175 min 50 °C / 198 min 55 °C / 90 min 50 °C / 120 min 35°C / 20 min 15 min	24h 8 65 °C / 205 min 55 °C / 175 min 50 °C / 198 min 55 °C / 90 min 50 °C / 120 min 35°C / 20 min 35°C / 20 min 15 min	6 65 °C / 205 min 55 °C / 175 min 45 °C / 235 min 65 °C / 90 min 50 °C / 120 min	6 65 °C / 205 min 55 °C / 175 min 45 °C / 235 min 65 °C / 90 min 50 °C / 120 min 50 °C / 30 min -	24h 7 - 50 °C / 198 min - 50 °C / 120 min 50°C / 30 min	24h 5 - 50 °C / 198 min 60 °C / 90 min 50 °C / 120 min 50 °C / 30 min -	7 - 50 °C / 198 min 60 °C / 90 min 50 °C / 120 min 50 °C / 30 min	- 24h 5 65 °C / 205 min 55 °C / 175 min 45 °C / 235 min 60 °C / 90 min
6 65 °C / 205 min 55 °C / 175 min 45 °C / 220 min 60 °C / 90 min 50 °C / 120 min	4 65 °C / 205 min - 45 °C / 230 min 60 °C / 90 min - 50 °C / 30 min - - - - - - - - - - - - - - - - - - -	8 65 °C / 205 min 55 °C / 175 min 50 °C / 198 min 55 °C / 90 min 35°C / 20 min 35°C / 20 min 15 min 55-65 °C / 150 min • •	24h 8 65 °C / 205 min 55 °C / 175 min 50 °C / 198 min 50 °C / 190 min 50 °C / 20 min 35 °C / 20 min 35 °C / 20 min 55-65 °C / 150 min • •	6 65 °C / 205 min 55 °C / 175 min 45 °C / 235 min 65 °C / 90 min 50 °C / 120 min 50 °C / 30 min - - - - - - - - - - - - -	6 65 °C / 205 min 55 °C / 175 min 45 °C / 235 min 50 °C / 235 min 50 °C / 120 min 50 °C / 30 min - - - - - - - - - - - -	• 24h 7 - 50 °C / 198 min - 50 °C / 120 min 50°C / 30 min • 55-65 °C / 150 min • •	24h 5 - 50 °C / 198 min 60 °C / 90 min 50 °C / 120 min 50 °C / 120 min 55-65 °C / 150 min • • • •	7 - - 50 °C / 198 min 60 °C / 90 min 50 °C / 120 min 50 °C / 120 min - 55-65 °C / 150 min - - - - - - -	- 24h 5 65 °C / 205 min 55 °C / 175 min 45 °C / 235 min 60 °C / 90 min - 50°C / 30 min - - - - - -
6 65 °C / 205 min 55 °C / 175 min 45 °C / 220 min 60 °C / 90 min 50 °C / 120 min 50 °C / 30 min - - - - - - - - - - - - - - - - -	4 65 °C / 205 min - 45 °C / 230 min 60 °C / 90 min - 50°C / 30 min - - - - - - -	8 65 °C / 205 min 55 °C / 175 min 50 °C / 198 min 55 °C / 90 min 50 °C / 120 min 35°C / 20 min 15 min	24h 8 65 °C / 205 min 55 °C / 175 min 50 °C / 198 min 55 °C / 90 min 50 °C / 120 min 35°C / 20 min 35°C / 20 min 15 min	6 65 °C / 205 min 55 °C / 175 min 45 °C / 235 min 65 °C / 90 min 50 °C / 120 min	6 65 °C / 205 min 55 °C / 175 min 45 °C / 235 min 50 °C / 235 min 50 °C / 120 min 50 °C / 30 min - - - - - - - - - - - -	24h 7 - 50 °C / 198 min - 50 °C / 120 min 50°C / 30 min	24h 5 - 50 °C / 198 min 60 °C / 90 min 50 °C / 120 min 50 °C / 30 min -	7 - 50 °C / 198 min 60 °C / 90 min 50 °C / 120 min 50 °C / 30 min	- 24h 5 65 °C / 205 min 55 °C / 175 min 45 °C / 235 min 60 °C / 90 min
6 65 °C / 205 min 55 °C / 175 min 45 °C / 220 min 60 °C / 90 min 50 °C / 120 min 50 °C / 30 min - - - - - - - - - - - - - - - - -	4 65 °C / 205 min - 45 °C / 230 min 60 °C / 90 min - 50 °C / 30 min - - - - - - - - - - - - - - - - - - -	8 65 °C / 205 min 55 °C / 175 min 50 °C / 198 min 55 °C / 90 min 35°C / 20 min 35°C / 20 min 15 min 55-65 °C / 150 min • •	24h 8 65 °C / 205 min 55 °C / 175 min 50 °C / 198 min 50 °C / 190 min 50 °C / 20 min 35 °C / 20 min 35 °C / 20 min 55-65 °C / 150 min • •	6 65 °C / 205 min 55 °C / 175 min 45 °C / 235 min 65 °C / 90 min 50 °C / 120 min 50 °C / 30 min - - - - - - - - - - - - -	6 65 °C / 205 min 55 °C / 175 min 45 °C / 235 min 50 °C / 235 min 50 °C / 120 min 50 °C / 30 min - - - - - - - - - - - -	• 24h 7 - 50 °C / 198 min - 50 °C / 120 min 50°C / 30 min • 55-65 °C / 150 min • •	24h 5 - 50 °C / 198 min 60 °C / 90 min 50 °C / 120 min 50 °C / 120 min 55-65 °C / 150 min • • • • •	7 - - 50 °C / 198 min 60 °C / 90 min 50 °C / 120 min 50 °C / 120 min - 55-65 °C / 150 min - - - - - - -	- 24h 5 65 °C / 205 min 55 °C / 175 min 45 °C / 235 min 60 °C / 90 min - 50°C / 30 min - - - - - -
6 65 °C / 205 min 55 °C / 175 min 45 °C / 220 min 50 °C / 30 min 50 °C / 30 min - - - - - - - - - - - - - - - - - - -	4 65 °C / 205 min 60 °C / 90 min - 50°C / 30 min - - - - - - - - - - - - - - - - - - -	8 65 °C / 205 min 55 °C / 175 min 50 °C / 198 min 55 °C / 90 min 55 °C / 90 min 15 min 55-65 °C / 150 min • • • • • • • • • • •	24h 8 65 °C / 205 min 55 °C / 175 min 50 °C / 198 min 55 °C / 90 min 35 °C / 20 min 35 °C / 20 min 15 min 55-65 °C / 150 min • • • • •	6 65 °C / 205 min 55 °C / 175 min 65 °C / 235 min 50 °C / 230 min 50 °C / 120 min 50 °C / 30 min - - - - - - - - - - - - - - - - - - -	6 65 °C / 205 min 55 °C / 175 min 65 °C / 235 min 65 °C / 230 min 50 °C / 120 min 50 °C / 30 min - - - - - - - - - - - - - - - - - - -	• 24h 7 - - 50 °C / 198 min 50 °C / 198 min 50 °C / 120 min 50 °C / 150 min • • • • • •	24h 5 - - 50 °C / 198 min 60 °C / 90 min 50 °C / 120 min 50 °C / 120 min 55-65 °C / 150 min • • • • • • •	7 - - 50 °C / 198 min 60 °C / 90 min 50 °C / 120 min 50 °C / 120 min 50 °C / 150 min - - - - - - - - - - - - - - - - - - -	- 24h 5 65 °C / 205 min 55 °C / 175 min 45 °C / 235 min 60 °C / 90 min - 50°C / 30 min - - - - - - - - - - - - - - - - - - -
6 65 °C / 205 min 55 °C / 175 min 45 °C / 220 min 50 °C / 30 min 50 °C / 30 min 50 °C / 30 min - - - - - - - - - - - - - - - - - - -	4 65 °C / 205 min - 45 °C / 20 min 60 °C / 90 min - 50°C / 30 min - - - - - - - - - - - - - - - - - - -	8 65 °C / 205 min 55 °C / 175 min 50 °C / 198 min 55 °C / 90 min 55 °C / 20 min 35°C / 20 min 15 min 55-65 °C / 150 min • • • • • • • • • • • • • • • • • • •	24h 8 65 °C / 205 min 55 °C / 175 min 50 °C / 198 min 50 °C / 190 min 50 °C / 20 min 35 °C / 20 min 15 min 55-65 °C / 150 min • • • • • • • • • • Compact Sliding -	6 65 °C / 205 min 55 °C / 175 min 65 °C / 235 min 50 °C / 230 min 50 °C / 20 min 50 °C / 30 min - - - - - - - - - - - - - - - - - - -	6 65 °C / 205 min 55 °C / 175 min 65 °C / 235 min 50 °C / 230 min 50 °C / 30 min - - - - - - - - - - - - - - - - - - -	• 24h 7 - 50 °C / 198 min 50 °C / 198 min 50°C / 30 min 55-65 °C / 150 min • • • • • • • •	24h 5 - - 50 °C / 198 min 60 °C / 90 min 50 °C / 120 min 50 °C / 120 min 55-65 °C / 150 min • • • • • • • • • • • • • • • • • •	7 - - 50 °C / 198 min 60 °C / 90 min 50 °C / 120 min 50 °C / 120 min 55-65 °C / 150 min - - - - - - - - - - - - - - - - - - -	24h 5 65 °C / 205 min 55 °C / 175 min 45 °C / 235 min 60 °C / 90 min - 50°C / 30 min - - 50°C / 30 min - - - - - - - - - - - - - - - - - - -
6 65 °C / 205 min 55 °C / 175 min 45 °C / 220 min 50 °C / 30 min 50 °C / 30 min - - - - - - - - - - - - - - - - - - -	4 65 °C / 205 min - 60 °C / 90 min 60 °C / 90 min - 50 °C / 30 min - - - - - - - - - - - - - - - - - - -	8 65°C / 205 min 55°C / 175 min 50°C / 198 min 50°C / 198 min 55°C / 20 min 35°C / 20 min 15 min 55-65°C / 150 min • • • • • • • • • • • • • • • • • • •	24h 8 65 °C / 205 min 55 °C / 175 min 50 °C / 198 min 50 °C / 190 min 50 °C / 20 min 35 °C / 20 min 35 °C / 20 min 55-65 °C / 150 min • • • • • • • • • • • • • • • • • • •	6 65 °C / 205 min 55 °C / 175 min 65 °C / 235 min 50 °C / 230 min 50 °C / 200 min 50 °C / 200 min 65 °C / 90 min 65 °C / 90 min 60 min 70 min	6 65 °C / 205 min 55 °C / 175 min 65 °C / 235 min 65 °C / 230 min 50 °C / 120 min 50 °C / 30 min - - - - - - - - - - - - - - - - - - -	• 24h 7 - - 50 °C / 198 min 50 °C / 198 min 50 °C / 120 min 50 °C / 150 min • • • • • • •	24h 5 - - 50 °C / 198 min 60 °C / 90 min 50 °C / 120 min 50 °C / 120 min 55-65 °C / 150 min • • • • • • •	7 - - 50 °C / 198 min 60 °C / 90 min 50 °C / 120 min 50 °C / 120 min 50 °C / 150 min - - - - - - - - - - - - - - - - - - -	24h 24h 5 65 °C / 205 min 55 °C / 175 min 45 °C / 235 min 60 °C / 205 min 55 °C / 175 min 45 °C / 235 min 60 °C / 30 min - - 50°C / 30 min - - - - - - - - - - - - - - - - - - -
6 65 °C / 205 min 45 °C / 220 min 50 °C / 175 min 50 °C / 120 min 50 °C / 120 min 50 °C / 30 min	4 65 °C / 205 min 60 °C / 90 min 50 °C / 30 min - - - - - - - - - - - - - - - - - - -	8 65 °C / 205 min 55 °C / 175 min 50 °C / 198 min 55 °C / 90 min 55 °C / 20 min 35°C / 20 min 15 min 55-65 °C / 150 min • • • • • • • • • • • • • • • • • • •	24h 8 65 °C / 205 min 55 °C / 175 min 50 °C / 198 min 55 °C / 90 min 55 °C / 20 min 35°C / 20 min 35°C / 20 min 55-65 °C / 150 min • • • • • • • • • • • • • • • • • • •	6 65 °C / 205 min 55 °C / 175 min 65 °C / 235 min 50 °C / 230 min 50 °C / 30 min - - - - - - - - - - - - - - - - - - -	6 65 °C / 205 min 55 °C / 175 min 65 °C / 235 min 50 °C / 120 min 50 °C / 120 min 50 °C / 30 min - - - - - - - - - - - - - - - - - - -	• 24h 24h 7 - 50 °C / 198 min 50 °C / 198 min 50°C / 30 min 50°C / 30 min • • • • • • • • • • • • • • • • • • •	24h 5 - - 50 °C / 198 min 60 °C / 90 min 50 °C / 120 min 50 °C / 120 min 50° C / 120 min 50° C / 120 min 50° C / 120 min 6 - - - - - - - - - - - - - - - - - -	7 - - 50 °C / 198 min 60 °C / 90 min 50 °C / 120 min 50 °C / 120 min - - 55-65 °C / 150 min - - - - - - - - - - - - - - - - - - -	24h 24h 5 65 °C / 205 min 55 °C / 175 min 45 °C / 235 min 60 °C / 90 min - 50°C / 30 min - - 50°C / 30 min - - - - - - - - - - - - - - - - - - -
6 65 °C / 205 min 55 °C / 175 min 45 °C / 220 min 50 °C / 30 min 50 °C / 30 min - - - - - - - - - - - - - - - - - - -	4 65 °C / 205 min 60 °C / 90 min 50 °C / 30 min - 50 °C / 30 min - - - - - - - - - - - - - - - - - - -	8 65 °C / 205 min 55 °C / 175 min 50 °C / 198 min 55 °C / 20 min 35 °C / 20 min 15 min 55-65 °C / 150 min 6 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0	24h 8 65 °C / 205 min 55 °C / 175 min 50 °C / 198 min 55 °C / 90 min 55 °C / 20 min 35 °C / 20 min 15 min 55-65 °C / 150 min • • • • • • • • • • • • • • • • • • •	6 65 °C / 205 min 55 °C / 175 min 65 °C / 235 min 50 °C / 230 min 50 °C / 20 min 50 °C / 20 min 50 °C / 20 min - - - - - - - - - - - - - - - - - - -	6 65 °C / 205 min 55 °C / 175 min 65 °C / 235 min 65 °C / 230 min 50 °C / 120 min 50 °C / 30 min - - - - - - - - - - - - - - - - - - -	• • 24h 7 - 50°C / 198 min 50°C / 198 min 50°C / 30 min 50°C / 150 min 55-65°C / 150 min • • • • • • • • • • • • • • • • • • •	24h 5 - 50 °C / 198 min 60 °C / 90 min 50 °C / 120 min 50 °C / 120 min 55-65 °C / 150 min • • • • • • • • • • • • • • • • • • •	7 - - 50 °C / 198 min 60 °C / 90 min 50 °C / 120 min 50°C / 120 min 50°C / 150 min - - - - - - - - - - - - - - - - - - -	24h 5 65 °C / 205 min 55 °C / 175 min 45 °C / 235 min 60 °C / 90 min - - 50°C / 30 min - - - - - - - - - - - - - - - - - - -
6 65 °C / 205 min 45 °C / 220 min 50 °C / 175 min 50 °C / 120 min 50 °C / 120 min 50 °C / 30 min	4 65 °C / 205 min 60 °C / 90 min 50 °C / 30 min - - - - - - - - - - - - - - - - - - -	8 65 °C / 205 min 55 °C / 175 min 55 °C / 198 min 55 °C / 20 min 35°C / 20 min 35°C / 20 min 55-65 °C / 150 min • • • • • • • • • • • • • • • • • • •	24h 8 65 °C / 205 min 55 °C / 175 min 50 °C / 198 min 55 °C / 90 min 55 °C / 20 min 35°C / 20 min 35°C / 20 min 55-65 °C / 150 min • • • • • • • • • • • • • • • • • • •	6 65 °C / 205 min 55 °C / 175 min 65 °C / 235 min 50 °C / 120 min 50 °C / 120 min 50 °C / 30 min - - - - - - - - - - - - - - - - - - -	6 65 °C / 205 min 55 °C / 175 min 65 °C / 235 min 50 °C / 120 min 50 °C / 120 min 50 °C / 30 min - - - - - - - - - - - - - - - - - - -	• 24h 24h 7 - 50 °C / 198 min 50 °C / 198 min 50°C / 30 min 50°C / 30 min • • • • • • • • • • • • • • • • • • •	24h 5 - - 50 °C / 198 min 60 °C / 90 min 50 °C / 120 min 50 °C / 120 min 50° C / 120 min 50° C / 120 min 50° C / 120 min 6 - - - - - - - - - - - - - - - - - -	7 - - 50 °C / 198 min 60 °C / 90 min 50 °C / 120 min 50 °C / 120 min - - 55-65 °C / 150 min - - - - - - - - - - - - - - - - - - -	24h 24h 5 65 °C / 205 min 55 °C / 175 min 45 °C / 235 min 60 °C / 90 min - 50°C / 30 min - - 50°C / 30 min - - - - - - - - - - - - - - - - - - -
6 65 °C / 205 min 55 °C / 175 min 45 °C / 220 min 50 °C / 20 min 50 °C / 30 min 50 °C / 30 min 40 °C 9 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0	4 65 °C / 205 min 60 °C / 90 min 50 °C / 90 min - - - - - - - - - - - - - - - - - - -	8 65 °C / 205 min 55 °C / 175 min 50 °C / 198 min 55 °C / 90 min 55 °C / 20 min 35°C / 20 min 15 min 55-65 °C / 150 min • • • • • • • • • • • • • • • • • • •	24h 8 65 °C / 205 min 55 °C / 175 min 50 °C / 198 min 50 °C / 190 min 50 °C / 20 min 35 °C / 20 min 35 °C / 20 min 55-65 °C / 150 min • • • • • • • • • • • • • • • • • • •	6 65 °C / 205 min 55 °C / 175 min 65 °C / 235 min 50 °C / 230 min 50 °C / 20 min 50 °C / 20 min 50 °C / 20 min 50 °C / 20 min 6 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0	6 65 °C / 205 min 55 °C / 175 min 65 °C / 235 min 50 °C / 230 min 50 °C / 30 min - - - - - - - - - - - - - - - - - - -	• • 24h 7 - 50 °C / 198 min 50 °C / 198 min 50°C / 30 min 50°C / 30 min 55-65 °C / 150 min • • • • • • • • • • • • • • • • • • •	24h 5 - 50 °C / 198 min 60 °C / 90 min 50 °C / 120 min 50 °C / 120 min 55-65 °C / 150 min • • • • • • • • • • • • • • • • • • •	7 - - 50 °C / 198 min 60 °C / 90 min 50 °C / 120 min 50 °C / 120 min 55 - 65 °C / 150 min - - - - - - - - - - - - - - - - - - -	24h 5 65 °C / 205 min 55 °C / 175 min 45 °C / 235 min 60 °C / 90 min - 50°C / 30 min - - 50°C / 30 min - - - - - - - - - - - - - - - - - - -
6 65 °C / 205 min 55 °C / 175 min 45 °C / 220 min 50 °C / 30 min 50 °C / 30 min - - - - - - - - - - - - - - - - - - -	4 65 °C / 205 min 60 °C / 90 min - 50°C / 30 min - - - - - - - - - - - - - - - - - - -	8 65 °C / 205 min 55 °C / 175 min 55 °C / 198 min 55 °C / 90 min 55 °C / 20 min 35°C / 20 min 55-65 °C / 150 min • • • • • • • • • • • • • • • • • • •	24h 8 65 °C / 205 min 55 °C / 175 min 50 °C / 198 min 55 °C / 90 min 55 °C / 20 min 35 °C / 20 min 35 °C / 20 min 55-65 °C / 150 min • • • • • • • • • • • • • • • • • • •	6 65 °C / 205 min 55 °C / 235 min 65 °C / 235 min 50 °C / 120 min 50 °C / 120 min - - - - - - - - - - - - - - - - - - -	6 65 °C / 205 min 55 °C / 235 min 65 °C / 235 min 50 °C / 120 min 50 °C / 30 min - - - - - - - - - - - - - - - - - - -	• • 24h 7 - 50 °C / 198 min 50 °C / 198 min 50°C / 30 min 50°C / 30 min • • • • • • • • • • • • • • • • • • •	24h 5 - - 50°C / 198 min 60°C / 90 min 50°C / 120 min 50°C / 120 min 55-65°C / 150 min • • • • • • • • • • • • • • • • • • •	7 - 50 °C / 198 min 60 °C / 90 min 50 °C / 120 min 50 °C / 120 min 50 °C / 120 min 6 - 55-65 °C / 150 min 6 - - - - - - - - - - - - - - - - - -	24h 24h 5 65 °C / 205 min 55 °C / 175 min 45 °C / 235 min 60 °C / 205 min 55 °C / 175 min 45 °C / 235 min 60 °C / 30 min - 50°C / 30 min - 50°C / 30 min - - 50°C / 30 min - - 50°C / 30 min - - - - - - - - - - - - - - - - - - -
6 65 °C / 205 min 55 °C / 175 min 45 °C / 220 min 50 °C / 20 min 50 °C / 30 min 50 °C / 30 min 40 °C 9 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0	4 65 °C / 205 min 60 °C / 90 min 50 °C / 90 min - - - - - - - - - - - - - - - - - - -	8 65 °C / 205 min 55 °C / 175 min 50 °C / 198 min 55 °C / 90 min 55 °C / 20 min 35°C / 20 min 15 min 55-65 °C / 150 min • • • • • • • • • • • • • • • • • • •	24h 8 65 °C / 205 min 55 °C / 175 min 50 °C / 198 min 50 °C / 190 min 50 °C / 20 min 35 °C / 20 min 35 °C / 20 min 55-65 °C / 150 min • • • • • • • • • • • • • • • • • • •	6 65 °C / 205 min 55 °C / 175 min 65 °C / 235 min 50 °C / 230 min 50 °C / 20 min 50 °C / 20 min 50 °C / 20 min 50 °C / 20 min 6 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0	6 65 °C / 205 min 55 °C / 175 min 65 °C / 235 min 50 °C / 230 min 50 °C / 30 min - - - - - - - - - - - - - - - - - - -	• • 24h 7 - 50 °C / 198 min 50 °C / 198 min 50°C / 30 min 50°C / 30 min 55-65 °C / 150 min • • • • • • • • • • • • • • • • • • •	24h 5 - 50 °C / 198 min 60 °C / 90 min 50 °C / 120 min 50 °C / 120 min 55-65 °C / 150 min • • • • • • • • • • • • • • • • • • •	7 - - 50 °C / 198 min 60 °C / 90 min 50 °C / 120 min 50 °C / 120 min 55 - 65 °C / 150 min - - - - - - - - - - - - - - - - - - -	24h 5 65 °C / 205 min 55 °C / 175 min 45 °C / 235 min 60 °C / 90 min - 50°C / 30 min - - 50°C / 30 min - - - - - - - - - - - - - - - - - - -
6 65 °C / 205 min 55 °C / 175 min 45 °C / 220 min 50 °C / 30 min 50 °C / 30 min - - - - - - - - - - - - - - - - - - -	4 65 °C / 205 min 60 °C / 90 min - 50°C / 30 min - - - - - - - - - - - - - - - - - - -	8 65 °C / 205 min 55 °C / 175 min 55 °C / 90 min 55 °C / 20 min 55 °C / 20 min 15 min 55-65 °C / 150 min • • • • • • • • • • • • • • • • • • •	24h 8 65 °C / 205 min 55 °C / 175 min 50 °C / 198 min 55 °C / 90 min 55 °C / 20 min 35°C / 20 min 55-65 °C / 150 min • • • • • • • • • • • • • • • • • • •	6 65 °C / 205 min 55 °C / 175 min 65 °C / 235 min 50 °C / 120 min 50 °C / 120 min 50 °C / 120 min - - - - - - - - - - - - - - - - - - -	6 65 °C / 205 min 55 °C / 175 min 65 °C / 235 min 50 °C / 230 min 50 °C / 120 min 50 °C / 30 min - - - - - - - - - - - - - - - - - - -	• • 24h 7 - 50 °C / 198 min 50 °C / 198 min 50°C / 30 min 55°-65 °C / 150 min • • • • • • • • • • • • • • • • • • •	24h 5 - 50 °C / 198 min 60 °C / 90 min 50 °C / 120 min 50 °C / 120 min 55-65 °C / 150 min • • • • • • • • • • • • • • • • • • •	7 - 50 °C / 198 min 60 °C / 90 min 50 °C / 120 min 50 °C / 120 min 55-65 °C / 150 min • • • • • • • • • • • • • • • • • • •	24h 5 65 °C / 205 min 55 °C / 175 min 45 °C / 235 min 60 °C / 90 min - - - - - - - - - - - - - - - - - - -
6 65°C / 205 min 55°C / 175 min 45°C / 220 min 50°C / 30 min 50°C / 30 min - - - - - - - - - - - - - - - - - - -	4 65 °C / 205 min 60 °C / 90 min 50 °C / 90 min - 50 °C / 30 min - - - - - - - - - - - - - - - - - - -	8 65 °C / 205 min 55 °C / 175 min 55 °C / 198 min 55 °C / 20 min 35°C / 20 min 35°C / 20 min 35°C / 20 min 55-65 °C / 120 min 55-65 °C / 100 min 6 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0	224h 8 65 °C / 205 min 55 °C / 175 min 50 °C / 198 min 55 °C / 90 min 50 °C / 120 min 35 °C / 20 min 15 min 55-65 °C / 150 min • • • • • • • • • • • • • • • • • • •	6 65 °C / 205 min 55 °C / 175 min 65 °C / 30 min 50 °C / 30 min - - - - - - - - - - - - - - - - - - -	6 65 °C / 205 min 55 °C / 175 min 65 °C / 235 min 50 °C / 230 min 50 °C / 20 min 50 °C / 20 min 50 °C / 30 min - - - - - - - - - - - - - - - - - - -	• • 24h 7 - 50 °C / 198 min 50 °C / 198 min 50°C / 30 min 55-65 °C / 150 min 55-65 °C / 150 min • • • • • • • • • • • • • • • • • • •	24h 5 - 50 °C / 198 min 60 °C / 90 min 50 °C / 120 min 50 °C / 120 min 55-65 °C / 150 min • • • • • • • • • • • • • • • • • • •	7 - 50 °C / 198 min 60 °C / 90 min 50 °C / 120 min 50 °C / 120 min 55-65 °C / 150 min • • • • • • • • • • • • • • • • • • •	24h 5 65 °C / 205 min 55 °C / 175 min 45 °C / 235 min 60 °C / 90 min - 50°C / 30 min - - 50°C / 30 min - - - - - - - - - - - - - - - - - - -
6 65°C / 205 min 55°C / 175 min 45°C / 220 min 50°C / 30 min 50°C / 30 min 45°C / 30 min 50°C / 30 min 40°C 40°C 40°C 40°C 40°C 40°C 40°C 40°C	4 65 °C / 205 min 60 °C / 90 min 50 °C / 90 min - - - - - - - - - - - - - - - - - - -	8 65°C / 205 min 55°C / 175 min 55°C / 198 min 55°C / 20 min 35°C / 20 min 36°C / 20 m	224h 8 65 °C / 205 min 55 °C / 175 min 50 °C / 198 min 55 °C / 90 min 50 °C / 120 min 35 °C / 20 min 55 - 65 °C / 150 min • • • • • • • • • • • • • • • • • • •	6 65°C / 205 min 55°C / 175 min 65°C / 235 min 50°C / 30 min 50°C / 30 min - - - - - - - - - - - - - - - - - - -	6 65 °C / 205 min 55 °C / 175 min 65 °C / 235 min 50 °C / 230 min 50 °C / 20 min 50 °C / 20 min 50 °C / 20 min 50 °C / 20 min 6 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0	• • 24h 7 - 50 °C / 198 min 50 °C / 198 min 50°C / 30 min 50°C / 30 min 50°C / 150 min 6 • • • • • • • • • • • • • • • • • •	24h 5 - - 50°C / 198 min 60°C / 90 min 50°C / 120 min 50°C / 120 min 50°C / 120 min 50°C / 150 min 0 - - - - - - - - - - - - - - - - - -	7 - - 50 °C / 198 min 60 °C / 90 min 50 °C / 120 min 50 °C / 120 min 55 - 65 °C / 150 min • • • • • • • • • • • • • • • • • • •	24h 5 65 °C / 205 min 55 °C / 175 min 45 °C / 235 min 60 °C / 90 min 50 °C / 30 min - 50 °C / 30 min - - 50 °C / 30 min - - 50 °C / 30 min - - 50 °C / 30 min - - - - - - - - - - - - -
6 65 °C / 205 min 45 °C / 220 min 50 °C / 30 min 50 °C / 30 min 50 °C / 30 min 45 °C / 30 min 50 °C / 30 min 40 °C 40 °C	4 65 °C / 205 min 60 °C / 90 min 50 °C / 30 min - - - - - - - - - - - - - - - - - - -	8 65 °C / 205 min 55 °C / 175 min 55 °C / 198 min 55 °C / 20 min 35°C / 20 min 35°C / 20 min 35°C / 20 min 55-65 °C / 150 min • • • • • • • • • • • • • • • • • • •	24h 24h 8 65 °C / 205 min 55 °C / 175 min 50 °C / 198 min 55 °C / 90 min 50 °C / 120 min 35 °C / 20 min 35 °C / 20 min 9 15 min 55-65 °C / 150 min 0 0 0 0 0 0 0 0 0 0 0 0 0	6 65 °C / 205 min 55 °C / 175 min 65 °C / 235 min 65 °C / 235 min 50 °C / 120 min 50 °C / 120 min 50 °C / 30 min 45 °C / 30 min 50 °C / 30 min 50 °C / 30 min 45 °C / 30 min 50 °C / 30 min 45 °C / 30 min 50 °C / 30 min 45 °C / 30 min 50 °C / 30 mi	6 65 °C / 205 min 55 °C / 175 min 65 °C / 235 min 65 °C / 235 min 50 °C / 120 min 50 °C / 120 min 50 °C / 30 min - - - - - - - - - - - - - - - - - - -	• • 24h - - 50 °C / 120 min 50 °C / 120 min 50°C / 30 min • • • • • • • • • • • • • • • • • • •	24h 5 - - 50°C / 198 min 60°C / 90 min 50°C / 120 min 50°C / 120 min 55-65°C / 150 min 4 - - - - - - - - - - - - - - - - - -	7 - 50 °C / 198 min 60 °C / 90 min 50 °C / 120 min 50 °C / 120 min - 55-65 °C / 150 min - - - - - - - - - - - - - - - - - - -	24h 24h 5 65 °C / 205 min 55 °C / 175 min 45 °C / 235 min 60 °C / 205 min 55 °C / 175 min 45 °C / 235 min 60 °C / 30 min - 50°C / 30 min - - 50°C / 30 min - - - - - - - - - - - - - - - - - - -
6 65°C / 205 min 55°C / 175 min 45°C / 220 min 50°C / 30 min 50°C / 30 min 45°C / 30 min 45°C / 30 min 40°C 40°C 40°C 40°C 40°C 40°C 40°C 40°C	4 65 °C / 205 min 60 °C / 90 min - 50°C / 30 min - - - - - - - - - - - - - - - - - - -	8 65 °C / 205 min 55 °C / 175 min 55 °C / 198 min 55 °C / 20 min 35° C / 20 min 35° C / 20 min 15 min 55-65 °C / 150 min • • • • • • • • • • • • • • • • • • •	24h 24h 8 65 °C / 205 min 55 °C / 175 min 50 °C / 120 min 35°C / 20 min 35°C / 20 min 35°C / 20 min 0 0 0 0 0 0 0 0 0 0 0 0 0	6 65 °C / 205 min 55 °C / 175 min 65 °C / 235 min 65 °C / 30 min 50 °C / 120 min 50 °C / 30 min - - - - - - - - - - - - - - - - - - -	6 65 °C / 205 min 55 °C / 175 min 65 °C / 235 min 65 °C / 30 min 50 °C / 120 min 50 °C / 120 min 61 min 61m	• • 24h 7 - 50 °C / 198 min 50 °C / 198 min 50 °C / 198 min 55 • 65 °C / 150 min • • • • • • • • • • • • • • • • • • •	24h 5 - - 50 °C / 198 min 60 °C / 90 min 50 °C / 120 min 50 °C / 120 min 55-65 °C / 150 min 4 - - - - - - - - - - - - - - - - - -	7 - - 50 °C / 198 min 60 °C / 90 min 50 °C / 120 min 55-65 °C / 150 min • • • • • • • • • • • • • • • • • • •	24h 24h 5 65 °C / 205 min 55 °C / 175 min 45 °C / 235 min 60 °C / 90 min - 50°C / 30 min - 50°C / 30 min - - - - - - - - - - - - -
6 65°C / 205 min 55°C / 175 min 45°C / 220 min 50°C / 30 min 50°C / 30 min 45°C / 30 m	4 65 °C / 205 min 60 °C / 90 min - 50°C / 30 min - - - - - - - - - - - - - - - - - - -	8 65 °C / 205 min 55 °C / 175 min 55 °C / 198 min 55 °C / 20 min 35 °C / 20 min 35 °C / 20 min 35 °C / 120 min 9 °C / 120 °C / 120 min 9 °C / 120 °C		6 65 °C / 205 min 55 °C / 175 min 65 °C / 235 min 50 °C / 120 min 50 °C / 120 min - - - - - - - - - - - - - - - - - - -	6 65 °C / 205 min 55 °C / 175 min 65 °C / 235 min 50 °C / 230 min 50 °C / 120 min 50 °C / 30 min - - - - - - - - - - - - - - - - - - -	• • • • • • • • • • • • • • • • • • •	24h 5 - 50 °C / 198 min 60 °C / 90 min 50 °C / 120 min 50 °C / 120 min 50 °C / 120 min 50 °C / 120 min 4 55-65 °C / 150 min 4 0 0 0 0 0 0 0 0 0 0 0 0 0	7 - - 50 °C / 198 min 60 °C / 90 min 50 °C / 120 min 50 °C / 120 min 50°C / 120 min - - - - - - - - - - - - - - - - - - -	24h 5 65 °C / 205 min 55 °C / 175 min 45 °C / 235 min 60 °C / 90 min - - 50°C / 30 min - - - - - - - - - - - - - - - - - - -
6 65°C / 205 min 55°C / 175 min 45°C / 220 min 50°C / 30 min 50°C / 30 min - - - - - - - - - - - - - - - - - - -	4 65 °C / 205 min 60 °C / 90 min - 50°C / 30 min - - - - - - - - - - - - - - - - - - -	8 65 °C / 205 min 55 °C / 175 min 55 °C / 198 min 55 °C / 20 min 35°C / 20 min 4000000000000000000000000000000000000	24h 8 65 °C / 205 min 55 °C / 175 min 50 °C / 198 min 55 °C / 90 min 50 °C / 120 min 35 °C / 20 min 55 - 65 °C / 150 min • • • • • • • • • • • • • • • • • • •	6 65 °C / 205 min 55 °C / 175 min 65 °C / 235 min 50 °C / 230 min 50 °C / 230 min - - - - - - - - - - - - - - - - - - -	6 65 °C / 205 min 55 °C / 175 min 65 °C / 235 min 50 °C / 230 min 50 °C / 230 min 50 °C / 30 min - - - - - - - - - - - - - - - - - - -		24h 5 - 50 °C / 198 min 60 °C / 90 min 50 °C / 120 min 50 °C / 120 min 50 °C / 120 min 55-65 °C / 150 min 0 0 0 0 0 0 0 0 0 0 0 0 0	7 - 50 °C / 198 min 60 °C / 90 min 50 °C / 120 min 50 °C / 120 min 55-65 °C / 150 min • • • • • • • • • • • • • • • • • • •	24h 5 65 °C / 205 min 55 °C / 175 min 45 °C / 235 min 60 °C / 90 min - 50°C / 30 min - 50°C / 30 min - - 50°C / 30 min - - - - - - - - - - - - -
6 65°C / 205 min 55°C / 175 min 45°C / 220 min 50°C / 30 min 50°C / 30 min 45°C / 30 m	4 65 °C / 205 min 60 °C / 90 min - 50°C / 30 min - - - - - - - - - - - - - - - - - - -	8 65 °C / 205 min 55 °C / 175 min 55 °C / 198 min 55 °C / 20 min 35 °C / 20 min 35 °C / 20 min 35 °C / 120 min 9 °C / 120 °C / 120 min 9 °C / 120 °C		6 65 °C / 205 min 55 °C / 175 min 65 °C / 235 min 50 °C / 120 min 50 °C / 120 min - - - - - - - - - - - - - - - - - - -	6 65 °C / 205 min 55 °C / 175 min 65 °C / 235 min 50 °C / 230 min 50 °C / 120 min 50 °C / 30 min - - - - - - - - - - - - - - - - - - -	• • • • • • • • • • • • • • • • • • •	24h 5 - - 50 °C / 198 min 60 °C / 90 min 50 °C / 120 min 50 °C / 120 min 55-65 °C / 150 min • • • • • • • • • • • • • • • • • • •	7 - - 50 °C / 198 min 60 °C / 90 min 50 °C / 120 min 50 °C / 120 min 50°C / 120 min - - - - - - - - - - - - - - - - - - -	24h 5 65 °C / 205 min 55 °C / 175 min 45 °C / 235 min 60 °C / 90 min - - 50°C / 30 min - - - - - - - - - - - - - - - - - - -

DISHWASHERS

edesə

All the boxes marked with a ${\scriptstyle \bullet}$ are equivalent to a Yes

edesə

WASHING MACHINE		1					
EWF-10400 WH	172	EWF-9400 MTBK	172	EWF-9401 WH	173	EWF-8403 WH	173
EWF-9400 WH	174	EWF-8402 WH	174	EWF-7201 X	175	EWF-7201 WH	175
				NEW		NEW	
EWF-6000 WH	176	EWS-8401 WH	176	BUILT IN WASHER-DRYER EWS-8400 I	177	BUILT IN WASHER EWF-9400 I	177
DRYER							
ESC-8161 WH	178	ESP-8150 WH	178				





WASHERS AND DRYERS

The most complete range EDESA

Since we were not sure which one you would choose, in Edesa we offer you the most complete range.

Free installation washing machines from 6 kg, for those who Large format dryer, to dry up to 8 kg, which adapts do not get dirty a lot, up to 10 kg, for large families. All of them adapting to your liking, with larger displays or Led indicators, with different settings and above all, looking for the most energy efficient, thanks to among others the Silence Inverter technology.

to your needs with its 16 drying programs. From fast programs (30, 45 and 60 minutes), to specific programs for delicate or baby's clothes. In addition, you can use the deferred programming function for up to 12 hours.

In addition to front-loading washing machines, we also adapt to your needs with integration models, both 8 kg washing machines and 9 kg washing/drying machines (8 kg washing and 6 kg drying).



A large hatch, suitable for duvets and blankets

In Edesa we value ergonomics and handling. Life is moving so fast and, with it, we grow ourselves, our homes and our laundry.

Forget the uncomfortable and small hatches of old washing machines and try Edesa. The loading and unloading of duvets, blankets, sheets or towels has never been so easy, thanks to the dimensions of its hatch up to 33 cm.



edesə

"Easy-to-use" design

The new aesthetics of the washing machine's control panels exceed the standards of the market.

To the comfort and simplicity of its panel and the easy-to-use metallic programmer control, we add the renewed pictograms and the cheerful blue Edesa to improve the appearance of the appliance we coexist with.

Remaining time or washing phase indicators

To better schedule your time, Edesa washing machines show the remaining washing time on its display; thus, forgetting about the laundry.

And if you are looking for simplicity, some are provided with a LED indicator which show at what washing phase it is.





Our washing machines consume the required water and energy in accordance to the quantity of clothes being laundered.

Reducing greenhouse gas emissions is part of our global commitment, which is why we are working on reducing the energy consumption of our washing machines to reach again the maximum energy classification according to the recent delegated regulation (EU) 2019/2023. So that you and your family can enjoy a cleaner world, the values have been rescaled, with classes A+++, A++ and A+ disappearing, starting from class A. This does not mean that now your washing machine consumes more than before, but that the scale has changed.

Starting up the washing machine, whatever the clothes you have, won't be a waste anymore, since they only consume based on the load.

With your new Edesa class A washing machine, you will have significant energy and economic savings on your electricity bill, as well as a lower environmental impact.



edesə

Silence Inverter



Thanks to the "Silence Inverter" system washing machines are really efficient, achieving an A.

The Inverter motor reduces friction, guaranteeing a longer lifetime to our washing machine.

In this way we get a more stable washing machine, with less movement when spinning, and silence.

With the inverter motors you will have triple tranquility; you will notice a lower consumption of electricity in your bill, less noise and the guarantee of 10 years in its motor.



Special programs

Deferred programming function up to 24h

Washing machines and dryers which adapt to our schedule and lifestyle. The deferred programming function allows you to delay its start up to 24 hours.

You decide when the washing starts up, so laundry will be ready when you get home.

Fast programs... designed for people with little time, who need to wash clothes for daily use. In just 30, 45 or 60 minutes your clothes will get ready, and you would have optimized time, water and energy.

"My program" And if you are one of those who do not resign yourselves and prefer making your own rules, Edesa offers the programmable function, so you choose your ideal launder with "My program".

Recharge: The reload function allows you to add additional laundry after the wash cycle has started. This is a very useful feature if you have forgotten to add a garment or need to wash something urgently.

Washing Machine Cleaning Program: Regular washing machine cleaning prevents the formation of mildew and unpleasant odors, ensuring a more effective cleaning of the laundry.

Do you want to take care of your favorite SPORT clothes?

With Edesa we offer the "Sport" program, ideal for technical clothing.

Do you want the SILK SHIRTS AND BLOUSES, WOOL SWEATERS AND YOUR BABY'S MOST DELICATE CLOTHES TO BE AS BEAUTIFUL AS THE FIRST DAY? WITH THE "DELICATE", "WOOL" AND "BABY CLOTHES" programs, forget your worries.

With the 'Delicate', 'Wool', and 'Baby Clothes' programs, forget about worries.







edesə

edesə

Steam washing:

ave time and effort in ironing thanks to the reduction of wrinkles with steam washing. In addition, steam removes stubborn stains, bacteria, germs and odors without the need for harsh detergents that are harmful to your clothes and your skin,

Efficient Consumption: Despite being an additional function, steam washing consumes 35% less water and 20% less energy compared to traditional cycles.





edesa





10 kg a free standing washer							9 kg a free standing washer					
EWF-1	0400 W	Н	White		NEW		EWF-	9400 MT	ВК	Black m	att	NEW
Cod.:	925270568	3 - EAN:	84222483	59368			Cod.:	92527056	9 - EAN:	84222483	59399	
Α		~	Ş				Α	() kg	~	С.		
ENERGY EFFICIENCY	WASHING CAPACITY	MOTOR SILENCE INVERTER	STEAM	PHASE INDICATOR	REMAINING WASHING TIME INDICATOR		ENERGY EFFICIENCY	WASHING CAPACITY	MOTOR SILENCE INVERTER	STEAM	PHASE INDICATOR	REMAINING WASHING TIME INDICATOR
,h ↓	LED		10	11 V			h	LED		10	!!	
DELAYED START	LED DISPLAY	MY PROGRAM	10 YEAR MOTOR WARRANTY	WITH PLUG	CLEAN WASHING MACHINE		DELAYED START	LED DISPLAY	MY PROGRAM	10 YEAR MOTOR WARRANTY	WITH PLUG	CLEAN WASHING MACHINE
-Front load -Silence Inv	ing washing verter moto							ding washin overter moto	0	e		

-1 to 10 kilos capacity

-1.400 rpm maximum spin speed

-Energy class A

-Childproof safety lock and door-lock

-18 programmes with 16 wash programmes. Special programs: Fast 15 and 59 min, mixed, baby-clothes, jeans and duvet -Steam wash

-Independent temperature and spin speed selectors

-Led technology display: program delay up to 24 hours, duration and remaining washing time

-Function selector: program delay up to 24 hours, prewash and extra rinse

-Noise reduction and cushioning foam





-18 programmes with 16 wash programmes. Special programs: Fast 15 and 59 min, mixed, baby-clothes, jeans and duvet -Steam wash

-Independent temperature and spin speed selectors -Led technology display: program delay up to 24 hours, duration and remaining washing time

-Function selector: program delay up to 24 hours, prewash and extra rinse

-Noise reduction and cushioning foam



edesə





9 KG A FREE STANDING WASHER										
EWF-9401 W	NEW									
Cod.: 92527056										
ENERGY EFFICIENCY EFFICIENCY WASHING CAPACITY	MOTOR SILENCE INVERTER	STEAM	PHASE INDICATOR	REMAINING WASHING TIME INDICATOR						
-Front loading washi	MY PROGRAM	10 YEAR MOTOR WARRANTY	WITH PLUG	CLEAN WASHING MACHINE						

Front loading washing machine
 Silence Inverter motor

- -1 to 9 kilos capacity
- -1.400 rpm maximum spin speed
- -Energy class A
- -Childproof safety lock and door-lock
- -18 programmes with 16 wash programmes. Special programs: Fast 15 and 59 min, mixed, baby-clothes, jeans and duvet -Steam wash
- -Independent temperature and spin speed selectors
- -Led technology display: program delay up to 24 hours,
- duration and remaining washing time
- -Function selector: program delay up to 24 hours, prewash and extra rinse
- -Noise reduction and cushioning foam



8 KG A					
EWF-8	8403 WH	1	White		NEW
Cod.:	92527056	5 - EAN:	84222483	59337	
Α	8 kg	C	E		
ENERGY EFFICIENCY	WASHING CAPACITY	MOTOR SILENCE INVERTER	STEAM	PHASE INDICATOR	REMAINING WASHING TIME INDICATOR
/1 h	LED	\overleftrightarrow	10	#	



-Front loading washing machine

- -Silence Inverter motor
- -1 to 8 kilos capacity
- -1.400 rpm maximum spin speed
- -Energy class A
- -Childproof safety lock and door-lock
- -18 programmes with 16 wash programmes. Special programs: Fast 15 and 59 min, mixed, baby-clothes, jeans and duvet -Steam wash
- -Independent temperature and spin speed selectors
- -Led technology display: program delay up to 24 hours, duration and remaining washing time
- -Function selector: program delay up to 24 hours, prewash and extra rinse
- -Noise reduction and cushioning foam



edesə





9 kg a free Standing Washer					8 kg a free standing washer							
EWF-9	7400 WH	l	White		NEW		EWF-8	8402 WH	I	White		NEW
Cod.: 925270572 - EAN: 8422248359429						Cod.: 925270571 - EAN: 8422248359412						
Α	9 kg	7	Ş				Α	8 kg	7	¢		
ENERGY EFFICIENCY	WASHING CAPACITY	MOTOR SILENCE INVERTER	STEAM	PHASE INDICATOR	REMAINING WASHING TIME INDICATOR		ENERGY EFFICIENCY	WASHING CAPACITY	MOTOR SILENCE INVERTER	STEAM	PHASE INDICATOR	REMAINING WASHING TIME INDICATOR
h	LED		10	!!			h	LED	\overleftrightarrow	10	!!	
DELAYED START	LED DISPLAY	MY PROGRAM	10 YEAR MOTOR WARRANTY	WITH PLUG	CLEAN WASHING MACHINE		DELAYED START	LED DISPLAY	MY PROGRAM	10 YEAR MOTOR WARRANTY	WITH PLUG	CLEAN WASHING MACHINE
-Front loading washing machine				-	Front load	ding washing	g machine	•				

-Silence Inverter motor

- -1 to 9 kilos capacity
- -Variable consumption depending on load
- -1.400 rpm maximum spin speed

-Energy class A

-Childproof safety lock and door-lock

-16 programmes with 13 wash programmes

-Steam wash

-Independent temperature and spin speed selectors

-Led technology display: program delay up to 24 hours, duration and remaining washing time

-Special programs: Fast 15 min, mixed, baby-clothes, sports and duvet

-Function selector: program delay up to 24 hours, prewash and extra rinse



- -Silence Inverter motor
- -1 to 8 kilos capacity
- -Variable consumption depending on load
- -1.400 rpm maximum spin speed
- -Energy class A
- -Childproof safety lock and door-lock

-16 programmes with 13 wash programmes. Special programs: Fast 15 min, mixed, baby-clothes, sports and duvet

-Steam wash

-Independent temperature and spin speed selectors

-Led technology display: program delay up to 24 hours, duration and remaining washing time

-Function selector: program delay up to 24 hours, prewash and extra rinse



edesə





7 kg a free standing washer									
EWF-7	7201 X		Stainless	NEW					
Cod.:									
Α	(7) kg	C	ę э						
ENERGY EFFICIENCY	WASHING CAPACITY	MOTOR SILENCE INVERTER	STEAM	PHASE	REMAINING WASHING TIME INDICATOR				
h	LED	\overleftrightarrow	10	÷					
DELAYED START	LED DISPLAY	MY PROGRAM	10 YEAR MOTOR WARRANTY	WITH PLUG	CLEAN WASHING MACHINE				

-Front loading washing machine

- -Silence Inverter motor
- -1 to 7 kilos capacity
- -Variable consumption depending on load
- -1.200 rpm maximum spin speed

-Energy class A

-Childproof safety lock and door-lock

-18 programmes with 16 wash programmes. Special programs: Fast 15 and 59 min, mixed, baby-clothes, jeans and duvet -Steam wash

-Independent temperature and spin speed selector

-Led technology display: program delay up to 24 hours, duration and remaining washing time

-Function selector: program delay up to 24 hours, prewash and extra rinse



7 KG D FREE STANDING WASHER									
EWF-2	7201 WH	1	White	NEW					
Cod.: 925270570 - EAN: 8422248359405									
D	(7) kg	C	С Э	h	\overleftrightarrow				
ENERGY EFFICIENCY	WASHING CAPACITY	MOTOR SILENCE INVERTER	STEAM PREWASH	DELAYED START	MY PROGRAM				



-Front loading washing machine

- -1 to 7 kilos capacity
- -1.200 rpm maximum spin speed
- -Energy class D
- -Childproof safety lock and door-lock

-15 programmes with 12 wash programmes. Special programs: Fast 15 min, mixed, baby-clothes, sports and cotton color

-Independent temperature and spin speed selector -Led technology display: program delay up to 12 hours, duration and remaining washing time

-Function selector: program delay up to 12 hours and extra rinse



edesa





8/6 KG D FREE STANDING WASHER-DRYER

EWS-8401 WH	White
Cod.: 925270576 - EA	N: 8422248376952



















MACHINE





STEAM PREWASH

-Front loading washing machine

White

L

REMAINING

WASHING TIME INDICATOR

- -1 to 6 kilos capacity
- -1.000 rpm maximum spin speed
- -Energy class D

D

ENERGY EFFICIENC

WITH PLUG

- -Childproof safety lock and door-lock
- -23 programmes with 19 wash programmes.

6 KG D FREE STANDING WASHER

Cod.: 925270557 - EAN: 8422248344449

DELAYED START

EWF-6000 WH

WASHING CAPACITY

- -Special programs: Fast 15, 30 and 45 min, mixed and delicated
- programs -Special Function: Drum Cleaning
- -Steam wash

-Function selector: program delay up to 3/6/9 hours and extra rinse





- -1 to 8 kilos washing capacity.
- -Condensation dryer system
- -1 to 6 kg dryer capacity
- -Reversing system: alternate drum rotation for uniform drying
- -1.400 rpm maximum spin speed
- -Energy efficiency class: A-D
- -Childproof safety lock and door-lock
- -15 programmes with 13 wash programmes.
- -Special Function: Drum Cleaning
- -Steam wash

-Independent temperature and spin speed selector -Led technology display: program delay up to 24 hours, duration and remaining washing time



8/6 KG B/E BUILT IN WASHER-DRYER **EWS-8400-I** White

Cod.: 925270558 - EAN: 8422248344456



-Front loading built in washing-drying machine

- -Silence Inverter motor
- -1 to 8 kilos washing capacity.
- -Condensation dryer system
- -1 to 6 kg dryer capacity
- -Variable consumption depending on load
- -1.400 rpm maximum spin speed
- -Energy efficiency class: B-E
- -Childproof safety lock and door-lock
- -16 programmes with 13 wash programmes. Special: wash-dry
 60 min, mixed, baby-clothes, jeans, sport and customized
 -Independent temperature and spin speed selector
- -Independent temperature and spin speed selector -Led technology display: program delay up to 24 hours, duration and remaining washing time

-Function selector: program delay up to 24 hours and extra rinse. Dry degree selector





edesa

9 KG A BUILT IN WASHER								
EWF-9400 I	White							
Cod.: 925270559 - EAN: 8422248344463								



-Front loading built in washing machine -Silence Inverter motor

- -1 to 9 kilos washing capacity.
- -1.400 rpm maximum spin speed
- -Energy class A
- -Childproof safety lock and door-lock

-16 programmes with 13 wash programmes. Special programs: Fast 15 min, mixed, baby-clothes, sports and duvet -Steam wash

-Independent temperature and spin speed selector

- -Led technology display: program delay up to 24 hours, duration and remaining washing time
- -Function selector: program delay up to 24 hours and extra rinse



WASHERS AND DRYERS

edesa

NEW

61

WITH





8 KG B FREE STANDING DRYER					8 KG B FREE STANDING DRYER				
ESC-8	161 WH		White		ESP-81	50 WH		White	è
Cod.: 936270487 - EAN: 8422248344470					Cod.: 9	936270488	- EAN:	842224837	816
G	(B) kg	(i)		!!	B	(B) kg	(h		
ENERGY EFFICIENCY	WASHING CAPACITY	DELAYED START	PHASE	WITH PLUG	ENERGY EFFICIENCY	WASHING CAPACITY	DELAYED	PHASE INDICATOR	

-Front loading drying machine

-Condensation dryer system

-1 to 8 kg dryer capacity

-Reversing system: alternate drum rotation for uniform drying

-Variable consumption depending on load

-Energy efficiency class: G

-Childproof safety lock and door-lock

-16 programmes. Special programs: quick, antu creased, cool, delicate and, baby-clothes

-Function selector: program delay 3, 6, 9 ó 12 hours

-Front loading drying machine

- -Heat pump drying system
- -1 to 8 kg dryer capacity
- -Reversing system: alternate drum rotation for uniform drying
- -Variable consumption depending on load
- -Energy efficiency class: B
- -Childproof safety lock and door-lock
- -16 programmes. Special programs: quick, antu creased, cool, and, baby-clothes
- -Led technology display: program delay up to 24 hours, duration and remaining washing time

-Options: deferred programming up to 24 hours, drying level, anti-wrinkle and drying time selection




WASHERS AND DRYERS

edesə



WASHERS AND DRYERS

WASHERS AND DRYERS

Code	925270568	925270569	925270566	925270565	925270572	925270571	
EAN	8422248359368	8422248359399	8422248359344	8422248359337	8422248359429	8422248359412	
Model	EWF-10400 WH	EWF-9400 MTBK	EWF-9401WH	EWF-8403WH	EWF-9400 WH	EWF-8402 WH	
Finish	White	White	Black matt	White	White	White	
Product fiche according to EU Regulation 2019/2023			Diddittiidii				
Rated capacity (kg)	10	9	9	8	9	8	
Energy efficiency class (1)	A	A	A	A	A	A	
Water consumption in litres [per cycle], based on the ECO programme (3)	52	50	50	48	39	42	
Spin speed (rpm) - Rated capacity	1351	1351	1351	1350	1400	1400	
Spin-drying efficiency class (4)	B	B	B	B	B	B	
Type	Free standing	Free standing					
Airbone acoustical noise emissions in the spinning phase (dBA)	72 A	72 A	72 A	72 A	74 B	72 A	
Airbone acoustical noise amision class (spninning phase) Product dimensons	A	A	A	A	В	A	
Height min/max [mm]	850/860	850/860	850/860	850/860	845/865	845/865	
Width [mm]	595	595	595	595	595	595	
Depth [mm]	540	540	540	521	550	510	
Adjustable legs	•	•	•	•	•	•	
Cabinet and door dimensions							
Minimum cabinet height [mm]	-	-	-	-	-	-	
Minimum cabinet width [mm]	-	-	-	-	-	-	
Minimum cabinet depth [mm]	-	-	-	-	-	-	
General features							
Motor type	Silence Inverter	Silence Inverter					
Hatch door diameter [cm]				0		01.1.1	
Drum type	Stainless Steel	Stainless Steel					
Foam reduction system	• + Weight		• + Weight			• • + Weight	
Load self adjustment Recommended load indication	• + weight	• + Weight	• + weighi	• + Weight	• + Weight	• + weighi	
Foam recognition	-	-	-	-	•	-	
5	LED Digital	LED Digital					
Control type	Display	Display	Display	Display	Display	Display	
Independent washing temperature selection	•	•	•	•	•	•	
Independent spinning speed selection	•	•	•	•	•	•	
Delay start [h]	24h	24h	24h	24h	24h	24h	
Start / Pause key	•	•	•	•	•	•	
Countdown display	•	•	•	•	•	•	
Washing cycle display	•	•	•	•	•	•	
Programmes No. of washing machine/washing programmes	18/16	18/16	18/16	18/16	16/13	16/13	
Cotton	• / • + steam	•	•				
Color cotton	-	-	-	-	-	-	
Sintetic	•	•	•	•	•	•	
Delicates	-	-	-	-	-	-	
ECO	•	•	•	•	•	•	
20°C	•	•	•	•	•	•	
Wool	•	•	•	•	•	•	
Hand wash	-	-	-	-	-	-	
Quick [min]	59'	59'	59'	59'	-	-	
Express 15	•	•	•	•	•	•	
Mix	•	•	•	•	•	•	
Sport clothes	-	-	-	-	•	•	
Baby clothes	• / • + steam	 + steam 	 + steam 				
Customized Jeans	•	•	•	•	•	•	
Steam			•	•	-	-	
Anti-allergy	• / • + steam	• + steam	• + steam				
Shirts	-	-	-	-	-	-	
Duvets	•	•	•	•	•	•	
Dark linen	-	-	-	-	•	•	
Drum cleaning	•	•	•	•	•	•	
Prewash	•	•	•	•	•	•	
Extra rinse	•	•	•	•	•	•	
Anti-stain	-	-	-	-	•	•	
Faster	•	•	•	•	-	-	
Pause + load	•	•	•	•	•		
Temperature selection	*/20/30/40/60/90				*/20/30/40/60/90	*/20/30/40/60/90	
Spin speed selection	-/400/600/800/	-/400/600/800/	-/400/600/800/	-/400/600/800/	-/400/600/800/	-/600/800/	
	1000/1200/1400	1000/1200/1400	1000/1200/1400	1000/1200/1400	1000/1400	1000/1400	
Safety Child have been							
Child-lock door	•	•	•	•	•	•	
Anti-flooding system	•	•	•	•	•	•	
Power and water connection	220.240	220.240	220.240	220-240	220.240	220-240	
Voltage range [V] Frecuency [Hz]	220-240 50	220-240 50	220-240 50	220-240 50	220-240 50	50	
Rated power [W]	1.950	1.950	1.950	1.950	1.650	1.800	
Rated current [A]	1.950	1.950	1.950	1.950	-	-	
Type of plug	Schuko	Schuko	Schuko	Schuko	- Schuko	- Schuko	
	-	-	-	-	-	-	
Power cora lengin immi							
Power cord length [mm] Inlet water hose length [mm]	-	-	-	-	-	-	

edesa

All the boxes marked with a • are equivalent to a Yes

Accessories /

NOT INCLUDED • INCLUDED

Washing standard programs: 40 °C and 60 °C cotton. (1) Class range from A +++ (more efficient) to G (less efficient). (2) Annual energy average consumption based on 220 standard wash cycles using 40 °C and 60 °C cotton program, full load and half load and low consumption program. (3) Annual water average consumption based on 220 standard wash cycles using 40 °C cotton program, full load and half load and low consumption program. (3) Annual water average consumption based on 220 standard wash cycles using 40 °C cotton program, full load and half load and low consumption program. The real water consumption depends on the conditions of use. (4) Class range from A (more efficient) to G (less efficient).

DRYER

ed	esə

925270573	925270570	925270557	925270559	925270558
8422248372862 EWF-7201 X	8422248359405 EWF-7201 WH	8422248344449 EWF-6000 WH	8422248344463 EWF-9400 I	8422248344456 EWS-8400 I
EWF-7201 A			EWF-7400 I	EVV3-0400 I
Stainless steel	White	White	Built-in	Built-in
7	7	6	9	8-6
A	D	D	A	B-E
45	41	43	48	48 - 90
1150 C	1200 B	1000 C	1400 B	1400 B
Free standing	Free standing	Free standing	Built-in	Built-in
72	76	80	76	76
A	В	C	В	В
850/860	845	850	825	825
595	595	595	595	595
400	458	400	545 •	565 •
•	•	•	•	•
-	-	-	825	825
-	-	-	600	600
-	-	-	580	600
Silence Inverter	Standard	Standard	Silence Inverter	Silence Inverter
33		28,80	31	31
Stainless Steel	Stainless Steel	Stainless Steel	Stainless Steel	Stainless Steel
• • + Weight	•	•	• + Weight	 + Weight
• + weighi	•	-	-	• + weight
-	-	-	-	-
LED Digital	LED	LED Digital	LED Digital	LED Digital
Display		Display	Display	Display
•	•	•	•	•
• 24h	• 12h	•	•	•
24I1 •	•	•		
•	-	•	•	•
•	-	•	•	•
18/16	15/12	23/19	16/13	16/13
• / • + steam	•	•	•	•
-	•	-	-	-
•	-	•	•	•
•	•	•	•	•
•		-	-	-
•	•	•	•	•
-	-	•	•	•
59'	-	•	•	•
•	•	-	-	-
• / • + steam	•	•	•	•
-	•	•	•	•
• / • + steam	•	•	•	•
•	-	-	-	-
_	-	•	•	-
•	-	-	-	-
-	•	-	-	-
•	•	-	-	-
-	•	-	-	-
•	•	•	-	-
•	•	•	•	•
-	-	-	-	-
•	-	-	-	-
•	•			
*/20/30/40/60/90	• */20/40/60/95	*/20/30/40/60/90	*/20/30/40/60/90	*/20/30/40/60/90
*/20/30/40/60/90 -/400/600/800/ 1000/1200	*/20/40/60/95 -/600/800/ 1000/1200	*/20/30/40/60/90 -/600/800/1000	*/20/30/40/60/90 -/600/800/1000/ 1200/1400	*/20/30/40/60/90 -/600/800/1000/ 1200/1400
-/400/600/800/ 1000/1200	-/600/800/ 1000/1200	-/600/800/1000	-/600/800/1000/ 1200/1400	-/600/800/1000/ 1200/1400
-/400/600/800/	-/600/800/		-/600/800/1000/	-/600/800/1000/
-/400/600/800/ 1000/1200	-/600/800/ 1000/1200	-/600/800/1000	-/600/800/1000/ 1200/1400 •	-/600/800/1000/ 1200/1400
-/400/600/800/ 1000/1200	-/600/800/ 1000/1200	-/600/800/1000	-/600/800/1000/ 1200/1400 •	-/600/800/1000/ 1200/1400
-/400/600/800/ 1000/1200 • -	-/600/800/ 1000/1200 •	-/600/800/1000 • •	-/600/800/1000/ 1200/1400 •	-/600/800/1000/ 1200/1400 •
-/400/600/800/ 1000/1200 - 220-240	-/600/800/ 1000/1200 • • 220-240	-/600/800/1000 • • 220-240	-/600/800/1000/ 1200/1400 • • 220-240	-/600/800/1000/ 1200/1400 • • 220-240
-/400/600/800/ 1000/1200 • - 220-240 50	-/600/800/ 1000/1200 • • 220-240 50	-/600/800/1000 • 220-240 50	-/600/800/1000/ 1200/1400 • • 220-240 50 1.950 10	-/600/800/1000/ 1200/1400 • 220-240 50
-/400/600/800/ 1000/1200 • - 220-240 50 1.950 10 Schuko	-/600/800/ 1000/1200 • • 220-240 50	-/600/800/1000 • • 220-240 50 2.000 10 Schuko	-/600/800/1000/ 1200/1400 • • 220-240 50 1.950 10 Schuko	-/600/800/1000/ 1200/1400 • • 220-240 50 1.900 10 Schuko
-/400/600/800/ 1000/1200 - 220-240 50 1.950 10 Schuko 1,5	-/600/800/ 1000/1200 • • 220-240 50 1.800	-/600/800/1000 • 220-240 50 2.000 10 Schuko 1,5	-/600/800/1000/ 1200/1400 • • 220-240 50 1.950 10 Schuko 1,5	-/600/800/1000/ 1200/1400 • • 220-240 50 1.900 10 Schuko 1,5
-/400/600/800/ 1000/1200 • - 220-240 50 1.950 10 Schuko	-/600/800/ 1000/1200 • • 220-240 50 1.800	-/600/800/1000 • • 220-240 50 2.000 10 Schuko	-/600/800/1000/ 1200/1400 • • 220-240 50 1.950 10 Schuko	-/600/800/1000/ 1200/1400 • • 220-240 50 1.900 10 Schuko

ControlImage: control block keyImage: control block keyBlocked filter indicatorImage: control block keyImage: control block keyBlocked filter indicatorImage: control block keyImage: control block keyAnti-crease keyImage: control block keyImage: control block keyOn/Off keyImage: control block keyImage: control block keyStart delay options [h]3-6-9-1224Programme and displayImage: control block keyImage: control block keyStart delay options indicatorImage: control block keyImage: control block keyEnd of cycle indicatorImage: control block keyImage: control block keyEnd of cycle indicatorImage: control block keyImage: control block keyEnd of cycle indicatorImage: control block keyImage: control block keyFrogrammingImage: control block keyImage: control block keyAcustic indicator for programme endedImage: control block keyImage: control block keyFull tank indicatorImage: control block keyImage: control block keyQuick programme (anticreasers)60' and 30'Image: control block keyQuick programme (anticreasers)60' and 30'Image: control block keyQuick programme (anticreasers)60' and 30'Image: control block keyQuick programmeImage: control block keyImage: control block keyQuick programmeImage: control block keyImage: control block keySintefic programmeImage: control block keyImage: control block keyCot	Code EAN Model	936270487 8422248344470 ESC-8161 WH	936270488 8422248378161 ESP-8150 WH
Capacity conton [kg]88Delicate textilies dying capacity [kg]111Dryar typeCondensationHeat pumpPeragy efficiency class [2]88Total annual energy consumption i cotton hull (ad [khh]2.561Energy consumption - ototon hull (ad [khh]2.561Energy consumption - ototon hull (ad [khh]0.380.5Standby time (leff-on mode) [mi]10-Dying time - cotton hull (ad [mi]10-Dying time - cotton hull (ad [mi]10-Condensation efficiency - cotton hull (ad [Mi]80.187Condensation efficiency - cotton hull (ad [Mi]80.182Naverage dripting time - cotton hull (ad [Mi]80.182Condensation efficiency - cotton hull (ad [Mi]80.182Naverage condensation efficiency - cotton [Mi]8-Condensation efficiency - cotton [Mi]8-Self condustator cuvetteWater tank for steam [Mi]4.84.6Noisture monitoring systemFeet and wheels22ControlDelayed start programme keySelection block key		White	White
Dyper type Condensition Heat pump B Tertary efficiency class [2] B B Tend annual energy consumption (kWh/year) [3] 541 119 Energy consumption - cotton full load [Wh] 2.56 119 Energy consumption - cotton full load [Wh] 0.38 0.5 Energy consumption - cotton full load [mh] 10 - Drying time - cotton full load [mh] 112 10 Condensation efficiency class B C Condensation efficiency - cotton full load [M] 80.1 87 Condensation efficiency - cotton full load [M] 69 64 General features Front Front Dating file Front Front Front Set adusting system 60 6 6 Door measurement [cm] 37.5 52 52 Reversing system: double sense movement 6 6 6 Door measurement [cm] 37.5 52 52 Reversing system: double sense movement 6 6 6 Door measurement [cm]		8	8
Energy efficiency class [2]BSEnergy consumption - cotton full load [kWh]5.51119Energy consumption - cotton full load [kWh]2.56119Energy consumption - of mode [W]0.280.5Energy consumption - of mode [W]0.280.5Standay time (elf-on mode) [mi]1010Drying time - cotton full load [min]900.6Average drying time - cotton full load [min]80.187Condensation efficiency - cotton full load [min]80.187Condensation efficiency - cotton full load [min]6944Condensation efficiency - cotton full load [min]6944Average condensation efficiency - cotton [S]80.187Average condensation efficiency - cotton [S]80.187Average condensation efficiency - cotton [S]80100Dom walking the estandingFree-standingFree-standingSelf adjusting consumption according to load109100Dom walking the estanding4.84.6Moisture monitoring system00Fost filter222Reversing system: double sense movement00Colick dry022Sale dol wheels222Control000Sale dol wheels000Control000Sale dol wheels000Control000Sale dol wop onis [h]3-6-			
Total annual energy consumption (why) energy consumption - action full load [Whi) 7.4 Energy consumption - action full load [Whi] 2.56 Energy consumption - action full load [Whi] 0.28 Energy consumption - action full load [Whi] 0.28 Energy consumption - action full load [min] 10 Drying time - action full load [min] 10 Drying time - action full load [min] 8 Condensation efficiency - action full load [%] 80.1 Average adriptine - action full load [%] 80.1 Condensation efficiency - action full load [%] 80.1 Average adriptine - action full load [%] 80.1 Buillin / free-standing Front Buillin / free-standing Front Buillin / free-standing 109 Doar measurement [cm] 37.5 Doar measurement [cm] 4.8 Mater tank for steam [] 4.8 Mater tank for steam [] 4.8 Peet and wheels 2 feat and 2 wheel Dalayed start programme atystem 6 Board dalay approximate key 6 Stard feay options [h] 3-6-9-12 <			
Energy consumption - cotton full load [kWh] Energy consumption - cotton hull load [kWh] Energy consumption is tandby (left-mode) [W] Standby time (left-on mode) [M] Dying time - cotton full load [min] Dying time - cotton full load [min] Average drying time - cotton full load [min] Condensation efficiency - cotton full load [min] Condensation efficiency - cotton full load [min] Standby time full back [min] Condensation efficiency - cotton full load [min] Standby time full back [min] Condensation efficiency - cotton full load [min] Self adjusting (db(1)] Everage condensation efficiency - cotton [min] Noise level drying (db(1)] Self adjusting consumption according to load Durm volume [min] Dorm sourcement [cm] Self adjusting consumption according to load Durm volume [min] Dorm sourcement [cm] Reversing system: double sense movement Quick dry Feet and wheels Conden stator cuvette Self adjusting consumption according to load Dor measurement [cm] Reversing system: double sense movement Quick dry Feet and wheels Control Deloyed start programme key Selection block key Blocked filter indicator Anth-crease key On/Off key Start levo poptions [n] Repartment key Selection block key Blocked filter indicator Anth-crease key On/Off key Start devo poptions [n] N° of tatal drying consume key Selection block key Blocked filter indicator Anth-crease indicator A		-	
Energy consumption - off mode [W] 0.28 Energy consumption is standaby (left-mode) [W] 0.8 Standaby time - colton full cod [min] 10 Dying time - colton full cod [min] 90 Average drying time - colton full cod [Min] 90 Average drying time - colton full cod [Min] 90 Condensation efficiency - cotton full cod [Min] 80,1 Ordensation efficiency - cotton full cod [Min] 80,1 Noise level drying [db[A] 80,1 Condensation efficiency - cotton full cod [Min] 80,1 Noise level drying [db[A] 69 Central features			
Energy consumption is standay (inel+node) [W] 0.8 0.5 Standay time (left-on mode) [min] 10 - Drying time - cotton full load [min] 140 - Average drying time - cotton full load [min] 112 C Condensation efficiency - cotton full load [Min] 80,1 87 Condensation efficiency - cotton full load [Min] 80,1 87 Condensation efficiency - cotton full load [Min] 80,1 87 Average condensation efficiency - cotton [Min] 80,1 87 Condensation efficiency - cotton [Min] 80,1 87 Self adjusting consumption according to load - - Drum volume [I] 109 100 00 Door measurement [cm] 37,5 52 - Reversing system: double sense movement - - - Fiels and wheels 2 feets and 2 wheel - - Contol - - - - Delayed start programme key - - - - Delayed start programme key - <			
Standby time (left-on mode) [min] 10 - Drying time - cotton full load [min] 140 - Drying time - cotton full load [min] 12 - Condensation efficiency - cotton full load [%] 80,1 87 Condensation efficiency - cotton full load [%] 80,1 87 Condensation efficiency - cotton full load [%] 80,1 82 Average condensation efficiency - cotton full load [%] 80,1 82 Noise level drying [db(A)] 69 64 General features - - Loading type Front Front Front Self adjusting consumption according to load - - Drum volume [1] 109 100 100 Dor measurement [cm] 4.8 4.6 - Reversing system: double sense movement - - - Ouick dry - - - - Selection block key - - - - Selection block key - - - - <t< td=""><td>• •</td><td></td><td>0.5</td></t<>	• •		0.5
Drying time - cotton full load [min]140Drying time - cotton full load [min]90Average drying time - cotton full load [min]112Condensation efficiency - cotton full load [%]80.1Retract drying time - cotton full load [%]80.1Retract droitens droitency - cotton full load [%]80.1Neerage condensation efficiency - cotton full load [%]80.1Builtin / free-standingFrontFrontFrontBuiltin / free-standingFree-standingSelf adjusting consumption according to load0Dor measurement [cn]37.5Removable condensator cuvette0Water tank for steam [I]4.8Advisture monitoring system0Feet and wheels2 test and 2 wheelsContol10Delayed start programme key0Selection block key0Blocked filter indicator0Anti-crease key0On/Of Key0Start delay options [h]3-6-9-12Start delay options [h]3-6-9-12Programme and display1In operation indicator0Anti-crease key0On/Of Key0Start delay options [h]3-6-9-12Start delay options [h]3-6-9-12Programme0Cotton indicator0Anti-crease indicator0Programme0Cotton indicator0Programme0Cotton indicator0Programme0 <tr<< td=""><td></td><td></td><td>-</td></tr<<>			-
Average drying time - cotton full load [min] 112 Condensation efficiency class 8 C Condensation efficiency - cotton full load [%] 80.1 87 Average condensation efficiency - cotton full load [%] 80.1 87 Noise level drying [db[A]] 69 64.4 General features		140	
Condensation efficiency costsBCCondensation efficiency - cotton hall load [%]80.187Condensation efficiency - cotton hall load [%]80.187Average condensation efficiency - cotton [%]80.182Noise level driving [db(A)]6964Condensation efficiency - cotton [%]6964Condensation efficiency - cotton [%]6964Self adjusting consumption according to load00Dum volume [I]109100Dor measurement [Cm]4.84.6Moisture monitoring system00Feet and wheels2 leets and 2 wheelContool00Delayed start programme key00Selection block key00Blocked filter indicator00Anti-crease key00On/Off Key10In operation indicator00Anti-crease indicator00Programme and display10Start delay options [h]3-6-9-122Start delay options [h]3-6-9-120Cotton blocked indicator00Programme and cottor for programme ended00<			
Condensation efficiency - cotton hall load [%] 80.1 87 Condensation efficiency - cotton [%] 80.1 87 Noise level drying (db(A)] 69 64 Condensation efficiency - cotton [%] 80.1 82 Noise level drying (db(A)] 69 64 Ceneral features Free-standing Free-standing Data dijusting consumption according to load • • Dorn measurement [cm] 37.5 52 Removable condensator cuvette • • • Water tank for steam [] 4.8 4.6 • Reversing system: double sense movement • • • Glick dry • • • • Selection block key • • • • Blocked filter indicator • • • • Anti-crease key • • • • Contol • • • • Selection block key • • • •			C
Contensation efficiency - action [%] 80.1 87 Average condensation efficiency - action [%] 80.1 82 Noise level drying [db(A]] 69 64 General features Front Front Built-in / tree-standing Free-standing Free-standing Self adjusting consumption according to load • - Drum volume [I] 109 100 100 Door measurement [cm] 37.5 52 Reversing system • - Reversing system: double sense movement • • • - - Reversing system: double sense movement • • • - - - - - - - - - - - - - - - - - - - - - - - - - - - - - - - - - - - - - - - - -	,	-	-
Noise level drying [db[A]] 69 64 General fedures Front Front Built-in / free-standing Free-standing Free-standing Self adjusting consumption according to load • • Drum volume [I] 109 100 100 Daor measurement [cm] 37.5 52 Reservable condensator cuvette • Water tank for steam [I] 4.8 4.6 Moisture monitoring system • • Reversing system: double sense movement • • • • • Quick dry 2 2 feet and wheels 2 feets and 2 wheels		80,1	87
General featuresFront Front Front Front Front Front Front Front Front Front Front Front Front Front Front Front Front Front Front Front Front Front Front Front Front Front Front Front Front Front Front Front Front Front Front Front Front Front Front Front Front Front Front Front Front Front Front Front Front Front Front Front Front Front Front Front Front Front Front Front Front Front Front Front Front Front Front Front Front Front Front Front Front Front Front Front Front Front Front Front Front Front Front Front Front Front Front Front Front Front Front Front Front Front Front Front Front Front Front Front Front Front Front Front Front Front Front Front Front Front Front Front Front Front Front Front Front Front Front Front Front Front Front Front Front Front Front Front Front Front Front Front Front Front Front Front Front Front Front Front Front Front Front Front Front Front Front Front Front Front Front Front Front Front Front Front Front Front Front Front Front Front Front Front Front Front Front Front Front Front Front Front Front Front Front Front Front Front Front Front Front Front Front Front Front Front Front Front Front Front Front Front Front Front Front Front Front Front Front Front Front	· · · · ·	,	
Landing typeFrontFrontBuilt-in / free-standingFree-standingBuilt-in / free-standingFree-standingDrum volume [I]109100Dorn measurement [cm]37,552Removable condensator cuvette4.84.6Water tank for steam [I]4.84.6Moisture monitoring systemFloss filterReversing system: double sense movementQuick dry2222Feet and wheels2222ControlDelayed start programme keyBlacked filter indicatorAnth-crease keyOn/Off keyStart delay options [h]3-6-9-1224-Programme and displayLEDLEDLEDLEDStart/pouse programme keyEnd of cycle indicatorAnti-crease indicatorProgramming control typeMechanicElectronicExtra line programme (aceation)ProgrammingProgramme (min]Af5'30'Vapour programme (aceation)Extra line programme (aceation)Programming-		69	64
Built-in / free-standingFree-standingFree-standingSelf adjusting consumption according to load00Dorn masurement [cm]0000Bor measurement [cm]4,84,6Mater tank for steam [l]4,84,6Moisture monitoring system00Floss filter00Reversing system: double sense movement00Quick dry000Feet and wheels2 feets and 2 wheek2 feets and 2 wheekContol000Delayed start programme key00Selection black key00Blocked filter indicator00Anti-crease key00On/Off key00Start delay options [h]3-6-9-1224Programme and displayLEDLEDStart delay options [h]3-6-9-1224Programme and displayLEDLEDStart delay options [h]3-6-9-1224Programming control type00Selection blacked indicator00End of cycle indicator00Free and thing programme (anticreasers)60' and 30'Quick programme (anticreasers)60' and 30'<		Front	Front
Drum volume [I] 109 100 Door measurement [cm] 37,5 52 Removable condensator cuvette • • Water tank for steam [I] 4.8 4.6 Moisture monitoring system • • Floss filter • • Reversing system: double sense movement • • Quick dry • • Feet and wheels 2 treets and 2 wheets 2 treets and 2 wheets Control • • Delayed start programme key • • Selection block key • • Blocked filter indicator • • Anti-crease key • • • On/Off key • • • Start delay options [h] 3-6-9-12 24 Programme and display LED LED Start delay options [h] 3-6-9-12 24 Programme and display LED LED Start delay options [h] 3-6-0 • An	•		
Door measurement [cm]37,552Removable condensator cuvetteWater tank for steam [I]4,84,6Moisture monitoring systemFloss filterReversing system: double sense movementQuick dayFeet and wheels2 trests and 2 wheels2 trests and 2 wheelsControlDelayed start programme keySelection block keyBlocked filter indicatorAnti-crease keyOn/Off keyStart delay options [h]Trogramme and displayLEDLEDStart/pause programme keyIn operation indicatorAnti-crease indicatorSelection blocked indicatorFrogrammingProgrammingExtra time programme (anticreasers)60' and 30'Quick programme (anticreasers)60' and 30'Quick programmeSintelic programme-Automatic programme-Sintelic programme-Delicates programme-Sintelic programme-Delicates programme-Delicates programme-Delicates programme-Delicates programme-Delicates programme-Delicates programme-			-
Removable condensator cuvette•Water tank for steam [I]4.84.6Moisture monitoring system••Reversing system: double sense movement••Quick dry•••Feet and wheels2 feets and 2 whees2 feets and 2 wheesControl••Delayed start programme key••Selection block key••Blocked filter indicator••Anti-crease key••On/Off key••Start delay options [h]3-6-9-1224Programme and displayEEDEEDSelection block de indicator••Anti-crease indicator••Selection blocked indicator••Forgamming control typeMechanicElectronicAcustic indicator or••Fult ank indicator••Fult ank indicator••Fult ank indicator or••Programme (anticreasers)60' and 30'•Quick programme (anticreasers)60' and 30'•Quick programme•••Start ding programme••Edition programme••Start ding safety••Cotton programme••Delicates programme••Cotton programme••Start ding safety••Cotton programme••Delicat			
Water tank for steam [I]4.84.6Moisture monitoring system••Floss filter••Reversing system: double sense movement••Quick dry•••Feet and wheelsZetest and ZwheelsZetest and ZwheelsZetest and ZwheelsControl•••Delayed start programme key•••Blocked filter indicator•••Anti-crease key•••On/Off key•••Start delay options [h]3-6-9-1224Programme and displayEEDEEDIn operation indicator••Anti-crease indicator••Anti-crease indicator••Forgaraming control typeMechanicElectronicAcustic indicator for programme ended••Full ank indicator••Programming control typeMechanic•Pull tank indicator••Pull ta			-
Floss filter••Reversing system: double sense movement••Quick dry2feets and 2 wheek2feets and 2 wheekControl•Delayed start programme key••Blocked filter indicator••Anti-crease key••On/Off key3-6-9-1224Start delay options [h]3-6-9-1224Programme and displayLEDLEDStart delay options [h]••Programme and displayLEDEterStart delay options [h]••Programme and displayLEDStart delay options [h]•Programme and displayLEDStart delay options [h]•Programme and displayLEDStart delay options [h]•Programming control typeMechanicFul tank indicator•Ful tank indicator•Ful tank indicator•Programming•Cuick programme (anticreasers)60' and 30'Quick programme (anticreasers)60' and 30'Quick programme•Cotton programme•Automatic programme•Sintelic programme•Sintelic programme•Delicates programme•Cotton programme•Sintelic programme•Delicates programme•Sintelic programme•Sintelic programme•Cotton programme•Cotton pr			4,6
Reversing system: double sense movement•Quick dry••Feet and wheels2 feets and 2 wheesControl•Delayed start programme key•Blocked filter indicator•Anti-crease key•On/Off key•Start delay options [h]3-6-9-12Programme and displayLEDStart/pause programme key•In operation indicator•Anti-crease indicator•Start/pause programme key•In operation indicator•Anti-crease indicator•Selection blocked indicator•End of cycle indicator•Frogramming control typeMechanicFult ank indicator•Fult ank indicator•Programme (anticreasers)60' and 30'Quick programme (anticreasers)60' and 30'Quick programme (anticreasers)•Quick programme (actreation)•Easy-iron programme•Sintetic programme•Automatic programme•Automatic programme•Delicates programme•Sofety systems•Heating sofety•Heating sofety•Delicates programme•Automatic programme•Automatic programme•Delicates programme•Sofet graphing•Delicates programme•Cotton programme•Delicates programme• <td></td> <td>•</td> <td>-</td>		•	-
Quick dry••Feet and wheels2 feets and 2 wheels2 feets and 2 wheelsControl••Delayed start programme key••Selection block key••Blocked filter indicator••Anti-crease key••On/Off key••Start delay options [h]3-6-9-1224Programme and displayLEDLEDStart delay options indicator••In operation indicator••Anti-crease indicator••End of cycle indicator••End of cycle indicator••Frogramming control typeMechanicElectronicAcustic indicator for programme ended••Full tank indicator••Programming2•Quick programme [anticreasers]60' and 30'Quick programme [actreation]•Easy-iron programme [actreation]•Easy-iron programme•Cotton programme•Quick programme•Quick programme•Delicates programme•Delicates programme•Cotton programme•Cotton programme•		•	•
Feet and wheels2 feet and 2 wheels2 feet and 2 wheelsControlImage: Control of Cont		•	•
Delayed start programme key•Selection block key•Blocked filter indicator•Anti-crease key•On/Off key•Start delay options [h]3-6-9-12Programme and displayLEDIn operation indicator•Anti-crease indicator•Anti-crease indicator•Selection blocked indicator•End of cycle indicator•Programming control typeMechanicProgramming•Extra time programme ended•Full tank indicator•Programming•Extra time programme (anticreasers)60' and 30'Quick programme [min]45'N° of total drying programme•Quick programme (acteration)•Easy-iron programme (acteration)•Easy-iron programme•Quited programme•Quited programme•Quited programme•Quited programme•Cotton programme•Quited programme•Delicates programme•Cotton programme•Delicates programme•Connection•Current [A]12Valoue [W]220-240 /50Zonout [A]12Voltage [W] / Frequency [Hz]220-241Voltage [W] / Frequency [Hz]50Soft programme•Height with worktop [mm]815Height with worktop [mm]815Height without w		2 feets and 2 wheels	2 feets and 2 wheels
Selection block key••Blocked filter indicator••Anti-crease key••On/Off key13-6-9-1224Programme and displayLEDLEDStart/pause programme key••In operation indicator••Anti-crease indicator••Eled of cycle indicator••Frogramming control typeMechanicElectronicAcustic indicator for programme ended••Full tank indicator••Programming••Extra time programme (anticreasers)60' and 30'Quick programme (anticreasers)60' and 30'Quick programme (anticreasers)16Automatic programme•Extra time programme•Cotton programme (acreation)•Easy-iron programme•Easy-iron programme•Automatic programme•Output2Statel programme•Statel programme•Cotton programme•Belicates programme•Statel programme•Statel programme•Statel programme•Delicates programme•Statel programme•Cotton programme•Statel programme•Statel programme•Programme•Statel programme•Statel programme•Statel programme• <t< td=""><td>Control</td><td></td><td></td></t<>	Control		
Blocked filter indicator•Anti-crease key•On/Off key•Start delay options [h]3-6-9-12Programme and displayIEDIt operation indicator•In operation indicator•End of cycle indicator•End of cycle indicator•Frogramming control typeMechanicProgramming control typeMechanicAcustic indicator for programme ended•Full tank indicator•Full tank indicator•Programming•Extra time programme (anticreases)60' and 30'Quick programme (mini)45'Vapour programme (arectains)•Easy-iron programme•Automatic programme•Automatic programme•Sintetic programme•Sintetic programme•Delicates programme•Sintetic programme•Sintetic programme•Current [A]12Valouer [V] / Frequency [Hz]220-240 /50Stotale [V] / Frequency [Hz]220-240 /50Connection•Height with worktop [mm]845Height without worktop [mm]845Height without worktop [mm]615Height without worktop [mm]615Hold power [W]220-241Stota pow		•	•
Anti-crease key••On/Off key3-6-9-1224Start delay options [h]3-6-9-1224Programme and displayLEDLEDStart/pause programme key••In operation indicator••Anti-crease indicator••Selection blocked indicator••End of cycle indicator••ProgrammingMechanicElectronicAcustic indicator for programme ended••Full tank indicator••Fungamming*•Extra time programme2•Vapour programme [ntin]45'30'Quick programme [ntin]45'30'N° of total drying programmes1616Easy-iron programme••Quick programme••Cotton programme••Sintefic programme••Delicates programme••Sport programme••Super tip affety••Current [A]1212Voltage [V] / Frequency [Hz]220-240 /50Zobard ystems••Height with worktop [mm]845B45845Height with worktop [mm]815Sistis815Vidtag range [V]220-241Solo 5050Rate concertion•Corter top*Corter top*Solo 5050Solo 50 <td>,</td> <td>•</td> <td>•</td>	,	•	•
On/Off key••Start delay options [h]3-6-9-1224Programme and displayLEDLEDStart/pouse programme key••In operation indicator••Anti-crease indicator••Selection blocked indicator••End of cycle indicator••Programming control typeMechanicElectronicAcustic indicator for programme ended••Full tank indicator••Vapour programme (anticreasers)60' and 30'•Quick programme (anticreasers)60' and 30'•Quick programme (anticreasers)1616Ventilation programme (acreation)••Easy-iron programme (acreation)••Leasy-iron programme••Jeans programme••Outomatic programme••Jeans programme••Sintetic programme••Delicates programme••Sufter systems••Heating safety••Connection••Current [A]1212Voltage [V] / Frequency [Hz]20220-240 /50220-240 /50220-240 /50220-240 /50220-240 /50220-240 /502002700Dimensions•Height with worktop [mm]815Height with worktop [mm]615Height with worktop [mm]615 <td></td> <td>•</td> <td>•</td>		•	•
Programme and displayLEDLEDStart/pause programme key••In operation indicator••Anti-crease indicator••Selection blocked indicator••End of cycle indicator••Programming control typeMechanicElectronicAcustic indicator for programme ended••Full tank indicator••Programming••Extra time programme (anticreasers)60' and 30'•Quick programme (anticreasers)60' and 30'•Quick programme (anticreasers)1616Ventilation programme (aereation)••Easy-iron programme••Automatic programme••Jeans programme••Cotton programme••Delicates programme••Mixed programme••Mixed programme••Mixed programme••Mixed programme••Connection••Current [A]1212Urital power [W]27002700Dimensions••Height with out worktop [mm]815815Width [mm]595595Dimensions depth [mm]595505Dimensions depth [mm]595505Dimensions depth [mm]615615Voltage range [V]220-241220-241Voltage range [V] <t< td=""><td></td><td>•</td><td>•</td></t<>		•	•
Start/pause programme key•In operation indicator•Anti-crease indicator•Anti-crease indicator•End of cycle indicator•Programming control typeMechanicAcustic indicator for programme ended•Full tank indicator•Programming•Extra time programme (ntin)45'Vapour programme (ntin)45'Quick programme (ntin)•M* of total drying programmes16Cattor programme•Automatic programme•Automatic programme•Qator programme•Cotton programme•Automatic programme•Delicates programme•Sintefic programme•Mixed programme•Connection•Current [A]12Current [A]12Valtage [V] / Frequency [Hz]220-240 /50Zotou2700Dimesions•Height with worktop [mm]815Height without worktop [mm]815Bits615Observer (M]220-241Yoltage range [V]220-241Yoltage range [V]595<			
In operation indicator•Anti-crease indicator•Selection blocked indicator•End of cycle indicator•Programming control typeMechanicAcustic indicator for programme ended•Full tank indicator•Programming•Extra time programme (anticreasers)60' and 30'Quick programme (anticreasers)60' and 30'Quick programme (anticreasers)60' and 30'Quick programme (antereation)•Easy-iron programme (aceration)•Easy-iron programme•Quart programme•Quart programme•Automatic programme•Quart programme•Quart programme•Quart programme•Cothon programme•Quart programme•	•	LED	
Selection blocked indicator•End of cycle indicator•Programming control typeMechanicAcustic indicator for programme ended•Full tank indicator•Programming•Extra time programme (anticreasers)60' and 30'Quick programme (min]45'N° of total drying programme (aereation)•Easy-iron programme•Easy-iron programme•Automatic programme•Jeans programme•Sintefic programme•Delicates programme•Sintefic programme•Sintefic programme•Mixed programme•Safety systems•Heating safety•Courrent [A]12Current [A]12Picatopewer [W]2700Dimensions•Height with worktop [mm]845Height with worktop [mm]615Frequency [Hz]50Systems•Height without worktop [mm]615Othage range [V]220-241Yoltage range [V]220-241Power connection•Voltage range [V]220-241Power connection•Voltage range [V]50So50Rated power [W]2700Quoted power [W]2700Power connection•Voltage range [V]50So50Rated power [W]2700Quoted power [W]2700 <tr< td=""><td></td><td>•</td><td>-</td></tr<>		•	-
End of cycle indicator•Programming control typeMechanicElectronicAcustic indicator for programme ended••Full tank indicator••Programming2•Extra time programme (anticreasers)60' and 30'•Quick programme (min]45'30'N° of total drying programmes1616Ventilation programme (aereation)••Easy-iron programme••Automatic programme••Automatic programme••Jeans programme••Cotton programme••Delicates programme••Mixed programme••Safety systems••Heating safety••Current [A]1212Voltage [V] / Frequency [Hz]220-240 /50Total power [W]595595Dimensions depth [mm]615615Power connection••Voltage range [V]220-241220-241Voltage range [V]27002700Dimensions depth [mm]615615Power connection••Voltage range [V]27002700Rated power [W]27002700Rated power [W]27002700Rated power [W]27002700Rated power [W]61616Type of plugSchukoSchuko		•	•
Programming control typeMechanicElectronicAcustic indicator for programme ended•••Full tank indicator•••Programming2••Extra time programme (anticreasers)60' and 30'•Quick programme (anticreasers)60' and 30'•Quick programme (anticreasers)60' and 30'•Quick programme (anticreasers)1616Ventilation programme (aereation)••Easy-iron programme••Automatic programme••Jeans programme••Cotton programme••Cotton programme••Delicates programme••Delicates programme••Mixed programme••Mixed programme••Connection••Current [A]1212Current [A]1212Voltage [V] / Frequency [Hz]220-240 /50Total power [W]27002700Dimensions••Height with worktop [mm]815815Width [mm]595595Dimensions depth [mm]615615Power connection••Voltage range [V]27002700Voltage range [V]27002700Rated power [W]27002700Rated power [W]61616Type of plugSchukoSchuko		•	•
Acustic indicator for programme ended•Full tank indicator•Programming•Extra time programme (anticreasers)60' and 30'Quick programme (aereation)•Easy-iron programme•Automatic programme•Jeans programme•Jeans programme•Cotton programme•Cotton programme•Delicates programme•Sport programme•Mixed programme•Mixed programme•Connection•Current [A]12Voltage [V] / Frequency [Hz]220-240 /50Total power [W]2700Dimensions•Height without worktop [mm]815Height without worktop [mm]615Mith [mm]595Dimensions depth [mm]615Power connection•Voltage range [V]220-241220-241220-241Power (W]2700Automatic programme50So50Rated power [W]2700Rated power [W]2700Rated power [W]2700Rated power [W]2700Rated power [W]50So for plug50So holks50	,	Mechanic	• Flectronic
Programming2Extra time programme2Vapour programme (anticreasers)60' and 30'Quick programme (min]45'N° of total drying programmes16Ventilation programme (aereation)•Easy-iron programme•Automatic programme•Automatic programme•Jeans programme•Cotton programme•Delicates programme•Delicates programme•Delicates programme•Safety systems•Heating safety•Cornection•Current [A]12Voltage [V] / Frequency [Hz]220-240 /50Total power [W]2700Dimensions•Height with worktop [mm]845Height with worktop [mm]615Midd programe•Voltage range [V]220-241220-241220-241Power connection•Voltage program50Soft power [W]2700Pawer connection•Voltage range [V]50Soft power [W]2700Z0002700Rated power [W]2700Rated power [W]2700SochukoSchuko			
Extra time programme (anticreasers) 2 Vapour programme (anticreasers) 60' and 30' Quick programme [min] 45' 30' N° of total drying programmes 16 16 Ventilation programme (aereation) • • Easy-iron programme • • Automatic programme • • Jeans programme • • Cotton programme • • Sintetic programme • • Delicates programme • • Mixed programme • • • Mixed programme • • • Connection • • • Current [A] 12 12 12 Voltage [V] / Frequency [Hz] 220-240 /50 220-240 /50 220-240 /50 Total power [W] 2700 2700 2700 2700 Dimensions • • • • Height with worktop [mm] 845 845 845	Full tank indicator	•	•
Vapour programme (anticreasers)60' and 30'Quick programme [min]45'30'N° of total drying programmes1616Ventilation programme (aereation)••Easy-iron programme••Automatic programme••Jeans programme••Jeans programme••Cotton programme••Delicates programme••Sintetic programme••Delicates programme••Safety systems••Heating safety••Cornection••Current [A]1212Voltage [V] / Frequency [Hz]220-240 /50Total power [W]27002700Dimensions••Height without worktop [mm]815Height without worktop [mm]595Dimensions depth [mm]615Power connection•Voltage range [V]220-241Pourent [A]16Trecuency [Hz]50So50Rated power [W]2700Rated power [W]2700Rated power [M]16Topp of plugSchukoSchukoSchuko		0	
Quick programme [min] 45' 30' N° of total drying programmes 16 16 Ventilation programme (aereation) • • Easy-iron programme • • Automatic programme • • Jeans programme • • Jeans programme • • Cotton programme • • Cotton programme • • Delicates programme • • Sport programme • • Mixed programme • • Mixed programme • • Connection • • Current [A] 12 12 Current [A] 12 12 Voltage [V] / Frequency [Hz] 220-240 /50 220-240 /50 Total power [W] 2700 2700 2700 Dimensions • • • Height with worktop [mm] 845 845 Height without worktop [mm] 595 595			
Ventilation programme (aereation)•Easy-iron programme•Automatic programme•Automatic programme•Jeans programme•Cotton programme•Cotton programme•Delicates programme•Delicates programme•Sport programme•Mixed programme•Safety systems•Heating safety•Connection•Current [A]12Voltage [V] / Frequency [Hz]220-240 /50Total power [W]2700Dimensions•Height with worktop [mm]845B45845Width [mm]595Dimensions depth [mm]615Voltage range [V]220-241Valtage range [V]220-241Power connection•Voltage programe50So50Rated power [W]2700Z0002700Rated power [M]16Type of plugSchukoSchukoSchuko			30'
Easy-iron programme•Automatic programme•Jeans programme•Cotton programme•Sintetic programme•Delicates programme•Delicates programme•Softety systems•Heating safety•Cornection•Current [A]12Voltage [V] / Frequency [Hz]220-240 /50Total power [W]2700Dimensions•Height with worktop [mm]845B455845Width [mm]595Dimensions depth [mm]615Voltage range [V]220-241220-241220-241Power connection•Voltage range [V]2700Z0002700Rated power [W]270020002700Rated power [W]270027002700Rated power [M]16Type of plugSchukoSchukoSchuko		16	
Automatic programme • Jeans programme • Cotton programme • Sintetic programme • Delicates programme 2 Delicates programme • Mixed programme • Mixed programme • Safety systems • Heating safety • Connection • Current [A] 12 12 Voltage [V] / Frequency [Hz] 220-240 /50 220-240 /50 Total power [W] 2700 2700 Dimensions • • Height with worktop [mm] 845 845 Height without worktop [mm] 595 595 Dimensions depth [mm] 615 615 Power connection • • Voltage range [V] 220-241 220-241 Yourge range [V] 2700 2700 Rated power [W] 2700 2700 Rated power [W] 2700 2700 Rated power [M] 16			
Jeans programme • Cotton programme • Sintetic programme • Delicates programme 2 Sport programme • Mixed programme • Mixed programme • Safety systems • Heating safety • Connection • Current [A] 12 Voltage [V] / Frequency [Hz] 220-240 /50 Total power [W] 2700 Dimensions • Height with worktop [mm] 845 Height withwout worktop [mm] 815 Bits 815 Width [mm] 595 Dimensions depth [mm] 615 Power connection • Voltage range [V] 220-241 Yeoup 50 So 50 Rated power [W] 2700 Rated power [W] 2700 Rated power [M] 16 Top of plug Schuko		-	-
Sintetic programme • • Delicates programme 2 2 Sport programme • • Mixed programme • • Safety systems • • Heating safety • • Connection 12 12 Current [A] 12 220-240 /50 Total power [W] 2700 2700 Dimensions • • Height with worktop [mm] 845 845 Height without worktop [mm] 815 815 Width [mm] 595 595 Dimensions depth [mm] 615 615 Power connection • • Voltage range [V] 220-241 220-241 Voltage range [V] 220-241 220-241 Voltage range [V] 2700 2700 Rated power [W] 2700 2700 Rated power [W] 2700 2700 Rated current [A] 16 16 Type of plug Sc		•	•
Delicates programme 2 2 Sport programme • • Mixed programme • • Safety systems • • Heating safety • • Connection • • Current [A] 12 12 Voltage [V] / Frequency [Hz] 220-240 /50 220-240 /50 Total power [W] 2700 2700 Dimensions • • Height with worktop [mm] 845 845 Height without worktop [mm] 8115 815 Width [mm] 595 595 Dimensions depth [mm] 6115 6115 Power connection • • Voltage range [V] 220-241 220-241 Voltage range [V] 220-241 220-241 Voltage power [W] 2700 2700 Rated po		•	•
Sport programme • • Mixed programme • • Safety systems • • Heating safety • • Connection • • Current [A] 12 12 Voltage [V] / Frequency [Hz] 220-240 /50 220-240 /50 Total power [W] 2700 2700 Dimensions • • Height with worktop [mm] 845 845 Height without worktop [mm] 595 595 Dimensions depth [mm] 615 615 Power connection • • Voltage range [V] 220-241 220-241 Yourge range [V] 220-241 220-241 Voltage range [V] 200 2700 Rated power [W] 2700 2700 Rated power [W] 2700 2700 Rated current [A] 16 16 Type of plug Schuko Schuko		•	•
Mixed programme • Safety systems - Heating safety • Connection - Current [A] 12 12 Voltage [V] / Frequency [Hz] 220-240 /50 220-240 /50 Total power [W] 2700 2700 Dimensions - - Height with worktop [mm] 845 845 Height with worktop [mm] 595 595 Dimensions depth [mm] 615 615 Power connection - - Voltage range [V] 220-241 220-241 Frecuency [Hz] 50 50 Rated power [W] 2700 2700 Rated current [A] 16 16 Type of plug Schuko Schuko			_
Heating safety • Connection I Current [A] 12 Voltage [V] / Frequency [Hz] 220-240 /50 Total power [W] 2700 Dimensions 2700 Height with worktop [mm] 845 Height without worktop [mm] 815 Width [mm] 595 Dimensions depth [mm] 615 Voltage range [V] 220-241 Yoltage range [V] 500 Rated power [M] 2700 Rated power [M] 16 Type of plug Schuko		•	•
Connection Image: science scie			
Current [A] 12 12 Voltage [V] / Frequency [Hz] 220-240 /50 220-240 /50 Total power [W] 2700 2700 Dimensions		•	•
Voltage [V] / Frequency [Hz] 220-240 /50 220-240 /50 Total power [W] 2700 2700 Dimensions		12	12
Dimensions 845 Height with worktop [mm] 845 Height without worktop [mm] 815 Width [mm] 595 Dimensions depth [mm] 615 Power connection 615 Voltage range [V] 220-241 Voltage range [V] 50 Rated power [W] 2700 Rated current [A] 16 Type of plug Schuko	Voltage [V] / Frequency [Hz]		
Height with worktop [mm] 845 845 Height without worktop [mm] 815 815 Width [mm] 595 595 Dimensions depth [mm] 615 615 Power connection 220-241 220-241 Voltage range [V] 50 50 Rated power [W] 2700 2700 Rated current [A] 16 16 Type of plug Schuko Schuko		2700	2700
Height without worktop [mm] 815 815 Width [mm] 595 595 Dimensions depth [mm] 615 615 Power connection 220-241 220-241 Voltage range [V] 200 200 Frecuency [Hz] 50 50 Rated power [W] 2700 2700 Rated current [A] 16 16 Type of plug Schuko Schuko		845	845
Width [mm] 595 595 Dimensions depth [mm] 615 615 Power connection	•		
Power connection Image: Connection Voltage range [V] 220-241 220-241 Frecuency [Hz] 50 50 Rated power [W] 2700 2700 Rated current [A] 16 16 Type of plug Schuko Schuko	Width [mm]		
Voltage range [V] 220-241 220-241 Frecuency [Hz] 50 50 Rated power [W] 2700 2700 Rated current [A] 16 16 Type of plug Schuko Schuko		615	615
Frecuency [Hz] 50 50 Rated power [W] 2700 2700 Rated current [A] 16 16 Type of plug Schuko Schuko		220-241	220-241
Rated power [W] 2700 2700 Rated current [A] 16 16 Type of plug Schuko Schuko			
Type of plug Schuko Schuko	Rated power [W]	2700	2700
	Type of plug Power cord length [mm]	Schuko 1,6	Schuko 1,6

WASHERS AND DRYERS

edesə

UNDERMOUNT MAKALU BE 50X40 1C R-10 192	MAKALU BE 45X40 1C R-10 192	MAKALU BE 40X40 1C PLUS R-10 193	MAKALU BE 40X40 1C R-10 193
FUJI BE 50X40 1C 194	FUJI BE PLUS 45X40 1C 194	FUJI BE 45X40 1C 195	FUJI BE 40X40 1C PLUS 195
NEW	NEW	NEW	NEW
FUJI BE 40X40 1C R-60 196	FUJI BE 34X40 1C 196	FUJI BE 50X40 1C R10 BK 198	TOP MOUNT FUJI BE 45X40 1C R10 BK 198
NEW		NEW	NEW
FUJI BE 40X40 1C R10 BK 199	VELETA SE 80 2C 200	VELETA SE 86 1C1E REV 200	VELETA SE 86 1C1E ED 201
NEW	NEW	NEW	NEW
VELETA SE 86 1C1E EI 201	VELETA SE 79 1C1E REV 202	VELETA SE 79 1C1E ED 202	VELETA SE 79 1C1E EI 203
NEW	NEW	NEW	NEW



VELETA SE 50 1C 203	K2 SE 84 2C	204 K2 SE 84 1C	1E REV 204	K2 SE 49 1C	205
	() () ()			H	
KS SE 44	205				
NEW					
				The states	1 A





Broad range

When you cook for friends, when you tidy the table after a family meal or when you enjoy a little while alone, you want everything to be perfect.

The kitchen is a place where we want comfort for you and your family.

The sink is one of the most important elements of our kitchen, for the number of times we use it per day, and for being the area of food preparation or washing.

So, why not choosing a sink according to your needs and your likes? EDESA HAS IT.







We know that the market is looking for quality and durability in its products, that is why we are committed to you and we offer you 50 years of guarantee for your sink. Almost a whole life!.

(Excluded from the Warranty, damages caused by the wear of accessories, gaskets, rubbers etc., as well as the damages caused by improper handling, improper use or use of abrasive products or substances)

Formats according to each kitchen

The Edesa range of sinks allows you to choose between different formats, so that you can pick the one you prefer and the one that best fits in your cooking place.

Round and casual shapes for the most classic ones, square shapes with rounded edges to make better use of space, and square shapes with straight edges for the most modernists.

One of the advantages of this last model is that the base in an inverted pyramid shape helps to drain better thanks to its pyramidal base and the radius of 10, preventing the formation of wells of stagnant water, dirt or lime stains of dried drops on the surface of the bowl.

The quietness and serenity in your home matter to us

All Edesa sinks are equipped with different elements that help the soundproofing when kitchen utensils are fallen or deposited inside.

The fact that the whole sink is manufactured in a single piece achieve to absorb better the noise.

The joints are reinforced with materials that avoid vibrations and minimize annoying noises, as much as possible, when throwing the cutlery and dishes inside the bowl.

Accessories that facilitate assembly

All Edesa sinks include the necessary accessories for the installation in the correct way, either under the worktop or on the worktop.

edesə

The Makalu range of Edesa is groundbreaking and innovative, designed to please, with a unique style. It will be a key element in your kitchen.

The objective of the brand production team is to optimize the manufacturing processes and obtain quality products.

This time we want to surprise with a sink whose radius is 10. Something unusual in the market, because it requires advanced techniques in this area.

Aesthetically, it is unique and enhances even more the inverted pyramidal shape of the base of the sink.

This type of sinks can be installed under worktop, your kitchen will look spectacular!

In addition to using noble materials, the entire sink is manufactured in a single piece, the joints are reinforced, the bowl is made with soundproofing elements, and the outer base is covered to minimize the noise as much as possible by dropping the pots into the bowl of cooking.



Anti-condensation coating. It prevents mold formation and provides extra protection to the sink against rust and to the furniture against condensation.

The base with the inverted pyramid shape facilitates the drainage of water. In addition, puddles or lime stains from dried drops at the base of the tray are avoided.





The decorative Edesa veneer of the overflow gives to the sink a more professional, more elegant and much more sophisticated look.

> The material with which we manufacture these stainless steel sinks, AISI 304, is an ecological material of 1.2mm thickness.

The basket or square drain valve gives a plus to the modern and avant-garde style.

SQUARE OR ROUND DRAIN VALVE? YOU CHOOSE

Different formats for different personalities with Edesa.

If you prefer a classic style, you can choose the round basket type valve that includes the Veleta, K2 and Fuji ranges.

If you prefer something subtle and elegant, the best option is the Makalu range.





On worktop or under worktop

There are mainly two types of installation.

The first one, on top, is the most common installation system. It is where the sink rests on the worktop itself and it is embedded.

Its installation is very fast and simple, thanks to the use of staples in the assembly.

The second option would be under worktop. This system of placement offers a completely smooth worktop and avoids the projections, since the sink is under the worktop. Thus, harmony and visual continuity are achieved in the kitchen, as well as facilitating cleaning.







Our users do not settle for less, and you?

We reward the quality and durability of the product.

That is why all Edesa sinks are made with Austenitic AISI 304 stainless steel of the highest quality, to avoid any type of oxidation or corrosion due to water.

The material with which we manufacture these products is not porous, that makes its smooth and soft surface can be cleaned very easily.

Without forgetting that it is resistant for many years. The Edesa sinks have a thickness of up to 1.2mm of steel, thus minimizing the scratches or the marks produced by the blows during use.

This steel in addition to providing brightness and strength, is the type of stainless steel of highest quality that exists in the market for the domestic environment.

We win space with Edesa

Because it is much easier to turn and lift a pot when there is space, in Edesa, we think it is fundamental to gain as much space as possible.

Therefore, we emphasize our efforts in designing deeper basins, up to 25 cm.

This will allow us to obtain extra cubic centimeters, speeding up our movements and avoiding spilling water out of the bowl.

Never before was so easy to clean the oven trays or the paella pans.



e of edesa & **e** of ecological

The material with which we manufacture these AISI 304 stainless steel is ecological.

About 60 % of the stainless steel used is recycled. We take care of the environment, because that is the way to take care of you.

ACCESORIOS

Drain pipe and round basket

07699016 EAN-13: 8422248085724

Drain pipe for sinks with double square bowl, decorative sheet in rectangular overflow and drain valve. Drain tube, siphon and basket are included.

07699015 EAN-13: 8422248085717



Drain pipe for sinks with a single square bowl, decorative sheet in rectangular overflow and drain valve. Drain tube, siphon and basket are included.



07699002 EAN-13: 8422248084536

Drain pipe for sinks with double round bowl and drain valve. Drain tube, siphon and basket are included.



07699001 EAN-13: 8422248084529

Drain pipe for sinks with a single round bowl and drain valve. Drain tube, siphon and basket are included.

Drain tube and square basket



07699003 EAN-13: 8422248084543

Drain pipe for sinks with inverted pyramid base, with a single bowl, decorative sheet in rectangular overflow and square drain valve. Drain tube, siphon and basket are included.



Fixing clip

07699006 EAN-13: 8422248084574

Fixing system in clip-on format for sinks on worktop.

07699007 EAN-13: 8422248084581

Fixing system in clip-on format for sinks on worktop.

07699008 EAN-13: 8422248084598

Fixing system in clip-on format for sinks under worktop.

Edesa overflow plate

07699009 EAN-13: 8422248084604

Rectangular decorative metal sheet of the brand in overflow with satin finish.

Metallic plug

07699004 EAN-13: 8422248084550

Metallic plug for the tap hole.

Sealing tape

07699013 EAN-13: 8422248084642

3.2 m tape to seal the base of the sink on the worktop.

07699014 EAN-13: 8422248084659

1.8 m tape to seal the base of the sink on the worktop.















UNDERMOUNT

30

UNDERN									
MAKA	LU BE 5	0x40 1C	CR-10	S. stee	el 304				
Cod.: 950270029 - EAN: 8422248081177									
AISI 304	~_	V 2m	J.	\bigcirc	760 cm				
304 STAINLESS STEEL	UNDERMOUNT	20 CM DEEP	ULTRA THICK S. STEEL	ONE BOWL	FOR 60 CM FORNITURE				
50	R.10								
50 YEARS WARRANTY	RADIUS 10 MM								

- -1.2mm thinkness 304 stainless steel undermount sink or flush instalation sink and radius 10 mm
- -1 square with inverted pyramid surface bowl
- -Sink without tap hole
- -20 cm bowl depth
- -Noise absorber foam
- -Bowl anti condensation coating
- -Drainpipe with square 3 1/2" valve
- -Included accessories: square valve, syphon and overflow tube -Installation in 60 cm furniture

Pack of 5 sinks

Ean-13: 8422248081160 - Cod.: 950270028



UNDERMOUNT

MAKALU BE 45x40 1C R-10	S. steel 304
Cod.: 950270031 - EAN: 8422248081	191

20 Cm













50

50 YEARS WARRANTY

RADIUS 10 MM

- -1.2mm thinkness 304 stainless steel undermount sink or flush instalation sink and radius 10 mm
- -1 square with inverted pyramid surface bowl
- -Sink without tap hole
- -20 cm bowl depth
- -Noise absorber foam
- -Bowl anti condensation coating
- -Drainpipe with square 3 1/2" valve

-Included accessories: square valve, syphon and overflow tube -Installation in 60 cm furniture

Pack of 5 sinks

Ean-13: 8422248081184 - Cod.: 950270030



⁺ measurements in mm





UNDERMOUNT

MAKALU BE 40x40 1C PLUS R-10 S. steel 304

Cod.: 950270033 - EAN: 8422248081450











UNDERMOUNT 25 CM DEEP









AISI 304

50 YEARS WARRANTY

UNDERMOUNT

MAKALU BE 40x40 1C R-10

Cod.: 950270027 - EAN: 8422248081153

20 CM DEEP



UNDERMOUNT

RADIUS 10 MM





ONE BOWL



S. steel 304



304 STAINLESS STEEL



- -1.2mm thinkness 304 stainless steel undermount sink or flush instalation sink and radius 10 mm
- -1 square with inverted pyramid surface bowl
- -Sink without tap hole
- -25 cm bowl depth
- -Noise absorber foam
- -Bowl anti condensation coating
- -Drainpipe with square 3 1/2" valve
- -Included accessories: square valve, syphon and overflow tube -Installation in 50 cm furniture

Pack of 5 sinks

Ean-13: 8422248081207 - Cod.: 950270032



- -1.2mm thinkness 304 stainless steel undermount sink or flush instalation sink and radius 10 mm
- -1 square with inverted pyramid surface bowl
- -Sink without tap hole
- -20 cm bowl depth
- -Noise absorber foam
- -Bowl anti condensation coating
- -Drainpipe with square 3 1/2" valve

-Included accessories: square valve, syphon and overflow tube -Installation in 50 cm furniture

Pack of 5 sinks

Ean-13: 8422248081146 - Cod.: 950270026



⁺ measurements in mm







UNDERMOUNT					UNDER	MOUNT				
FUJI BE 50X4	0 1C	S. steel 30	04	NEW	FUJI	BE PLUS	45X40 1	C S. st	eel 304	NEW
Cod.: 95027006	3 - EAN:	842224837	3050		Cod.:	95027006	4 - EAN: 8	84222483	73067	
AISI 304 304 STAINLESS UNDERMOUNT	ULTRA THICK S. STEEL	ONE BOWL	FOR 50 CM FORNITURE	50 YEARS WARRANTY	AISI 304 304 STAINLESS STEEL	UNDERMOUNT	ULTRA THICK S. STEEL	ONE BOWL	FOR 50 CM FORNITURE	50 YEARS WARRANTY

-0.8mm thinkness 304 stainless steel undermount sink or flush instalation sink

- -1 square bowl
- -Sink without tap hole
- -18 cm bowl depth
- -Noise absorber foam
- -Drainpipe with round 3 1/2" valve

-Included accessories: round valve, tap cover, syphon and overflow tube

-Installation in 60 cm furniture

-0.8mm thinkness 304 stainless steel undermount sink or flush instalation sink

- -1 square bowl
- -Sink without tap hole
- -20 cm bowl depth
- -Noise absorber foam
- -Drainpipe with round 3 1/2" valve
- -Included accessories: round valve, syphon and overflow tube -Installation in 50 cm furniture











UNDERMOUNT	0 1C	S. steel 3	304	NEW		RMOUNT BE 40X4	0 1C PLI	US S. sto	eel 304	NEW
Cod.: 95027005	50 - EAN:	842224837	71100		Cod.	95027005	1 - EAN:	84222483	70271	
AISI 304 STAINLESS UNDERMOUNT	ULTRA THICK S. STEEL	ONE BOWL	FOR 50 CM FORNITURE	50 YEARS WARRANTY	AISI 304 STAINLESS STEEL	UNDERMOUNT	ULTRA THICK S. STEEL	ONE BOWL	FOR 50 CM FORNITURE	50 YEARS WARRANTY

- -0.8mm thinkness 304 stainless steel undermount sink or flush instalation sink
- -1 square bowl
- -Sink without tap hole
- -18 cm bowl depth
- -Noise absorber foam
- -Drainpipe with round 3 1/2" valve
- -Included accessories: round valve, syphon and overflow tube -Installation in 50 cm furniture
- -0.8mm thinkness 304 stainless steel undermount sink or flush instalation sink -1 square bowl
- -Sink without tap hole
- -20 cm bowl depth
- -Noise absorber foam
- -Drainpipe with round 3 1/2" valve

-Included accessories: round valve, syphon and overflow tube -Installation in 45 cm furniture











UNDERMOUNT					UNDER	MOUNT				
FUJI BE 40X4	0 1C R-60) S. ste	el 304	NEW	FUJI	BE 34x40) 1C	S. s [.]	teel 304	
Cod.: 9502700)52 - EAN:	842224	18370288	3	Cod.:	9502700)19 - EAN	: 84222	4808108	5
				\sim						\sim
	J.	\odot	745 cm	50	AISI 304		J.	\bigcirc	745 cm	50

-0.8mm thinkness 304 stainless steel undermount sink or flush instalation sink

- -1 square bowl
- -Sink without tap hole
- -18 cm bowl depth
- -Noise absorber foam
- -Drainpipe with round 3 1/2" valve

-Included accessories: round valve, syphon and overflow tube -Installation in 45 cm furniture -0.7mm thinkness 304 stainless steel undermount sink or flush instalation sink

- -1 square bowl
- -Sink without tap hole
- -18 cm bowl depth
- -Noise absorber foam
- -Drainpipe with round 3 1/2" valve

-Included accessories: round valve, syphon and overflow tube -Installation in 45 cm furniture

















UNDERMOUNT

FUJI BE 50X40 1C R10 BK S. steel 304 NEW Cod.: 950270067 - EAN: 8422248378222

UNDERMOUNT

FUJI BE 45X40 1C R10 BKs. steel 304 NEW Cod.: 950270066 - EAN: 8422248378215





304 STAINLESS UNDERMOUNT STEEL

ULTRA THICK S. STEEL ONE BOWL



50

60

cm

50 YEARS WARRANTY

-0.8mm thinkness 304 stainless steel undermount sink or flush instalation sink

- -1 square bowl
- -Sink without tap hole
- -20 cm bowl depth

-Noise absorber foam

-Drainpipe with round 3 1/2" valve

-Included accessories: round valve, syphon and overflow tube -Installation in 45 cm furniture

-0.7mm thinkness 304 stainless steel undermount sink or flush instalation sink -1 square bowl -Sink without tap hole

-20 cm bowl depth

-Noise absorber foam -Drainpipe with round 3 1/2" valve

-Included accessories: round valve, syphon and overflow tube -Installation in 45 cm furniture









UNDERMOUNT

 FUJI BE 40X40 1C R10 BK. steel 304
 NEW

 Cod.: 950270065 - EAN: 8422248378208



-0.7mm thinkness 304 stainless steel undermount sink or flush instalation sink

- -1 square bowl
- -Sink without tap hole
- -20 cm bowl depth
- -Noise absorber foam
- -Drainpipe with round 3 1/2" valve
- -Included accessories: round valve, syphon and overflow tube -Installation in 45 cm furniture



* measurements in mm

50 YEARS WARRANTY









TOP MO	JUNT					TOP M	OUNT				
VELET	A SE 80	2C S	. steel 304		NEW	VELE	FA SE 86	1C1E R	EV S. st	teel 304	NEW
Cod.:	9502700)53 - EAN	1: 842224	4837029	5	Cod.:	950270	059 - EAN	1: 84222	4837115	5
AISI 304	-	J.	\bigcirc	180 cm	50	AISI 304	-	J.	\bigcirc	750 cm	50
304 STAINLESS	TOP MOUNT	ULTRA THICK	ONE BOWL	FOR 50 CM	50 YEARS	304 STAINLESS	TOP MOUNT	ULTRA THICK	ONE BOWL	FOR 50 CM	50 YEARS

-0.8mm thinkness 304 stainless steel built-in countertop sink

- -2 square bowls
- -Sink with tap hole
- -20 cm bowl depth
- -Noise absorber foam
- -Drainpipe with round 3 1/2" valve
- -Included accessories: round valves, tap covers, syphon and overflow tube
- -Installation in 80 cm furniture

- -0.8mm thinkness 304 stainless steel built-in countertop sink
- -1 square bowl and 1 draining rack
- -Sink with tap hole
- -18 cm bowl depth
- -Noise absorber foam
- -Drainpipe with round 3 1/2" valve
- -Included accessories: round valve, tap cover, syphon and overflow tube
- -Installation in 50 cm furniture























cm

FOR 50 CM FORNITURE

-0.8mm thinkness 304 stainless steel built-in countertop sink -1 square bowl and 1 draining rack

- -Sink with tap hole
- -18 cm bowl depth
- -Noise absorber foam
- -Drainpipe with round 3 1/2" valve

-Included accessories: round valve, tap cover, syphon and overflow tube

-Installation in 50 cm furniture

- -0.8mm thinkness 304 stainless steel built-in countertop sink
- -1 square bowl and 1 draining rack
- -Sink with tap hole
- -18 cm bowl depth
- -Noise absorber foam
- -Drainpipe with round 3 1/2" valve

-Included accessories: round valve, tap cover, syphon and overflow tube

Installation in 50 cm furniture











TOP MOUNT TOP MOUNT NEW VELETA SE 79 1C1E REV S. steel 304 NEW **VELETA SE 79 1C1E ED** S. steel 304 Cod.: 950270060 - EAN: 8422248371162 Cod.: 950270056 - EAN: 8422248370325 AIS 304 45 cm 45 50 50 304 cm 304 STAINLESS STEEL FOR 50 CM FORNITURE 304 STAINLESS STEEL ULTRA THICK S. STEEL FOR 50 CM FORNITURE TOP MOUNT ULTRA THICK S. STEEL ONE BOWL 50 YEARS WARRANTY TOP MOUNT ONE BOWL 50 YEARS WARRANTY

-0.8mm thinkness 304 stainless steel built-in countertop sink

- -1 square bowl and 1 draining rack
- -Sink with tap hole
- -18 cm bowl depth
- -Noise absorber foam
- -Drainpipe with round 3 1/2" valve
- -Included accessories: round valve, tap cover, syphon and
- overflow tube
- -Installation in 45 cm furniture

-0.8mm thinkness 304 stainless steel built-in countertop sink

- -1 square bowl and 1 draining rack
- -Sink with tap hole
- -18 cm bowl depth
- -Noise absorber foam
- -Drainpipe with round 3 1/2" valve
- -Included accessories: round valve, tap cover, syphon and overflow tube
- -Installation in 45 cm furniture











TOP MC	JUNT					TOP MO	JUNT				
VELET	A SE 79	1C1E EI	S. ste	eel 304	NEW	VELET	A SE 50	1C	S. s [.]	teel 304	
Cod.:	9502700)57 - EAN	I: 842224	48370332	2	Cod.:	9502700	017 - EAN	l: 84222	4808106	1
AISI 304	-	J.	\odot	145 cm	50	AISI 304	-	J.	\odot	⊅ 50 cm	50
	TOP MOUNT	ULTRA THICK	ONE BOWL	FOR 50 CM	50 YEARS	304 STAINLESS	TOP MOUNT	ULTRA THICK	ONE BOWL	FOR 50 CM	50 YEARS

-0.8mm thinkness 304 stainless steel built-in countertop sink -1 square bowl and 1 draining rack

- -Sink with tap hole
- -18 cm bowl depth
- -Noise absorber foam
- -Drainpipe with round 3 1/2" valve

-Included accessories: round valve, tap cover, syphon and

overflow tube

-Installation in 45 cm furniture

- -0.7mm thinkness 304 stainless steel built-in countertop sink
- -1 square bowl
- -Sink with tap hole
- -18 cm bowl depth
- -Noise absorber foam
- -Drainpipe with round 3 1/2" valve

-Included accessories: round valve, tap cover, syphon and overflow tube

-Installation in 50 cm furniture











TOP MO	JUNT				
K2 SE	84 2C		S. st	eel 304	
Cod.:	9502700	09 - EAN	l: 842224	8080989	
AISI 304	-	J.	180 cm	50	
304 STAINLESS STEEL	TOP MOUNT	ULTRA THICK S. STEEL	FOR 50 CM FORNITURE	50 YEARS WARRANTY	

TOP M	JUNT				
K2 SE	84 1C1	E REV	S. s	teel 304	
Cod.:	9502700	011 - EAN	1: 84222	4808100	9
AISI 304	-	J.	\bigcirc	145 cm	50
304 STAINLESS STEEL	TOP MOUNT	ULTRA THICK S. STEEL	ONE BOWL	FOR 50 CM FORNITURE	50 YEARS WARRANTY

- -0.8mm thinkness 304 stainless steel built-in countertop sink -2 round bowls
- -Sink with tap hole
- -18 cm bowl depth
- -Noise absorber foam
- -Drainpipe with round 3 1/2" valve
- -Included accessories: round valves, tap covers, syphon and
- overflow tube
- -Installation in 80 cm furniture

-0.7mm thinkness 304 stainless steel built-in countertop sink

- -1 round bowl and 1 draining rack
- -Reversible sink with tap hole
- -17 cm bowl depth
- -Noise absorber foam
- -Drainpipe with round 3 1/2" valve
- -Included accessories: round valve, tap cover, syphon and
- overflow tube
- -Installation in 45 cm furniture













TOP MO	DUNT					TOP M	OUNT				
K2 SE	49 1C		S. st	eel 304		K2 SE	44		S. stee	el 304	NEW
Cod.:	9502700)42 - EAN	I: 842224	4819065	7	Cod.:	9502700)62 - EAN	I: 84222	4837112	4
AISI 304 304 STAINLESS STEEL		ULTRA THICK S. STEEL	ONE BOWL	FOR 50 CM FORNITURE	50 YEARS WARRANTY	AISI 304 304 STAINLESS STEEL	TOP MOUNT	ULTRA THICK S. STEEL	ONE BOWL	FOR 50 CM FORNITURE	50 YEARS WARRANTY

-0.7mm thinkness 304 stainless steel built-in countertop sink -1 round bowl -Sink with tap hole -20 cm bowl depth -Noise absorber foam

-Drainpipe with round 3 1/2" valve

-Included accessories: round valve, syphon and overflow tube -Installation in 45 cm furniture -0.8mm thinkness 304 stainless steel built-in countertop sink

- -1 square bowl
- -Sink with tap hole
- -16 cm bowl depth
- -Noise absorber foam
- -Drainpipe with round 3 1/2" valve

-Included accessories: round valve, syphon and overflow tube -Installation in 45 cm furniture





edesa

Code	950270029	950270031	950270033	950270027	950270063	950270064	950270050	950270051
EAN	8422248081177	8422248081191	8422248081450	8422248081153	8422248373050	8422248373067	8422248371100	8422248370271
Model	MAKALU BE 50x40 1C R-10	MAKALU BE 45x40 1C R-10	MAKALU BE 40x40 1C PLUS R-10	MAKALU BE 40x40 1C R-10	FUJI BE 50X40 1C /A	FUJI BE PLUS 45X40 1C	FUJI BE 45X40 1C	FUJI BE 40X40 1C PLUS /A
Dimensions								
Cutout dimension (width x lenght) [mm]	500 x 400	450 x 400	400 x 400	400 x 400	500 x 400	450 x 400	450 x 400	400 x 400
Dimensions (width x lenght x depth) [mm]	540 x 440 x 200	490 x 440 x 200	440 x 440 x 250	440 x 440 x 200	545 x 445 x 180	495 x 445 x 200	495 x 445 x 180	445 x 445 x 200
General Features								
Type of sink	Undermount	Undermount	Undermount	Undermount	Undermount	Undermount	Undermount	Undermount
Material	Stainless steel 304	Stainless steel 304	Stainless steel 304	Stainless steel 304	Stainless steel 304	Stainless steel 304	Stainless steel 304	Stainless steel 304
Steel thickness [mm]	1,2	1,2	1,2	1,2	0,8	0,8	0,8	0,8
Colour	Steel	Steel	Steel	Steel	Steel	Steel	Steel	Steel
Bowl and draining rack details								
Bowl quantity	1	1	1	1	1	1	1	1
Bowl form	Square with inverted pyramid surface	Square with inverted pyramid surface	Square with inverted pyramid surface	Square with inverted pyramid surface	Square	Square	Square	Square
Draining rack	-	-	-	-	-	-	-	-
Draining rack form	-	-	-	-	-	-	-	-
Tap hole	-	-	-	-	-	-	-	-
Noise absorber foam		•	•	•	•	•	•	•
Accessories								
Drainpipe type	Square 3 1/2"	Square 3 1/2"	Square 3 1/2"	Square 31/2"	Round 3 1/2"	Round 3 1/2"	Round 3 1/2"	Round 3 1/2"
Drainpipe quantity	1	1	1	1	1	1	1	1
Overflow tube		•	•	•	•	•	•	•

Code	950270052	950270019	950270067	950270066	950270065	950270053	950270059	950270054
EAN Model	8422248370288 FUJI BE 40X40 1C R-60 /A	8422248081085 FUJI BE 34x40 1C	8422248378222 FUJI BE 50X40 1C R10 BK	8422248378215 FUJI BE 45X40 1C R10 BK	8422248378208 FUJI BE 40X40 1C R10 BK	8422248370295 VELETA SE 80 2C /B	8422248371155 VELETA SE 86 1C1E REV	8422248370301 VELETA SE 86 1C1E ED /A
			IC RIUBR	IC RIV BR	IC RIUBR			.0.2.22 // .
Dimensions								
Cutout dimension (width x lenght) [mm]	400 x 400	340 x 400	500 x 400	450 x 400	400 x 400	770 x 480	840 x 480	840 x 480
Dimensions (width x lenght x depth) [mm]	445 x 445 x 180	370 x 430 x 180	540 x 440 x 200	490 x 440 x 200	440 x 440 x 200	790 x 500 x 180	860 x 500 x 180	860 x 500 x 180
General Features								
Type of sink	Undermount	Undermount	Undermount	Undermount	Undermount	Built-in coun- tertop	Built-in coun- tertop	Built-in coun- tertop
Material	Stainless steel 304	Stainless steel 304	Stainless steel 304	Stainless steel 304	Stainless steel 304	Stainless steel 304	Stainless steel 304	Stainless steel 304
Steel thickness [mm]	0,8	0,7	0,7	0,7	0,7	0,8	0,8	0,8
Colour	Steel	Steel	Black Steel	Black Steel	Black Steel	Steel	Steel	Steel
Bowl and draining rack details Bowl quantity	1	1	1	1	1	2	1	1
Bowl form	Square	Square	Square	Square	Square	Square	Square	Square
Draining rack	-	-	-	-	-	-	•	•
Draining rack form	-	-	-	-	-	-	Square	Square
Tap hole Noise absorber foam	-	-	-	-	-			
Accessories		·						·
Drainpipe type	Round 3 1/2"	Round 3 1/2"	Round 3 1/2"	Round 3 1/2"	Round 3 1/2"	Round 3 1/2"	Round 3 1/2"	Round 3 1/2"
Drainpipe quantity	1	1	1	1	1	2	1	1
Overflow tube	•	•	•	•	•	•	•	•
Code	9502700	55 9502700	60 95027005	6 950270057	950270017	950270009	950270011	950270042
EAN	8422248370							
Model	VELETA SE 1C1E EI /	86 VELETA SI	E 79 VELETA SE	79 VELETA SE 7		K2 SE 84 2C	K2 SE 84 1C1E REVERSIBLE	K2 SE 49 1C
Dimensions								
Cutout dimension (width x lenght) [mm]	840 x 48				480 x 480	820 x 420	820 x 420	Ø465
Dimensions (width x lenght x depth) [mm]	860 x 500 x	180 790x500x	180 790x500x1	80 790x500x180	0 500 x 500 x 180) 840 x 440 x 180	840 x 440 x 180	Ø485 x 160
General Features	Built-in cou	ın- Built-in co	un- Built-in cou	n- Built-in coun-	Built-in coun-	Built-in coun-	Built-in coun-	Duilt in cour
Type of sink	tertop	tertop	tertop	tertop	tertop	tertop	tertop	Built-in coun- tertop
Material	Stainless st 304	eel Stainless s: 304	teel Stainless st 304	eel Stainless stee 304	el Stainless steel 304	Stainless steel 304	Stainless steel 304	Stainless steel 304
Steel thickness [mm]	0,8	0,8	0,8	0,8	0,7	0,8	0,7	0,7
Colour	Steel	Steel	Steel	Steel	Steel	Steel	Steel	Steel
Bowl and draining rack details								
Bowl quantity	1	1	1	1	1	2	1	1
Bowl form	Square	Square		Square	Square	Round	Round	Round
Draining rack	•	•	•	•	-	-	•	-
Draining rack form Tap hole	Square	Square	Square	Square	-	-	Round	-
Noise absorber foam	•	•	•	•	•	•	•	•
Accessories						-	-	
Drainpipe type	Round 3 1/	2" Round 3 1,	/2" Round 3 1/2	2" Round 3 1/2"	Round 3 1/2"	Round 3 1/2"	Round 3 1/2"	Round 3 1/2"
Drainpipe quantity	1	1	1	1	1	2	1	1
Overflow tube	•		•	•		•	•	•

All the boxes marked with a \bullet are equivalent to a Yes Accessories / \circ NOT INCLUDED \bullet INCLUDED



Code	950270062			
EAN	8422248371124			
Model	KS SE 44			
Dimensions				
Cutout dimension (width x lenght) [mm]	460 x 460			
Dimensions (width x lenght x depth) [mm]	480 x 480 x 160			
General Features				
Type of sink	Built-in coun- tertop			
Material	Stainless steel 304			
Steel thickness [mm]	0,8			
Colour	Steel			
Bowl and draining rack details				
Bowl quantity	1			
Bowl form	Square			
Draining rack	-			
Draining rack form	-			
Tap hole	•			
Noise absorber foam	•			
Accessories				
Drainpipe type	Round 3 1/2"			
Drainpipe quantity	1			
Overflow tube				

TAPS

SEMI-PROFESSIONAL

YOSEMITE CROMO

HIGH SPOUT

VICTORIA CROMO

214

MARO CROMO

215

214

edesə

215

NIAGARA INOX





Are you looking for quietness and protection? With Edesa 5 more years

All taps include a 5-year warranty as standard to ensure your satisfaction.

This service offers the quality guaranteed by our qualified professionals.

Experience the protection that Edesa offers you, assured for a total of 5 years, the costs of repair and a service of qualified technical personnel and highly prepared for the repair and troubleshooting.

Damage caused by the wear of accessories, sealing gasket, tubes, cartridges, filters, etc.; as well as the damages caused by improper handling, improper use or use of abrasive products or substances are excluded from the Warranty.

edesa

edesə



In Edesa we bet for the brass and the stainless steel for the outside. The latter is one of the most popular materials in our market, very easy to clean and highly resistant to oxidation.

The other most used material in the tap sector is brass, which results from copper and zinc alloy.

They are noble materials that provide a much longer useful life, even when they are in continuously contact with water.



With Edesa, 304 stainless steel and the best finishes

Edesa taps have a perfect finish thanks to the high quality materials with which they are manufactured.

To ensure a lasting and useful life of your tap, we make sure that both the interior and the exterior of it pass our most demanding quality and durability controls.

Both the pipe and the controls, and the rest of the parts that make up the tap, are made of nonporous stainless materials, avoiding corrosion or rust, and facilitating the cleaning of the smooth and thin surface.





The mixer tap range that thinks of you

The brand opts for the mixer tap type, as it is the most requested by users.

It is the tap model that, with a single control, you can regulate both the flow of water and its temperature, thus achieving comfort and simplicity.

We adapt to the needs of the market, to offer the tap that best fits to your sink, either one or two bowls; and your kitchen.





We have opted for chrome and satin

Do you want a shiny sink? In that case, the chrome finish is your best option. They have a brilliant silver tone that will give to your kitchen a distinctive touch.

If you prefer something more subtle and elegant, sinks with satin finish are our recommendation.

Its maintenance is very simple and it is resistant to bumps or scratches.



Filling the large pots is no longer a problem thanks to the taps with high spout

Before, when you gathered the family for a feast at home, scrubbing the large pots could be quite an odyssey.

Now, with Edesa, it is easier, thanks to the high spout taps, the useful space inside the sink is multiplied.

edesə

Scrubbing will now be much simpler

In addition to the jet in aeration mode, Edesa presents a second possibility for your kitchen.

The shower mode offers a wider wetting area, which allows to maximize the operating radius.

In this way, cleaning or rinsing a large surface does not require any effort.



For those looking to save, the aeration system

Thanks to the diffuser system incorporated by the Edesa taps, a drastic saving of water and energy is achieved.

This is possible, thanks to combination of the flow of water with air, achieving a perfect and homogeneous pressure of the flow.

This aerator complies with the most stringent water saving regulations.

By limiting the water flow, you contribute to responsible consumption and save on your water and energy bill to generate hot water.

This aeration system is very easy to clean and installation.

Taps that can be extracted

That the tap is extractable up to 50 cm allows to direct the water jet to better rinse all the details of the most voluminous pots, the most fragile cups and tall glasses.





A smooth and precise handling is possible with Edesa

The cartridges that incorporate all the taps of the range allow a concise and meticulous handling of the control.

Thanks to the ceramic material, the cartridges suffer less wear and offer a perfect closure throughout its useful life. Thus, we avoid the drip effect.

This accessory, included in all Edesa taps, has been examined and evaluated by the technical quality team in tests of half a million cycles of use, in order to demonstrate its reliability and durability in your home.



Cold opening

Cold-opening faucets are a revolutionary solution for saving energy and water in the home. Unlike traditional faucets, they open exclusively with cold water, reducing energy consumption by up to 80%1. Let me explain why they are so beneficial:

Energy Savings: cold-opening faucets eliminate the need to heat water for every use. By starting with cold water, only the amount needed is heated, which significantly reduces energy consumption.

Consumption Awareness: By having immediate access to the cold tap, users become more conscious of the amount of water they use. This encourages responsible and sustainable use.

Cost Reduction: By saving energy, electricity bills are also reduced. In addition, these faucets can help you save money on hot water consumption.

Cold opening.

At Edesa we give you solutions to save energy and water at home. Reduce energy consumption by up to 80 % by eliminating the need to heat water for each use. By starting with cold water, only the necessary amount is heated, which significantly reduces energy and hot water consumption.







SEMI-PROFESSIONAL YOSEMITE PRO CROMO S. Steel

NEW Cod.: 951270029 - EAN: 8422248373258

REMOVABLE SPOUT



5 YEARS



-Brass tap with chromed finish style

-Handle control on the right side of the tap

-Triangular reinforcements for stable installation

-M10x1x3/8" Flexible connection tubes included

-Anti scale areator with 51/min flow limit

-Sink or cooktop instalation available

-Rotatory 360° curved high spout

-Anti-scale aerator system

-Ceramic cartridge included

-Shower function





"SHOWER" FUNCTION anti-scale AERATOI SYSTEM

SINGLE-LEVER

HIGH SPOUT



HIGH SPOUT



VICTORIA CROMO

REMOVABLE SPOUT

chromed

"SHOWER' FUNCTION

AERATO SYSTEM

NEW

5 YEARS WARRANT

- -Brass fixing-tap with chromed finish style
- -Removable and rotatory 360° curved high semi-profesional spout

Cod.: 951270028 - EAN: 8422248372022

- -Handle control on the right side of the tap
- -Anti scale areator with 51/min flow limit
- -Anti-scale aerator system
- -Shower function
- -Sink or cooktop instalation available
- -Ceramic cartridge included
- -Triangular reinforcements for stable installation
- -M10x1x3/8" Flexible connection tubes included





TAPS





HIGH SPOUT MARO CROMO NEW chromed Cod.: 951270030 - EAN: 8422248373708

REMOVABLE SPOUT





ANTI-SCALE

AERATOR









NEW

AERATO

-Two color brass fixing-tap with chromed finish style

ROTATOR' SPOUT

- -Removable and rotatory 360° L line form, high spout
- -Handle control on the right side of the tap -Anti scale areator with 5l/min flow limit
- -Anti-scale aerator system
- Shower function

SINGLE-LEVER

- -Sink or cooktop instalation available
- -Ceramic cartridge included

HIGH SPOUT

- -Triangular reinforcements for stable installation
- -M10x1x3/8" Flexible connection tubes included

- -304 stainless steel fixing-tap with satin finish style
- -Rotatory 360° curved high spout
- -Handle control on the right side of the tap
- -Anti scale areator with 51/min flow limit
- -Anti-scale aerator system
- -Sink or cooktop instalation available -Ceramic cartridge included
- -Triangular reinforcements for stable installation
- -M10x1x3/8" Flexible connection tubes included











high s	POUT					HIGH S	POUT				
NIAG		OMO	Chrom	ed	NEW	NIAG	ARA NE	GRO BI	ack		NEW
Cod.:	9512700)26 - EA	N: 84222	4837200	8	Cod.:	9512700	31 - EAN	N: 842224	1837803	1
SINGLE-LEVER 5 YEARS WARRANTY	HIGH SPOUT	ROTATORY SPOUT	REMOVABLE SPOUT	"SHOWER" FUNCTION	ANTI-SCALE AERATOR SYSTEM	SINGLE-LEVER 5 YEARS WARRANTY	HIGH SPOUT	ROTATORY SPOUT	REMOVABLE SPOUT	"SHOWER" FUNCTION	ANTI-SCALE AERATOR SYSTEM

- -Brass fixing-tap with chromed finish style -Rotatory 360° curved high spout
- -Handle control on the right side of the tap
- -Anti scale areator with 51/min flow limit
- -Anti-scale aerator system
- -Sink or cooktop instalation available
- -Ceramic cartridge included
- -Triangular reinforcements for stable installation -M10x1x3/8" Flexible connection tubes included

- -Brass fixing-tap with chromed finish style -Rotatory 360° curved high spout
- -Handle control on the right side of the tap
- -Anti scale areator with 51/min flow limit
- -Anti-scale aerator system
- -Sink or cooktop instalation available
- -Ceramic cartridge included
- -Triangular reinforcements for stable installation
- -M10x1x3/8" Flexible connection tubes included











LOW SPOUT Chromed NEW SL CROMO Chromed NEW Cod.: 951270025 - EAN: 8422248371988 8422248371988



-Brass fixing-tap with chromed finish style -Rotatory 360° line form short spout -Handle control on the frontal of the tap -Anti scale areator with 51/min flow limit

-Anti-scale aerator system

-Sink or cooktop instalation available

-Ceramic cartridge included

- -Triangular reinforcements for stable installation
- -M10x1x3/8" Flexible connection tubes included







TAPS

edesə

Code	951270029	951270028	951270030	951270027
EAN Model	8422248373258 YOSEMITE PRO CROMO /A	8422248372022	8422248373708	8422248372015
Model	YOSEMITE PRO CROMO /A	VICTORIA CROMO/B	MARO CROMO/B	NIAGARA INOX/C
Dimensions				
Dimensions (diameter, lenght) of spout braided hose [", cm]	3/8, 40	3/8, 40	3/8, 40	3/8, 40
Product dimensions (height x width x depth) [mm]	508 x 252 x 52	430 x 246 x 52	348x286x49	371 x 240 x 50
General Features				
Water tap type	Single-lever	Single-lever	Single-lever	Single-lever
Material	Brass	Stainless steel 304	Brass	Stainless Steel
Material of handle	Zinc	Stainless steel 304	Cast	Stainless Steel
Material of spout braided hose	Stainless steel 304	Silicone	Stainless steel	Stainless steel
Finish style	Chrome	Satin	Chrome	Satin
Instalation place	Sink, cooktop	Sink, cooktop	Sink, cooktop	Sink, cooktop
Flow limiter (I/min)	5	5	5	5
Spout and control details				
Spout type	Long	Long	Long	Long
Spout form	Semi-professional	Semi-professional	L form	Curved
Removable spout	-	-	-	-
Rotatory spout	360º	360º	360º	360º
Airy spout	•	•	•	•
Shower function	٠	•	•	0
Cold start	•	•	•	•
Control type	Handle	Handle	Handle	Handle
Control position	Right side	Right side	Right side	Right side
Accessories				
Cartridge type	Ceramic	Ceramic	Ceramic	Ceramic
Installation triangle	•	•	•	•

Code EAN	951270026 8422248372008	951270031 8422248378031	951270025 8422248371988
Model	NIAGARA CROMO /C	NIAGARA NEGRO	SL CROMO /B
Dimensions			
Dimensions (diameter, lenght) of spout braided hose [", cm]	3/8, 40	3/8, 40	3/8, 40
Product dimensions (height x width x depth) [mm]	371 x 240 x 50	365 x 218 x 50	140 x 250 x 50
General features			
Water tap type	Single-lever	Single-lever	Single-lever
Material	Brass	Brass	Brass
Material of handle	Cast	Cast	Cast
Material of spout braided hose	Stainless steel	Stainless steel	Stainless steel
Finish style	Chrome	Black	Chrome
Instalation place	Sink, cooktop	Sink, cooktop	Sink, cooktop
Flow limiter (I/min)	5	5	5
Spout and control details			
Spout type	Long	Long	Short
Spout form	Curved	Curved	Line
Removable spout	-	-	-
Rotatory spout	360º	360⁰	360º
Airy spout	•	•	•
Shower function	-	-	-
Cold start	•	-	•
Control type	Handle	Handle	Handle
Control position	Right side	Right side	Right side
Accessories			
Cartridge type	Ceramic	Ceramic	Ceramic
Installation triangle	•	•	•



The technical characteristics indicated in the catalogue must be verified by the THE MANUFACTURER.

Non-contractual photographs. CATA Electrodomésticos S.L.U. reserves the right to modify the characteristics of its products without prior notice. © Design, layout, images and content are the property of CATA Electrodomésticos S.L.U.

FRIDGES & FREEZERS

DUAL NF	FULL NF	LED		88		LED			@*	∐ ▼
METAL DUAL NO FROST	FULL NO FROST	INTERIOR/ EXTERIOR LED DISPLAY	LED ARRAY	INTERIOR/EXTE- RIOR LED DIGI- TAL DISPLAY		LED LIGHTNING	SUITABLE FOR CAMPER	HOLIDAYS FUNCTION	SUPER FUNCTION	WITH PLUG
DISHW	ASHE	RS								
~	⁹⁰	30	\mathcal{Q}	\mathbf{Q}				$\overline{\bigcirc}$	10	÷
INVERTER MOTOR	EXPRESS 90' PROGRAMME	FAST 30' PROGRAMME	DELAY START	GLASS	AUTOMATIC PROGRAM	AUTOMATIC DOOR OPENING	SUITABLE FOR TABLETS ALL IN ONE	TRIPLE SECURITY SYSTEM	10 YEARS WARRANTY	WITH PLUG
2	[[]	₩¢	ů	3	¢					
SILENCE	TOTAL CLEAN	HYGIENE	BOTTLES	3RD CUTLERY RACK	EXTRA DRYING					
WASH	ERS &	DRYER	S							
(10) kg	9 kg	(8) kg	(7) kg	(6 kg	LED		(h			10
CAPACITY	CAPACITY	CAPACITY	CAPACITY	CAPACITY	LED DISPLAY	MY PROGRAMME	DELAY START	REMAINING TIME INDICATOR	WASHING PHASE INDICATOR	10 YEARS WARRANTY
7	জ্	÷		Ø						
INVERTER MOTOR	STEAM	WITH PLUG	CLEAN WASHING MACHINE	PRO HYGIENE	RELOAD					
SINKS										
-C	-	↓ 25m	¥20m	¥1ª	J.		00	\bigcirc		AISI 304
COUNTERTOP	UNDERMOUNT	25CM DEPTH OF THE BOWL	25CM DEPTH OF THE BOWL	25CM DEPTH OF THE BOWL	ULTRA GROSS STAINLESS STEEL	REVERSIBLE	2 BOWLS	1 BOWL	DRAINING RACK	304 STAINLESS STEEL
780 cm	160 cm	750 cm	145 cm	50	R.10 mm					
FOR 80 CM FORNITURE	FOR 60 CM FORNITURE	FOR 50 CM FORNITURE	FOR 45 CM FORNITURE	50 YEARS WARRANTY	RADIUS 10 MM					
TAPS										
		Ŷ				5				
SINGLE-LEVER	HIGH SPOUT	ROTATORY SPOUT	REMOVABLE SPOUT	SHOWER FUNCTION	ANTI-SCALE AERATOR SYSTEM	5 YEARS WARRANTY				



CATA ELECTRODOMÉSTICOS S.L.U. Tlf: +34 938 594 100.- Fax +34 938 594 101. www.cata.com - www.edesa.com - www.cnagroup.es - cna@cnagroup.es Headquarters: c/ Anabel Segura, 11, Edif. A, 3a pl. 28108. Alcobendas (Madrid. Spain) Factory: c/ del Ter, 2, Apdo. 9. 08570. Torelló (Barcelona. Spain)

